

(June 9, 1932)

DETERMINATION OF THE CORROSIVITY OF SOILS

The following abstracts and summaries have been prepared from recent publications relating to methods of determining the corrosivity of different soils with respect to ferrous metals and are intended to give a fairly complete outline of what has been accomplished in this field. Where more detailed information is desired, the unabridged articles should be consulted.

Bureau of Standards publications referred to may be obtained from the Superintendent of Documents, Government Printing Office, Washington, D. C. at the following prices:

Correlation of Certain Soil Characteristics with Pipe Line Corrosion. I. A. Denison. Research Paper No. 363. 5 cents.

Pipe Line Currents and Soil Resistivity as Indicators of Local Corrosive Soil Areas. E. R. Shepard. Research Paper No. 298. 15 cents.

1. Corrosiveness of soils with respect to iron and steel.  
H. D. Holler, Bureau of Standards. Industrial and Engineering Chemistry, 21, p. 750; August 1929. - A method of studying soil corrosion based on the relation of salt content, acidity, and corrosiveness of soil to rainfall is suggested. The corrosiveness of soils as indicated by the initial losses of buried specimens in humid areas of the United States has been correlated with their acidity.

The total acidity of soils may be estimated by titration using the hydrogen electrode; and also by comparing the pH value of the soil in water and in a potassium chloride solution. A relation exists between the ability of a soil to react on iron with liberation of hydrogen and its total acidity as indicated by titration.

The corrosiveness of a soil in humid regions may possibly be indicated by its total acidity or by its action on iron with evolution of hydrogen.

on 10 of the  
document in  
the

CONFIDENTIAL

The attached document contains information which is being furnished to you for your information only. It is not to be distributed outside your organization.

The attached document contains information which is being furnished to you for your information only. It is not to be distributed outside your organization.

CONFIDENTIAL

The attached document contains information which is being furnished to you for your information only. It is not to be distributed outside your organization.

The attached document contains information which is being furnished to you for your information only. It is not to be distributed outside your organization.

The attached document contains information which is being furnished to you for your information only. It is not to be distributed outside your organization.

20

21

The attached document contains information which is being furnished to you for your information only. It is not to be distributed outside your organization.

2. Correlation of certain soil characteristics with pipe line corrosion. I. A. Denison, Bureau of Standards. Bur. Standards J. Research 7, Oct., 1931. Research Paper No. 363. - Corrosion experienced in the operation of a group of pipe lines in Ohio was found to be related to the kinds of soil which occur along a 32-mile section of the lines. Soils of the Brookston series in this area are noncorrosive. Soils of the Nappanee series proved to be corrosive wherever they occurred. The Wauseon soils occurring on slopes or slight ridges were observed to be corrosive. Other sandy and sandy-loam soils not underlain by glacial material apparently have little corrosive action. A satisfactory correlation was found to obtain between the exchangeable hydrogen present in the soils and corrosiveness as indicated by the quantity of pipe replaced in 1,000-foot intervals. The hydrogen ion concentration of soil samples in normal potassium chloride solution is a fairly satisfactory index to the corrosiveness of the soils studied except in the case of slightly buffered sands. Both methods, however, tend to exaggerate the corrosiveness of well-drained sandy soils.

An accelerated laboratory test of soil corrosiveness involving the corrosion of a steel disk in contact with moist soil is also described. The results obtained paralleled the quantity of pipe replacements fairly closely in the case of heavy soils. The degree of corrosiveness indicated by the test is influenced by the acidity, texture, and probably by the structure of the soils studied. Since only a qualitative study of the factors influencing the test has been made, the test can not at this time be considered a reliable index of soil corrosiveness except in the case of soils similar to those tested.

The methods described for identifying corrosive soils which involve determinations of acidity are probably most reliable in the case of related soils which differ from one another chiefly in their contents of exchangeable hydrogen. The data obtained from the tests are probably insufficient to indicate the relative corrosiveness of soils having widely different physical and chemical characteristics.

3. Analyzing the merits of soil corrosion survey work as developed for the Amarillo-Denver Line. Wm. Thompson Smith. Western Gas, p.30, Feb., 1931. - The relative corrosiveness of the soil at various points along a pipe line right of way may be estimated in advance as a basis for the specification of the degree of protection to be applied in different sections. The most commonly used and generally accepted means of estimation is based upon simple observation of surface conditions. As an alternative, a detailed soil-corrosion survey involving simultaneous consideration of chemical and topographical characteristics was first



employed in the construction of the Amarillo-Denver natural gas pipe line. The inspection of this line at 66 points by the American Gas Association two years after installation affords a basis for studying the relative merits of the two methods. Consideration of available data led the author to the following conclusions:

1. The substantial accuracy of the results of a soil corrosion survey as used by Ford, Bacon & Davis, Inc., is confirmed, for alkali soils.

2. The probable accuracy of such a survey in other soil conditions is indicated.

3. The specification of the degree of protection to be used on a pipe line is more exactly in accord with the actual requirements when based on a soil corrosion survey than when based upon surface inspection alone.

4. The variation from the degree of protection necessary, as indicated by actual inspection after service, tends toward provision of excess coating in the case of a soil corrosion survey and toward inadequate protection in the case of surface inspection alone.

5. Agreement by independent observers as to the degree of corrosiveness of the soil at any location is not absolute even when based on inspection data of pipe after service.

6. It is unsafe to base a decision to eliminate protection at any point on the old method of simple inspection of the surface of the ground alone.

7. It is relatively safe to base specifications of pipe protection on the results of a thorough soil-corrosion survey.

8. Substantial agreement in the comparative rating of soil samples as to relative corrosiveness, although a matter of judgment, is possible by independent workers.

9. Using the data from a soil-corrosion survey, substantial agreement is possible in the independent specification of the degree of protection for specific sections of pipe lines.

10. In the instance studied, soil-corrosion survey specifications would have entailed an expenditure for pipe protection of 6.4 per cent more than actually required. The actual construction program (although only in part substituting simple surface observation for a soil corrosion survey) expended only 75.1 per cent of the amount actually required for adequate protection.



11. This study has shown no one factor or small group of factors affecting corrosion which may safely be taken as an index of the comparative corrosiveness of soils at various locations.

4. A.G.A.-Bureau of Standards field study of long gas lines. Scott Ewing, Research Associate, American Gas Association, Bureau of Standards. American Gas Association Monthly, p.70, Feb. 1931.- An inspection of the Amarillo-Denver line at 65 locations, two years after installation led the author to the following conclusions.

The data fail to indicate that light coatings such as paints and cut-backs have any protective value. The light, cut-back, coating used on some portions of the line was found to be in all stages of disintegration. Where it was in good shape, it is doubtful if bare pipe would corrode, and where the soil was corrosive the pipe was pitted. A cold coat containing asbestos fiber, used on some portions of the line was examined in only three places, which is not sufficient for a positive conclusion.

There does not appear to be any relation between the electrical resistance of these coatings and their condition, the resistance being very low wherever it was measured. The condition of these coatings does not appear to be related to either the colloidal content of the soil or its specific resistance when saturated.

The results of this study indicate that if an enamel is used as a pipe coating it should be hard, because the harder the enamel the better it resists soil action. The only limit to hardness is the tendency of the enamel to crack. A much harder enamel can be used in warm weather, so it is a decided advantage to apply it then.

There is a fair correlation between the soil types and the recommendations resulting from the corrosion survey. In order to make coating recommendations in this region as accurate as those made for this line the following procedure is sufficient: Make a soil map of the line and (2) measure the resistivity of a number of soil samples, taken with proper care along the line.

5. Pipe line currents and soil resistivity as indicators of local corrosive soil areas. E. R. Shepard, Bureau of Standards. Bur. Standards J. Research, 6, April, 1931. Research Paper No. 298. - The present tendency in the protection of pipe lines against soil corrosion is away from a uniform coating for the entire length of the line and toward the application of coatings

... of the ... ..  
... ..  
... ..

... ..  
... ..  
... ..

... ..  
... ..  
... ..

... ..  
... ..  
... ..

... ..  
... ..  
... ..

... ..  
... ..  
... ..

... ..  
... ..  
... ..



selected with respect to the corrosive character of the soils involved. This calls for a knowledge of varying soil conditions and a means of locating local corrosive soil areas. Such areas, commonly termed "hot spots", are prevalent in many types of soils, and it is in these regions that pipe lines suffer the greatest deterioration. The location of such corrosive areas is a matter of considerable importance, both with respect to the selection of coatings for new pipe lines and the reconditioning of old ones.

An extensive investigation of a dozen pipe lines ranging from the Gulf coast to southern Kansas revealed an apparent correlation between pipe-line currents, soil resistivity, and corrosion. Galvanic currents of measurable magnitudes were found to be flowing on all pipe lines examined. As a rule, lines were found to be collecting current in areas of normal and high soil resistivity and losing current in areas of low resistivity. Many cases of abrupt loss or discharge of current occurred in soils of unusually low resistivity. In such areas the pipe lines were found to be badly corroded.

Although no direct relation was found to exist between electrical resistivity of soils and their corrosiveness, abrupt changes in resistivity and unusually low resistivity were found to be significant with respect to corrosion. Soils having a resistivity of about 500 ohm-centimeters or less were invariably found to be highly corrosive. A better relation between resistivity and corrosiveness exists in alkali than in acid soils.

To expedite the measurement of soil resistivity, a simple piece of apparatus was developed, consisting of two metal-tipped oak rods with a milliammeter mounted on one and a small flashlight battery on the other. By measuring the apparent resistance between the metal terminals, the approximate resistivity of the soil can be calculated if the constant of the apparatus is known. Since polarization is largely a cathode effect, it can be partly eliminated by making the cathode terminal much larger than the anode, thereby reducing the current density on it. A low resistance meter, such as a milliammeter, is found to be preferable to a voltmeter as with the former practically the full voltage of the test battery is applied between the electrodes, irrespective of the meter reading, while with the latter a large part of the battery voltage is consumed within the meter itself.

This apparatus permits of making frequent and rapid tests of earth resistivity along a pipe line or along a projected pipe line. Although it is not claimed that absolute values of resistivity are obtained with this apparatus, the results are sufficiently accurate for all practical purposes provided the soil is not too dry. It is important that earth be tested at

... to the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...

... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...

... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...

... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...

... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...

... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...  
... the ... of the ...

the pipe level and where there is sufficient moisture to afford nearly maximum conductivity. Damp soil which will pack in the hand will usually show conductivity approaching that in a saturated condition.

The technique of surveying pipe lines for galvanic currents and soil resistivity is discussed.

6. Relation of long line currents to soil corrosion. Stanley Gill and W. F. Rogers, Gulf Oil Companies, Research Department, Houston, Texas. Physics, 1, No.3, p.194, September, 1931. - "Stray currents" from street electric railways and the like give rise to rapid corrosion of buried pipe lines. A type of currents similar to "stray currents", but which occur at long distances from any possible external source of electric current, has been found on pipe lines. These currents are known as "long line currents" and are supposed to originate between the soil and the pipe. They frequently follow the pipe for miles without any change in amperage. To determine possible influence of these currents upon corrosion, measurements of their value were made on an 8-inch oil line upon which much corrosion trouble had been experienced. The line was removed from the ground and the extent of corrosion determined by inspection. Electrical resistivities of numerous samples of soil were determined.

From the data obtained, the following conclusions are drawn:

1. Discharge or accumulation of electric currents of the class which have been termed "long line currents" is, in general, without influence upon corrosion of buried pipe lines.
2. Electrical resistivity of soil correlates to a certain extent with corrosion of buried pipe; the relationship is not sufficiently consistent to be of practical value.
3. There is no consistent relationship between soil resistivity and the accumulation or discharge of "long line currents".

A more detailed discussion of the several classes of current affecting pipe lines will be found in the paper by Logan, Rogers and Putnam "Pipe Line Currents", Trans. of A.P.I. Meeting, Section IV, p.116 (1930) and also in a paper by Gill and Rogers, "Electric currents carried in lines", Oil and Gas Journal, 29, T158 (1930).



7. Soil Corrosivity Surveys. K. H. Logan, Bureau of Standards. American Petroleum Institute Production Bulletin No. 207 - June 1931, page 142. Oil and Gas Journal - June 4, 1931. Pipe Line News - December 1931. - The author states briefly the essential features of a number of tests for the corrosiveness of soils now in use in various parts of the country. The details of manipulation depend on the operator. The following general conclusions are given.

Most, if not all, of the methods for identifying corrosive soils have been shown by their originators to be reasonably satisfactory under some condition. None of the methods have been used extensively enough to permit defining their limitations. The best way to do this would be to try out each method along a number of pipe lines in various parts of the country, determining at the same time the condition of the line. Until the results of such tests are available, it would probably be advisable for the soil survey engineer to check his results by the use of two widely different methods, selecting the methods after determining whether the soils are acid or alkaline. He might start with a method involving soil resistivity, indications of which will probably be significant if the resistivity is low. If the resistivity is high, the total acidity of the soil should also be investigated. Since soil conditions may change radically with the season, it will be well to give careful consideration to topography, drainage, and rainfall. The services of an expert familiar with the identification of soils will reduce the number of tests necessary and the chances that some corrosive soils will be missed. If due care is used, it may be expected that a very large percentage of the corrosive and non-corrosive soils will be located.

A bibliography is given.

8. Determining the corrosivity of soils. E. R. Shepard, Bureau of Standards. The Oil and Gas Journal, page T-40, June 4, 1931.- Although in general the alkaline soils of the West and certain southern soils appear to be the most destructive to pipes, there are no geographical limits to the areas in which acute corrosion may occur.

The experience of nearly every pipe line company and utility operator, which is also supported by the Bureau's data, indicates that a large proportion of the destructive corrosion occurring on their systems is confined to relatively small areas. The problem of locating or predetermining such areas, particularly the so-called "hot-spots" or excessively corrosive soils, is of great importance to the pipe owners, both in connection with the protection of new lines and the reconditioning or repair of old ones.



No satisfactory method of predetermining the corrosivity of soils has yet been discovered, although several methods which are more or less applicable to certain types of soils have been proposed and used. Chemical analyses have generally proven disappointing although in some instances such tests are indicative of corrosive properties. A brief description is given of several tests which have recently been proposed for determining soil corrosivity, all of which involve electrical resistivity as the chief factor.

An analysis of the Bureau of Standards corrosion data indicates that for alkaline soils there exists a fair correlation between corrosivity and electrical resistivity, while for acid soils there appears to be no satisfactory relation,

This observed relation of resistivity to corrosivity in many soils is confirmed by a study which the Bureau of Standards carried out along a number of pipe lines in the southern states during the spring and summer of 1930. The primary purpose was to determine the relation of electric currents on pipe lines to corrosion, but measurements of soil resistivity also were made and these added greatly to the value of the investigation.

Measurable currents of galvanic origin were found on all pipe lines examined and marked variations in soil resistivity were discovered along most of the lines. In general the collecting areas, or those sections in which current flowed from the soil to the pipe, were regions of normal or high resistivity, while the discharge zones were usually relatively small in extent and were regions of low resistivity. On eight of the nine lines explored, abrupt changes in soil resistivity from high to low values were accompanied by unusually high rates of discharge of current from the pipe to the earth, and in such areas excessive corrosion was usually found to be in progress. In short, hot spots or excessively corrosive areas of limited extent can be located by either a study of galvanic currents on the line or by the measurement of soil resistivity. While no direct quantitative relation was found to exist between corrosion and soil resistivity it is significant that soils having a resistivity of about 500 ohm-cm. or less were invariably found to be highly corrosive.

Until further correlations are obtained, covering a wide variety of soil conditions, resistivity values should be considered as indicative of corrosive areas only when the resistivity is unusually low or where abrupt changes are observed.

1. 1950  
2. 1951  
3. 1952  
4. 1953  
5. 1954  
6. 1955  
7. 1956  
8. 1957  
9. 1958  
10. 1959  
11. 1960  
12. 1961  
13. 1962  
14. 1963  
15. 1964  
16. 1965  
17. 1966  
18. 1967  
19. 1968  
20. 1969  
21. 1970  
22. 1971  
23. 1972  
24. 1973  
25. 1974  
26. 1975  
27. 1976  
28. 1977  
29. 1978  
30. 1979  
31. 1980  
32. 1981  
33. 1982  
34. 1983  
35. 1984  
36. 1985  
37. 1986  
38. 1987  
39. 1988  
40. 1989  
41. 1990  
42. 1991  
43. 1992  
44. 1993  
45. 1994  
46. 1995  
47. 1996  
48. 1997  
49. 1998  
50. 1999  
51. 2000  
52. 2001  
53. 2002  
54. 2003  
55. 2004  
56. 2005  
57. 2006  
58. 2007  
59. 2008  
60. 2009  
61. 2010  
62. 2011  
63. 2012  
64. 2013  
65. 2014  
66. 2015  
67. 2016  
68. 2017  
69. 2018  
70. 2019  
71. 2020  
72. 2021  
73. 2022  
74. 2023  
75. 2024  
76. 2025  
77. 2026  
78. 2027  
79. 2028  
80. 2029  
81. 2030

The first part of the document is devoted to the collection of data on the economic situation in the country. It includes information on the production of goods and services, the volume of investments, and the state of the external trade relations.

The second part of the document is devoted to the analysis of the economic situation in the country. It includes information on the growth of the economy, the structure of the economy, and the state of the external trade relations.

The third part of the document is devoted to the analysis of the economic situation in the country. It includes information on the growth of the economy, the structure of the economy, and the state of the external trade relations.

The fourth part of the document is devoted to the analysis of the economic situation in the country. It includes information on the growth of the economy, the structure of the economy, and the state of the external trade relations.



9. Relation of pipe line currents and soil resistivity to corrosion. C. R. Weidner and L. E. Davis, The Prairie Pipe Line Company. American Petroleum Institute Production Bulletin No. 208, December 1931, page 36. The Oil and Gas Journal, November 12, 1931, page 41. - The authors describe the results of soil resistivity and pit depth measurements on 58 miles of 8-inch oil pipe lines in Oklahoma. Long-line currents were measured on 11.4 miles of the line. The apparatus and methods used were the same as those employed by Shepard. The authors summarize their findings as follows:

#### Long-Line Currents

Although the long-line current data are incomplete, the following observations appear warranted:

1. The magnitude and fluctuations of long-line currents were greater than those observed by previous investigators. A maximum of over 6.85 amperes was observed in several places.
2. Long-line currents are not constant, but may vary from time to time, due probably to moisture content of the soil, terrestrial magnetic currents, solar activity, and probably other causes.
3. The depth of pits seems to be dependent on the magnitude of the current. Taking into consideration the age of the pipe, 8 years, and the low resistivities in many places, the pit depths were not large. However, an average of the current measurement showed about 0.5 ampere, which probably was not large enough to cause serious loss of metal.
4. Loss of current is not always indicative of serious pitting, unless concentrated at points of low resistivity. Conversely, when the line is picking up current, it cannot be definitely said that there will be no pitting. Pitting may occur along such stretches if there is sufficient leakage at points of low resistivity.
5. Long-line current measurements furnish a rapid and inexpensive method of examining existing pipe lines to determine the portions that need reconditioning. Such measurements must, however, be supplemented with resistivity measurements.
6. In attempting to take measurements of long-line currents on a pipe line paralleling a telegraph line within a few feet, evidence of stray current of considerable magnitude was found.



### Soil Resistivity

1. It requires extreme care to obtain the resistivity, or even the relative resistivity, of the soil along a pipe line. An experienced observer is required for accurate measurements.
2. Shepard's apparatus is more useful to discover corrosive soil than the data presented indicate.
3. There is not much pitting in sand, gravel or rocks where it is impossible to measure resistivity with Shepard's apparatus.
4. Clays with extremely low resistance were always wet enough even in summer to obtain good resistivity measurements.
5. Where deep pits were found, soil of low resistance usually could be found at some depth.
6. Deep pits did not always coincide with soil of low resistance, but frequently were found in the next joint.
7. The resistivity of the soil below pipe depth is of some importance. Such observations sometimes discover soils of low resistance containing salts, which are absorbed by the top soil.
8. In soils of high resistance a hard rust scale sometimes forms, which seems to protect the pipe against further corrosion.
9. In soils of low resistance, where pitting is rapid, there is no scale or rust formation. The pipe is wet most of the time, and the corrosion products are white, yellow or green.

### Conclusions

The data which have been presented indicate many variations and irregularities. This may be due largely to trying to analyze one variable, such as soil resistivity, when several are involved in the determination of soil corrosivity. Errors in observation must also be considered. No definite conclusions can, therefore, be drawn until more data are available. However, taking into consideration these limitations, the authors have concluded tentatively that:

INDEX

Introduction	1
Chapter I	10
Chapter II	25
Chapter III	40
Chapter IV	55
Chapter V	70
Chapter VI	85
Chapter VII	100
Chapter VIII	115
Chapter IX	130
Chapter X	145
Chapter XI	160
Chapter XII	175
Chapter XIII	190
Chapter XIV	205
Chapter XV	220
Chapter XVI	235
Chapter XVII	250
Chapter XVIII	265
Chapter XIX	280
Chapter XX	295
Chapter XXI	310
Chapter XXII	325
Chapter XXIII	340
Chapter XXIV	355
Chapter XXV	370
Chapter XXVI	385
Chapter XXVII	400
Chapter XXVIII	415
Chapter XXIX	430
Chapter XXX	445
Chapter XXXI	460
Chapter XXXII	475
Chapter XXXIII	490
Chapter XXXIV	505
Chapter XXXV	520
Chapter XXXVI	535
Chapter XXXVII	550
Chapter XXXVIII	565
Chapter XXXIX	580
Chapter XL	595
Chapter XLI	610
Chapter XLII	625
Chapter XLIII	640
Chapter XLIV	655
Chapter XLV	670
Chapter XLVI	685
Chapter XLVII	700
Chapter XLVIII	715
Chapter XLIX	730
Chapter L	745
Chapter LI	760
Chapter LII	775
Chapter LIII	790
Chapter LIV	805
Chapter LV	820
Chapter LVI	835
Chapter LVII	850
Chapter LVIII	865
Chapter LIX	880
Chapter LX	895
Chapter LXI	910
Chapter LXII	925
Chapter LXIII	940
Chapter LXIV	955
Chapter LXV	970
Chapter LXVI	985
Chapter LXVII	1000

1. There is some correlation between long-line currents and corrosion. In general, galvanic currents gradually accumulate on pipe lines through soils of high resistance, and in most cases discharge from the lines in soils of low resistance. If current density is relatively high and the discharge is abrupt, deep pitting is usually experienced.
2. There is considerable correlation between depth of pits and resistivity. This is of practical value in soil corrosivity surveys. Soil resistivities of less than 1,000 ohms are usually indicative of severe pitting. If due care is used, it may be expected that a large percentage of the corrosive soils will be located.
3. The results of this investigation leads to conclusions that agree closer to Shepard's than those of Gill and Rogers.

Discussion of Weidner and Davis Paper

American Petroleum Institute Production Bulletin No. 208, December  
1931, Pages 45-52.

Stanley Gill - Gulf Oil Companies

A detailed analysis of the data is given and the following conclusions reached:

A protection program predicated upon the resistivity classification would involve coating 26 per cent of the total length of pipe, and would result in protection of 74.7 per cent of the points on which actual corrosion was experienced. A "no coating" program would involve no expenditure for resistivity survey or protective coating, but would leave unprotected all of the corrosive spots. In practical operation many of these corrosive spots could be pre-determined by experience; undoubtedly a considerable number are located in salt water drains, stream crossings, cinder fills, and the like. Such points would obviously merit protection, even without data on soil resistivity. It is our opinion, which is supported by the data presented by Mr. Weidner and Mr. Davis, that resistivity surveys cannot be economically used as the basis for pipe line protection programs.

Charles Fitzgerald - The Pure Oil Pipe Line Company of Texas

The results of a soil survey along 88 miles of pipe line in East Texas are described. Following are some of the conclusions.



The quantitative correlation which exists between resistivity and corrosion should not be anticipated between long-line currents and corrosion. Total corrosion and pitting rate, being functions of both local action and long-line currents, are dominated by the properties of the soil as expressed by resistivity. The ratio of long-line current effect to local action varies greatly; and, therefore, the former can have no exact relation to total corrosion or pitting rate. Resistivity measurements indicate where there is a tendency to corrode under conditions of sufficient moisture. Long-line current measurements show whether corrosion is active at the time, and define the limits of the section affected. If it could be determined for a specific set of conditions, the ratio probably would remain fairly constant.

For practical usefulness of these methods in the maintenance of pipe lines, the following procedure is suggested:

1. Find the hot spots by soil resistivity.
2. Check them by current measurements.
3. Apply insulation until the current has been reduced to negligible amounts.
4. Take all electrical readings when the soil is moist.

K. H. Logan and E. R. Shepard - U. S. Bureau of Standards.

Soil characteristics vary so in different localities that what may be applicable in one territory may be found entirely impracticable in another. The correlations found by Mr. Weidner and Mr. Davis, while by no means perfect, indicate a worth-while relation between soil resistivity and pipe life in the territory covered by their tests. Their data on pipe line currents appear to have a directional value, and no doubt can be used in some locations as an auxiliary to the measurement of soil resistivity in locating corrosive areas.

A very satisfactory correlation between soil resistivity and pipe life has been reported by A. B. Allyne, Southern Counties Gas Company, Los Angeles, in the Gas Age Record, August 22, 1931. It is apparent from Mr. Allyne's data that the alkali soils of the West lend themselves particularly well to the resistivity test, and that average pipe life can be predicted with a fair degree of accuracy by this method. In other soils, such as those in which Mr. Weidner and Mr. Davis worked, the relation is somewhat less pronounced; while in some regions it may be possible that no worth-while relation exists. Other





pipe line companies are making similar tests in other territories, and it should be a matter of a comparatively short time before we can say rather definitely in what territories and in what types of soil the resistivity test is of practical value.

Most of the electrical tests which have been devised to determine the corrosive properties of soil involve soil resistivity in one way or another, and several of the methods compared by us appear to give substantially the same results; i.e., we can usually discriminate between highly corrosive and non-corrosive soil by any of these electrical tests. Until it has been demonstrated that some more precise or complicated measurement is of greater significance than those obtained with the simple apparatus now in use, we see no reason for resorting to greater expense and pains in determining soil properties.

#### 10. Distribution soil surveys by the Shepard rod method.

A. B. Allyne, Chemist, Southern Counties Gas Co., Los Angeles. Western Gas, August 1931, page 127; also Gas Age Record, August 22, 1931, page 269. - In order to get a check on the apparatus before actually starting the survey, a number of locations were picked in which the life of steel pipe was actually known from past experience. After collecting a large number of these readings, it was found that in most cases at least, there was a marked agreement between the resistivity findings and the actual life of pipe. These data were then used to establish the scale readings in terms of life of pipe.

This segregation gave the following range of readings for three ranges of pipe life.

Rod readings, Ohm-cm.	Probable life of bare steel pipe, years
0-1000	0-9
1000-2500	9-15
2500-10,000	15 or more

It has been found that a single operator can make about 25 to 30 tests per day, depending upon the mileage covered and the nature of the soil into which the auger must penetrate. At this rate it is estimated that the city of Santa Barbara can be completely surveyed in from a month to six weeks.

The cost per test has been roughly calculated to be between 25 and 30 cents. This is total cost and includes equipment, salary, transportation and technical supervision. A rapid computation will show the entire cost of the survey to be negligible in comparison with the value of the information it will make available.



The soil maps resulting from these surveys will be used as atlases for future pipe protection work. In addition to this, as a second check, it is planned that all ditches in which pipe is to be laid will be tested every 50 feet prior to installation.

It is roughly estimated that the survey of our entire system can be completed in somewhat less than two years. So many factors influence this time period that no more definite a figure can be estimated until the work has further progressed.

At this writing it may be said, in conclusion, that the Shepard rod method appears to be a simple and rapid medium for obtaining the desired approximation in pipe line protection work. Future developments and the completed maps themselves are awaited with no little interest.

11. Experiments with the conductivity method of measuring soil corrosivity. Chas. F. Turner, The East Ohio Gas Company. American Gas Association Distribution Conference, Birmingham, April 6, 1932. - Conclusions. 1. The conductivity method of forecasting the degree of corrosive action of our acid soils on steel pipe has shown a number of inconsistencies sufficient to indicate that it is by no means infallible. But on the other hand many many cases have been found where low resistances are coincident with bad corrosion and pitting in the space of a comparatively few years, even months. The preponderance of these cases lends encouragement to the work.

2. Moisture is one variable which in our opinion must be considered in interpreting from resistivity readings the probable life expectancy of pipe. We cannot at this time agree that measurements made at saturation furnish the proper criterion by which to fix the degree of corrosivity; an array of evidence to the contrary must be considered.

Readings taken in a ditch following a rain are no more consistent than when taken in the same ditch which appears dry, but they are often of an entirely different order of degree - which are we to take as the right ones?

3. Experience to date indicates that where resistivities up to 200 ohm-cm are encountered the pipe will last about 2 yrs. before a puncture may be expected. The survey on the 16-inch line and numerous other tests made in the City lead to observation that whenever a soil shows a resistivity of about 1200 ohm-cm the pipe has an age very close to 15 years and there are apt to be numerous pits more than two-thirds through the pipe.

of the  
in  
for

of the survey will be  
in which I  
the following  
I have

of the survey  
of the survey  
of the survey  
of the survey

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

of the survey will be  
in which I  
the following  
I have

4. Summarizing all the work that we have done with the conductivity method of determining the corrosiveness of the acid soils with which we are dealing, we are convinced that while there are many things in the results obtained which remain unexplained we have found it very useful in helping to determine pipe failures. We also believe that a survey over a proposed right-of-way for a pipe line is well worth the time and money spent in making it, and we propose to carry out such a plan whenever we have occasion to renew or relocate sections of our transmission system.

12. Methods for estimating the corrosiveness of acid soils toward iron and steel. I. A. Denison, Bureau of Standards. The Oil and Gas Journal, June 16, 1932. - Although acid soils are widely distributed, occupying the greater part of the United States east of the Great Plains, the great differences in the corrosiveness of these soils toward ferrous metals have not been explained, nor are satisfactory methods available for estimating their corrosiveness. Recently, therefore, a special study has been made of the results of tests in these soils, in the hope of finding some means of predicting the corrosion which will occur and thus determining when it is worth the cost to cover pipe lines with some protective coating.

Since the useful life of iron and steel pipe underground is determined by the rate of development of pits rather than by a general loss of metal from the pipe's surface, it is especially important that methods be available which will indicate the tendency of acid soils to induce pitting. Consequently, in this recent work the average rate of pitting of ferrous specimens removed from test locations of the Bureau of Standards after eight years' burial was compared with the total acidity of samples of soil collected at the test sites.

The total acidity values of the samples of soil were determined from titration curves prepared by plotting the pH values of a soil suspension, to which increasing quantities of alkali were added, against quantity of base and noting the point of inflection in the curve. Since this method could not be applied successfully to organic soils because of the strong tendency of organic matter to adsorb alkali directly, an indirect method was employed in estimating the acidity of such soils.

The results of the comparison show that in the types of soil considered, the rate of pitting increases with acidity of the soil, the relation being roughly linear. This relation does not apply to sandy soils, which are less corrosive than their

... ..  
... ..  
... ..  
... ..  
... ..

11.  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..  
... ..

values for acidity would indicate. It is probable that a more satisfactory relation between pitting and acidity might be obtained for the soils of a limited area, in which certain characteristics of soils affecting corrosiveness other than acidity are subject to less variation than in the large area represented by this study.

Since for practical purposes, as in the location of corrosive areas for the protection of pipe lines, it is only necessary to divide soils into several groups on the basis of their corrosiveness, it would seem that acidity methods might prove of value in distinguishing areas differing in corrosiveness. However, in employing these methods it is important that they be applied only to soils in which acidity is likely to be an important factor in corrosion. They are applicable generally to soils occurring in regions having an annual rainfall above 30 inches. The eastern parts of Nebraska, Kansas, Oklahoma and Texas may be considered to mark the western limit of the occurrence of acid soils.

THE EXHIBITS  
OF THE  
CASE OF  
THE  
STATE OF  
NEW YORK  
IN  
SUPPORT OF  
THE  
PROSECUTION  
IN  
THE  
CASE OF  
THE  
STATE OF  
NEW YORK  
VS.  
THE  
DEFENDANT

EXHIBIT  
NO. 1  
PAGE 1

THE EXHIBITS  
OF THE  
CASE OF  
THE  
STATE OF  
NEW YORK  
IN  
SUPPORT OF  
THE  
PROSECUTION  
IN  
THE  
CASE OF  
THE  
STATE OF  
NEW YORK  
VS.  
THE  
DEFENDANT





