

MAR 13 1923

LIBRARY

DEPARTMENT OF COMMERCE.

BUREAU OF STANDARDS.

CIRCULAR OF THE BUREAU OF STANDARDS.

No. 13.

[10th edition. Issued February 7, 1923.]

UNITED STATES GOVERNMENT SPECIFICATIONS FOR
LARGE TUNGSTEN FILAMENT INCANDESCENT
ELECTRIC LAMPS.

FEDERAL SPECIFICATIONS BOARD.

STANDARD SPECIFICATION NO. 23.

This Specification was officially adopted by the Federal Specifications Board on February 15, 1922, for the use of the Departments and Independent Establishments of the Government in the purchase of incandescent electric lamps. Revision approved February 6, 1923.

CONTENTS.

	Page.
Introductory statement.....	2
I. General specifications.....	5
1. General conditions.....	5
2. Definitions and standards.....	6
(a) Electrical units.....	6
(b) Unit of light intensity.....	6
(c) Photometric measure.....	6
(d) Large lamps.....	6
(e) Type.....	6
(f) Size of lamp.....	7
(g) Shape and size of bulb.....	7
(h) Base.....	7
(i) Rated volts or rated amperes.....	7
(j) Regular lamps.....	7
3. Return of rejected lamps.....	7
4. Cancellation of contract.....	7
II. Test specifications.....	7
1. Mechanical and physical inspection test.....	7
(a) Selection of lamps for mechanical and physical inspection test.....	7
(b) Test quantity.....	8
(c) Bulbs.....	8
(d) Bases.....	8
(e) Filaments.....	8

Reference book not to be
from the library.

II. Test specifications—Continued.	
1. Mechanical and physical inspection test—Continued.	Page.
(f) Leading-in wires	8
(g) General	8
(h) Marking	8
(i) Rejection for mechanical and physical defects	8
(j) Rejection for major defects	9
2. Initial rating test	9
(a) Selection of lamps for initial rating test	9
(b) Test quantity	9
(c) Rejection for defective rating	10
(d) Changes in efficiency	10
3. Life performance test	10
(a) Selection and test quantity of lamps for life performance test	10
(b) Life-test voltages	11
(c) Voltage regulation	11
(d) Lamp life	11
(e) Inherent quality criterion	11
(f) Life corrections	11
(g) Guaranteed inherent quality	11
(h) Method of computation	12
(i) Rejection for failure to meet guaranteed inherent quality	12
(j) Measurement of lumens	12
(k) Determination of lumen maintenance	12
(l) Guaranteed lumen maintenance	13
(m) Rejection for failure to meet guaranteed lumen maintenance	13
(n) Guaranteed life	14
(o) Method of computation	14
(p) Rejection for deficient life	14
III. Tables of tolerances and comparison data	15
IV. Manufacturers' schedules of commercial ratings	16

INTRODUCTORY STATEMENT.

An informal conference called by the engineers of the various Government departments, and attended by them, by representatives of the manufacturers of incandescent lamps in the United States, and by representatives of the Bureau of Standards and the Electrical Testing Laboratories, was held in Washington, February 25 to 27, 1907, at which specifications for electric incandescent lamps, then including only the carbon class, were adopted. These specifications were revised at further conferences held in 1908, 1909, and 1910. In the revision made in 1909, schedules for metallized carbon, tantalum, and tungsten lamps were added. In 1910 carbon lamps were placed on the same basis as the other classes, namely, a rating in watts instead of in candlepower.

No general conference of the lamp manufacturers and Government engineers has been held since 1910, but the general specifications and schedules were thoroughly revised in April, 1912, after informal conferences between representatives of the Bureau

of Standards and of the various departments of the Government, and after consultation with representatives of various lamp manufacturers.

Five further revisions have been made by the bureau after consulting with representative manufacturers. These revisions were made in 1913, 1915, 1917, 1921, and the latest, for the present (tenth) edition, in 1922. This edition marks the passing of carbon filament lamps, since no specifications for them are included, and the title of the circular has been changed accordingly. Future purchases of this class of lamps by the Federal Government are expected to be very small, and such purchases will be made under the specifications of the ninth edition.

In the ninth edition noteworthy changes were made in the test procedure specified for tungsten lamps. The most notable of these changes was the abandonment of the long-established provision that the life of test lamps should be considered as ended when the candlepower had fallen to 80 per cent of the initial value. The specification of such an end point is convenient and reasonable in the testing of carbon lamps, because those lamps will often burn for a long period after they have become so blackened that they should not be continued in use. In tungsten lamps, however, means have been found to prevent excessive blackening of the bulbs, so that the lamps normally burn out before their efficiency has fallen enough to justify replacing them. The new tests are therefore based on the total life to the time of burn out, thus conforming more nearly to actual practice in the use of lamps.

The performance of the lamp throughout its life is taken into account through two provisions. One of these is the evaluation of life-test results on the basis of average efficiency throughout life, instead of the initial efficiency; the other is a requirement that the average light flux during the life of the lamp must not fall below a specified percentage of the initial flux. In the calculation of life-test results on the basis of average efficiency the earlier part of the life of a lamp is, in effect, given much greater weight than the latter part, because the efficiency is relatively high at first and gradually decreases. While it is proper to allow some weighting of life periods in this way, the specifications were intended to provide for lamps which would give the normal 1,000 hours of actual service. In this edition, therefore, an explicit provision to this effect has been added.

One clause of the specifications which has given rise to much discussion is that which permits the manufacturer on notice to the buyer to reduce the efficiency rating of any size of lamps by as much as 4 per cent. This provision was originally adopted during the war to allow for manufacturing difficulties arising from the unsettled conditions of the time, but it has worked so well in practice that it has been retained. Lamps are essentially a variable product. Without this clause it would be necessary to set the specified efficiencies correspondingly lower, so that any reasonably good factory could be sure of meeting the requirements for all sizes of lamps at all times. Having this provision, the manufacturers are willing that the specified efficiencies shall be high enough to constitute a challenge to the skill of their engineering staffs. A factory which encounters special difficulties can take advantage of a lower efficiency rating, but in so notifying the buyer it advertises its failure to keep up with the leaders in the industry. The effect is therefore to stimulate a very active competition in improving the quality of the lamps, and, in fact, the number of cases in which manufacturers holding Government contracts have reduced their efficiency ratings is very small in comparison with those in which increases above the specified ratings have been made. In this connection it is of interest to note that with a single exception the current ratings on all sizes of lamps are appreciably higher than those in force in 1921.

This provision for adjustment of specified efficiency ratings should not be confused with the tolerances which are allowed for efficiency and wattage ratings and for the test results for small numbers of samples. These tolerances are necessary in order to allow for unavoidable variations in making individual lamps and for probable departures of test results from the true average quality of the lamps represented by the samples.

On account of the desirability of standardizing a small number of voltage ratings the lamp schedules recognize specifically only the 5-volt steps in the 110-120-volt range and 10-volt steps in the 220-250-volt range. It is understood that for the present lamps of other voltages within the usual range will be furnished under the same specifications, but users will ultimately find it advantageous to bring their circuits to one of the standard voltages.

Criticisms and suggestions concerning these specifications and lamp ratings are invited from both manufacturers and users of lamps. All such suggestions will be carefully considered when the specifications are again revised.

These specifications have been prepared, primarily, for the use of the departments of the Government in purchasing incandescent lamps, but it seems desirable, on account of the thoroughness with which the subject has been studied and discussed, that the specifications should be available to the general public. In circulating them, however, the bureau desires to call attention to the necessity of extreme caution in the application of the tests described. Only those thoroughly instructed in the art of lamp manufacture and in the science of photometry should undertake to determine upon the acceptability of lamps under the terms of these specifications.

Complete specifications for the purchase of large tungsten filament incandescent lamps consist of the following sections:

- I. General specifications.
- II. Test specifications.
- III. Tables of tolerances and comparison data.
- IV. Manufacturers' schedules of commercial ratings.

Sections I, II, and III describe in detail the tests and methods that may be employed for the determination of the inherent quality of the lamps. Section IV consists largely of dimensions and of ratings which affect the economy of operation of lamps of a given quality. The values given in Section IV of this circular are considered at the present time to represent good practice under conditions of use most commonly prevailing in the United States, and are therefore made a part of the specifications under which the United States Government purchases such lamps.

I. GENERAL SPECIFICATIONS.

1. GENERAL CONDITIONS.

Incandescent lamps to be furnished under these specifications shall be new lamps. The full provisions of these specifications shall apply only to lamps specifically mentioned in the Tables of Tolerances and Comparison Data, and to no other lamps, except by mutual written agreement. These specifications shall not apply to any frosted, bowl-enameled, etched, or colored lamps, or to lamps other than those with the usual clear glass bulbs, unless specifically included by mutual written agreement. These specifications in so far as they refer exclusively to mechanical and physical characteristics shall apply to any tungsten filament lamps regularly listed in the manufacturer's current schedules.

All tests shall be made in a competent and expert engineering manner at the expense of the purchaser, excepting that when initial tests and inspections are made at the factory the manu-

facturer will be required to supply the necessary equipment, assistance, current, and facilities for making such initial tests and inspections. The manufacturer shall have the privilege of witnessing and verifying all tests of its lamps made hereunder, and shall also have the privilege of obtaining copies of the results of the tests of its lamps and of having access to the records of such tests at all reasonable times. Prompt notice of the result of lamp tests will be given the manufacturer. With the consent of the manufacturer, the method of test procedure may be modified in any particular whenever such modification is desirable to secure test results in a more practicable, representative, and accurate manner.

2. DEFINITIONS AND STANDARDS.

(a) ELECTRICAL UNITS.—The values of the electrical units in these specifications are the international units which have been in force since January 1, 1911.

(b) UNIT OF LIGHT INTENSITY.—The unit of light intensity shall be the international candle as maintained by the Bureau of Standards at Washington, D. C.

(c) PHOTOMETRIC MEASURE.—The basis of photometric measure for all lamps shall be total flux expressed in lumens, but, if desired, the equivalent luminous intensity expressed in spherical candles may be used. In the case of vacuum lamps the initial lumens or spherical candles may be calculated from measured values of the mean horizontal candlepower by the use of initial spherical reduction factors given in the Manufacturers' Schedules of Commercial Ratings, in which case allowance shall be made for such changes as may occur in spherical reduction factors during life performance test of all lamps. For lamps having filaments giving an initial ratio of mean spherical to mean horizontal candlepower different from the values given in the tables the horizontal candlepower measurements shall be corrected by an initial spherical reduction factor determined by the Bureau of Standards or other authority mutually agreed upon, and the life performance values shall be equivalent to those given in the tables.

(d) LARGE LAMPS.—Lamps are classified under two styles—large and miniature. "Large lamps" designates broadly lamps regularly fitted with other than miniature bases. All lamps covered by these specifications are large lamps.

(e) TYPE.—The word "type" is used to distinguish between lamps which differ in general construction or are designed for different classes of service.

(f) **SIZE OF LAMP.**—The size of incandescent lamps is expressed in rated watts or rated lumens.

(g) **SHAPE AND SIZE OF BULB.**—The shape of a bulb is designated by a letter: S indicates it is straight side; G indicates round (globular); PS indicates pear shape; T indicates tubular. The size of bulb is expressed by a number defining the greatest diameter in eighths of an inch (S-17, straight side bulb, $\frac{17}{8}$ or $2\frac{1}{8}$ inches greatest diameter; G-18½, round bulb, 18½ eighths or $2\frac{5}{8}$ inches in diameter).

(h) **BASE.**—There are five varieties of bases—miniature screw, candelabra screw, bayonet, medium screw, and mogul screw. Medium and mogul screw bases only are used on lamps covered by these specifications.

(i) **RATED VOLTS OR RATED AMPERES.**—The rated volts or rated amperes of a lamp are the volts or amperes for which the lamp is designed as indicated on the label.

(j) **REGULAR LAMPS.**—Regular lamps are lamps whose construction conforms to that regarded as standard and are so listed by the manufacturer. Only large regular lamps are covered by these specifications.

3. RETURN OF REJECTED LAMPS.

Lamps which have not been used and are rejected under the terms of these specifications may be returned to the manufacturer at his expense and no payment made therefor. All lamps placed in service shall be considered as accepted.

4. CANCELLATION OF CONTRACT.

A contract for lamps furnished under these specifications may be canceled in the event that the total quantity of lamps represented on life performance tests exceeds in value 25 per cent of the face value of the contract and is represented on life performance test by at least 50 lamps and is rejectable as an aggregate quantity under Life Performance Test, paragraphs (i), (m), or (p), or in the event that the total quantity of lamps is represented by not less than 200 lamps completed on the life performance test and is rejectable as an aggregate quantity under these specifications.

II. TEST SPECIFICATIONS.

1. MECHANICAL AND PHYSICAL INSPECTION TEST.

(a) **SELECTION OF LAMPS FOR MECHANICAL AND PHYSICAL INSPECTION TEST.**—From the packages of lamps of any one size, type, and voltage offered for acceptance the inspector may choose

as a lot to be inspected any individual package or any group of packages. From each lot of lamps to be inspected there shall be selected at random the test quantity for the purpose of determining the mechanical and physical characteristics of the lamps. The manufacturer may present lamps for mechanical and physical inspection test which have not been sufficiently burned or seasoned to have reached stable values of wattage and lumens.

(b) TEST QUANTITY.—The test quantity shall consist of not less than 5 per cent of each lot of lamps being inspected, and in no case shall be less than 10 lamps. The lamps so selected shall be known as the inspection-test lamps. In case the lot to be inspected comprises more than one package, the inspection-test lamps shall be selected proportionately from the several packages.

(c) BULBS.—Bulbs shall be uniform in size and shape, clear, clean, and free from flaws and blemishes detrimental to service.

(d) BASES.—Moisture-proof medium or mogul screw bases, fitted with glass insulation, shall be used on all lamps unless otherwise specified, and when bases have extended skirts the latter shall be insulated from the screw shell. The bases shall be firmly and accurately fitted to the bulbs with moisture-proof cement. The shells and skirts of the bases shall be of brass of good quality.

(e) FILAMENTS.—The filaments shall be uniform and free from imperfections, spots, and discolorations detrimental to service.

(f) LEADING-IN WIRES.—Leading-in wires shall be securely attached to the ends of the filaments and shall be securely attached, without excess of solder, to the terminals of the base which make contact with the socket. The threads of the base shall be free from solder.

(g) GENERAL.—The lamps shall be well made and free from defects and imperfections which would prevent their meeting satisfactorily the lighting service conditions. All lamps shall conform to the manufacturer's standard shapes and sizes of bulbs and forms of filament.

(h) MARKING.—One or more labels showing the rating and the manufacturer's name or trade-mark shall be placed on the bulb or the base of each lamp. The labels on the lamps shall show the rated watts and volts (or voltage of the circuit upon which a stated number of lamps are to burn in series), or the rated lumens and amperes.

(i) REJECTION FOR MECHANICAL AND PHYSICAL DEFECTS.—The inspection-test lamps shall be inspected for physical defects, and when so inspected, if 20 per cent or more of the test lamps show

physical defects incompatible with good workmanship, good service, or with any clause of these specifications, the particular lot which has thus been inspected and from which the test quantity was selected, may be rejected without further test, provided that the inspection test is made at the factory. If the inspection test is made elsewhere than at the factory, the percentage of defective lamps required for rejection shall be 30 per cent.

(j) REJECTION FOR MAJOR DEFECTS.—Also, when so inspected, if the number of the inspection-test lamps that are inoperative, or that would unquestionably give poor service (such defects to be mutually agreed upon), exceeds the quantity indicated in the table below for the number of lamps inspected, the particular lot which has thus been inspected and from which the test quantity was selected may be rejected without further test.

Total number of test lamps inspected.	Number of vitally defective lamps required for rejection (see 1 (j) above).	
	When inspection test is made at the factory.	When inspection test is made elsewhere.
Above 400.....	More than 3 per cent of number inspected...	More than 5 per cent of number inspected.
400-301.....	More than 10 lamps.....	More than 20 lamps.
300-201.....	More than 7 lamps.....	More than 14 lamps.
200-101.....	More than 5 lamps.....	More than 10 lamps.
100-51.....	More than 3 lamps.....	More than 6 lamps.
50 and less.....	More than 2 lamps.....	More than 4 lamps.

2. INITIAL RATING TEST.

(a) SELECTION OF LAMPS FOR INITIAL RATING TEST.—From the packages of lamps of any one type, size, and voltage offered for acceptance at any one time the inspector may choose as a lot to be inspected any individual package or any group of packages. From each lot of lamps to be inspected there shall be selected at random the test quantity for the purpose of making the initial rating test, or the test may be made upon the same lamps that were selected for the mechanical and physical inspection test. Lamps may be presented for initial rating test that have not been sufficiently burned or seasoned to have reached stable values of wattage and lumens, but such of these lamps as are selected for the initial rating test must be properly seasoned before the test is begun.

(b) TEST QUANTITY.—The test quantity shall consist of not less than 5 per cent of each lot of lamps being inspected, and in no case shall be less than 10 lamps. The lamps so selected shall be known as the rating-test lamps. In case the lot to be inspected

comprises more than one package the rating-test lamps shall be selected proportionately from the several packages.

(c) REJECTION FOR DEFECTIVE RATING.—Lamps shall be tested at rated volts, amperes, or lumens. When tested at the factory, the particular lot which has thus been inspected may be rejected without further test if 20 per cent or more of the rating-test lamps therefrom selected depart from the manufacturer's standard initial rating in effect at the time of manufacture of the lamps by more than the initial rating tolerances given in the tables of tolerances. The initial rating thus used shall not be more than 4 per cent lower than the standard initial rating in effect at the time of inspection. When tested elsewhere than at the factory, the percentage required for rejection shall be 30 per cent.

(d) CHANGES IN EFFICIENCY.—For the purpose of maintaining the rated life given in the Manufacturers' Schedules of Commercial Ratings the initial rated lumens per watt (and therewith, proportionately, the mean lumens per watt) of any size of lamps may, upon notice from the manufacturer, be changed, but not numerically decreased by more than 4 per cent. The initial rating tolerance specified shall apply to the lamps at the changed rated lumens per watt.

3. LIFE PERFORMANCE TEST.

(a) SELECTION AND TEST QUANTITY OF LAMPS FOR LIFE PERFORMANCE TEST.—For the purpose of selecting lamps for the life performance test, packages containing less than 100 lamps of any one type, size, and voltage may be grouped to aggregate not more than 250 lamps, and for the purposes of this test these groups will be called package groups. In case the lot of lamps of any one size, type, and voltage offered for acceptance consists of 1,000 lamps or less, there shall be selected from the rating-test lamps representing each package of 100 lamps or more, or representing each package group, the one lamp which approximates most closely to the average of these rating-test lamps. The lamps thus selected will be designated as the life-test lamps. If the lot of lamps exceeds 1,000 lamps, life-test lamps will be selected from the first 1,000 lamps as above directed, and for each 500 (or part thereof) by which the lot exceeds 1,000 an additional life-test lamp shall be similarly selected from the rating-test lamps representing any one of the additional packages. Not more than one life-test lamp shall be selected from any package or package

group, except that a second or duplicate lamp may be reserved to replace this life-test lamp in case of accidental breakage or damage during test.

(b) LIFE-TEST VOLTAGES.—Life-test lamps shall be operated on the test rack at voltages (or currents) corresponding either to the initial rated lumens per watt as given in the Manufacturers' Schedules of Commercial Ratings, or the suggested initial test lumens per watt as given in the Tables of Tolerances and Comparison Data, or any special efficiency mutually agreed upon. Operation at approximately the voltages indicated is sanctioned, provided proper life corrections are made.

(c) VOLTAGE REGULATION.—Accurate recording voltmeter records shall be obtained during the test to show the variation of the voltage on the circuit. Variations of voltage are not to exceed one-quarter of 1 per cent above and below the test voltage.

(d) LAMP LIFE.—The life of a lamp is the number of hours life of the lamp to burn out. Lamps broken in handling or when current is not on them shall not be counted to reduce the average lamp life. In case any life-test lamps (and their duplicates) are broken or damaged before the test is completed, the average life of all lamps of the same type, size, and voltage tested under the same contract shall be assigned to the package or group of packages represented by such broken or damaged life-test lamps. Any lamp which shows a relatively sudden and marked decline in light output shall be considered to have terminated its life when its light output passes below 60 per cent of its initial light output.

(e) INHERENT QUALITY CRITERION.—The accepted measure of inherent quality of incandescent lamps is the average hours life to burn out, as determined in accordance with these specifications at any stipulated mean lumens per watt throughout life. For purposes of comparison of different lots of lamps, and for a permanent historical basis of record, standard comparison mean lumens per watt are given in the tables of comparison data. These standard comparison efficiencies were originally (in 1920) based on an average life on test of 500 hours.

(f) LIFE CORRECTIONS.—All life corrections from one efficiency to another are to be made in accordance with life-efficiency relations mutually agreed upon or as determined by the Bureau of Standards at Washington, D. C.

(g) GUARANTEED INHERENT QUALITY.—The lamps furnished under these specifications are guaranteed to give an average total

life to burn out, as determined in accordance with these specifications, not less than the rated total life specified in the Manufacturers' Schedules of Commercial Ratings (as modified by the life tolerances given in paragraph (i) of article 3, Life Performance Test) at the mean lumens per watt specified in the Manufacturers' Schedules of Commercial Ratings (or as may be modified by article 2, Initial Rating Test, paragraph (d), Changes in Efficiency). The conformity of a group of lamps with the inherent quality guarantee is determined by correcting the average life of the group from the mean efficiency at which the lamps operate during the life-performance test to the mean efficiency upon which the guaranteed life is based.

(h) METHOD OF COMPUTATION.—The individual lamps shall be tested at voltages (or currents) corresponding to equal initial efficiencies and the average number of hours life to burn out determined for the group of lamps. The mean efficiency throughout life of any group of lamps shall be determined as the quotient of the total lumen hours and watt hours of the group when so tested. The average life obtained on test shall be corrected from the computed mean efficiency throughout life to the mean lumens per watt specified in the Manufacturers' Schedules of Commercial Ratings. Obtaining the mean efficiency as the quotient outlined in the preceding paragraph is identical with a determination of it as the average of the mean efficiencies throughout life of the individual lamps, the mean efficiency of each lamp being weighted in proportion to the life of the lamp:

(i) REJECTION FOR FAILURE TO MEET GUARANTEED INHERENT QUALITY.—Any group of lamps, provided such group is represented by at least five lamps on life-performance test, may be rejected if the average hours life of the group, when corrected to the mean lumens per watt throughout life specified in the Manufacturers' Schedules of Commercial Ratings (or as may be modified by article 2, Initial Rating Test, paragraph (d), Changes in Efficiency), falls below the guaranteed life by more than the life tolerance specified (see p. 13) for the number of test lamps averaged.

(j) MEASUREMENT OF LUMENS.—Life-test lamps shall be measured for lumens and amperes (or volts) at their labeled volts (or amperes) at reasonable intervals during the test. Unless otherwise mutually agreed, these intervals of measurement shall be as specified in the following paragraph:

(k) DETERMINATION OF LUMEN MAINTENANCE.—The measure of lumen maintenance for an individual lamp shall be its mean

lumens throughout the test, expressed as a percentage of its initial lumens. The measure of lumen maintenance for a group of lamps shall be the mean lumens in per cent of average initial lumens and shall be determined by averaging the above percentages for the individual lamps, the percentage for each individual lamp being weighted in proportion to the life of the lamp. A simple and practical method of determining the desired mean lumens in per cent of average initial lumens for a group of lamps is to average, with equal weight, all readings on individual lamps representing (i. e., taken at the mid-points of) successive equal test intervals. A sufficient degree of accuracy will be obtained if readings are taken on the surviving individual lamps at times corresponding to 20, 60, and 100 per cent of the anticipated average test life and thereafter at succeeding intervals equal to 40 per cent of the anticipated average test life.

Life Tolerances.¹

Number of lamps averaged.	Allowable per cent variation from guaranteed life.	Number of lamps averaged.	Allowable per cent variation from guaranteed life.	Number of lamps averaged.	Allowable per cent variation from guaranteed life.
250 and above.....	5	24-20.....	12	9.....	19
249-100.....	6	19-18.....	13	8.....	20
99-55.....	7	17-16.....	14	7.....	21
54-45.....	8	15-14.....	15	6.....	23
44-35.....	9	13-12.....	16	5.....	25
34-30.....	10	11.....	17		
29-25.....	11	10.....	18		

¹ On account of the natural and inherent variations in individual lamp performance, the average test results of a small number of test samples can not be depended upon to indicate exactly the average for the larger quantity from which the test samples were selected. The tables of allowable variations are devised in accordance with the observed accuracy of lamp-testing methods and the observed variations in lamp performance.

(l) GUARANTEED LUMEN MAINTENANCE.—The guaranteed lumen maintenance of a group of lamps is expressed by the mean lumens in per cent of average initial lumens specified in the Manufacturers' Schedules of Commercial Ratings, except as modified by paragraph (m).

(m) REJECTION FOR FAILURE TO MEET GUARANTEED LUMEN MAINTENANCE.—When tested in accordance with the foregoing test specifications, any group of lamps may be rejected, provided such group is represented on life performance test by at least five lamps, and provided the mean lumens in per cent of average initial lumens, as above derived, falls below the per cent specified in the Manufacturers' Schedules of Commercial Ratings by more than the tolerance specified below for the number of lamps tested.

Lumen Maintenance Tolerances.¹

Number of lamps tested.	Allowable variation in per cent mean lumens of average initial lumens.	Number of lamps tested.	Allowable variation in per cent mean lumens of average initial lumens.
100 and above.....	1	24-10.....	3
99-25.....	2	9-5.....	4

¹ On account of the natural and inherent variations in individual lamp performance, the average test results of a small number of test samples can not be depended upon to indicate exactly the average for the larger quantity from which the test samples were selected. The tables of allowable variations are devised in accordance with the observed accuracy of lamp-testing methods and the observed variations in lamp performance.

(*n*) GUARANTEED LIFE.—In addition to conforming with the quality guaranties above stated, the lamps furnished under these specifications are further guaranteed to give an average total life not less than the total life specified in the Manufacturers' Schedules of Commercial Ratings (as modified by the life tolerances given in paragraph (*i*) of article 3, Life Performance Test), when tested at, or corrected to, the initial rated lumens per watt specified in the Manufacturers' Schedules of Commercial Ratings (or as may be modified by article 2, Initial Rating Test, paragraph (*d*), Changes in Efficiency).

(*o*) METHOD OF COMPUTATION.—The individual lamps shall be tested at voltages (or currents) corresponding to equal initial efficiencies and the average number of hours life to burn out determined for the group of lamps. The average life obtained on test shall be corrected from the initial test efficiency to the rated initial lumens per watt specified in the Manufacturers' Schedules of Commercial Ratings.

(*p*) REJECTION FOR DEFICIENT LIFE.—Any group of lamps, provided such group is represented by at least five lamps on life performance test, may be rejected if the average life of the group, when corrected to the rated initial lumens per watt specified in the Manufacturers' Schedules of Commercial Ratings (or as it may be modified by article 2, Initial Rating Test, paragraph (*d*), Changes in Efficiency) falls below the guaranteed life by more than the life tolerance specified in paragraph (*i*) above for the number of test lamps averaged.

III. TABLES OF TOLERANCES AND COMPARISON DATA.

Vacuum Tungsten Filament Lamps for General Lighting Service on 110, 115, and 120 Volt Multiple Circuits.

Lamp.		Initial rating tolerances at rated voltage.		Suggested comparison data.	
Watts.	Bulb.	Lumens per watt above or below standard.	Total watts above or below standard.	Initial lumens per watt for life test.	Standard comparison mean lumens per watt.
		Per cent.	Per cent.		
10.....	S-17.....	8	10	8.9	8.3
15.....	S-17.....	6	8	9.3	8.8
25.....	S-17.....	6	8	10.3	9.3
40.....	S-19.....	6	8	11.1	9.9
50.....	S-19.....	6	8	11.3	9.8
60.....	S-21.....	6	8	11.6	9.8

Gas-Filled Tungsten Filament Lamps for General Lighting Service on 110, 115, and 120 Volt Multiple Circuits.

75.....	PS-22.....	14	14	13.2	11.1
100.....	PS-25.....	12	14	14.4	12.1
150.....	PS-25.....	12	14	15.8	13.3
200.....	PS-30.....	12	13	17.2	14.8
300.....	PS-35.....	12	13	18.6	15.7
500.....	PS-40.....	12	12	20.0	16.9
750.....	PS-52.....	12	12	21.3	18.2
1,000.....	PS-52.....	12	12	22.6	18.7

Vacuum Tungsten Filament Lamps for Use on 220, 230, 240, and 250 Volt Multiple Circuits.

25.....	S-19.....	8	10	8.8	8.1
50.....	S-19.....	8	10	9.9	9.2
100.....	S-30.....	8	10	10.9	9.2

Gas-Filled Tungsten Filament Lamps for Constant-Current Street Lighting Circuits.

Lamp.			Initial rating tolerances at rated amperes.		Suggested comparison data.	
Amperes.	Lumens.	Bulb.	Lumens above or below standard.	Total watts above or below standard.	Test amperes for life test. ¹	Standard comparison mean lumens per watt.
			Per cent.	Per cent.		
6.6.....	600	S-24½.....	15	13	6.864	14.0
6.6.....	800	S-24½.....	14	12	6.864	15.2
6.6.....	1,000	S-24½.....	14	11	6.864	16.1
6.6.....	2,500	PS-35.....	14	10	6.864	18.5
6.6.....	4,000	PS-35.....	14	10	6.864	18.5
6.6.....	6,000	PS-40.....	14	10	6.864	18.5
15.0.....	4,000	PS-40.....	16	12	15.600	20.5
20.0.....	6,000	PS-40.....	16	12	20.800	21.5
20.0.....	10,000	PS-40.....	16	12	20.800	22.2

¹ When the lamps comprising a life test are tested at the same current, the life-test results shall first be corrected to a uniform initial efficiency before making any further computations.

IV. MANUFACTURERS' SCHEDULES OF COMMERCIAL RATINGS.¹

SCHEDULE 1.—Tungsten Filament Lamps for 110, 115, and 120 Volt Multiple Service.

VACUUM LAMPS.

Watts.	Rated initial lumens.	Mean lumens per cent of average initial lumens.	Rated initial lumens per watt.	Mean lumens per watt, per cent of initial.	Hours life.	Spherical reduction factor.	Bulb.	Screw base.	Maximum overall length.	Light center length.	Position of burning.
10.....	82	92	8.2	96	1,000	0.77	S-17	Medium	5 ¹ / ₁₆	Inches.	Any.
15.....	130	92	8.7	95	1,000	.78	S-17	do	5 ¹ / ₁₆	Do.
25.....	240	87	9.6	91	1,000	.78	S-17	do	5 ¹ / ₁₆	Do.
40.....	404	85	10.1	89	1,000	.78	S-19	do	5 ¹ / ₁₆	Do.
50.....	510	82	10.2	87	1,000	.78	S-19	do	5 ¹ / ₁₆	Do.
60.....	618	81	10.3	85	1,000	.79	S-21	do	5 ¹ / ₁₆	Do.

GAS-FILLED LAMPS.

75.....	885	91	11.8	91	1,000	PS-22	Medium	6 ¹ / ₁₆	4 ¹ / ₁₆	Any.
100.....	1,310	91	13.1	91	1,000	PS-25	do	7 ¹ / ₁₆	5 ¹ / ₁₆	Do.
150.....	2,145	90	14.3	90	1,000	PS-25	do	7 ¹ / ₁₆	5 ¹ / ₁₆	Do.
200.....	3,060	90	15.3	91	1,000	PS-30	do	8 ¹ / ₁₆	6	Do.
300.....	4,950	90	16.5	91	1,000	PS-35	Mogul	9 ¹ / ₁₆	7	Tip down.
500.....	9,050	90	18.1	90	1,000	PS-40	do	10 ¹ / ₁₆	7	Do.
750.....	14,325	85	19.1	85	1,000	PS-52	do	13 ¹ / ₁₆	9 ¹ / ₂	Do.
1,000....	19,700	85	19.7	85	1,000	PS-52	do	13 ¹ / ₁₆	9 ¹ / ₂	Do.

SCHEDULE 2.—Vacuum Tungsten Filament Lamps for 220, 230, 240, and 250 Volt Multiple Service.

25.....	195	93	7.8	96	1,000	0.79	S-19	Medium	5 ⁸ / ₁₆	Any.
50.....	455	86	9.1	90	1,000	.79	S-19	do	5 ¹ / ₁₆	Do.
100.....	1,030	82	10.3	85	1,000	.79	S-30	do	8	Do.

SCHEDULE 3.—Gas-Filled Tungsten Filament Lamps for Constant-Current Street Lighting Circuits.

6.6 AMPERES.

Rated initial lumens.	Mean lumens per cent of average initial lumens.	Rated initial lumens per watt.	Mean lumens per watt, per cent of initial.	Hours life.	Average volts.	Average watts.	Bulb.	Screw base.	Maximum overall length.	Light center length.	Position of burning.
600.....	100	13.4	100	1,350	6.8	44.8	S-24 ¹ / ₂	Mogul	Inches.	Inches.	Any.
800.....	100	14.5	100	1,350	8.4	55.2	S-24 ¹ / ₂	do	7 ¹ / ₁₆	5 ³ / ₁₆	Do.
1,000....	100	15.2	100	1,350	10.0	65.8	S-24 ¹ / ₂	do	7 ¹ / ₁₆	5 ³ / ₁₆	Do.
2,500....	100	16.4	100	1,350	23.0	152.0	PS-35	do	9 ¹ / ₁₆	7	Do.
4,000....	100	16.4	100	1,350	37.0	244.0	PS-35	do	9 ¹ / ₁₆	7	Do.
6,000....	100	16.6	100	1,350	54.7	361.0	PS-40	do	10 ¹ / ₁₆	7	Do.

15 AMPERES.

4,000....	100	18.0	100	1,350	14.8	222.0	PS-40	Mogul	12 ¹ / ₁₆	a 9 ¹ / ₂	Tip down.
-----------	-----	------	-----	-------	------	-------	-------	-------	---------------------------------	---------------------------------	-----------

20 AMPERES.

6,000....	96	19.3	95	1,350	15.5	311.0	PS-40	Mogul	12 ¹ / ₁₆	a 9 ¹ / ₂	Tip down.
10,000...	92	19.3	92	1,350	25.9	518.0	PS-40	do	12 ¹ / ₁₆	a 9 ¹ / ₂	Do.

^a This lamp, if made for tip-up burning, has a light center length of 8¹/₁₆ inches.

¹ These ratings apply to the United States Government contract for the fiscal year 1923-24, except as they may be modified in accordance with article 2, Initial Rating Test, paragraph (d) Changes in Efficiency, of Section II. Revised ratings are published by the manufacturers from time to time, and in making contracts it is generally advisable to use the current schedules.