NISTIR 8167-10

NIST Time and Frequency Bulletin

Kathryn Stephenson, Editor

This publication is available free of charge from: https://doi.org/10.6028/NIST.IR.8167-10



NISTIR 8167-10

NIST Time and Frequency Bulletin

Kathryn Stephenson, Editor Time and Frequency Division Physical Measurement Laboratory

This publication is available free of charge from: https://doi.org/10.6028/NIST.IR.8167-10

October 2017



U.S. Department of Commerce Wilbur L. Ross, Jr., Secretary

NIST TIME AND FREQUENCY BULLETIN NIST IR 8167-10

No. 719 October 2017

| 1. | GENERAL BACKGROUND INFORMATION | 2 |
|----|--|----|
| 2. | TIME SCALE INFORMATION | 2 |
| 3. | BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS | 4 |
| 4. | NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS | 4 |
| 5. | UTC (NIST) – AT1 PARAMETERS | .5 |
| | | |

This bulletin is published monthly. Address correspondence to:

Kathryn Stephenson, Editor Time and Frequency Division National Institute of Standards and Technology 325 Broadway Boulder, CO 80305 (303) 497-3295 Email: kathryn.stephenson@nist.gov



U.S. DEPARTMENT OF COMMERCE, Wilbur L. Ross, Jr., Secretary NATIONAL INSTITUTE OF STANDARDS AND TECHNOLOGY, Walter Copan, NIST Director and Under Secretary of Commerce for Standards and Technology

1. GENERAL BACKGROUND INFORMATION

ACRONYMS AND ABBREVIATIONS USED IN THIS BULLETIN

- minute

min

ACTS - Automated Computer Time Service

BIPM - Bureau International des Poids et Mesures

GPS - Global Positioning System

IERS - International Earth Rotation Service

MC - Master Clock

MJD - Modified Julian Date

NIST - National Institute of Standards and Technology - nanosecond ns SI - International System of Units - microsecond μs - Atomic Time - millisecond TΑ ms - International Atomic Time TAI - second S

USNO - United States Naval Observatory
UT1 - Universal Time (Astronomical)
UTC - Coordinated Universal Time

2. TIME SCALE INFORMATION

The values listed below are based on data from the IERS, the USNO, and NIST. The UTC(USNO,MC) - UTC(NIST) values are averaged measurements from all available common-view GPS satellites (see bibliography on page 5). UTC - UTC(NIST) data are on page 3.

| 0000 HOURS COORDINATED UNIVERSAL TIME | | | | | | |
|---------------------------------------|-------|--------------------------|--------------------------------------|--|--|--|
| Sept 2017 | MJD | UT1-UTC(NIST) (±5 ms) | UTC(USNO,MC) - UTC(NIST) (±20 ns) | | | |
| 7 | 58003 | 334 ms | -4 ns | | | |
| 14 | 58010 | 328 ms | -3.5 ns | | | |
| 21 | 58017 | 322 ms | -3.7 ns | | | |
| 28 | 58024 | 316 ms | -6.4 ns | | | |
| | | | | | | |

The master clock pulses used by the WWV, WWVH, and WWVB time-code transmissions are referenced to the UTC (NIST) time scale. Occasionally, 1 s is added to the UTC time scale. This second is called a leap second. Its purpose is to keep the UTC time scale within ± 0.9 s of the UT1 astronomical time scale, which changes slightly due to variations in the Earth's period of rotation.

NOTE: No leap second will be added at the end of June 2017.

Positive leap seconds, beginning at 23 h 59 min 60 s UTC and ending at 0 h 0 min 0 s UTC, were inserted in the UTC time scale on 30 June 1972, 1981-1983, 1985, 1992-1994, 1997, 2012, 2015 and on 31 December 1972-1979, 1987, 1989, 1990,1995, 1998, 2005, 2008, 2016.

The use of leap seconds ensures that UT1 - UTC will always be held within ± 0.9 s. The current value of UT1 - UTC is called the DUT1 correction. DUT1 corrections are broadcast by WWV, WWVH, WWVB, and ACTS and are printed below. These corrections may be added to the received UTC time signals in order to obtain UT1.

+0.3 s beginning 0000 UTC 29 June 2017
+0.4 s beginning 0000 UTC 30 March 2017
+0.5 s beginning 0000 UTC 26 January 2017
+0.6 s beginning 0000 UTC 01 January 2017
-0.4 s beginning 0000 UTC 17 November 2016
-0.3 s beginning 0000 UTC 01 September, 2016
-0.1 s beginning 0000 UTC 24 March 2016
+0.0 s beginning 0000 UTC 31 January 2016
+0.1 s beginning 0000 UTC 31 January 2016
+0.1 s beginning 0000 UTC 26 November 2015
+0.2 s beginning 0000 UTC 11 September 2015
+0.3 s beginning 0000 UTC 01 July 2015
-0.7 s beginning 0000 UTC 28 May 2015
-0.6 s beginning 0000 UTC 19 March 2015

The difference between UTC(NIST) and UTC has been within ± 100 ns since July 6, 1994. The table below shows values of UTC - UTC(NIST) as supplied by the BIPM in their *Circular T* publication for the most recent 310-day period in which data are available. Data are given at ten-day intervals. Five-day interval data are available in *Circular T*.

| 0000 Hours Coordinated Universal Time | | | | | | |
|---------------------------------------|-------|-------------------|--|--|--|--|
| DATE | MJD | UTC-UTC(NIST), ns | | | | |
| Sept. 23, 2017 | 58019 | 2.2 | | | | |
| Sept. 13, 2017 | 58009 | 1.7 | | | | |
| Sept. 3, 2017 | 57999 | 0.6 | | | | |
| Aug. 24, 2017 | 57989 | 1.2 | | | | |
| Aug. 14, 2017 | 57979 | 3.4 | | | | |
| Aug. 4, 2017 | 57969 | 2.7 | | | | |
| Jul. 25, 2017 | 57959 | 1.6 | | | | |
| Jul. 15, 2017 | 57949 | 0.7 | | | | |
| Jul. 5, 2017 | 57939 | 0.6 | | | | |
| Jun. 25, 2017 | 57929 | 1 | | | | |
| Jun. 15, 2017 | 57919 | 0 | | | | |
| Jun. 5, 2017 | 57909 | -1.3 | | | | |
| May 26, 2017 | 57899 | -3.8 | | | | |
| May 16, 2017 | 57889 | -4.3 | | | | |
| May 6, 2017 | 57879 | -3.8 | | | | |
| Apr. 26, 2017 | 57869 | 0.5 | | | | |
| Apr. 16, 2017 | 57859 | 6.9 | | | | |
| Apr. 6, 2017 | 57849 | 10 | | | | |
| Mar. 27, 2017 | 57839 | 5.5 | | | | |
| Mar. 17, 2017 | 37829 | -4.9 | | | | |
| Mar. 7, 2017 | 37819 | -6.6 | | | | |
| Feb. 25, 2017 | 57809 | -5.1 | | | | |
| Feb. 15, 2017 | 57799 | -2 | | | | |
| Feb. 5, 2017 | 57789 | -0.6 | | | | |
| Jan. 26, 2017 | 57779 | -0.6 | | | | |
| Jan. 16, 2017 | 57769 | -1.2 | | | | |
| Jan. 6, 2017 | 57759 | -1.4 | | | | |
| Dec. 27, 2016 | 57749 | -1.2 | | | | |
| Dec. 17, 2016 | 57739 | -2.6 | | | | |
| Dec. 7, 2016 | 57729 | -1.3 | | | | |
| Nov. 27, 2016 | 57719 | 0.9 | | | | |
| Nov. 17, 2016 | 57709 | 1.6 | | | | |
| Nov. 7, 2016 | 57699 | 1.2 | | | | |
| Oct. 28, 2016 | 57689 | 1.8 | | | | |

3. BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS

| | OUTAGES OF 5 MINUTES OR MORE | | | | | | PHASE PERTURBATIONS 2 ms | | | |
|---------|------------------------------|----------------|--------------|--------------|------------------|--------------|--------------------------|--------------|------------|--|
| Station | Sept 2017 | MJD | Began UTC | Ended UTC | Freq. | Sept 2017 | MJD | Began UTC | End UTC | |
| WWVB | 09-04-17 09-16-17 | 58000 58012 | 2140 0325 | 2218 0358 | 60 kHz 60 kHz | None | | | | |
| WWV | None | | | | | None | | | | |
| WWVH | None | | | | | None | | | | |

4. NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS

Primary frequency standards developed and operated by NIST are used to provide accuracy (rate) input to the BIPM and to provide the best possible realization of the SI second. NIST-F1 and NIST F-2, cold-atom cesium fountain frequency standards, have served as the U.S. primary standards of time and frequency since 1999. The uncertainty of NIST-F2 is currently about 1 part in 10¹⁶.

The AT1 scale is run in real-time by use of data from an ensemble of cesium standards and hydrogen masers. It is a free-running scale whose frequency is maintained as nearly constant as possible by choosing the optimum weight for each clock that contributes to the computation.

UTC(NIST) is generated as an offset from our real-time scale AT1. It is steered in frequency towards UTC by use of data published by the BIPM in its *Circular T*. Changes in the steering frequency will be made, if necessary, at 0000 UTC on the first day of the month, and occasionally at mid-month. A change in frequency is limited to no more than ± 2 ns/day. The frequency of UTC(NIST) is kept as stable as possible at other times.

UTC is generated at the BIPM by use of a post-processed time-scale algorithm and is not available in real-time. The parameters that we use to generate UTC(NIST) in real-time are therefore based on an extrapolation of UTC from the most recent available data.

References:

Allan, D.W.; Hellwig, H.; and Glaze, D.J., "An accuracy algorithm for an atomic time scale," Metrologia, Vol.11, No.3, pp. 133-138 (1975).

Allan, D.W.; Davis, D.D.; Weiss, M.A.; Clements, A.; Guinot, B.; Granveaud, M.; Dorenwendt, K.; Fischer, B.; Hetzel, P.; Aoki, S.; Fujimoto, M.; Charron, L.; and Ashby, N., "Accuracy of international time and frequency comparisons via global positioning system satellites in common-view," IEEE Transactions on Instrumentation and Measurement, Vol. IM-34, pp.118-125 (1985).

Heavner, T.P.; Jefferts, S.R.; Donley; E.A.; Shirley, J.H. and Parker, T.E., "NIST F1; recent improvements and accuracy evaluations," Metrologia, Vol. 42, pp. 411-422 (2005).

Jefferts, S.R.; Shirley, J.; Parker, T.E.; Heavner, T.P.; Meekhof, D.M.; Nelson, C., Levi, F.; Costanza, G.; De Marchi, A.; Drullinger, R.; Hollberg, L.; Lee, W.D.; and Walls, F.L., "Accuracy evaluation of NIST-F1," Metrologia, Vol. 39, pp. 321-336 (2002).

Lewandowski, W. and Thomas, C., "GPS Time transfer," Proceedings of the IEEE, Vol. 79, pp. 991-1000 (1991).

Parker, T.E.; Jefferts, S.R.; Heavner, T.P.; and Donley, E.A., "Operation of the NIST-F1 caesium fountain primary frequency standard with a maser ensemble, including the impact of frequency transfer noise," Metrologia, Vol. 42, pp. 423-430 (2005).

Weiss, M.A.; Allan, D.W., "An NBS Calibration Procedure for Providing Time and Frequency at a Remote Site by Weighting and Smoothing of GPS Common View Data," IEEE Transactions on Instrumentation and Measurement, Vol. IM-36, pp. 572-578 (1987).

5. UTC(NIST) - AT1 PARAMETERS

The table below lists parameters that are used to define UTC(NIST) with respect to our real-time scale AT1. To find the value of UTC(NIST) - AT1 at any time T (expressed as a Modified Julian Date, including a fraction if needed), the appropriate equation to use is the one for which the desired T is greater than or equal to the entry in the T_0 column and less than the entry in the last column. The values of $x_{\rm ls}$, x, and y for that month are then used in the equation below to find the desired value. The parameters x and y represent the offsets in time and frequency, respectively, between UTC(NIST) and AT1; the parameter $x_{\rm ls}$ is the number of leap seconds applied to both UTC(NIST) and UTC, as specified by the IERS. Leap seconds are not applied to AT1.

| UTC(NIST) - AT1 = $x_{ls} + x + y(T - T_0)$ | | | | | | | |
|---|---------------------|------------------|-------------|-------------------------|-------------------------------|--|--|
| Month | x _{Is} (s) | <i>x</i> (ns) | y (ns/d) | Τ ₀ (MJD) | Valid until 0000 on: (MJD) | | |
| Nov 17 | -37 | -451178.25 | -37.10* | 58058 | 58088 | | |
| Oct 17 | -37 | -450695.95 | -37.10 | 58045 | 58058* | | |
| Oct 17 | -37 | -450029.95 | -37.00 | 58027 | 58045 | | |
| Sep 17 | -37 | 449659.95 | -37.00 | 58017 | 58027 | | |
| Sep 17 | -37 | 448915.95 | -37.20 | 57997 | 58017† | | |
| Aug 17 | -37 | 448619.95 | -37.1 | 57989 | 57997 | | |
| Aug 17 | -37 | 448360.85 | -36.9 | 57982 | 57989† | | |
| Aug 17 | -37 | -448101.15 | -37.1 | 57975 | 57982† | | |
| Aug 17 | -37 | -447765.9 | -37.25 | 57966 | 57975† | | |
| Jul 17 | -37 | -447058.15 | -37.25 | 57947 | 57966 | | |
| Jul 17 | -37 | -446612.35 | -37.15 | 57935 | 57947† | | |
| Jun 17 | -37 | -446278 | -37.15 | 57926 | 57935 | | |
| Jun 17 | -37 | -445643.05 | -37.35 | 57909 | 57926† | | |
| Jun 17 | -37 | -445492.85 | -37.55 | 57905 | 57909† | | |
| May 17 | -37 | -445230 | -37.55 | 57898 | 57905 | | |
| May 17 | -37 | -444745.75 | -37.25 | 57885 | 57898† | | |
| May 17 | -37 | -444448.55 | -37.15 | 57877 | 57885† | | |
| May 17 | -37 | -444338 | -36.85 | 57874 | 57877† | | |
| Apr 17 | -37 | -444190.6 | -36.85 | 57870 | 57874 | | |
| Apr 17 | -37 | -443935.45 | -36.45 | 57863 | 57870† | | |
| Apr 17 | -37 | -443418.15 | -36.95 | 57849 | 57863† | | |
| Apr 17 | -37 | -443231.4 | -37.35 | 57844 | 57849† | | |
| Mar 17 | -37 | -443156.7 | -37.35 | 57842 | 57844 | | |
| Mar 17 | -37 | -442621.2 | -38.25 | 57828 | 57842† | | |
| Mar 17 | -37 | -442099.7 | -37.25 | 57814 | 57828† | | |
| Mar 17 | -37 | -442062.85 | -36.85 | 57813 | 57814† | | |
| Feb 17 | -37 | -441325.85 | -36.85 | 57793 | 57813 | | |
| Feb 17 | -37 | -441029.45 | -37.05 | 57785 | 57793† | | |
| Jan 17 | -37 | -439880.9 | -37.05 | 57754 | 57785 | | |
| Dec 16 | -36 | -439547.45 | -37.05 | 57745 | 57754 | | |
| Dec 16 | -36 | -439287.05 | -37.2 | 57738 | 57745† | | |
| Dec 16 | -36 | -438770.45 | -36.90 | 57724 | 57738† | | |
| Dec 16 | -36 | -438733.45 | -37.00 | 57723 | 57724† | | |
| Nov 16 | -36 | -438030.45 | -37.00 | 57704 | 57723 | | |

[†] Rate change in mid-month

^{*}Provisional value