Bureau of Standards



The program of research on building materials and structures, carried on by the National Bureau of Standards, was undertaken with the assistance of the Central Housing Committee, an informal organization of governmental agencies concerned with housing construction and finance, which is cooperating in the investigations through a subcommittee of principal technical assistants.

# CENTRAL HOUSING COMMITTEE

# SUBCOMMITTEE ON TECHNICAL RESEARCH

WALTER JUNGE, Chairman,	ARTHUR C. SHIRE, Vice Chairman,
Federal Housing Administration.	United States Housing Authority.
STEPLING B	MARCH Secretary

STERLING R. MARCH, Secretary.

ALBERT G. BEAR,	George E. Knox,
Veterans' Administration.	Yards and Docks (Navy).
PIERRE BLOUKE,	VINCENT B. PHELAN,
Federal Home Loan Bank Board.	National Bureau of Standards (Com-
CARROLL W. CHAMBERLAIN,	merce).
Procurement Division (Treasury).	Edward A. Poynton,
JOSEPH M. DALLAVALLE,	Office of Indian Affairs (Interior).
Public Health Service.	GEORGE W. TRAYER,
John Donovan,	Forest Service (Agriculture).
Farm Security Administration (Agri-	Elsmere J. Walters,
culture).	Construction Division (War).

#### Chairmen of Sections

Specifications		Mate	rials	Main	Maintenance		
CARROLL W.	CHAMBERLAIN	Elsmere J	. WALTERS	John H.	Schaefer		
	Mechanical Equipment			Methods and Practices			
	ROBERT K. THU	LMAN					

## NATIONAL BUREAU OF STANDARDS

STAFF COMMITTEE ON ADMINISTRATION AND COORDINATION

HUGH L. DRYDEN, Chairman.

Mechanics and Sound.

Phaon H. Bates,	GUSTAV E. F. LUNDELL,
Clay and Silicate Products.	Chemistry.
HOBART C. DICKINSON,	Addams S. McAllister,
Heat and Power.	Codes and Specifications.
WARREN E. EMLEY,	HENRY S. RAWDON,
Organic and Fibrous Materials.	Metallurgy.

The Forest Products Laboratory of the United States Department of Agriculture is cooperating with both committees on investigations of wood constructions.

[For list of BMS publications and how to purchase, see cover page III.]

UNITED STATES DEPARTMENT OF COMMERCE · Harry L. Hopkins, Secretary NATIONAL BUREAU OF STANDARDS · Lyman J. Briggs, Director

# BUILDING MATERIALS and STRUCTURES

# **REPORT BMS26**

Structural Properties of

"Nelson Pre-Cast Concrete Foundation" Wall Construction Sponsored by the Nelson Cement Stone Company, Inc.

by HERBERT L. WHITTEMORE, AMBROSE H. STANG, and CYRUS C. FISHBURN



ISSUED OCTOBER 9, 1939

The National Bureau of Standards is a fact-finding organization; it does not "approve" any particular material or method of construction. The technical findings in this series of reports are to be construed accordingly.

UNITED STATES GOVERNMENT PRINTING OFFICE · WASHINGTON · 1939 FOR SALE BY THE SUPERINTENDENT OF DOCUMENTS, WASHINGTON, D. C. · PRICE IO CENTS

# Foreword

This report is one of a series issued by the National Bureau of Standards on the structural properties of constructions intended for low-cost houses and apartments. Practically all of these constructions were sponsored by groups within the building industry which advocate and promote the use of such constructions and which have built and submitted representative specimens as outlined in report BMS2, Methods of Determining the Structural Properties of Low-Cost House Constructions. The sponsor is responsible for the representative character of the specimens and for the description given in each report. The Bureau is responsible for the test data.

This report covers only the load-deformation relations and strength of the foundation walls of a house when subjected to compressive, transverse, concentrated, impact, and racking loads by standardized methods simulating the loads to which the wall would be subjected in actual service.

The National Bureau of Standards does not "approve" a construction, nor does it express an opinion as to the merits of a construction for the reasons given in reports BMS1 and BMS2. The technical facts on this and other constructions provide the basic data from which architects and engineers can determine whether a construction meets desired performance requirements.

LYMAN J. BRIGGS, Director.

# Structural Properties of "Nelson Pre-Cast Concrete Foundation" Wall Construction Sponsored by the Nelson Cement Stone Company, Inc.

by HERBERT L. WHITTEMORE, AMBROSE H. STANG, and CYRUS C. FISHBURN

#### CONTENTS

	Page	Page
Foreword	11	IV. Wall BV—Continued.
I. Introduction	. 1	1. Sponsor's statement—Continued.
II. Sponsor and product	2	(2) Nine-foot wall speci-
III. Specimens and tests	2	mens 8
IV. Wall BV	2	(c) Comments &
1. Sponsor's statement	. 2	2. Compressive load
(a) Materials	2	3. Transverse load6
(b) Description	. 2	4. Concentrated load
(1) Three-foot wall speci-	-	5. Impact load
mens	. 2	6. Racking load

#### ABSTRACT

For the program on the determination of the structural properties of low-cost house constructions, the Nelson Cement Stone Co. submitted 18 specimens representing their "Nelson Pre-Cast Concrete Foundation" construction for walls.

The specimens were subjected to compressive, transverse, concentrated, impact, and racking loads. The transverse, concentrated, and impact loads were applied to both faces of the specimens. For each of these loads, three like specimens were tested. The deformation under load and the set after the load was removed were measured for uniform increments of load, except for concentrated loads, for which the set only was determined. The results are presented in graphs and in tables.

#### I. INTRODUCTION

In order to provide technical facts on the performance of constructions which might be used in low-cost houses, to discover promising constructions, and ultimately to determine the properties necessary for acceptable performance, the National Bureau of Standards has invited the building industry to cooperate in a program of research on building materials and structures for use in low-cost houses and apartments. The objectives of this program

158693°-39

are described in report BMS1, Research on Building Materials and Structures for Use in Low-Cost Housing, and that part of the program relating to the structural properties in report BMS2, Methods of Determining the Structural Properties of Low-Cost House Constructions.

As a part of the research on structural properties, six masonry wall constructions have been subjected to a series of standardized laboratory tests to provide data on the properties of some constructions for which the behavior in service is generally known. These data are given in report BMS5, Structural Properties of Six Masonry Wall Constructions. The results of similar tests made on wood-frame constructions by the Forest Products Laboratory of the United States Department of Agriculture are given in BMS25, Structural Properties of Conventional Wood-Frame Constructions for Walls, Partitions, Floors, and Roofs.

The present report describes the structural properties of a foundation wall construction sponsored by one of the manufacturers in the building industry. The specimens were subjected to compressive, transverse, concentrated, impact, and racking loads, simulating loads to which the walls of a house are subjected. In actual service, compressive loads on a foundation wall are produced by the weight of the floor, walls, roof, furniture and occupants, wind load on adjoining walls, and snow and wind loads on the roof. Transverse loads on a foundation wall are produced by earth pressure, concentrated loads by accidental contact with heavy objects, and racking loads by earth pressure on adjoining foundation walls.

The deformation and set under each increment of load were measured because, considered as a structure, the suitability of a wall construction depends not only on its resistance to deformation when loads are applied, but also on its ability to return to its original size and shape when the load is removed.

#### II. SPONSOR AND PRODUCT

The specimens were submitted by the Nelson Cement Stone Co., Inc., East Braintree, Mass., and represented a foundation wall construction marketed under the trade name "Nelson Pre-Cast Concrete Foundation." This construction consisted of precast, ribbed reinforced-concrete panels for foundation walls, designed to be erected by crane trucks.

#### III. SPECIMENS AND TESTS

The wall construction was assigned the symbol BV and the specimens were assigned the designations given in table 1.

TABLE 1.-Specimen designations, wall BV

Specimen designation	Load	Load applied
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Compressive Transversedo Concentrated do Impactdo Packing	Upper end. Inside face. Outside face. Inside face. Outside face. Inside face. Outside face.

<sup>a</sup> These specimens were undamaged portions of the impact specimens.

The specimens were tested in accordance with BMS2, Methods of Determining the Structural Properties of Low-Cost House Constructions, which also gives the requirements for the specimens and describes the presentation of the results of the tests, particularly the load-deformation graphs.

The tests were begun December 14, 1938, and completed February 3, 1939. The tests

were made either on the 28th or the 29th day after the specimens were cast. The sponsor's representative did not witness the tests.

#### IV. WALL BV

1. Sponsor's Statement

(a) Materials

Cement.—Edison Cement Co.'s "Edison Portland Plus Cement."

Sand.—Pit sand, moisture content 4 percent. The sieve analysis of the sand is given in table 2.

TABLE 2	-Sieve	analysis	of	the	sand,	wall	BV
---------	--------	----------	----	-----	-------	------	----

Sieve number,	Passing, by
U. S. Std.	weight
4 15 50 100	Percent 95 45 16 7

Gravel.—Pit gravel, washed, maximum size ¾ in.; moisture content about 1 percent.

Concrete.—One part of cement, 2.8 parts of dry sand, and 4.2 parts of dry gravel, by weight. Slump  $3\frac{1}{2}$  in.

Mesh.—Mild-steel wire, cold-drawn, complying with ASTM Standard A82–34, No. 12 gage (0.1055-in. diam), galvanized, welded in a 6- by 6-in. mesh in rolls 4 ft wide; weight, 0.13 lb/ft<sup>2</sup>. Consolidated Expanded Metal Co.'s "Steelcrete."

Reinforcement bars.—Rail-steel, deformed, complying with ASTM Standard A 16–35,  $\frac{1}{2}$  in. round and  $\frac{3}{8}$  in. round. Northern Steel Co.

Anchor nuts.—Mild steel, square, unfinished, ¾ in., American standard.

#### (b) Description

(1) Three-foot wall specimens.—The 3-ft wall specimens were 8 ft 0 in. high, 3 ft 0 in. wide, and 10 in. thick. Each specimen was a reinforced-concrete slab with reinforced-concrete ribs at the sides and ends. The specimens were cast with the inside face down, and the outside dimensions varied as much as  $\frac{1}{4}$  in. from the nominal dimensions. A sheet-steel core was used to form the inside face. The web of the specimen was reinforced by mesh, A, shown in figure 1, and the vertical and horizontal ribs by reinforcement, B and C, respectively. The reinforcement and concrete were placed in the form, and the outside face was screeded to a rough, level surface. There were two holes, 1 in. in diam and  $4\frac{3}{4}$  in. deep, in the upper end of the specimen, with a  $\frac{3}{4}$ -in. anchor nut embedded at the bottom of each hole, to receive bolts for handling the panels and bolts for fastening the sill. There were no grooves in the vertical edges of the specimens.

The mesh, A, was a single shect placed  $1\frac{1}{2}$  in. from the outside face. The shcets for different specimens varied in width from 2 ft 9 in. to 3 ft 0 in., and in length from 7 ft 9 in. to 8 ft 0 in. The edges of the sheet were bent into the ribs. The mesh in these specimens was not like the mesh regularly used by the sponsor for wall panels of this construction. In the mesh regularly used the vertical wires are spaced 12 in., and the spacing of the horizontal wires ranges from 2 in. at the lower end to 7 in. at the upper end of the wall panels.

The vertical reinforcement, B, consisted of one %-in. diam deformed bar, about 7 ft 9 in. long, in each vertical rib, and spaced in different specimens from 1 to 4 in. from the inside edge of the rib.

The horizontal reinforcement, C, consisted of one  $\frac{1}{2}$ -in. diam deformed bar in each horizontal rib, except for specimens BV-C2, C3, and I6 which had  $\frac{3}{2}$ -in. diam bars. The bars were about 2 ft 9 in. long, and were spaced in different specimens from 2 to 4 in. from the inside edge of the rib.

(2) Nine-foot wall specimens.—The 9-ft wall specimens were 8 ft 0 in. high, 9 ft 0 in. wide, and 10 in. thick. The specimens were similar to the 3-ft specimens and had intermediate vertical ribs, spaced 3 ft 0 in. on centers, as shown in figure 2. There were no grooves in the vertical edges of the specimens.

The mesh, A, was in two sheets, each 4 ft 0 in. high and 9 ft 0 in. long, placed  $1\frac{1}{2}$  in. from the outside face. The vertical reinforcement, B, in the ribs at each edge of the specimen was a  $\frac{3}{4}$ -in. diam bar, except for specimen BV-R1which had a  $\frac{1}{2}$ -in. diam bar in one rib. The horizontal reinforcement, C, was  $\frac{1}{2}$ -in. diam bars about 8 ft 9 in. long. The vertical reinforcement, D, in the intermediate ribs was  $\frac{1}{2}$ -in.



FIGURE 1.—Three-foot wall specimen BV, showing inside face.

A, mesh; B, vertical reinforcement; C, horizontal reinforcement.

diam bars, except for specimen *BV–R1*, which had a %-in. diam bar in one intermediate rib.

The price of this construction in Washington, D. C., as of July 1937, was \$0.35/ft<sup>2</sup>.

#### (c) Comments

These foundation wall panels are cast in horizontal wood forms with sheet-steel cores and are transported to the building site by truck and erected by means of a crane truck. Openings for windows, ventilators, and pipes are provided by cores set in the form. The panels are made full wall height and in widths up to 15 ft. The standard thicknesses of the panels are 10, 11, and 12 in.

When erected, the panels rest on a pouredconcrete footing with a <sup>1</sup>/<sub>2</sub>-in. mortar bed between footing and panel. The mortar mix is 1 part of cement to 3 parts of sand, by volume. The vertical edges of the panels are grooved, 1<sup>3</sup>/<sub>4</sub> in. wide by <sup>3</sup>/<sub>4</sub> in. deep, and the panels are spaced <sup>3</sup>/<sub>4</sub> in. apart. The spaces and the grooves are filled with grout, 1 part of cement to 3 parts of sand, by volume. Corner panels are



FIGURE 2.—Nine-foot wall specimen BV, showing inside face. A, mesh; B, vertical reinforcement in edge ribs; C, horizontal reinforcement; D, vertical reinforcement in intermediate ribs.



FIGURE 3.-Wall specimen BV-C1 under compressive load.



FIGURE 4.—Compressive load on wall BV.

Load-shortening (open circles) and load-set (solid circles) results for specimens BV-CI, C2, and C3. The load was applied 3.33 in. from the inside edge of the ribs. The loads are in kips per foot of actual width of specimen.

made with a wide-faced vertical rib and a groove to match the edge of the adjacent panel. The joints between panels are raked about ¾-in. deep on the outside face and filled with asphalt mastic below ground level and with a linseed-oil and asbestos-fiber calking compound above ground. No waterproofing or other finish is required for the panels themselves. Anchorage for the superstructure is provided by a connection to the threaded nuts embedded in the top ribs.

There have been 26 houses built with the "Nelson Pre-Cast Concrete Foundation." Plans have been developed for a precast reinforcedconcrete wall construction similar to the foundation wall, but thinner, and with lighter reinforcement. The sponsor proposes to erect the panels in three horizontal courses for a height of one story. The first course will be from the top of the foundation to the bottom of the windows, the second course from the bottom of the windows to the top of the windows, and the third course from the top of the windows to the wall plate, or to the bottom of the second-story windows. The panels will be made in lengths up to 24 ft. The walls will be insulated by loose-fill insulation placed between the ribs of each panel. Furring strips, imbedded in the edges of the ribs, will provide for attaching various inside faces. The outside finish will be east in the panels.

#### 2. Compressive Load

Wall specimen BV-C1 under compressive load is shown in figure 3. The results for wall specimens BV-C1, C2, and C3 are shown in table 3 and in figures 4 and 5.

The shortenings and sets shown in figure 4 for a height of 8 ft were computed from the values obtained from the compressometer readings. The compressometers were attached to the upper and lower bearing plates. The gage length of the compressometers was 8 ft  $\frac{1}{2}$  in.

For each of the specimens the concrete cracked in several places. The first cracks occurred at loads of 26, 20, and 18 kips/ft for specimens C1, C2, and C3, respectively, near the upper end of each specimen, in both the face and one rib.



FIGURE 5.—Compressive load on wall BV.

Load-lateral deflection (open circles) and load-lateral set (solid circles) results for specimens BV-Cl, C2, and C3. The load was applied 3.33 in, from the inside edge of the ribs. The loads are in kips per foot of actual width of specimen. The deflections and sets are for a gage length of 7 ft 9 in., the gage length of the deflectometers. Each specimen deflected toward the outside face.

			_	
Load	Load applied	Speci- men desig- nation	Maxi- mum height of drop	Maxi- mum load
Compressive	{Upper end, 3.33 in. from the inside edge of the ribs.	$\left\{\begin{array}{c} C1\\ C2\\ C3\end{array}\right.$	ft	<sup>a</sup> Kips/ft 28.0 36.8 39.5
	A verage			34.8
Transverse	Inside face; span, 7 ft 6 in	$\left\{\begin{array}{c} T1\\T2\\T3\end{array}\right.$		<i>lb/ft</i> <sup>2</sup> 491 415 385
	Avcrage			430
Do	Outside face; span, 7 ft 6 in	$\left\{\begin{array}{c} T4\\T5\\T6\end{array}\right.$		422 540 406
	Average.			456
Concentrated	Inside face	$\left\{\begin{array}{c} P1\\ P2\\ P3\end{array}\right.$		<i>lb</i> b 1,000 b 1,000 b 1,000
	A verage			b 1,000
Do	Outside face	$\left\{\begin{array}{c} P4\\ P5\\ P6\end{array}\right.$		<sup>b</sup> 1,000 <sup>b</sup> 1,000 <sup>b</sup> 1,000
	Average			<sup>b</sup> 1,000
1mpact	Inside face; span, 7 ft 6 in	$\left\{\begin{array}{c}I1\\I2\\I3\\I3\end{array}\right.$	7.0 6.0 6.5	
	Average		6.5	
Do	Outside face; span, 7 ft 6 in	$\left\{\begin{array}{c}I4\\I5\\I6\end{array}\right.$	b 10.0 c 10.0 c 10.0	
	Average			
Racking	Near upper cnd	$\left\{\begin{array}{c} R1\\ R2\\ R2\end{array}\right\}$		<sup>a</sup> Kips/ft <sup>b</sup> 5, 56 <sup>b</sup> 5, 56
	Average	<u>( R3</u>		<sup>b</sup> 5. 56

TABLE 3.—Structural properties, wall BV [Weight, 51.7 lb/ft<sup>2</sup>]

A kip is 1,000 lb.
Test discontinued. Specimen did not fail.
Test discontinued. Specimen damaged.

At the maximum loads each of the specimens failed by crushing of the inside edges of the vertical ribs just below the top horizontal rib and rupturing of the outside face just below this rib.

### 3. TRANSVERSE LOAD

Wall specimen BV-T3 under transverse load is shown in figure 6. The results are shown in table 3 and in figure 7 for wall specimens BV-T1, T2, and T3, loaded on the inside face, and in figure 8 for wall specimens BV-T4, T5, and T6, loaded on the outside face.

The transverse loads were applied with the specimens in a horizontal position. The initial



FIGURE 6.—Wall specimen BV-T3 under transverse load.



FIGURE 7.-Transverse load on wall BV, load applied to inside face.

Load-deflection (open circles) and load-set (solid circles) results for specimens BV-T1, T2, and T3 on the span 7 ft 6 in.



FIGURE 8.—*Transverse load on wall BV, load applied to outside face.* 

Load-deflection (open circles) and load-set (solid circles) results for specimens BV-T4, T5, and T6 on the span 7 ft 6 in.

deflection and set readings shown in figures 7 and 8 were taken under a load of about 65  $lb/ft^2$  caused by the weight of the specimen between the supporting rollers and the weight of the loading apparatus.

The loads were applied to the inside edges of the ribs of specimens T1, T2, and T3. Each of these specimens failed by rupture of the concrete transversely across the specimen at or between the loading rollers.

For specimens  $T_4$ ,  $T_5$ , and  $T_6$  the concrete in the longitudinal ribs cracked in several places between the supporting rollers, the cracks starting at the inside edge of the ribs and extending to about midthickness. The first cracks occurred at loads of 170, 219, and 235 lb/ft<sup>2</sup> and deflections of 0.05, 0.08, and 0.09 in. for specimens  $T_4$ ,  $T_5$ , and  $T_6$ , respectively. At the maximum loads each of the specimens failed by rupture of the concrete in both ribs diagonally between a supporting roller and the nearest loading roller, and rupture of the concrete between ribs transversely across the specimen under this loading roller.

#### 4. Concentrated Load

Wall specimen  $BV-P_4$  under concentrated load is shown in figure 9. The results are shown in table 3 and in figure 10 for wall specimens BV-P1, P2, and P3, loaded on the inside face, and in figure 11 for wall specimens BV-P4, P5, and P6, loaded on the outside face.

The concentrated loads were applied to the inside face of specimens P1, P2, and P3 between the ribs. There was no measurable indentation for any of these three specimens after a load of 1,000 lb had been applied.

The concentrated loads were applied to the outside face of specimens  $P_4$ ,  $P_5$ , and  $P_6$ , between the side ribs and from  $1\frac{1}{2}$  to  $2\frac{1}{2}$  ft from one end. The indentations after a load of 1,000 lb had been applied were 0.000, 0.002, and 0.002 for specimens  $P_4$ ,  $P_5$ , and  $P_6$ , respectively, and no other effect was observed.

#### 5. Impact Load

Wall specimen BV-I5 during the impact test is shown in figure 12. The results are shown in table 3 and in figure 13 for wall specimens BV-I1, I2, and I3, loaded on the inside face, and in figure 14 for wall specimens BV-I4, I5, and I6, loaded on the outside face.

The impact loads were applied to the center of the inside face of specimens I1, I2, and I3,



FIGURE 9.—Wall specimen BV-P4 under concentrated load.





FIGURE 10.—Concentrated load on wall BV, load applied to inside face.

Load-indentation results for specimens  $BV\mathchar`-\mathchar -\mathchar`-\mathchar`-\$ 

FIGURE 11.—Concentrated load on wall BV, load applied to outside face.

Load-indentation results for specimens BV-P4, P5, and P6.



FIGURE 12.—Wall specimen BV-I5 during the impact test.



FIGURE 13.—Impact load on wall BV, load applied to inside face.

Load-deflection (open circles) and load-set (solid circles) results for specimens BV-11, 12, and 13 on the span 7 ft 6 in.

the sandbag striking midway between the ribs. At drops of 5, 4.5, and 4 ft and deflections of 0.19, 0.17, and 0.16 in. for specimens I1, I2, and I3, respectively, the outside face of each specimen cracked transversely across or part way across the specimen near midspan. At drops of 6, 5, and 5 ft, respectively, these cracks opened about  $\frac{1}{3}$  in. and extended to the inside edge of the ribs. At the maximum drops each of the specimens failed by breaking into two or three pieces, which were held only by the reinforcement.

The impact loads were applied to the center of the outside face of specimens I4, I5, and I6, the sandbag striking midway between the ribs. At drops of 4, 3, and 6.5 ft and deflections of 0.21, 0.14, and 0.35 in. for specimens I4, I5, and I6, respectively, both ribs cracked near midspan, the crack extending from the edge of the ribs to the base (intersection with inside face). At drops of 9.5, 8.5, and 7 ft, respectively, the inside face of each specimen cracked transversely between the ribs near midspan. For specimen I4 the set after a drop of 10 ft was 0.055 in., and there were several cracks in the edges of the ribs. For specimen I5 at a drop of 9 ft the inside face cracked longitudinally adjacent to both ribs for a length of about 3 ft near midspan, and at a drop of 10 ft these cracks opened and penetrated to the outside face. The set after the 10-ft drop was 0.391 in. For specimen I6 at a drop of 8 ft the outside face cracked transversely across the specimen near midspan, the crack extending through to the inside face; and at a drop of 10 ft there were several cracks in the inside face radiating from the center of the specimen below where the sandbag struck. The set after the 10-ft drop was 0.031 in.

#### 6. RACKING LOAD

Wall specimen BV-R1 under racking load is shown in figure 15. The results for wall specimens BV-R1, R2, and R3 are shown in table 3 and in figure 16.

The deformations and sets for a height of 8 ft were computed from the values obtained from the measuring-device readings. The gage length of the measuring device was 6 ft 7 in.

For specimens R2 and R3 at loads of 3 and 3.5 kips/ft, respectively, the top rib cracked



FIGURE 14.—Impact load on wall BV, load applied to outside face.

Load-deflection (open circles) and load-set (solid circles) results for specimens BV-14, 15, and 16 on the span 7 ft 6 in .



FIGURE 15.—Wall specimen BV-R1 under racking load.



FIGURE 16.—Racking load on wall BV.

Load-deformation (open circles) and load-set (solid circles) results for specimens BV-R1, R2, and R3. The loads are in kips per foot of actual width of specimen.

vertically near the loaded corner,  $1\frac{1}{2}$  ft from the corner for specimen R2 and 3 ft for specimen R3. The sets after a load of 5.56 kips/ft had been applied were 0.022, 0.018, and 0.005 in. for specimens R1, R2, and R3, respectively, and no other effect was observed.

The description, drawings, and sponsor's comments were prepared by E. J. Schell and G. W. Shaw of the Bureau's Building Practice and Specifications Section, under the supervision of V. B. Phelan, from information furnished by the sponsor and from the specimens themselves.

The structural properties were determined by the Engineering Mechanics Section, under the supervision of H. L. Whittemore and A. H. Stang, and the Masonry Construction Section, under the supervision of D. E. Parsons, with the assistance of the following members of the professional staff: F. Cardile, H. Dollar, M. Dubin, A. H. Easton, A. S. Endler, C. D. Johnson, A. J. Sussman, and L. R. Sweetman.

WASHINGTON, MAY 6, 1939.

### BUILDING MATERIALS AND STRUCTURES REPORTS

The following publications in this series are now available by purchase from the Superintendent of Documents at the prices indicated:

BMS1	Research on Building Materials and Structures for Use in Low-Cost Housing	10¢
BMS2	Methods of Determining the Structural Properties of Low-Cost House Constructions	10¢
BMS3	Suitability of Fiber Insulating Lath as a Plaster Base	10¢
BMS4	Accelerated Aging of Fiber Building Boards	10¢
BMS5	Structural Properties of Six Masonry Wall Constructions	15¢
BMS6	Survey of Roofing Materials in the Southeastern States	15¢
BMS7	Water Permeability of Masonry Walls	10¢
BMS8	Methods of Investigation of Surface Treatment for Corrosion Protection of Steel	10¢
BMS9	Structural Properties of the Insulated Steel Construction Company's "Frameless-Steel"	
	Constructions for Walls, Partitions, Floors, and Roofs	10¢
BMS10	Structural Properties of One of the "Keystone Beam Steel Floor" Constructions Spon-	
	sored by the H. H. Robertson Company	10¢
BMS11	Structural Properties of the Curren Fabrihome Corporation's "Fabrihome" Construc-	
	tions for Walls and Partitions	10ć
BMS12	Structural Properties of "Steelox" Constructions for Walls, Partitions, Floors, and Roofs	
	Sponsored by Steel Buildings, Inc.	15é
BMS13	Properties of Some Fiber Building Boards of Current Manufacture	10é
BMS14	Indentation and Recovery of Low-Cost Floor Coverings	10ć
BMS15	Structural Properties of "Wheeling Long-Span Steel Floor" Construction Sponsored	
	by the Wheeling Corrugating Company	10¢
BMS16	Structural Properties of a "Tilecrete" Floor Construction Sponsored by Tilecrete Floors.	
	Inc	10¢
BMS17	Sound Insulation of Wall and Floor Constructions	10¢
BMS18	Structural Properties of "Pre-Fab" Constructions for Walls, Partitions, and Floors	
	Sponsored by the Harnischfeger Corporation	10¢
BMS19	Preparation and Revision of Building Codes	15¢
BMS20	Structural Properties of "Twachtman" Constructions for Walls and Floors Sponsored by	•
	Connecticut Pre-Cast Buildings Corporation	10¢
BMS21	Structural Properties of a Concrete-Block Cavity-Wall Construction Sponsored by the	
	National Concrete Masonry Association	10¢
BMS22	Structural Properties of "Dun-Ti-Stone" Wall Construction Sponsored by the W. E.	•
	Dunn Manufacturing Company	10¢
BMS23	Structural Properties of a Brick Cavity-Wall Construction Sponsored by the Brick	
	Manufacturers Association of New York, Inc.	10¢
BMS24	Structural Properties of a Reinforced-Brick Wall Construction and a Brick-Tile Cavity-	
	Wall Construction Sponsored by the Structural Clay Products Institute	10¢
BMS25	Structural Properties of Conventional Wood-Frame Constructions for Walls, Partitions,	
	Floors, and Roofs	15¢

# How To Purchase BUILDING MATERIALS AND STRUCTURES REPORTS

On request, the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., will place your name on a special mailing list to receive notices of new reports in this series as soon as they are issued. There will be no charge for receiving such notices.

An alternative method is to deposit with the Superintendent of Documents the sum of \$5, with the request that the reports be sent to you as soon as issued, and that the cost thereof be charged against your deposit. This will provide for the mailing of the publications without delay. You will be notified when the amount of your deposit has become exhausted.

If 100 copies or more of any report are ordered at one time, a discount of 25 percent is allowed. Send all orders and remittances to the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C.

