

The program of research on building materials and structures, carried on by the National Bureau of Standards, was undertaken with the assistance of the Central Housing Committee, an informal organization of governmental agencies concerned with housing construction and finance, which is cooperating in the investigations through a subcommittee of principal technical assistants.

CENTRAL HOUSING COMMITTEE

SUBCOMMITTEE ON TECHNICAL RESEARCH

WALTER JUNGE, Chairman. Federal Housing Administration. A. C. SHIRE, Vice Chairman. United States Housing Authority.

STERLING R. MARCH, Secretary

Albert G. Bear,	GEORGE E. KNOX,
Veterans' Administration.	Yards and Docks (Navy).
PIERRE BLOUKE, Federal Home Loan Bank Board (Fed- eral Loan Agency).	VINCENT B. PHELAN, National Bureau of Standards (Com-
CARROLL W. CHAMBERLAIN, Public Buildings Administration (Fed-	Edward A. Poynton.
eral Works Agency).	Office of Indian Affairs (Interior).
JOSEPH M. DALLAVALLE, Public Health Service (Federal Security	George W. TRAYER, Forest Service (Agriculture).
Agency). Јонн Donovan,	Elsmere J. Walters,
Farm Security Administration (Agri- culture).	Construction Division (War).

CHAIRMEN OF SECTIONS

Specifications Ma		aterials			Maintenance				
CARROLL	W.	CHAMBERLAIN	Elsmere	J.	WALTERS		John	H.	Schaefer
		Mechanical Equip:	ment	Methods and Practices					
		ROBERT K. THUI	MAN						

NATIONAL BUREAU OF STANDARDS

STAFF COMMITTEE ON ADMINISTRATION AND COORDINATION

HUGH L. DRYDEN, Chairman.

Mechanics and Sound.

PHAON H. BATES,	GUSTAV E. F. LUNDELL,	
Clay and Silicate Products.	Chemistry.	
HOBART C. DICKINSON,	Addams S. McAllister,	
Heat and Power.	Codes and Specifications.	
WARREN E. EMLEY,	HENRY S. RAWDON,	
Organic and Fibrous Materials.	Metallurgy.	

The Forest Products Laboratory of the United States Department of Agriculture is cooperating with both committees on investigations of wood constructions.

[For list of BMS publications and how to purchase, see cover page III.]

UNITED STATES DEPARTMENT OF COMMERCE · Harry L. Hopkins, Secretary NATIONAL BUREAU OF STANDARDS · Lyman J. Briggs, Director

BUILDING MATERIALS and STRUCTURES

REPORT BMS36

Structural Properties of Wood-Frame Wall, Partition, Floor, and Roof Constructions with "Red Stripe" Lath Sponsored by The Weston Paper and Manufacturing Co.

by HERBERT L. WHITTEMORE and AMBROSE H. STANG

with the collaboration of Тномая R. C. Wilson Forest Products Laboratory Forest Service, United States Department of Agriculture



ISSUED JANUARY 2, 1940

The National Bureau of Standards is a fact-finding organization; it does not "approve" any particular material or method of construction. The technical findings in this series of reports are to be construed accordingly.

UNITED STATES GOVERNMENT PRINTING OFFICE · WASHINGTON · 1940 FOR SALE BY THE SUPERINTENDENT OF DOCUMENTS, WASHINGTON, D. C. · PRICE IO CENTS

Foreword

This report is one of a series issued by the National Bureau of Standards on the structural properties of constructions intended for low-cost houses and apartments. Practically all of these constructions were sponsored by groups within the building industry which advocate and promote the use of such constructions and which have built and submitted representative specimens as outlined in report BMS2, Methods of Determining the Structural Properties of Low-Cost House Constructions. The sponsor, therefore, is responsible for the description of the specimens and the method of fabrication. The Bureau is responsible for the method of testing and the test data.

This report covers only the load-deformation relations and strength of the structural elements when subjected to compressive, transverse, concentrated, impact, and racking loads by standardized methods simulating the loads to which the elements would be subjected in actual service. It may be feasible later to determine the heat transmission at ordinary temperatures and the fire resistance of these same constructions.

The Forest Products Laboratory, Forest Service, United States Department of Agriculture, collaborated in the tests of constructions having wood structural members.

The National Bureau of Standards does not "approve" a construction, nor does it express an opinion as to the merits of a construction, for the reasons given in reports BMS1 and BMS2. The technical facts presented in this series provide the basic data from which architects and engineers can determine whether a construction meets desired performance requirements.

LYMAN J. BRIGGS, Director.

Structural Properties of Wood-Frame Wall, Partition, Floor, and Roof Constructions with "Red Stripe" Lath Sponsored by The Weston Paper and Manufacturing Co.

by HERBERT L. WHITTEMORE and AMBROSE H. STANG

with the collaboration of THOMAS R. C. WILSON, Forest Products Laboratory, Forest Service, United States Department of Agriculture

CONTENTS

	Page		Page
Foreword	11	IV. Materials—Continued.	
I. Introduction	2	11. Roofing	9
II. Sponsor and product	2	(a) Asphalt	9
III. Specimens and tests	3	(b) Caps	9
IV. Materials	3	V. Wall $BQ_{}$	9
1. Sources of information	3	1. Description, sponsor's statement	9
2. Wood	4	(a) Four-foot wall specimens	9
(a) Framing for walls and parti-		(b) Eight-foot wall specimens	10
tions	4	2. Compressive load	11
(b) Framing for floors and roofs	4	3. Transverse load	12
(c) Sheathing and subflooring	4	4. Concentrated load	13
(d) Bevel siding	4	5. Impact load	14
(e) Bridging	4	6. Racking load	15
(f) Flooring	4	VI. Partition BR	16
(g) Spacers and grounds	4	1. Description, sponsor's statement	16
3. "Red Stripe" lath	6	2. Concentrated load	17
(a) Description	6	3. Impact load_	18
(b) Physical properties	7	VII. Floor BS	19
4. Nails	7	1. Description, sponsor's statement	19
5. Plaster	7	2. Transverse load	21
6. Sheathing paper	9	3. Concentrated load	21
7. Tacks	9	4. Impact load	21
8. Size	9	VIII. Roof <i>BT</i>	21
9. Paints	9	1. Description, sponsor's statement	21
(a) Outside	9	2. Transverse load	24
(b) Inside	9	3. Concentrated load	25
10. Shellac varnish	9	IX. Comments by sponsor	25

ABSTRACT

For the program on the determination of the structural properties of low-cost house constructions, The Weston Paper and Manufacturing Co. submitted 30 specimens representing wood-frame wall, partition, floor, and roof constructions with "Red Stripe" lath.

The wall specimens were subjected to compressive, transverse, concentrated, impact, and racking loads; the partition specimens to concentrated and impact loads; the floor specimens to transverse, concentrated, and impact loads; and the roof specimens to transverse and concentrated loads. For each of the loads three like specimens were tested. The transverse, concentrated, and impact loads were applied to both faces of the wall specimens, and for each of these loads six like specimens were tested. The deformation under load and the set after the load was removed were measured for uniform increments of load, except for concentrated loads, for which the set only was determined. The results are presented in graphs and in tables.

I. INTRODUCTION

To provide technical facts on the performance of constructions which might be used in lowcost houses, to discover promising new constructions, and ultimately to determine the properties necessary for acceptable performance in actual service, the National Bureau of Standards has invited the cooperation of the building industry in a program of research on building materials and structures suitable for low-cost houses and apartments. The objectives of this program are described in report BMS1, Research on Building Materials and Structures for Use in Low-Cost Housing, and that part of the program relating to structural properties in report BMS2, Methods of Determining the Structural Properties of Low-Cost House Constructions.

Masonry constructions and wood constructions of types which have been extensively used in this country for houses were included in the program because their behavior under widely different service conditions is known to builders and the public. The reports on these constructions are BMS5, Structural Properties of Six Masonry Wall Constructions, and BMS25, Structural Properties of Conventional Wood-Frame Constructions for Walls, Partitions, Floors, and Roofs. The masonry specimens were built by the Masonry Construction Section of this Bureau, and the wood-frame specimens were built and tested by the Forest Products Laboratory at Madison, Wis.

The present report describes the structural properties of constructions sponsored by one of the manufacturers in the building industry. The specimens were subjected to compressive. transverse, concentrated, impact, and racking loads, simulating loads to which the elements of a house are subjected. In actual service, compressive loads on a wall are produced by the weight of the roof, by second floor and secondstory walls, if any, by furniture and occupants. and by snow and wind loads on the roof. Transverse loads on a wall are produced by the wind, concentrated loads by furniture or accidental contact with heavy objects, and racking loads by the action of the wind on adjoining walls. On nonload-bearing partitions, impact loads may be applied accidentally by furniture or by a person falling against a partition, and concentrated loads by furniture or by a ladder or other object leaning against a partition. Transverse loads are applied to floors by furniture and by the occupants; concentrated loads by furniture, for example, the legs of a piano; and impact loads by objects falling on the floor or by persons jumping on the floor. Transverse loads are applied to roofs by wind and snow; concentrated loads by persons walking on the roof and by tools and equipment when the roof is constructed and repaired.

The deflection and set under each increment of load were measured because, considered as a structure, the suitability of a construction depends not only on its resistance to deformation when loads are applied, but also on whether it returns to its original size and shape when the loads are removed.

II. SPONSOR AND PRODUCT

The specimens were submitted by The Weston Paper and Manufacturing Co., Dayton, Ohio, and represented wood-frame constructions with a fabricated paper-stock lath marketed under the trade name "Red Stripe." The constructions consisted of conventional woodframe walls, partitions, floors, and roofs, with lath and plaster as one or both faces.

III. SPECIMENS AND TESTS

The specimens represented four elements of a house, which were assigned the following symbols: wall, BQ; partition, BR; floor, BS; and roof, BT. The specimens were assigned the designations given in table 1.

TABLE 1.—Specimen designations

Element	Con- struction symbol	Specimen des- ignation	Load	Load applied
Wall Do Do Do Do Do Do Do	BQ BQ BQ BQ BQ BQ BQ BQ	C1, C2, C3 T1, T2, T3 T4, T5, T6 P1, P2, P3 * P4, P5, P6 * I1, I2, I3 I4, I5, I6 R1, R2, R3	Compressive Transverse do Concentrated do Racking	Upper end. Inside face. Outside face. Inside face. Inside face. Inside face. Outside face. Upper end.
Partition	$BR \\ BR$	P1, P2, P3 ª	Concentrated	Either face.
Do		I1, I2, I3	Impact	Do.
Floor	BS	T1, T2, T3	Transverse	Upper face.
Do	BS	P1, P2, P3 ^a	Concentrated	Do.
Do	BS	I1, I2, I3	Impact	Do.
Roof	$BT \\ BT$	T1, T2, T3	Transverse	Do.
Do		P1, P2, P3 b	Concentrated	Do.

^a The concentrated and impact loads were applied to the same specimens. The concentrated load was applied first. ^b The concentrated and transverse loads were applied to the same specimens. The concentrated load was applied first.

The specimens were tested in accordance with BMS2, Methods of Determining the Structural Properties of Low-Cost House Constructions, which also gives the requirements for the specimens and describes the presentation of the results of the tests, particularly the load-deformation graphs. Thomas R. C. Wilson, of the Forest Products Laboratory, Madison, Wis., cooperated with the Bureau staff in this work by giving advice and making suggestions on the technique of testing wood structures.

For the compressive load the thickness of the wall was taken as the thickness of the structural portion, that is, the distance from the inside surface of the stude to the outside surface of the The eompressive load was applied onestuds. third this thickness from the inside surface of the studs. The shortenings and sets were measured by means of eompressometers attached to the steel loading plates through which the load was applied to the specimen, not attached to the specimen as described in BMS2. This was done because in wood-frame constructions under empressive load there is considerable local shortening caused by crushing of the floor plate and top plate at the ends of the studs. Therefore, the shortening of the entire specimen is not proportional to the value obtained from compressometers attached near each end of the specimen.

The deformations under racking load were measured with a right-angle deformeter, consisting of a steel channel and a steel angle braced to form a rigid connection. In use, the channel of the deformeter rested along the top of the specimen, with the steel angle extending downward in the plane of the specimen. Two pins passed snugly through holes in the channel into the top of the specimen. Two dial micrometers were attached to a steel block which was in contact with the floor plate of the specimen at the stop. The spindles of the micrometers were in contact with rigid extensions of the steel angle of the deformeter. The gage length (distance from the top of the specimen to the center of the block) was 7 ft 11¼ in. The micrometers were graduated to 0.001 in. and readings were recorded to the nearest division. This deformeter was used instead of the taut-wire mirror-scale device described in BMS2.

Before applying the loads, the speed of the movable head of the testing machine was measured under no load. For compressive loading the speed was 0.072 in./min, for transverse loads on walls the speed was 0.14 in./min, on floors it was 0.173 in./min, and on roofs it was 0.24 in./min. These speeds were recommended by the Forest Products Laboratory.

The specimens were tested on the 28th day following the application of the finish coat of plaster. The tests were begun November 23, 1938 and completed December 9, 1938. The sponsor's representative witnessed the tests.

IV. MATERIALS

1. Sources of Information

Unless otherwise stated the information on materials was obtained from the sponsor and from inspection of the specimens. The Forest Products Laboratory assisted the sponsor by identifying the species of the wood in the framing. The Heat Transfer Section of this Bureau assisted by determining the thermal conductivity of the lath, the Paper Section by determining the other physical properties of the lath, and the Lime and Gypsum Section by determining the properties of the plaster.

2. Wood

(a) Framing for Walls and Partitions

Studs, floor plates, top plates, and girts, Douglas-fir, *Pseudotsuga taxifolia*, No. 1 common, S4S (surfaced four sides), 1% by 35% in. (nominal 2 by 4 in.).

(b) Framing for Floors and Roofs

Joists, rafters, and end members, longleafsouthern-pine, identified as southern yellow pine, Pinus sp., No. 1 common, S4S, 1% by 7½ in. (nominal 2 by 8 in.).

(c) Sheathing and Subflooring

Shortleaf-southern-pine, Pinus sp., No. 2 common, dressed and matched, tongued-andgrooved, ${}^{25}\!\!/_{2}$ in. thick by 5¼ in. face width (nominal 1 by 6 in.).

(d) Bevel Siding

Red-cypress, *Taxodium distichum*, select, grade C or better, $\frac{7}{16}$ by $\frac{3}{16}$ by $\frac{5}{2}$ in.

(e) Bridging

Shortleaf-southern-pine, *Pinus sp.*, No. 2 common, rough, 1 by 3 in.

(f) Flooring

White-oak, *Quercus sp.*, plain-sawed, clear, tongued-and-grooved, end-matched, ¹³/₆ in. thick by 2¼ in. face width, Jackson Lumber Co.'s "Merit Brand."

(g) Spacers and Grounds

Shortleaf-southern-pine, *Pinus sp.*, No. 2 common, S4S. Spacers for walls and partitions were ${}^{25}\!/_{2}$ by ${}^{5}\!/_{3}$ in. (nominal 1 by 4 in.), and for floors and roofs ${}^{25}\!/_{32}$ by ${}^{623}\!/_{32}$ in. (nominal 1 in. thick). Grounds were ${}^{25}\!/_{32}$ by ${}^{15}\!/_{3}$ in. (nominal 1 by 2 in.).

After each specimen was tested, one face was removed to expose the framing members, and photographs were taken showing the knots and failures. Typical frames of each of the constructions are shown in figures 1 to 4, inclusive.



FIGURE 1.—Wall BQ. Typical specimen.

The species of the woods were identified by examination of a sample of the framing of each specimen.

The moisture content of the wood (except bridging, spacers, and grounds) is given in table 2. An electrical moisture meter was used when determining the moisture content. The moisture meter was graduated for Douglas fir and for longleaf pine. To determine the correction factor of the meter, 21 samples from the wall and partition frames and 9 samples from the floor and roof frames were dried in an oven at 212° F until the weight was constant. The moisture content was the difference between the initial weight and the weight when dry,



FIGURE 2.—Partition BR. Typical specimen.



FIGURE 3.—Floor BS. Typical specimen.



FIGURE 4.—Roof BT. Typical specimen.

divided by the weight when dry. The average value for the Douglas fir (wall and partition) samples was 1.0 less than the average of the meter readings, and the average value of the longleaf-pine (floor and roof) samples was 1.0 greater than the average of the meter readings. Therefore, the moisture content of the Douglas fir was obtained by subtracting 1.0 from the meter readings, and the moisture content of the longleaf pine was obtained by adding 1.0 to the meter readings. The results were rounded to the nearest whole number.

Tabli	e 2	-Mc	oistur	e c	ontent	of	the	wood
[Detern	nined	on th	ne day	the	speeim	en	was t	tested]

	Construe-	Moisture eontent ª			
Wood	tion symbol	Mini- mum	Maxí- mum	A ver- age	
		Percent	Percent	Percent	
Energing Developen	(BQ	9	23	15	
Framing, Douglas in	1 <i>BŘ</i>	12	18	15	
Framing longloaf southern pine	<i>BS</i>	12	25	19	
Framing, longlear-southern-pine	$BT_{}$	13	25	19	
Sheathing shortleaf southern-pine	fBQ	12	19	16	
sheathing, shortlear-southern-pine.	BT	17	24	20	
Subflooring, shortleaf-southern- pine.	BS	16	23	19	
Bevel siding, red-express	BQ	9	13	11	
Flooring, white-oak	<i>BŠ</i>	8	13	10	

^a Based on the weight when dry.

The moisture content of the wood in each specimen was determined on each stud or joist. The moisture content was determined on about one-half of the pieces of sheathing, subflooring, and bevel siding, and on about 10 pieces of the flooring. The meter reading, corrected according to the manufacturer's recommendations, was taken as the moisture content.

3. "Red Stripe" Lath

(a) Description

Fiberboards, corrugated, double-wall, 4 ft 0 in. by 1 ft 4 in., % in. thick. The boards consisted of a flat filler at midthickness, a corrugated sheet on each side of the filler, and a flat facing on each corrugated sheet.

The filler was "Auglaise" chipboard, 0.020 in. thick, weight 60 to 65 lb/1,000 ft². The corrugated sheets were built up of two sheets of strawboard, 0.009 in. thick, combined (duplexed) with an asphalt-base compound, weight 17.4 lb/1,000 ft², and then corrugated with class A flutes, 5/16 in. high, 32 corruga-

tions per foot. The corrugations were parallel to the 4-ft edges of the lath. The facings were gray news liner, 0.025 in. thick, weight 78 to $80 \text{ lb}/1,000 \text{ ft}^2$. Each facing sheet consisted of two plies; the inner ply was sized in the beater with rosin and starch to increase the moisture resistance, the outer ply was unsized to increase the adhesion of the plaster.

The corrugated sheets were combined with the filler by tapioca starch applied to the inner tips of the corrugations. The facings were combined with the corrugated sheets by sodium silicate, 42° Baumé, applied to the outer tips of the corrugations at a temperature of 75° F. Each edge of the lath was beveled from both sides by rollers and then coated with a patented bituminous compound to increase the moisture resistance.

(b) Physical Properties

The thermal conductivity at 86° F mean temperature was 0.49 (Btu/hr ft^2)/(°F/in).

 TABLE 3.—Moisture content of "Red Stripe" lath
 [Determined on the day the specimen was tested]

Construction symbol	Moisture content «					
Construction symbol	Minimum	Maximum	Average			
BQ BR	Percent 7 8	Percent 10 10	Percent			
BS BT	87	11 11				

^o Based on the weight when dry.

The water absorption, measured in accordance with Federal Specification LLL-F-321a, Fiber-Board; Insulating, was 32 percent, based on the apparent volume. Therefore, the lath did not comply with the requirement for water absorption (maximum, 5 percent) for elass B, Lath (for plaster base). Corrected for the 50-percent air space, the water absorption was almost 70 percent. The lath was tested for water penetration by the method developed by F. T. Carson and described in BMS4, Accelerated Aging of Fiber Building Boards. After 3 weeks there was no evidence that water had penetrated the lath. The water-vapor permeability was determined on a circular sample of the lath sealed with wax over the mouth of a 95-mm petri culture dish containing 50 g of

185264°-39-2

anhydrous CaCl₂ as a desiccant. The assembly was placed in a room maintained at 71° F and 65-percent relative humidity and was weighed periodically. The steady rate of penetration of water vapor was 5.4 g/m² per day.

The moisture content of the lath, determined by drying in an oven at 212° F until the weight was constant, is given in table 3.

4. Nails

The nails were made from steel wire, with the exception of the flooring nails. The description is given in table 4.

TABLE 4.—Description of nails

Type	Size	Length	Steel wire gage	Diameter	U.S. Standard gage	Thickness	Head diam	Finish
BoxDo DoCommon DoFinishing Flooring, cut Plasterboard Roofing, barbed.	Penny 6 6 8 16 20 6 8 8	$\begin{array}{c} in.\\ 17\%\\ 2\\ 2^{3\%}\\ 3^{1/2}\\ 4\\ 2^{1/2}\\ 2^{1/2}\\ 1^{1/4}\\ 1\end{array}$	No. 131/2 121/2 121/2 8 6 13 121/2 11 111/2	<i>in.</i> 0. 0858 . 0985 . 0985 . 162 . 192 . 0915 . 0985 . 1205 . 113	No.	in.	in.	Cement-coated. Bright. Cement-coated. Bright. Do. Do. Do. Blued. Galvanized.

5. Plaster

The plaster was applied in two coats. The base coat was approximately 1 part of neat gypsum plaster and 2 parts of dry Potomac River building sand, by weight. The finish coat was 1 part of gaging plaster and 3 parts of hydrated finishing lime, by volume. The neat gypsum plaster, the gaging plaster, and the finishing lime were United States Gypsum Co.'s "Red Top." The plastering contractor was instructed to apply the plaster to the specimens as he would to the walls and ceilings of a house.

The following properties of the plaster were determined in accordance with Federal Specification SS-P-401, Plaster; Gypsum. The time of set of the neat gypsum plaster was 15 hr and the average tensile strength of six samples was 270 lb/in². The neat gypsum plaster complied with the requirements of the Federal specification for time of set and tensile strength.

A sample consisting of 1 part of neat gypsum plaster and 2 parts of sand, by weight, at a consistency of 18 (18 g of water to 100 g of sanded mixture at $\frac{1}{2}$ -in. slump), had a time of set of 8 hr and a tensile strength of 155 lb/in². Accelerator was added to the sanded plaster by the contractor to decrease the time of set to 4 hr. The tensile strength of the sanded plaster for some of the specimens was determined on samples taken on the job from some of the batches of the wet plaster. The plaster was cast in briquet molds and cured in accordance plaster which has been sanded on the job. The tensile strength of each batch tested exceeded the specified minimum tensile strength for ready-sanded, scratch-coat plaster.

The proportions of plaster and sand in the set plaster were determined in accordance with the proposed revision of C26-33,¹ Standard Method of Testing Gypsum and Gypsum Products. The proportions for sanded plaster, by weight, were 1 part of plaster to 1.79 parts of



FIGURE 5.—Typical cracks in the base coat of the plaster.

with paragraph F-2f(1), Federal Specification SS-P-401. The tensile strength of the sanded plaster is given in table 5.

TABLE 5.—Tensile strength of sanded plaster

[Determined when weight was constant within 0.1 percent]

Batch No.	Specimens	Tensil e strength
		lb/in.
1	BQ-C1, C2, T1	12
2	BQ-C3, T2, T3	15
3	BQ-T4, T5, R1	16
4	BQ-T6, I4, I5	11.
5	BQ-R2, R3; BR-I3, P3	11.
6	BO-13, P3 BS-T1 T2 T3 11 12 13	17.

The tensile strength of the different batches of the sanded plaster varied principally with the quantity of water in the plaster mix. There are no requirements in the Federal specification for the tensile strength of sanded sand for batch 5, and 1 part of plaster to 1.93 parts of sand for batch 6.

Before the finish coat of plaster was applied, it was observed that the base coat was cracked along most of the bituminous-coated edges of the lath. Since the plaster did not adhere well to this bituminous coating, there was also a tendency for the plaster to bulge outward prior to the cracking at the joints. This was especially noticeable in the floor and roof specimens. Because these specimens were horizontal and the plaster was applied to the lower face, the force of gravity accentuated the bulging of the plaster. Typical cracks in the base coat of the plaster are shown in figure 5. Although the finish coat of plaster concealed the cracks, the bulges at the edges of the lath were still noticeable.

¹ Proc. Am. Soc. Testing Materials 38, pt. 1, 1323 (1938).

6. Sheathing Paper

Red-rosin paper, weight 40 lb/108 ft², 36 in. width of roll. Bird & Son, Inc.

7. TACKS

Bill-poster tacks, ½ in. long, diam of head ¼ in., size No. 6.

8. Size

Decorator's size, alum-treated animal glue and mineral fillers. Recommended mixture for plaster, 1 lb to 6 qt of water. M. Ewing Fox Co.'s "Fox Decorator's Size."

9. PAINTS

(a) Outside

E. I. du Pont de Nemours and Co.'s "Dupont Outside White No. 40."

The outside paints were prepared as follows: Primer—a mixture of 1 gal of outside white,

3 pt of raw linseed oil, and 1 pt of turpentine.

Undercoat—a mixture of 1 gal of outside white and 1 pt of turpentine.

Finish—a mixture of 1 gal of outside white and 1 pt of linseed oil.

The formula for the outside white paint is given in table 6.

TABLE 6.—Formula for paint: outside white

[Composition, by weight: pigment, 63 percent; vehicle, 37 percent]

Pigment		Vehicle		
Ingredient	Content, by weight	lngredient	Content, by weight	
Titanium magnesium* White lead * Zinc oxide Titanium dioxide	Percent 32 33 30 5	Linseed oil Japan drier Mineral spirits	Percent 89 5 6	
Total	100	Total	100	

^a Mixture of 30 percent of titanium dioxide, 70 percent of magnesium sulfate ^b Basic carbonate, 51 percent: basic sulfate, 49 percent.

(b) Inside

E. I. du Pont de Nemours and Co.'s "Dupont Interior, Semi-Gloss, Ivory." The formula is given in table 7.

TABLE 7.--Formula for paint: interior, semigloss, ivory

[Composition, hy weight: pigment, 45 percent; vehicle, 55 percent]

Pigment	_	Vehicle		
Ingredient	Content, by weight	Ingredient	Content, by weight	
Titanium calcium pigment Titanium oxide Tinting colors (zine ycllow; french ocher)	Percent 77 19 4	Resin Processed linseed and china-wood oils Drier Mineral spirits	Percent 3 51 10 36	
Total	100	Total	100	

10. Shellac Varnish

White shellac, a mixture of 4 lb of gum shellac and 1 gal of alcohol. A. L. Webb and Sons' "Webb."

11. Roofing

(a) Asphalt

Asphalt-saturated rag felt 36 in. wide; two weights, 30 lb/100 ft² and 15 lb/100 ft². The Barrett Co.

(b) Caps

Sheet-steel, No. 31 U. S. Std. Gage (0.0109 in. thick), 1⁷/₁₆-in. diam, tinned and lacquered.

V. WALL BQ

1. Description, Sponsor's Statement

Wall BQ was a conventional wood frame with diagonal sheathing, sheathing paper, and wood bevel siding as the outside face, and lath and plaster as the inside face.

The price of this construction in Washington, D. C., as of July 1937, was \$0.37/ft².

(a) Four-Foot Wall Specimens

The 4-ft wall specimens were 8 ft 0 in. high, 4 ft 0 in. wide, and 5% in. thick, as shown in figure 6. Each specimen consisted of a wood frame to which the faces were fastened. The frame consisted of three studs, A, fastened to a floor plate, B, and a top plate, C, by nails. The outside face consisted of wood sheathing, D, sheathing paper, E, and wood bevel siding, F. The inside face consisted of lath, G, and plaster, H. The overhanging edges of the lath were supported by spacer blocks, I. The faces were covered with paint. Studs.—The studs, A, were Douglas fir, 1% by 3% in. (nominal 2 by 4 in), 7 ft 7% in. long, spaced 1 ft 4 in., on centers. The lower end of each stud was fastened to the floor plate by two 16d common nails driven from the bottom of the plate (not toenailed), and the upper end of each stud was fastened to the top plate by



FIGURE 6.—Four-foot wall specimen BQ.



two 16d common nails driven from the top of the lower member of the plate.

Floor plate.—The floor plate, B, was Douglas fir, $1\frac{5}{8}$ by $3\frac{5}{8}$ in. (nominal 2 by 4 in), 4 ft 0 in. long.

Top plate.—The top plate, C, consisted of two pieces of Douglas fir, $1\frac{5}{8}$ by $3\frac{5}{8}$ in. (nominal 2 by 4 in), 4 ft 0 in. long, fastened by three 16d common nails, one in each stud, driven from the top of the upper member of the plate.

Sheathing.—The sheathing, D, was shortleaf southern pine, ${}^{2}\%_{2}$ in. thick by 5¼ in. face width (nominal 1 by 6 in), tongued-and-grooved, fastened at an angle of 48° to the studs by 6d cement-coated box nails, two nails through each piece into each stud and into the top plate and floor plate for those pieces which were in contact with them.

Sheathing paper.—The sheathing paper, E, was laid transversely (across the specimen) over the sheathing and consisted of two sheets 3 ft 0 in. wide and one sheet 2 ft 6 in. wide, having two laps with the upper sheets lapping 3 in. over the lower sheets. The paper was fastened by one tack at each corner of each sheet, one tack serving for two sheets at overlapping corners.

Bevel siding.—The bevel siding, F, was 22 pieces of red cypress, $\frac{7}{16}$ by $\frac{3}{16}$ by $5\frac{1}{2}$ in., 4 ft 0 in. long, laid $4\frac{3}{4}$ in. to the weather, and fastened through the overlapping edges by 6d bright box nails, one at each stud.

Lath.—The lath, G, consisted of six courses of "Red Stripe" lath, each course 1 ft 4 in. high, with a small clearance between courses. There was a vertical joint in most courses, centered on a stud, with no clearance between boards at the joint. The lath was fastened to the stude by 1¼-in. plasterboard nails, five nails to each piece of lath at each stud; and to each plate by five nails, one at each stud and one at each end of the plate.

Spacer blocks.—The spacer blocks, I, were shortleaf southern pine, 2 % by 3% in., 6 in. long, and supported the overhanging edges of the lath. Each block was centered at a joint between lath courses and was fastened to the sheathing by one 6d finishing nail driven from the sheathing into the block and to the lath by four 1¼-in. plasterboard nails driven through the lath into the block. These spacer blocks are not used in a house.

Plaster.—The plaster, H, was $\frac{3}{6}$ in. thick and consisted of a base coat and a finish coat. The lath was dry when the plaster was applied.

Paint.—The outside face was painted with one primer coat, one under coat, and one finish coat of outside paint. The inside face was prepared for painting by the application of one coat of size and finished with one coat of inside paint. Paint and size were applied with a brush.

(b) Eight-Foot Wall Specimens

The 8-ft wall specimens were 8 ft 0 in. high, 8 ft 0 in. face width, and 5% in. thick. The specimens were similar to the 4-ft. specimens except that there were seven studs, spaced 1 ft 4 in. on centers, and no spacer blocks. There was a stud at each edge extending one-half its thickness beyond the faces, width over-all 8 ft 1% in.

2. Compressive Load

The results for wall specimens BQ-C1, C2, and C3 are shown in table 8 and in figures 7 and 8.

TABLE 8.—Structural properties of wall BQ

[Weight, 8.94 lb/ft²]

Load	Load applied	Speci- mcn desig- nation	Fail- ure of loaded face, height of drop	Fail- ure of oppo- site face, height of drop	Maxi- mum height of drop	Maxi- mum load
Compressive.	(Upper end, one- third the thickness (1.21) in.) from the inside surface of the studs (see section III).	$\left.\begin{array}{c} C_1\\ C_2\\ C_3\\ C_3\end{array}\right $	ft	ft	ft	^a Kips/ft 10, 87 9, 02 7, 55
	Average					9.15
Transverse{	Inside face; span, 7 ft 6 in.	$\left\{\begin{array}{c}T1\\T2\\T3\end{array}\right.$				lb/ft ² 227 230 205
	Average					221
Do{	Outside face; span, 7 ft 6 in.	$\left\{ \begin{array}{c} T4\\T5\\T6\end{array} \right.$				240 233 167
	Average					213
Concen trated	Inside face	$\left\{\begin{array}{c} P1\\ P2\\ P3\end{array}\right.$				<i>lb</i> 275 275 300
		1 P4				b 1 000
Do	Outside face	$\left\{ \begin{array}{c} P \delta \\ P 6 \end{array} \right $				^b 1,000 b 1,000
	A verage					ь 1,000
Impact{	Inside face; span, 7 ft 6 in.	$\left\{\begin{array}{c}I1\\I2\\I3\\I3\end{array}\right.$	4.5 5.5 4.0	(0) (0) (0)	d 10.0 d 10.0 d 10.0 d 10.0	
	Average		4. 7	(c)	d 10, 0	
Do{	Outside face; span, 7 ft 6 in.	$\left\{\begin{array}{c}I4\\I5\\I6\\I6\end{array}\right.$	(c) (c) (o)	4, 0 5, 5 4, 5	d 10, 0 d 10, 0 d 10, 0 d 10, 0	
	Average		(c)	4. 7	d 10.0	
Racking	Upper end	$\left\{\begin{array}{c} R1\\ R2\\ R3\end{array}\right.$				ⁿ Kips/ft 2, 12 1, 38 1, 58
						1.09



A kip is 1,000 lb.
 ^b Test discontinued. Specimen did not fail.
 ^c Face did not fail.
 ^d Test discontinued. Specimen damaged.



FIGURE 7.—Compressive load on wall BQ.

Load-shortening (open circles) and load-set (solid circles) results for specimens BQ-CI, C2, and C3. The load was applied 1.21 in. (one-third the thickness of the frame) from the inside surface of the studs. The loads are in kips per foot of actual width of specimen.



FIGURE 8.—Compressive load on wall BQ.

Load-lateral deflection (open circles) and load-lateral set (solid circles) results for specimens BQ-C1, C2, and C3. The load was applied 1.21 in. (one-third the thickness of the frame) from the inside surface of the studs. The loads are in kips per foot of actual width of specimen. The deflections and sets arc for a gage length of 7 ft 10 in., the gage length of the deflectometers.

Although the load was eccentric toward the inside face, each of the specimens deflected toward the inside face under loads up to the maximum load, probably because the stiffness of the plaster counteracted the effect of the eccentric load. After the maximum had been reached, specimens C1 and C2 deflected in the



FIGURE 9.—Transverse load on wall BQ, load applied to inside face.

Load-deflection (open circles) and load-set (solid circles) results for specimens BQ-TI, T2, and T3 on the span 7 ft. 6 in.

opposite direction, that is, toward the outside face, whereas specimen C3 continued to deflect toward the inside face. The change of direction of the deflection curves of specimens C1and C2 indicated local failure of the inside faces.

At loads of 6.2 and 4.0 kips/ft on specimens C1 and C2, respectively, the plaster at the bottom of the inside face began to crush. At the maximum loads on these two specimens the top plate crushed locally at the inside edge of the studs, the lath at the bottom of the specimen separated from the floor plate, and the plaster continued to crush. In specimen C3 at a load of 7.0 kips/ft the lath separated from the studs near the floor plate; at the maximum load the sheathing boards separated from each other and the top plate crushed locally at the outside edge of the studs, whereas

the floor plate crushed at the inside edge. After the maximum load had been reached, the studs cracked near midheight and continued to crush into both top plate and floor plate, the plaster cracked transversely and diagonally, and the joints in the sheathing boards opened wider.

3. TRANSVERSE LOAD

The results are shown in table 8 and in figure 9 for wall specimens BQ-T1, T2, and T3, loaded on the inside (plastered) face, and in figure 10 for wall specimens BQ-T4, T5, and T6, loaded on the outside face.

In specimens T1, T2, and T3 the plaster cracked longitudinally along each outer stud



FIGURE 10.—Transverse load on wall BQ, load applied to outside face.

Load-deflection (open circles) and load-set (solid circles) results for specimens BQ-T4, T5, and T6 on the span 7 ft. 6 in.

and transversely across the specimen in several places. The first longitudinal cracks occurred at loads of 120, 120, and 90 lb/ft² and deflections of 0.82, 0.71, and 0.61 in., respectively. The first transverse cracks occurred at lath joints at or near midspan at loads of 180, 195, and 195 lb/ft² and deflections of 1.57, 1.73, and 2.03 in., respectively. At loads of 195 and 135 lb/ft² for specimens T1 and T2, respec-

tively, one outer stud of each specimen ruptured under a loading roller. At the maximum load specimen T1 failed by rupture of the two remaining studs between loading rollers, the plaster was broken in several places, but the lath, the sheathing, and the siding were undamaged. Specimen T^2 failed by rupture of the center stud and partial rupture of the remaining outer stud under a loading roller. The plaster was broken in several places, one siding strip was split near midspan, and the siding and sheathing were separated from the studs under the ruptured outer stud. Specimen T3 failed by rupture of the center and one outer stud, and by partial rupture of the other outer stud between loading rollers. The plaster was broken in several places, but the lath, sheathing, and siding were undamaged.



FIGURE 11.—Concentrated load on wall BQ, load applied to inside face. Load-indentation results for specimens BQ-P1, P2, and P3.

In specimens T_4 , T_5 , and T_6 , loaded on the siding, the plaster cracked transversely in several places, about half the cracks occurring at lath joints. The first transverse cracks occurred between the loading rollers at loads of 60, 58, and 50 lb/ft² and deflections of 0.24, 0.28, and 0.24 in., respectively. At loads of 217 and 157 lb/ft² on specimens T_4 and T_6 ,

respectively, one outer stud of each specimen ruptured between the loading rollers. At the maximum load specimen T4 failed by rupture of the two remaining studs between the loading rollers, specimen T5 failed by rupture of all the studs between the loading rollers, and specimen T6 failed by rupture of the center stud and



FIGURE 12.—Concentrated load on wall BQ, load applied to outside face.

Load-indentation results for specimens BQ-P4, P5, and P6.

partial rupture of the remaining outer stud between loading rollers. The plaster was severely cracked, but the lath, sheathing, and siding were undamaged.

4. Concentrated Load

The results are shown in table 8 and in figure 11 for wall specimens BQ-P1, P2, and P3, loaded on the inside face, and in figure 12 for wall specimens BQ-P4, P5, and P6, loaded on the outside face.

The concentrated loads were applied to the inside face of specimens P1, P2, and P3 on the plaster midway between two studs, over a lath joint 2 ft. 8 in. from one end. Each of the specimens failed by punching of the disk through the plaster into the lath. Also, in specimens P1 and P2 the plaster over the two

adjacent studs cracked for about 1 ft along the studs on each side of the disk.

The concentrated loads were applied to the outside face of specimens P4, P5, and P6 on the wood bevel siding midway between studes and from 3 to 4 ft from one end. At loads of 900, 400, and 529 lb on specimens P4, P5, and P6, respectively, the siding split along the grain



FIGURE 13.—Impact load on wall BQ, load applied to inside face.

Height of drop-deflection (open circles) and height of drop-set (solid circles) results for specimens BQ-II, I_2 , and I_3 on the span 7 ft 6 in.

at one edge of the disk. For specimen P4 at a load of 1,000 lb the indentation was 0.084 in., and no other effect was observed. For specimens P5 and P6 at a load of 900 lb the wood crushed locally under the disk, and at the maximum load the specimens failed by punching of the disk through the siding strip.

5. Impact Load

The results are shown in table 8 and in figure 13 for wall specimens BQ-I1, I2, and I3, loaded on the inside face, and in figure 14 for wall specimens BQ-I4, I5, and I6, loaded on the outside face.

The impact loads were applied to the center of the inside face of specimens *I1*, *I2*, and *I3*, the sandbag striking the plaster directly over the center stud. In each specimen at the 3.5-ft drop, the plaster cracked locally under the bag. The plaster cracked longitudinally over an outer stud in each specimen at drops of 4.5, 1.5, and 7.5 ft, and deflections of 0.97. 0.48, and 1.30 in., respectively; it also cracked transversely over a lath joint near midspan at drops of 4.5, 3.5, and 2 ft, and deflections of 0.97, 0.80, and 0.59 in., respectively. At drops of 4.5, 5.5, and 4 ft, respectively, the inside face of each specimen failed and the plaster crushed locally where the sandbag struck. After a drop of 10 ft the sets were 0.118, 0.111, and 0.136 in., respectively; the plaster and lath were broken where the sandbag struck; and one of the outer stude of specimens I1 and I2 cracked, but the outside faces had not failed.



FIGURE 14.—Impact load on wall BQ, load applied to outside face.

Height of drop-deflection (open circles) and height of drop-set (solid circles) results for specimens BQ-I4, I5, and I6 on the span 7 ft 6 in.

The impact loads were applied to the center of the outside face of specimens I4, I5, and I6, the sandbag striking the wood bevel siding directly over the center stud. In each specimen at drops of 1.5, 0.5, 1.5 ft and deflections of 0.51, 0.24, and 0.52 in., respectively, the plaster cracked transversely at a lath joint near midspan. At drops of 4, 5.5, and 4.5 ft, respectively, the inside face of each specimen failed by further cracking of the plaster. In specimen I4 the center stud ruptured at a drop of 5 ft, and at a drop of 6 ft one outer stud ruptured. At a drop of 6.5 ft there was noticeable separation of the lath from the studs, and after the 8.5-ft drop there was

6. RACKING LOAD

Wall specimen BQ-R1 under racking load is shown in figure 15. The results for wall specimens BQ-R1, R2, and R3 are shown in table 8 and figure 16.



FIGURE 15.—Wall specimen BQ-R1 under racking load.

noticeable separation of the siding strips at midspan. After the 10-ft drop the set was 0.835 in. and several sections of lath had fallen from the specimen. In specimen I5 at a drop of 8.5 ft there was noticeable separation of the lath from the studs and at a drop of 9.5 ft the center stud cracked at midspan. After the 10-ft drop the set was 0.067 in. and most of the sections of lath had fallen from the specimen. In specimen I6 the lath separated noticeably from the studs at a drop of 8 ft and one outer stud ruptured at midspan at a drop of 9 ft. After the 10-ft drop the set was 0.133 in. and two sections of lath had fallen from the specimen near midspan. The racking load was applied to the top plate only, and the stop was in contact only with the floor plate at the diagonally opposite corner of the specimen. The specimens were loaded so that the diagonal sheathing was approximately at right angles to a line from the load to the stop. In each of the specimens the plaster cracked in one or in several places, either diagonally parallel to the line from load to stop, or vertically and horizontally along lath joints. The first significant cracks occurred at loads of 1.12, 1.12, and 1.50 kips/ft and deformations of 0.38, 1.03, and 2.17 in./8 ft in specimens R1, R2, and R3, respectively. At loads of 1.62, 1.00, and 1.00 kips/ft, respectively, there was noticeable displacement of the top plate with respect to the sheathing and the lath, the nails pulling through the edges of the sheathing and the lath. At the maximum load each of the specimens failed by shearing of the top plate and studs from the sheathing and lath and by displacement of the top plate horizontally with respect to the studs, the nails



FIGURE 16.—Racking load on wall BQ.

Load-deformation (open circles) and load-set (solid circles) results for specimens BQ-Rl, R2, and R3. The loads are in kips per foot of the face width of specimen (8 ft 0 in).

pulling from the studs and splitting some of the studs at the upper end.

VI. PARTITION BR

1. Description, Sponsor's Statement

Partition BR was a conventional wood frame with lath and plaster as both faces. The frame was similar to that of wall BQ, with the exception that there were girts at midheight and both faces were like the inside face of wall BQ.

The price of this construction in Washington, D. C., as of July 1937, was \$0.29/ft².

The partition specimens were 8 ft 0 in. high, 4 ft 0 in. wide, and 5% in. thick. Each specimen consisted of a wood frame to which two like faces were fastened. The frame consisted of three studs, A, shown in figure 17, fastened to a floor plate, B, a top plate, C, and girts, D, by nails. Both faces consisted of lath, E, and plaster, F. The overhanging edges of the lath were supported by spacer blocks, G. Both faces were coated with paint. Studs.—The studs, A, were Douglas fir, 1% by 3% in. (nominal 2 by 4 in), 7 ft 7% in. long, spaced 1 ft 4 in. on centers. The lower end of each stud was fastened to the floor plate by two 20d common nails driven from the bottom of the plate (not toenailed), and the upper end of each stud was fastened to the top plate



FIGURE 17.—Partition specimen BR.

A, studs; B, floor plate; C, top plate; D, girt; E, lath; F, plaster; G, spacer block.

by two 20d common nails driven from the top of the lower member of the plate.

Floor plate.—The floor plate, B, was Douglas fir, 1% by 3% in. (nominal 2 by 4 in), 4 ft 0 in. long.

Top plate.—The top plate, C, consisted of two pieces of Douglas fir, $1\frac{5}{8}$ by $3\frac{5}{8}$ in. (nominal 2 by 4 in), 4 ft 0 in. long, fastened by three 20d common nails, one in each stud, driven from the top of the top plate.

Girts.—The girts, D, were Douglas fir, 1½ by 3½ in. (nominal 2 by 4 in). The two inner pieces, 1 ft 2½ in. long, were fastened at midheight to the outer studs by either two 16d or two 20d common nails driven through the stud into the girt, and were toenailed to the center stud by two 6d bright box nails. The two outer pieces, $6\frac{5}{16}$ in. long, were placed and supported the overhanging edges of the lath. Each block was centered at a joint between lath courses, and was fastened to the lath by four 1¼-in. plasterboard nails driven through the lath into the block. These spacer blocks are not used in a house.

Plaster.—The plaster, F, was $\frac{3}{6}$ in thick and consisted of a base coat and a finish coat. The lath was dry when the plaster was applied. *Paint.*—Both faces were prepared for paint-



FIGURE 18.—Partition specimen BR-P2 under concentrated load.

between the outer studs and the edge of the specimen. They were toenailed to the studs by two 6d bright box nails.

Lath.—The lath, E, consisted of six courses of "Red Stripe" lath, each course 1 ft 4 in. high, with a small clearance between courses. There was a vertical joint in most courses, centered on a stud, with no clearance between boards at the joint. The lath was fastened to the studs by 1[']/₄-in. plasterboard nails, five nails to each piece of lath at each stud; and to each plate by five nails, one at each stud and one at each end of the plate.

Spacer blocks.—The spacer blocks, G, were shortleaf southern pine, ${}^{25}_{32}$ by $3\frac{5}{8}$ in., 6 in. long,

ing by the application of one coat of size and finished with one coat of interior paint. Paint and size were applied with a brush.

2. Concentrated Load

A steel disk, 1-in. diam, was placed on the face of the specimen and the concentrated loads applied to the disk. Partition specimen BR-P2 under concentrated load is shown in figure 18. The results for partition specimens BR-P1, P2, and P3 are shown in table 9 and in figure 19.

The concentrated loads were applied to one face of each specimen on the plaster midway between two studs over a lath joint. Each of



FIGURE 19.—Concentrated load on partition BR. Load-indentation result for specimens BR-P1, P2, and P3.





the specimens failed by punching of the disk through the plaster. Also, on specimen P3 the plaster over the two adjacent studes cracked for

about 1 ft along the studs on each side of the disk.

TABLE 9. -- Structural properties of partition BR

[Weight, 9.16 lb/ft 2]

Load	Load applied	Speci- men desig- na- tion	Fail- ure of loaded face, height of drop	Fail- ure of oppo- site face, height of drop	Maxi- mum height of drop	Maxi- mum load
Concentrated.	One face	$\left\{\begin{array}{c} P1\\ P2\\ P3\end{array}\right.$	ft	ft	ft	<i>lb</i> 190 295 225
	Average					237
Impact	$\left\{ \begin{matrix} \text{One face; span,} \\ 7 \text{ ft 6 in} \end{matrix} \right.$	$\left\{\begin{array}{c}II\\I2\\I3\\I3\end{array}\right.$	$6.5 \\ 6.5 \\ 5.0$	$ \begin{array}{c} 5.5 \\ 6.5 \\ 5.0 \\ \end{array} $	* 10.0 8.5 10.0	
	Average		6, 0	5.7		

* Test discontinued. Specimen damaged.

3. IMPACT LOAD

The results for partition specimens BR-I1, I2, and I3 are shown in table 9 and in figure 20.

The impact loads were applied to the center of one face of each specimen, the sandbag striking the plaster directly over the center stud. In each of the specimens the plaster on both faces cracked longitudinally along the studs and transversely across each specimen in several places. The first transverse cracks in the face not struck occurred at lath joints near midspan at drops of 0.5, 1.5, and 2.5 ft and deflections of 0.30, 0.52, and 0.86 in. for specimens I1, I2, and I3, respectively. The first transverse cracks in the face struck occurred at lath joints near midspan at drops of 3.5, 4.5, and 4 ft and deflections of 1.02, 1.17, and 1.17 in., respectively. At drops of 6.5 ft for specimens I1 and I2 and 5 ft for specimen I3, the face struck failed and the plaster crushed where the sandbag struck. At drops of 5.5, 6.5, and 5 ft for specimens I1, I2, and I3, respectively, the opposite face failed and the previous cracks widened. At a drop of 10 ft, the set for specimen I1 was 0.229 in., and no studs were broken. In specimen I2 both outer studs ruptured at a drop of 6.5 ft, the center stud ruptured at a drop of 7 ft, and the specimen broke into two pieces at a drop of 8.5 ft. In specimen I3 the center stud ruptured at a drop of 8.5 ft, and at a drop of 10 ft the sandbag broke completely through the specimen; the two outer studs were undamaged.

VII. FLOOR BS

1. Description, Sponsor's Statement

Floor BS was a conventional wood frame with diagonal subflooring and finish flooring as the upper face, and with lath and plaster as the lower face. The lower face was similar to the inside face of wall BQ. Joists.—The joists, A, were longleaf southern pine, 1% by 7½ in. (nominal 2 by 8 in.), 12 ft 2¾ in. long, spaced 1 ft 4 in. on centers. The ends of each joist were fastened to the end members, B, by four 16d common nails driven through the member into the joist.

End members.—The end members, B, were longleaf southern pine, 1% by 7½ in. (nominal 2 by 8 in.), 4 ft 0 in. long.

Bridging.—The bridging, C, was shortleaf southern pine, 1 by 3 in., 1 ft 5¼ in. long. Two



FIGURE 21.—Floor specime n BS. A, joist; B, end member; C, bridging; D, subflooring; E, sheathing paper; F, finish floor; G, lath; H, plaster; I, spacer block; J, ground strip.

The price of this construction in Washington, D. C., as of July 1937, was \$0.43/ft².

The floor specimens were 12 ft 6 in. long, 4 ft 0 in. wide, and 9% in. thick, as shown in figure 21. Each specimen consisted of a wood frame to which the faces were fastened. The frame consisted of three joists, A, fastened to end members, B, at each end by nails and braced at midlength by bridging, C. The upper face consisted of diagonal wood subflooring, D, sheathing paper, E, and finish flooring, F. The lower face consisted of lath, G, and plaster, H. The overhanging edges of the lath were supported by spacer blocks, I, and ground strips, J. The upper face was covered with shellac varnish. The lower face was covered with paint. pieces were placed crosswise, diagonally between the top and the bottom of adjacent joists at midlength, and fastened to the joists by three 8d box nails toenailed through the bridging into the joist.

Subflooring.—The subflooring, D, was shortleaf southern pine, ${}^{25}\!\!/_{32}$ in. thick by $5/\!\!/_4$ in. face width (nominal 1 by 6 in.), tongued and grooved, and fastened at an angle of 48° to the joists by 8d box nails; either one or two nails were driven through each piece into each joist and into the end members for those pieces which were in contact with them.

Sheathing paper.—The sheathing paper, E, consisted of two sheets, 3 ft 0 in. wide and 1 ft 7 in. wide, laid longitudinally to the specimen over the subflooring with a 7-in. lap,

and fastened to the subflooring at each end of the specimen by nine tacks.

Finish flooring.—The finish flooring, F, was white oak, $\frac{13}{16}$ in. thick by $2\frac{14}{4}$ in. face width, tongued-and-grooved, blind-fastened to each joist by one 8d cut flooring nail driven into each piece through the subflooring and into the joist. The flooring strip at one end of the



FIGURE 22.—Transverse load on floor BS.

Load-deflection (open circles) and load-set (solid circles) results for specimens BS-T1, T2, and T3 on the span 12 ft 0 in.

specimen was also fastened by three 8d finishing nails driven from the face of the strip into the end member. At the other end of the specimen a half strip was used to cover the exposed tongue of the preceding strip, and was fastened to the subflooring by three 6d cementcoated box nails toenailed from the exposed edge of the strip into the subflooring.

Lath.—The lath, G, consisted of "Red Stripe" lath, nine full courses and one course cut to 6 in. The lath was applied with a small clearance between courses and with a longitudinal joint in most courses, centered on a joist, with no clearance between lath boards at the joint. The lath was fastened to the joists by 1¼-in. plasterboard nails, five nails to each piece of lath at each joist; and to each end member by five nails, one at each joist and one at each end of the member.

Spacer blocks.—The spacer blocks, I, were shortleaf southern pine, ${}^{2}\%_{2}$ by ${}^{6}{}^{2}\%_{2}$ in., 6 in. long, and supported the overhanging edges of the lath. The blocks were centered at the joints between lath courses, and rested on ground strips. The blocks were fastened to the ground strips and subflooring by 6d cementcoated box nails, two nails toenailed through each block into the subflooring and two nails driven through the ground strip into the block.

Ground strips.—The ground strips, J, were shortleaf southern pine, ${}^{2}\%_{2}$ by 1% in., 12 ft 2% in. long. The lath was fastened to the ground strips by 1%-in. plasterboard nails, five



FIGURE 23.— Concentrated load on floor BS.

Load-indentation results for specimens BS-P1, P2, and P3.

nails for each course driven through the lath into the strip. The ground strips were cut at each lath course just before the specimen was tested, so that they did not affect the strength of the specimen. These ground strips and spacer blocks are not used in a house.

Plaster.—The plaster, H, was % in. thick and consisted of a base coat and a finish coat. The lath was dry when the plaster was applied.

Paint and varnish.—The upper face was finished with one coat of shellac varnish. The lower face was prepared for painting by the application of one coat of size and finished with one coat of inside paint. Varnish, size, and paint were applied with a brush.

2. TRANSVERSE LOAD

The results for floor specimens BS-T1, T2, and T3 are shown in table 10 and in figure 22.

TABLE 10.—Structural properties of floor BS

[Weight, 13.0 lb/ft2]

Load	Load applied	Speci- men desig- nation	Fail- ure of loaded face, height of drop	Fail- ure of oppo- site face, height of drop	Maxi- mum height of drop	Maxi- mum load
Transverse	Upper face; span, 12 ft 0 in. Average	$\left\{\begin{array}{c}T_1\\T_2\\T_3\end{array}\right.$	ft	ft	ft	
Concentrated.	Upper face	$\left\{\begin{array}{c} P1\\ P2\\ P3\end{array}\right.$				<i>lb</i> a 1,000 a 1,000 a 1,000
Impact	Average {Upper face; span, 12 ft 0 in.		(b) (b)	10.0 6.0 8.5	a 10.0 a 10.0 a 10.0 a 10.0	a 1, 000
	Average		(b)	8.2	^a 10. 0	

Test discontinued. Specimen did not fail.
Face did not fail.

On specimens T1, T2, and T3 the plaster cracked transversely at most of the lath joints. The first cracks occurred at loads of 35, 50, and 50 lb/ft^2 and deflections of 0.07, 0.14, and 0.17 in. in specimens T1, T2, and T3, respectively. At a load of 575 lb/ft² one outer joist of specimen T1 cracked between loading rollers, and at the maximum load the specimen failed by rupture of all the joists between the loading rollers. In specimen T2 at a load of 350 lb/ft^2 one outer joist cracked between loading rollers and at the maximum load the specimen failed by rupturing of the other outer joist and crushing at the top of the center joist under a loading roller. At the maximum load specimen T3 failed by rupture of an outer joist and the center joist between loading rollers. Neither the lath nor the flooring separated appreciably from the joists and no large pieces of plaster fell from the lath.

3. Concentrated Load

The results for floor specimens BS-P1, P2, and P3 are shown in table 10 and in figure 23.

The concentrated loads were applied to the upper face midway between joists over an endmatched joint in the finish flooring from 2 to 3 ft from one end. The indentations after a load of 1,000 lb had been applied were 0.008, 0.011, and 0.013 in., for specimens P1, P2, and P3, respectively, and no other effects were observed.

4. IMPACT LOAD

Floor specimen BS-I1 during the impact test is shown in figure 24. The results for floor specimens BS-I1, I2, and I3 are shown in table 10 and in figure 25.

The impact loads were applied to the center of the upper face on the flooring over the center joist. In specimens I1, I2, and I3 the plaster on the lower face cracked transversely at lath joints at one or two places. The first crack occurred near midspan at drops of 3.5, 3, and 1.5 ft and deflections of 0.39, 0.33, and 0.28 in. for specimens I1, I2, and I3, respectively. At drops of 10, 6, and 8.5 ft, respectively, the faces not struck failed by opening of the plaster cracks. After the 10-ft drop the sets were 0.047, 0.046, and 0.050 in., respectively, and no other effects were observed.

VIII. ROOF BT

1. Description, Sponsor's Statement

Roof BT was a conventional wood frame with wood sheathing and asphalt roofing as the upper face, and with lath and plaster as the lower face. The frame was like that of floor BS, with the exception that it was 2 ft longer; and the lower face was similar to that of floor BS.

The price of this construction in Washington, D. C., as of July 1937, was \$0.38/ft².

The roof specimens were 14 ft 6 in. long, 4 ft 0 in. wide, and 9% in. thick. Each specimen consisted of a wood frame to which the faces were fastened. The frame consisted of three rafters, A, shown in figure 26, fastened to end members, B, at each end by nails and braced at midlength by bridging, C. The upper face consisted of wood sheathing, D, and built-up



FIGURE 24.-Floor specimen BS-I1 during the impact test.



FIGURE 25.—Impact load on floor BS.

Height of drop-deflection (open circles) and height of drop-set (solid circles) results for specimens BS-II, 12, and I3 on the span 12 ft 0 in.

asphalt roofing, E. The lower face consisted of lath, F, and plaster, G. The overhanging edges of the lath were supported by spacer blocks, H, and ground strips, I. The lower face was covered with paint.

Rafters.—The rafters, A, were longleaf southern pine, 1% by 7½ in. (nominal 2 by 8 in.), 14 ft 2¾ in. long, spaced 1 ft 4 in. on centers. The ends of each rafter were fastened to the end members, B, by four 16d common nails driven through the end member into the rafter.

End members.—The end members, B, were longleaf southern pine, $1\frac{1}{6}$ by $7\frac{1}{2}$ in. (nominal 2 by 8 in.), 4 ft 0 in. long.

Bridging.—The bridging, C, was shortleaf southern pine, 1 by 3 in., 1 ft 5¼ in. long. The bridging pieces were placed diagonally between top and bottom of adjacent rafters and fastened to each by three 8d box nails toenailed through the end of the bridging into the rafters.

Sheathing.—The sheathing, D, was shortleaf southern pine, ${}^{2}\frac{5}{22}$ in. thick by 5¼ in. face width (nominal 1 by 6 in.), tongued-andgrooved on sides and fastened transversely across the rafters by 8d box nails; two nails were driven through each piece into each rafter and into the end members, for those pieces which were in contact with them.

Asphalt roofing.—The roofing, E, was threeply built-up roofing. The first ply was 30-lb asphalt-saturated felt in strips 36 in. wide, laid over the sheathing across the rafters with a at the joint. The lath was fastened to the rafters by 1¼-in. plasterboard nails, five nails to each course at each rafter; and to each end member by five nails, one nail at each rafter and at each end of the member.

Spacer blocks.- The spacer blocks, H, were shortleaf southern pine, ${}^{2}\!\!/_{32}$ by ${}^{6}\!\!/_{32}$ in., 6 in. long, and supported the overhanging edges of the lath. The blocks were centered at the joints between lath courses, and rested on



FIGURE 26.—Roof specimen BT. A, rafter; B, end member; C, bridging; D, sheathing; E, asphalt roofing; F, lath; G, plaster; H, spacer block; I, ground strip.

2-in. overlap, and fastened to the sheathing by 1-in. roofing nails, with roofing caps under the heads, spaced 7 in. along the laps and 12 in. along the longitudinal edges of the specimen. After mopping down with 30 lb of asphalt per 100 ft², 15-lb felt strips, 36 in. wide, were laid over this ply, with a 19-in. transverse overlap, thus forming two additional plies. Each 15-lb strip was mopped down with 30 lb of asphalt per 100 ft² before placing the next strip. The finished roofing thus consisted of three thicknesses of asphalt-saturated felt, each covered with an asphalt coating.

Lath.—The lath, F, consisted of "Red Stripe" lath, ten full courses and one course cut to 1 ft 2 in. The lath was applied with no clearance between courses and with a longitudinal joint in most courses, centered on a rafter, with no clearance between lath boards ground strips. The blocks were fastened to the ground strips and the sheathing by 8d box nails, two nails through the ground strips or sheathing into each block.

Ground strips.—The ground strips, I, were shortleaf southern pine, ${}^{25}\!\!_{32}$ by $1\frac{5}{5}$ in., 14 ft $2\frac{3}{4}$ in. long. The lath was fastened to the ground strips by $1\frac{1}{4}$ -in. plasterboard nails, five nails for each course driven through the lath into the ground strip. The ground strips were cut at every lath course just before the specimen was tested so that they did not affect the strength of the specimen. These ground strips and spacer blocks are not used in a house.

Plaster.—The plaster, G, was $\frac{3}{6}$ in. thick and consisted of a base coat and a finish coat. The lath was dry when the plaster was applied.

Paint.—The lower face was prepared for painting by the application of one coat of size,



FIGURE 27.-Roof specimen BT-T2 under transverse load.





and finished with one coat of inside paint. Both paint and size were applied with a brush.

2. TRANSVERSE LOAD

Roof specimen BT-T2 under transverse load is shown in figure 27. The results for roof specimens BT-T1, T2, and T3 are shown in table 11 and in figure 28.

TABLE 11.—Structural properties of roof BT [Weight, 11.5 lb/ft ?]

Load	Load applied	Speci- men desig- nation	Maxi- mum load
Transverse	Upper face; span, 14 ft 0 in	$\left\{ egin{array}{c} T1 \ T2 \ T3 \end{array} ight.$	lb/ft ² 282 218 223
	Average		241
Concentrated	Upper face	$\left\{ egin{array}{c} P1 \\ P2 \\ P3 \end{array} ight.$	<i>lb</i> a 1,000 a 1,000 a 1,000
	Average		a 1,000

* Test discontinued. Specimen did not fail.

No initial cracks were observed in the plaster surface of specimen T1, but on the surface of specimen T2 there were two cracks at lath joints $2\frac{1}{2}$ and 4 ft from an end of the specimen. In specimen T3 there was an initial crack at a lath joint under a loading roller.

In each of the specimens under load the plaster cracked transversely at most of the lath joints. The first cracks occurred at loads of 30, 45, and 23 lb/ft² and deflections of 0.17, 0.36, and 0.11 in. in specimens T1, T2, and T3, respectively. In specimens T1 and T2 at the maximum loads the specimens failed by rupture of an outer rafter and the center rafter at or between the loading rollers. In specimen T3at a load of 210 lb/ft² an outer rafter ruptured and at the maximum load the specimen failed by rupture of the two remaining rafters, all rafters breaking between the loading rollers. The lath sections were separated under the broken rafters of all specimens, but no lath or large pieces of plaster fell from the specimens.

3. Concentrated Load

The results for roof specimens BT-P1, P2 and P3 are shown in table 11 and in figure 29.

The concentrated loads were applied to the asphalt of the upper face midway between rafters, over a joint in the sheathing boards from 2 to 3 ft from one end. The indentations after a load of 1,000 lb had been applied were 0.277, 0.389, and 0.446 in., for specimens P1, P2, and P3, respectively, and no other effect was observed.

IX. COMMENTS BY SPONSOR

There are advantages in decreasing the transmission of heat and moisture through the walls of a house. This is particularly true if the house is air-conditioned. Therefore, there has been an increasing demand from the building industry for a low-cost lath which provides heat insulation and moisture resistance and is suitable for plastered walls, partitions, and ceilings.

Using the experience of 45 years in the manufacture of chipboard, strawboard, and jute liner board, "Red Stripe" lath for gypsum plaster was developed to meeet this demand. The two corrugated sheets in the lath provide strength and stiffness and the many enclosed air spaces decrease the heat transmission. Resistance to the transmission of moisture (vapor seal) is provided by the continuous asphalt coating in each corrugated sheet and by the bituminous coating on the edges of the lath.

The lath can be fastened to any wood frame either by lath nails or by "clip strips." It is



FIGURE 29.—Concentrated load on roof BT. Load-indentation results for specimens BT-P1, P2, and P3.

recommended that the lath be fastened to comply with American Standards Association A42.1–1938, Standard Specifications for Gypsum Plastering.

Lath having holes uniformly spaced over the surface is available. The holes provide a mechanical key for the plaster and are designed to increase the fire resistance of the wall.

It is estimated that this lath has been used on about 60 houses built during the past 3 years in the region between the Great Lakes and the Mason and Dixon line, where it has been subjected to wide variations in temperature and humidity. The physical properties of the plaster were determined by the Lime and Gypsum Section of the Bureau, under the supervision of L. S. Wells, with the assistance of W. F. Clark. The thermal conductivity of the lath was determined by H. W. Woolley, of the Heat Transfer Section of the Bureau. The physical properties of the lath were determined by the Paper Section of the Bureau under the supervision of B. W. Scribner, with the assistance of S. G. Weissberg.

The descriptions and drawings of the specimens were prepared by E. J. Schell, G. W. Shaw, and T. J. Hanley, of the Building Practice and Specifications Section, under the supervision of V. B. Phelan, from this information and from the specimens themselves. That Section also cooperated in the preparation of the report.

The structural properties were determined by the Engineering Mechanics Section, under the supervision of H. L. Whittemore and A. H. Stang, with the assistance of the following members of the professional staff: F. Cardile, R. C. Carter, H. Dollar, M. Dubin, A. H. Easton, A. S. Endler, C. D. Johnson, A. J. Sussman, and L. R. Sweetman.

WASHINGTON, August 18, 1939.

Ο

BUILDING MATERIALS AND STRUCTURES REPORTS

On request, the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., will place your name on a special mailing list to receive notices of new reports in this series as soon as they are issued. There will be no charge for receiving such notices. An alternative method is to deposit with the Superintendent of Documents the sum of \$5, with the request that the reports be sent to you as soon as issued, and that the cost thereof be charged against your deposit. This will provide for the mailing of the publications without delay. You will be notified when the amount of your deposit has become exhausted. If 100 copies or more of any paper are ordered at one time, a discount of 25 percent is allowed. Send all orders and remittances to the Superintendent of Documents, U. S. Government Printing

The following publications in this series are now available by purchase from the Superintendent of Documents at the prices indicated:

Office, Washington, D. C.

BMS1	Research on Building Materials and Structures for Use in Low-Cost Housing
BMS2	Methods of Determining the Structural Properties of Low-Cost House Constructions 1
BMS3	Suitability of Fiber Insulating Lath as a Plaster Base
BMS4	Accelerated Aging of Fiber Building Boards
BMS5	Structural Properties of Six Masonry Wall Constructions
DMS6	Survey of Doofing Materials in the Southeastone States
DMG7	Water Darmoshilty of Macapay Walls
DMO	Water remeability of Masonry Wats
DMGO	Methods of Investigation of Surface Treatment for Corrosion Protection of Steel1
BW28	Structural Properties of the Insulated Steel Construction Company's "Frameless-Steel"
	Constructions for Walls, Partitions, Floors, and Roots1
BMS10	Structural Properties of One of the "Keystone Beam Steel Floor" Constructions Spon-
	sored by the H. H. Robertson Co
BMS11	Structural Properties of the Curren Fabrihome Corporation's "Fabrihome" Construc-
	tions for Walls and Partitions1
BMS12	Structural Properties of "Steelox" Constructions for Walls, Partitions, Floors, and Roofs
	Sponsored by Steel Buildings, Inc.
BMS13	Properties of Some Fiber Building Boards of Current Manufacture
BMS14	Indentation and Recovery of Low-Cost Floor Coverings
BMS15	Structural Properties of "Wheeling Long-Span Steel Floor" Construction Sponsored by
DMDIO	the Wheeling Corrugating Co.
DMSIG	Structural Properties of a "Tilgerde" Floor Construction Sponsored by Tilgerde Floor
DIVISIO	Structural ropercies of a Theorete Floor Construction Sponsored by Theorete Floors,
DMOIM	Inc.
BMS17	Sound Insulation of Wall and Floor Constructions
BMS18	Structural Properties of "Pre-Fab" Constructions for Walls, Partitions, and Floors
	Sponsored by the Harnischleger Corporation1
BMS19	Preparation and Revision of Building Codes 1
BMS20	Structural Properties of "Twachtman" Constructions for Walls and Floors Sponsored by
	Connecticut Pre-Cast Buildings Corporation
BMS21	Structural Properties of a Concrete-Block Cavity-Wall Construction Sponsored by the
	National Concrete Masonry Association
BMS22	Structural Properties of "Dun-Ti-Stone" Wall Construction Sponsored by the W. E.
	Dunn Manufacturing Co
BMS23	Structural Properties of a Brick Cavity-Wall Construction Sponsored by the Brick
DINICEO	Manufacturers Association of New York Inc.
BMS24	Structural Properties of a Reinforced-Brick Wall Construction and a Brick-Tile Cavity-
DININGI	Wall Construction Sponsored by the Structural Clay Products Institute
DMS25	Structural Properties of Conventional Wood Frame Constructions for Walls, Partitions
D101520	Bloorg and Doofg
DMCOC	Floors, and Roots
BM520	Structural Properties of Nelson Pre-Cast Concrete Foundation wan Construction
DMCOF	Sponsored by the Nelson Cement Stone Co., Inc
BMS27	Structural Properties of "Bender Steel Home" wall Construction Sponsored by The
	Bender Body Co
BMS28	Backflow Prevention in Over-Rim Water Supplies 1
BMS29	Survey of Roofing Materials in the Northeastern States1
BMS30	Structural Properties of a Wood-Frame Wall Construction Sponsored by the Douglas
	Fir Plywood Association1
BMS31	Structural Properties of "Insulite" Wall and "Insulite" Partition Constructions Spon-
	sored by the Insulite Co1
BMS32	Structural Properties of Two Brick-Concrete-Block Wall Constructions and a Con-
	crete-Block Wall Construction Sponsored by the National Concrete Masonry
	Association 1
BMS35	Stability of Sheathing Papers as Determined by Accelerated Aging
BMS26	Structural Properties of Wood-Frame Well Partition Floor and Roof Constructions
D10000	with "Dad Graine" I ath Congoing by the Worten Dense and Monuferturing G.
	with neuperper Lam opensored by the weston raper and manufacturing Co. 1





X

v



•

.



