

Reference

NBS
PUBLICATIONS

American National Standard

for information systems –

representation of
geographic point locations
for information interchange

Adopted for Use by
the Federal Government

FIPS PUB 70-1

See Notice on Inside
Front Cover

ANSI X3.61-1986

JK

468

.A8A3

No. 70-1

1986

american national standards institute, inc.
1430 broadway, new york, new york 10018

This standard has been adopted for Federal Government use.

Details concerning its use within the Federal Government are contained in Federal Information Processing Standards Publication 70-1, Representation of Geographic Point Locations for Information Interchange. For a complete list of the publications available in the Federal Information Processing Standards Series, write to the Standards Processing Coordinator (ADP), Institute for Computer Sciences and Technology, National Bureau of Standards, Gaithersburg, MD 20899.

Research Information Center
National Bureau of Standards
Gaithersburg, Maryland 20899

ANSI[®]
X3.61-1986
Revision of
ANSI X3.61-1978

American National Standard
for Information Systems –
**Representation of
Geographic Point Locations
for Information Interchange**

Secretariat

Computer and Business Equipment Manufacturers Association

Approved June 23, 1986

American National Standards Institute, Inc

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

**American National Standards Institute
1430 Broadway, New York, New York 10018**

Copyright © 1986 by American National Standards Institute, Inc
All rights reserved.

No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without
the prior written permission of the publisher.

Printed in the United States of America

A2M487/7

Foreword (This Foreword is not part of American National Standard X3.61-1986.)

This standard provides uniform formats for representing geographic point location data in digital form for interchange between and among data systems and to enhance man-to-man communication. Geographic point location refers to the use of a coordinate system to define the position of a point which may be on, above, or below the earth's surface.

Suggestions for the improvement of this standard will be welcome. They should be sent to the Computer and Business Equipment Manufacturers Association, 311 First Street, NW, Suite 500, Washington, DC 20001.

This standard was processed and approved for submittal to ANSI by Accredited Standards Committee on Information Processing Systems, X3. Committee approval of the standard does not necessarily imply that all members voted for its approval. At the time it approved this standard, the X3 Committee had the following members:

Edward Lohse, Chair
Richard Gibson, Vice-Chair
Catherine A. Kachurik, Administrative Secretary

<i>Organization Represented</i>	<i>Name of Representative</i>
American Express	D. I. Seigal Lucille Durfee (Alt)
American Library Association	Paul Peters
American Nuclear Society	Geraldine C. Main D. R. Vondy (Alt)
AMP Incorporated	Patrick E. Lannan Edward Kelly (Alt)
Association for Computing Machinery	Kenneth Magel Jon A. Meads (Alt)
Association of the Institute for Certification of Computer Professionals	Thomas M. Kurihara
AT&T Communications	Henry L. Marchese Richard Gibson (Alt)
AT&T Technologies	Herbert V. Bertine Paul D. Bartoli (Alt) Stuart M. Garland (Alt)
Burroughs Corporation	Stanley Fenner
Control Data Corporation	Charles E. Cooper Keith Lucke (Alt)
Cooperating Users of Burroughs Equipment	Thomas Easterday Donald Miller (Alt)
Data General Corporation	John Pilat Lyman Chapin (Alt)
Data Processing Management Association	Christian G. Meyer Terrance H. Felker (Alt) Ward Arrington (Alt)
Digital Equipment Computer Users Society	William Hancock Dennis Perry (Alt)
Digital Equipment Corporation	Gary S. Robinson Delbert L. Shoemaker (Alt)
Eastman Kodak	Gary Haines Charleton C. Bard (Alt)
General Electric Company	Richard W. Signor William R. Kruesi (Alt)
General Services Administration	William C. Rinehuls Larry I. Jackson (Alt)
GUIDE International	Frank Kirshenbaum Sandra Swartz Abraham (Alt)
Harris Corporation	Walter G. Fredrickson Rajiv Sinha (Alt)
Hewlett-Packard	Donald C. Loughry
Honeywell Information Systems	Thomas J. McNamara David M. Taylor (Alt)

<i>Organization Represented</i>	<i>Name of Representative</i>
IBM Corporation	Mary Anne Gray
	Robert H. Follett (Alt)
IEFF Computer Society	Sava I. Sherr
	Thomas A. Varetoni (Alt)
	T. M. Kurihara (Alt)
Lawrence Berkeley Laboratory	David F. Stevens
	Robert L. Fink (Alt)
Moore Business Forms	Delmer H. Oddy
National Bureau of Standards	Robert E. Rountree
	James H. Burrows (Alt)
National Communications System	George W. White
NCR Corporation	Thomas W. Kern
	A. Raymond Daniels (Alt)
Prime Computer, Inc.	Arthur Norton
Railine Corporation	R. A. Petrash
Recognition Technology Users Association	Herbert F. Schantz
	G. W. Wetzel (Alt)
Scientific Computer Systems Corporation	James A. Baker
	Carl Haberland (Alt)
SHARE, Inc.	Thomas B. Steel
	Robert A. Rannie (Alt)
Sperry Corporation	Marvin W. Bass
	Jean G. Smith (Alt)
Texas Instruments, Inc.	Presley Smith
	Richard F. Trow, Jr (Alt)
3M Company	Paul D. Jahnke
	J. Wade Van Valkenburg (Alt)
Travelers Insurance Companies, Inc.	Joseph T. Brophy
U.S. Department of Defense	Fred Virtue
	Belkis Leong-Hong (Alt)
VIM	Chris Tanner
	Madeleine Sparks (Alt)
VISA U.S.A.	Jean T. McKenna
	Susan Crawford (Alt)
Wang Laboratories, Inc.	Marsha Hayek
	Joseph St. Amand (Alt)
Xerox Corporation	John L. Wheeler
	Roy Pierce (Alt)

Technical Committee X3L8 on Data Representation, which was responsible for the development of this standard, had the following members:

William H. Kenworthy, Chair	Theodore M. Albert
	Martin V. Appel
	Joseph E. Beltramea
	Philip H. Diamond
	Gordon R. Douglas
	Ronald L. Gatto
	Roy F. Hendrix
	Karen H. Kirkbride
	Duane J. Marquis
	Bruce K. Rosen
	Roy G. Saltman
	C. Ronald Trueworthy
	Arthur J. Wright
	Robert S. Drake (Alt)
	Steven M. Goldstein (Alt)
	Paul Haeftner (Alt)
	Paul R. Miller (Alt)
	Dwight H. Ormond (Alt)
	Robert L. Register (Alt)
	Paul J. Sorvo (Alt)
	Henry Tom (Alt)
	Lois A. Winneberger (Alt)

Contents

SECTION

PAGE

1. Purpose and Scope	6
2. Specifications for Geographic Point Location Systems	6
2.1 Representations for Latitude and Longitude	6
2.2 Representations for Universal Transverse Mercator System (UTM) ...	8
2.3 Representations for State Plane Coordinate Systems (SPCSs)	10
3. Specifications for Altitude Data (Optional)	16
3.1 General	16
3.2 Representation of Altitude	16
4. Related Publications	17

Tables

Table 1 Universal Transverse Mercator Zone Locations and Central Meridians	9
Table 2 Zone Representation Codes	11
Table 3 Jurisdictions and State Plane Coordinate Systems	12
Table 4 Jurisdictions, State Plane Coordinate Systems, and Alternate Zone Representations	13
Table 5 List of Publications Necessary for Conversion Computations on the State Plane Coordinate Systems	19

American National Standard for Information Systems –

Representation of Geographic Point Locations for Information Interchange

1. Purpose and Scope

Geographic point location refers to the use of a coordinate system to define the position of a point that may be on, above, or below the earth's surface.

This standard is designed to establish uniform formats for geographic point location data. It provides a means for representing these data in digital form for the purpose of interchanging information among data systems and for improving clarity and accuracy in interpersonal communications.

Specifically, this standard is intended to:

- (1) Provide for uniform representation of geographic point location data
- (2) Minimize the amount of human intervention required for communicating geographic point location data
- (3) Reduce the time required to format and transmit the elements of geographic point location data

There are many systems available for indicating point locations. This standard is applicable only to the three most widely used in the United States: Latitude and Longitude, the Universal Transverse Mercator (UTM) System, and State Plane Coordinate Systems (SPCS). These systems are mathematically interconvertible and are recognized officially by the many surveying and mapping agencies of federal and state governments. This standard does not provide a methodology for use of the three systems covered, nor does it recommend any particular system.

This standard applies to uniquely identified locations and does not necessarily apply to a series of coordinates at small intervals, such as digital cartographic data used to represent linear map features, terrain profiles, or elevation models.

For defining points on, above, or below the earth's surface or for describing the topography,

altitude is required. Therefore, specifications for altitude data are provided as an optional feature of this standard. For consistency with international usage, the word "altitude" is used in preference to elevation.

Determination of specific geographic point location information is the user's responsibility, as is the accuracy and reliability of the information. This standard does not prescribe file sequences, storage media, programming languages, or other features of information processing to be used in its implementation.

A list of references is provided in Section 4 and Table 5 for detailed information on the methodology, techniques, and applications of the three systems.

2. Specifications for Geographic Point Location Systems

2.1 Representations for Latitude and Longitude.

Latitude and longitude are coordinate representations that show locations on the surface of the earth using the earth's equator and the prime meridian (Greenwich, England) as the respective latitudinal and longitudinal origins.

Although there are applications in which only latitude or longitude needs to be recorded, both are usually stated. The sequencing of latitude and longitude then becomes important and is addressed in this standard. Because latitude and longitude are angular quantities, they are expressed in degrees, minutes, and seconds, or, optionally, in radians. The standard provides for the representation of latitude and longitude in decimal fractions of degrees, minutes, seconds, or radians. The designation of the Northern, Southern, Eastern, and Western Hemispheres is also treated.

2.1.1 Sequencing of Latitude and Longitude. Latitude shall be given first to the left when inscribed with longitude on one line, or above when latitude and longitude are given vertically in relationship to each other. Sequencing shall be from high order to low order (left-to-right direction) in expressing degrees, minutes, and seconds in either latitude or longitude. When a decimal fraction of a degree is used, neither minutes nor seconds may be expressed; similarly, when a decimal fraction of a minute is used, no seconds may be expressed.

2.1.2 Use of Separators. Separators are permissible to enhance understanding of the contents of data files. When separators are used, the following guidelines are to be followed:

(1) *Separators between Latitude and Longitude:* Latitude shall be separated from longitude by a comma or a blank. No other symbol shall be used as a separator between these items.

(2) *Separators between Elements within Latitude or Longitude:* No separators shall be used other than the decimal point, as specified in 2.1.3 through 2.1.6.

It is recognized that degrees, minutes, and seconds are conventionally denoted and separated in textual material by using superscripted symbols. For this standard, such designations have not been included as permissible primarily because many data processing machines cannot recognize or reproduce the conventional superscripts.

2.1.3 Representation of Degrees. For both latitude and longitude, when a decimal fraction of a degree is specified, it shall be separated from the whole number of degrees by a decimal point and expressed numerically to the number of places required by the desired precision.

2.1.3.1 Latitude. The degree of latitude shall be represented by a decimal number ranging from 0 through 90. For all values less than 10, a leading zero or blank shall be given (for example, 01, 15, or b3 where b represents a blank or space). All records in the same file shall use either leading blanks or zeros, but not both.

2.1.3.2 Longitude. The degrees of longitude shall be represented by a decimal number ranging from 0 through 180. For values less than 100, leading zero(s) or blanks shall be given (for example, 001, 027, b18, or bb3). All records in the same file shall use either leading blanks or zeros, but not both.

2.1.4 Representation of Minutes. For both latitude and longitude, the minutes shall be represented by a two-digit decimal number ranging from 00 through 59. For values less than 10, a leading zero

shall be given. When a location is indicated by degrees, minutes, and decimal fractions of a minute, the decimal fraction shall be separated from the whole number of minutes by a decimal point and expressed numerically to the number of places required by the desired precision.

2.1.5 Representation of Seconds. For both latitude and longitude, seconds shall be represented by a two-digit decimal number ranging from 00 through 59. For values less than 10, a leading zero shall be given. When a location is indicated by degrees, minutes, seconds, and decimal fractions of a second, the decimal fraction shall be separated from the whole number of seconds by a decimal point and expressed numerically to the number of places required by the desired precision.

2.1.6 Representation of Radians. Another way of representing latitude and longitude is by converting degrees to radians. One degree is equal to 0.017 453 292 519 943 radians.

2.1.6.1 Latitude. Radians of latitude shall be expressed as a one-digit number (0 or 1) followed by a decimal fraction. The maximum value of latitude in radians should not exceed one-half pi (1.570 796 327). See 2.1.8 for a discussion of the precision.

2.1.6.2 Longitude. Radians of longitude shall be expressed as a one-digit number (0, 1, 2, or 3) followed by a decimal fraction. The maximum value of longitude should not exceed pi (3.141 592 654). See 2.1.8 for a discussion of the necessary precision.

2.1.7 Representation of Hemispheric Information. Two methods of representing the hemisphere are permitted. If the alternate representation is used, that information must be included in the documentation accompanying the interchange.

With the exception of radian values, latitudes north of the equator may be specified by an uppercase "N" immediately following the last digit for latitude. Latitudes south of the equator may be designated by an uppercase "S" immediately following the last digit for latitude. A point on the equator shall be assigned to the Northern Hemisphere.

With the exception of radian values, longitudes east of the prime meridian may be specified by an uppercase "E" immediately following the last digit for longitude. Longitudes west of the prime meridian may be designated by an uppercase "W" immediately following the last digit for longitude. A point on the prime meridian shall be assigned to the Eastern Hemisphere. A point on the 180th meridian shall be assigned to the Western Hemisphere.

All radian values shall use the alternate representation of hemispheric information, which is as follows:

Latitudes north of the equator may be specified by a plus sign (+) immediately preceding the digits designating degrees. Latitudes south of the equator may be designated by a minus sign (−) preceding the digits designating degrees. A point on the equator shall be assigned to the Northern Hemisphere. Longitudes east of the prime meridian may be specified by a plus sign (+) immediately preceding the digits designating degrees of longitude. Longitudes west of the meridian may be designated by a minus sign (−) preceding the digits designating degrees. A point on the prime meridian shall be assigned to the Eastern Hemisphere. A point on the 180th meridian shall be assigned to the Western Hemisphere.

2.1.8 Precision. A point can be represented at various levels of precision, as illustrated in the numbered examples below. (Separation is shown by using a comma, with the understanding that a space (blank) could have been used instead of a comma.) The number of digits does not necessarily imply precision.

- | | |
|--|---|
| (1) Degrees and decimal fractions of a degree | 40.20364N,075.00420W
or +40.20364,−075.00420 |
| (2) Degrees and minutes | 4012N,07500W
or +4012, 07500 |
| (3) Degrees, minutes, and decimal fractions of a minute | 4012.22N,07500.25W
or +4012.22,−b7500.25 |
| (4) Degrees, minutes, and seconds | 401213N,0750015W
or +401213,−b750015 |
| (5) Degrees, minutes, seconds, and decimal fractions of a second | 401213.1N,0750015.1W
or +401213.1,−b750015.1 |
| (6) Radians | +0.7017,−1.3091 |

For longitude at the equator, and for latitude anywhere on the earth, the location of a point to the level of precision of 0.01 foot (0.003 meter) on the face of the earth corresponds approximately to angular values (on a great circle) of 0.00000000048 radian, 0.000000028 degree, 0.0000017 minute, or 0.00010 second. This accuracy is the preferred representation and is accomplished by use of the maximum precision in this standard.

Using these values, the preceding examples of latitude and longitude at this level of precision are as follows. The b represents a blank space.

- | | |
|---|---|
| (1) Degrees and decimal fractions of a degree | 40.20364255N,075.00420039W
or +40.20364255,−b75.00420039 |
| (3) Degrees, minutes, and decimal fractions of a minute | 4012.218553N,07500.252023W
or +4012.218553,−b7500.252023 |

- | | |
|--|---|
| (5) Degrees, minutes, seconds, and decimal fractions of a second | 401213.1132N,0750015.1214W
or +401213.1132,−b750015.1214 |
| (6) Radians | +0.7016859338,−1.3090702496 |

The number of decimal places to which any representation of latitude or longitude is carried must, of course, depend on the user's requirements, the accuracy of measuring instruments, and similar factors.

2.2 Representations for Universal Transverse Mercator System (UTM). The Universal Transverse Mercator (UTM) System provides rectangular coordinates that may be used to indicate locations of points on the surface of the earth. The unit of measure is the meter. A point is located by specifying a hemispheric indicator, a zone number, an easting value, and a northing value.

UTM is designed for world use between 80 degrees south latitude, and 84 degrees north latitude. The globe is divided into narrow zones, 6 degrees of longitude in width, starting at the 180 degree meridian of longitude and progressing eastward. The zones are numbered 1 through 60. Each zone has, as its east and west limits, a meridian of longitude. Each zone also has a critical meridian passing through the center of the zone. Table 1 demonstrates the coverage and central meridian of each zone.

A value of 500,000 meters is assigned to the central meridian of each zone in order to avoid negative numbers at the west edge of the zone. The values increase from west to east. For north-south values in the Northern Hemisphere, the equator is assigned 0 meters, and the numbers increase toward the North Pole. In the Southern Hemisphere, the equator has an implied value of 10,000,000 meters and the numbers decrease toward the South Pole.

The location of any point within a zone is given in relation to the central meridian within that zone and the equator. A point's north-south location is obtained by either adding or subtracting the point's distance north or south of the equator. Similarly, a point's east-west location is obtained by either adding or subtracting the point's distance east or west of the central meridian.

A point on the equator, if not otherwise specified, is assigned a default value of zero for its northing and is treated as if it were in the Northern Hemisphere. The default zone assignment for a point on a boundary meridian is the zone to the east of the point.

Table 1
Universal Transverse Mercator Zone Locations
and Central Meridians

Zone	Central Meridian	Range	Zone	Central Meridian	Range
01	177W	180W-174W	31	003E	000E-006E
02	171W	174W-168W	32	009E	006E-012E
03	165W	168W-162W	33	015E	012E-018E
04	159W	162W-156W	34	021E	018E-024E
05	153W	156W-150W	35	027E	024E-030E
06	147W	150W-144W	36	033E	030E-036E
07	141W	144W-138W	37	039E	036E-042E
08	135W	138W-132W	38	045E	042E-048E
09	129W	132W-126W	39	051E	048E-054E
10	123W	126W-120W	40	057E	054E-060E
11	117W	120W-114W	41	063E	060E-066E
12	111W	114W-108W	42	069E	066E-072E
13	105W	108W-102W	43	075E	072E-078E
14	099W	102W-096W	44	081E	078E-084E
15	093W	096W-090W	45	087E	084E-090E
16	087W	090W-084W	46	093E	090E-096E
17	081W	084W-078W	47	099E	096E-102E
18	075W	078W-072W	48	105E	102E-108E
19	069W	072W-066W	49	111E	108E-114E
20	063W	066W-060W	50	117E	114E-120E
21	057W	060W-054W	51	123E	120E-126E
22	051W	054W-048W	52	129E	126E-132E
23	045W	048W-042W	53	135E	132E-138E
24	039W	042W-036W	54	141E	138E-144E
25	033W	036W-030W	55	147E	144E-150E
26	027W	030W-024W	56	153E	150E-156E
27	021W	024W-018W	57	159E	156E-162E
28	015W	018W-012W	58	165E	162E-168E
29	009W	012W-006W	59	171E	168E-174E
30	003W	006W-000E	60	177E	174E-180W

Specification of the ellipsoid used for the UTM projection depends on the portion of the earth's surface being referenced. No provision is made within this standard to define ellipsoid codes or parameters. This information must be communicated within the documentation accompanying the data interchange.

2.2.1 Sequencing of UTM and Hemisphere Codes. The first item of information shall be a code to indicate the hemisphere in which the point is located. A plus sign (+) shall be used to indicate the Northern Hemisphere, and a minus sign (-) to indicate the Southern Hemisphere. The second item of information shall be the zone number indicating the six-degree longitudinal band in which the point is located (01, 02, . . . 60). The third item of information shall be the easting in meters. The last item of information shall be the northing in meters.

2.2.2 Precision. In order to provide the precision

equivalent to that used with the Latitude and Longitude and State Plane Coordinate Systems, UTM shall be recorded to three decimal places.

2.2.3 Use of Separators. Optional separators are permissible to enhance understanding of the contents of data files. When separators are used, the following guidelines shall be followed:

(1) *Separators between Hemisphere Code and Zone Number:* The hemisphere code shall not be separated from the zone number.

(2) *Separators between Zone Number and Easting Value:* The zone number shall be separated from the easting value by a comma or a blank.

(3) *Separators between Elements of UTM Measurements:* The easting value shall be separated from the northing value by a comma or a blank.

(4) *Separators for Precision:* For both easting and northing values, when a decimal fraction of a meter is specified, it shall be separated from the

unit value by a decimal point followed by three digits to provide the necessary precision. The following are examples of the use of UTM positional information:

+18,520381.516,3684572.632
 -18,520381.516,6315427.368

The above examples illustrate two points within the same zone that are equidistant from the equator—one in the Northern Hemisphere and one in the Southern Hemisphere.

The following are examples of UTM geographic point location codes.

Alaska	+05,426453.473,6596814.917
Point on the equator in Columbia, South America	+18,593681.510,0000000.000
A point one millimeter south of the one des- ignated immediately above	-18,593681.510,9999999.999

2.3 Representations for State Plane Coordinate Systems (SPCSs). The State Plane Coordinate Systems (SPCSs) are designed to define the locations of points within a geographic grid system. Similar systems were used in the nineteenth century, but the first formal use was in 1932. There are now State Plane Coordinate Systems in use in each of the 50 United States, as well as in the Commonwealth of Puerto Rico, the U.S. Virgin Islands, American Samoa, and Guam. The District of Columbia is included with the State of Maryland. State Plane Coordinate Systems represent separate, distinct systems for the political jurisdictions involved, as opposed to the universally applicable Latitude and Longitude (see 2.1) and Universal Transverse Mercator (UTM) Systems (see 2.2.).

Nine states, Puerto Rico, American Samoa, and Guam are covered individually by one State Plane Coordinate System or projection. The nine states are: Connecticut, Delaware, Maryland, New Hampshire, New Jersey, North Carolina, Rhode Island, Tennessee, and Vermont. The remaining 41 States and the Virgin Islands are covered individually by from two to ten SPCS projection zones. These systems fall into three general categories, based upon the conformal mapping projection methods utilized:

- (1) The Lambert Projection
- (2) The Transverse Mercator (TM) Projection (not to be confused with the UTM)
- (3) The Oblique Mercator Projection in south-eastern Alaska

A zone may be defined in one of three ways. In each of these three methods, an arbitrary point of origin in latitude and longitude is one element of the definition of the zone. The other element of definition varies with the conformal mapping projection system used in the zone:

- (1) *Lambert Projection*: Two standard parallels of latitude bounding the zone
- (2) *Transverse Mercator Projection*: One central (longitudinal) meridian at a designated longitude
- (3) *Alaska Oblique Mercator Projection*: As defined in detailed Alaska State Plane Coordinate System specifications (see Section 4).

The arbitrary point of origin for each zone is typically located outside the geographic area it covers. This is designed to meet the objective that no coordinate may have a negative value.

2.3.1 Jurisdictional Representation. This representation identifies the 50 states that comprise the United States, as well as the Commonwealth of Puerto Rico, the U.S. Virgin Islands, American Samoa, and Guam. There are two alternative methods for representation of jurisdictions: A two-character abbreviation and a two-digit numeric code. These representations can be found in Table 4 and are derived from FIPS PUB 5-1, "States and Outlying Areas of the United States (including the District of Columbia)." These representations are not used when the four-character zone representation is used (see 2.3.2.2).

2.3.2 Zone Representation. This representation uniquely identifies each of the zones or State Plane Coordinate Systems found within a jurisdiction as represented in accordance with 2.3.1. Two methods are provided in 2.3.2.1 and 2.3.2.2.

2.3.2.1 One-Character or Two-Character Representation. The first method for zone or SPCS representation provides for a left-justified code of one or two characters, which may be alphabetic or numeric. This code will accommodate all zones in the jurisdictions using SPCSs; it is mnemonic and is based on common nomenclature used in the jurisdictions to indicate specific zones. Table 2 shows this code; a "b" represents a blank (space) in the individual code entry. Table 3 is a summary listing of representations for the State Plane Coordinate Systems and zones within all jurisdictions.

2.3.2.2 Four-Character Representation. In this representation, each of the zones or SPCSs in each jurisdiction is uniquely identified by a four-character numeric code. Table 4 is a summary listing of the alternate representations for State Plane Coordinate Systems and zone codes within all jurisdictions. This representation uniquely identifies the jurisdiction as well as the zone.

Table 2
Zone Representation Codes

Code	SPCS Zone Represented	Jurisdictions Concerned
bb	Single zone in a state	Nine states, which have only one SPCS zone, American Samoa, Guam
SH	Offshore	Louisiana
Mb	Mainland	Massachusetts (one of two zones)
Ib	Island	Massachusetts (one of two zones)
CM	Central (TM)	Michigan (see Note 4)
Lb	Long Island	New York (one of four zones)
NC	North Central	Texas (one of five zones)
SC	South Central	Texas (one of five zones)
EC	East Central	Wyoming (one of four zones) (see Notes 1 and 2)
WC	West Central	Wyoming (one of four zones) (see Notes 1 and 2)
Eb	East	Many (see Table 4)
Sb	South	Many (see Table 4)
Wb	West	Many (see Table 4)
Nb	North	Many (see Table 4)
Cb	Central	Many (see Table 4)
01-10	Numerically designated zones	For the following states, as shown: Alaska 01 through 10 California 01 through 07 Hawaii 01 through 05 Wyoming 01 through 04 (see Notes 1 and 2)
Z1	Zone 1	Puerto Rico and U.S. Virgin Islands (St. John, St. Thomas) (see Note 3)
SX	Zone 2	U.S. Virgin Islands (St. Croix) (see Note 3)

NOTES:

(1) Wyoming is shown with two designations; it is shown in Table 3 in the same fashion. It is the only state with both alphabetic and numeric official zone designations.

(2) The codes indicated in 2.3.1 and 2.3.2 shall be applied to the zones indicated in Table 3. For Wyoming only, the numeric zone designations or the alphabetic zone designations are expected to be used separately, without intermixing of codes.

(3) The Commonwealth of Puerto Rico and the Territory of the U.S. Virgin Islands share one zone, except for the Island of St. Croix which is a second, separate zone.

(4) Although three Transverse Mercator zones were originally devised for Michigan by the U.S. Coast and Geodetic Survey, the State has mandated use of Lambert zones devised by Prof. R. M. Berry of the University of Michigan. The Lambert zones are designed for a special spheroid that, although related to the Clarke Spheroid of 1866, is a reference surface above that spheroid. Use of the Lambert zones has supplanted use of the Mercator.

Table 3
Jurisdictions and State Plane Coordinate Systems

Jurisdictions	Abbrev	Numeric Code	E	S	W	N	C	C M	E C	S C	W C	N C	M	I	Z I	S X	L	S H	Blank (One)	Zone Numbers
Alabama	AL	01	X		X															
Alaska	AK	02																		01-10
Arizona	AZ	04	X		X		X													
Arkansas	AR	05		X		X														
California	CA	06																		01-07
Colorado	CO	08		X		X	X													
Connecticut	CT	09																	X	
Delaware	DE	10																	X	
District of Columbia (See Maryland)																				
Florida	FL	12	X		X	X														
Georgia	GA	13	X		X															
Hawaii	HI	15																		01-05
Idaho	ID	16	X		X		X													
Illinois	IL	17	X		X															
Indiana	IN	18	X		X															
Iowa	IA	19		X		X														
Kansas	KS	20		X		X														
Kentucky	KY	21		X		X														
Louisiana	LA	22		X		X												X		
Maine	ME	23	X		X															
Maryland	MD	24																	X	
Massachusetts	MA	25											X	X						
Michigan	MI	26	X	X	X	X	X	X												
Minnesota	MN	27		X		X	X													
Mississippi	MS	28	X		X															
Missouri	MO	29	X		X	X														
Montana	MT	30		X		X	X													
Nebraska	NE	31		X		X														
Nevada	NV	32	X		X		X													
New Hampshire	NH	33																	X	
New Jersey	NJ	34																	X	
New Mexico	NM	35	X		X		X													
New York	NY	36	X		X		X										X			
North Carolina	NC	37																	X	
North Dakota	ND	38		X		X														
Ohio	OH	39		X		X														
Oklahoma	OK	40		X		X														
Oregon	OR	41		X		X														
Pennsylvania	PA	42		X		X														
Rhode Island	RI	44																	X	
South Carolina	SC	45		X		X														
South Dakota	SD	46		X		X														
Tennessee	TN	47																	X	
Texas	TX	48		X		X	X			X		X								
Utah	UT	49		X		X	X													
Vermont	VT	50																	X	
Virginia	VA	51		X		X														
Washington	WA	53		X		X														
West Virginia	WV	54		X		X														
Wisconsin	WI	55		X		X	X													
Wyoming	WY	56	X		X				X		X									01-04
American Samoa	AS	60																	X	
Guam	GU	66																	X	
Puerto Rico*	PR	72													X					
U.S. Virgin Islands*	VI	78													X	X				

*See note 3, Table 2.

Table 4
Jurisdictions, State Plane Coordinate Systems,
and Alternate Zone Representations

Jurisdiction Zone Name or Number	Abbreviation	Numeric Code	Zone Code
Alabama	AL	01	
East			0101
West			0102
Alaska	AK	02	
01 through 10			5001 through 5010
Arizona	AZ	04	
East			0201
Central			0202
West			0203
Arkansas	AR	05	
North			0301
South			0302
California	CA	06	
01 through 07			0401 through 0407
Colorado	CO	08	
North			0501
Central			0502
South			0503
Connecticut	CT	09	
Delaware	DE	10	
District of Columbia (See Maryland)			0600
Florida	FL	12	
East			0700
West			0901
North			0902
Georgia	GA	13	
East			0903
West			1001
Hawaii	HI	15	
01 through 05			1002
Idaho	ID	16	
East			5101 through 5105
Central			1101
West			1102
Illinois	IL	17	
East			1103
West			1201
Indiana	IN	18	
East			1202
West			1301
Iowa	IA	19	
North			1302
South			1401
Kansas	KS	20	
North			1402
South			1501
Kentucky	KY	21	
North			1502
South			1601
Louisiana	LA	22	
North			1602
South			1701
Offshore			1702
Maine	ME	23	
East			1703
West			1801
Maryland	MD	24	
Massachusetts	MA	25	
Mainland			1802
Island			1900
			2001
			2002

(Continued)

Table 4
Jurisdictions, State Plane Coordinate Systems,
and Alternate Zone Representations (Continued)

Jurisdiction Zone Name or Number	Abbreviation	Numeric Code	Zone Code
Michigan	M1	26	
Fast			2101
Central (Transverse Mercator)			2102
West			2103
North			2111
Central (Lambert)			2112
South			2113
Minnesota	MN	27	
North			2201
Central			2202
South			2203
Mississippi	MS	28	
East			2301
West			2302
Missouri	MO	29	
Fast			2401
Central			2402
West			2403
Montana	MT	30	
North			2501
Central			2502
South			2503
Nebraska	NF	31	
North			2601
South			2602
Nevada	NV	32	
East			2701
Central			2702
West			2703
New Hampshire	NH	33	2800
New Jersey	NJ	34	2900
New Mexico	NM	35	
East			3001
Central			3002
West			3003
New York	NY	36	
Fast			3101
Central			3102
West			3103
Long Island			3104
North Carolina	NC	37	3200
North Dakota	ND	38	
North			3301
South			3302
Ohio	OH	39	
North			3401
South			3402
Oklahoma	OK	40	
North			3501
South			3502
Oregon	OR	41	
North			3601
South			3602
Pennsylvania	PA	42	
North			3701
South			3702
Rhode Island	RI	44	3800
South Carolina	SC	45	
North			3901
South			3902

(Continued)

Table 4
Jurisdictions, State Plane Coordinate Systems,
and Alternate Zone Representations (Continued)

Jurisdiction Zone Name or Number	Abbreviation	Numeric Code	Zone Code
South Dakota	SD	46	
North			4001
South			4002
Tennessee	TN	47	4100
Texas	TX	48	
North			4201
North Central			4202
Central			4203
South Central			4204
South			4205
Utah	UT	49	
North			4301
Central			4302
South			4303
Vermont	VT	50	4400
Virginia	VA	51	
North			4501
South			4502
Washington	WA	53	
North			4601
South			4602
West Virginia	WV	54	
North			4701
South			4702
Wisconsin	WI	55	
North			4801
Central			4802
South			4803
Wyoming	WY	56	
East (01)			4901
East Central (02)			4902
West Central (03)			4903
West (04)			4904
Puerto Rico	PR	72	5201
U.S. Virgin Islands	VI	78	
St. John, St. Thomas			5201
St. Croix			5202
American Samoa	AS	60	5300
Guam	GU	66	5400

2.3.3 Sequencing of X Coordinates and Y Coordinates. The X coordinate, which is the east-west location indicator, shall precede (be to the left of, when on one line, and be above, when shown vertically) the Y coordinate, which is the north-south location indicator.

2.3.4 Use of Separators. Separators are permissible to enhance understanding of the contents of data files. When separators are used, the following guidelines shall be followed:

When a choice is indicated between a pair of separator symbols, one symbol alone shall be chosen, so that the same symbol is used as a separator between every field in a record where a separator is used. This is intended to facilitate data interchange. The items described in 2.3.1, 2.3.2, 2.3.5, and 2.3.6 shall be used in left-to-right sequence.

(1) *Separator between Jurisdictional Representation (2.3.1) and the One-Character or Two-Character Zone Representation (2.3.2):* A single comma or blank shall be used. If the four-character representation is chosen, it is preceded by a blank.

(2) *Separator between Zone Representation (2.3.2) and X Coordinate Representation (2.3.5):* A single comma or blank shall be used.

(3) *Separator between X Coordinate Representation (2.3.5) and Y Coordinate Representation (2.3.6):* A single comma or blank shall be used.

2.3.5 X Coordinate Representation. Three methods are available for the designation of this east-west location indicator: (1) the Lambert Projection, (2) the Transverse Mercator Projection, and (3) the Oblique Mercator Projection used in Alaska.

For each of these three methods, the precision requirements shall be the same as those for the Latitude and Longitude (2.1) and Universal Transverse Mercator (2.2) systems. This shall be at the maximum level for precision of 0.01 foot (0.003 meter).

The notation of an X coordinate in an existing SPCS may be expressed by a number of the general magnitude of NNNNNNN.NN. This will suffice for a range of X of not less than 0.01 foot and not more than 9,999,999.99 feet, and is considered to be appropriate for this standard.

As many digits as are required may be used for purposes of internal processing and storage of X coordinate data. For interchange purposes, the following conventions shall apply to the X coordinate representation:

(1) Leading zeros or blanks shall be used in numbers with fewer digits than the permissible maximum.

(2) Where a decimal fraction is used, it shall be one or two positions in length, as required (for example, .1, .15).

(3) Where a decimal fraction is not used, the X coordinate shall be not less than 0000001 foot, and not more than 9999999 feet.

Therefore, for interchange purposes, the maximum size coordinate shall consist of seven high-order decimal digits, that is, NNNNNNN.NN.

2.3.6 Y Coordinate Representation. The requirements for this coordinate shall be the same as those set forth in 2.3.5 for X coordinate representation.

2.3.7 Examples of SPCS Representation. The following are examples of SPCS representation (b represents a blank space):

A point in the Virginia North zone:

VA,Nb,2178364.86,0408632.16

b4501,2178364.86,0408632.16

51,Nb,2178364.86,0408632.16

A point in the Wyoming West Central zone:

WY,WC,0496132.81,3467187.28

b4903,0496132.81,3467187.28

56,WC,0496132.81,3467187.28

2.3.8 Z Coordinate Representation. The altitude coordinate is utilized in some applications, although it is not part of an official SPCS. See Section 3 for formatting of altitude data.

2.3.9 Conversion Computations. Publications containing projection tables for the State Plane Coordinate Systems are available to assist with conversion computations. These are listed in Section 4.

3. Specifications for Altitude Data (Optional)

3.1 General. Altitude of a point, as used in this standard, is defined as the vertical distance in meters either above or below a reference surface. In the United States, this reference surface is the National Geodetic Vertical Datum of 1929, which approximates mean sea level.

If altitude data are included in the representation of the point, those data shall follow the geographic data. They shall be separated by a comma or blank, whichever is used for the geographic portion.

3.2 Representation of Altitude

3.2.1 Precision. Representation of altitude may or may not contain a decimal point. If a representation for an altitude contains a decimal point, the

number of places after the decimal point should reflect the inherent precision of the measurement.

3.2.2 Altitude Data. All altitude measurements shall include a character specifying sign. All altitude measurements below the reference datum shall be designated by a minus sign (−) preceding the number. Measurements at or above the reference datum may be designated by a blank or a plus sign (+), but usage should be consistent throughout a set of data.

3.2.3 Unit of Measurement. When the point data are given in the State Plane Coordinate System, feet are used as the unit measure. Otherwise, the meter is assumed to be the unit measure and the use of feet is optional. When feet are used optionally, this information shall be specified in the documentation associated with the interchange.

3.2.4 Representation of Numbers. The representation for maximum precision in meters will consist of four digits before the decimal point and three digits after the decimal point, for a total of nine characters, including the character for the sign. The representation for maximum precision in feet will consist of five digits before the decimal point and two digits after the decimal point, for a total of nine characters, including the character for the sign. Leading zeros are required for use in numbers that are less than the prescribed maximum number of digits when the maximum precision is specified.

A permissible alternate representation of numbers is as follows: For ocean subsurface or for aircraft and spacecraft data, five or more digits are used before the decimal point, and the number of digits after the decimal point is reduced accordingly to maintain the total of nine characters.

The following are examples of altitude data (b represents a blank space):

Less than	
maximum precision	+45 −130 b200 b10.5
Maximum precision	+0132.417 −2067.008 b1054.020

3.2.5 Sequencing of Data. When present, the altitude data shall follow and be separated from the geographic coordinate data by either a comma or a blank, whichever is used within the geographic coordinate data, or shall be shown below the geographic coordinate data when displayed vertically.

3.2.6 Examples of Altitude Data Using Feet as the Optional Unit of Measurement (b represents a blank space)

Less than	
maximum precision	+125 −390 31625 31.5
Maximum precision	+13396.22 −16201.02 b13152.07

3.2.7 Examples of Altitude Data with Point Coordinate Data (b represents a blank space)

352215.2417N,0800000.1234W,+1000.467
+352215.2417b−0800000.1234bb1000.467
WY,WC,496132.81,3467187.28,+06172.53
+05.426453.473,6596814.917,b1000.467
+435698.2402,−1031213.5568,+bb45.663

4. Related Publications (see Table 5)

Claire, Charles N. State plane coordinates by automatic data processing. Coast and Geodetic Survey Publication No. 62-4. Washington, DC: 1968.

Mitchell, Hugh C.; Lansing, G. Simmons. The State Coordinate Systems (A Manual for Surveyors). Coast and Geodetic Survey Special Publication No. 235. Washington, DC: 1945.

Morgan, Charles O.; McNellis, Jesse M. FORTRAN IV program KANS, for the conversion of general land office locations to latitude and longitude coordinates. State Geological Survey Special Distribution Publication No. 42. Lawrence, Kansas: University of Kansas; 1969.

Renshaw, Richard W. Geo-references — The language of geobase systems. Presented at URISA Conference, San Francisco, California; 1972 August 29–September 2.

U.S. Department of the Army. Universal transverse mercator grid. Technical Report TR 5-241-8; 1958 July.

U.S. Department of Commerce. Geographic base file system; correction update-extension: Bureau of the census procedural manual for the review and correction of the addresses range edit (ADDEDIT) listing (GEO-MT 502); 1973 January.

U.S. Department of Commerce, National Bureau of Standards. States and outlying areas of the United States (including the District of Columbia). FIPS PUB 5.1. Washington, DC: 1970 June 15.

U.S. Department of Commerce, National Technical Information Service. Geoplanning research program systems conceptualization task 2 report. Des Moines, Iowa: 1973 April.

Table 5
List of Publications Necessary for Conversion
Computations on the State Plane Coordinate Systems

Coast and Geodetic Survey Special Publication Number	Publication Title	Coast and Geodetic Survey Special Publication Number	Publication Title
304	Plane Coordinate Projection Tables	286	Plane Coordinate Projection Tables
65-1	Alabama	318	Nebraska
257	Alaska	317	Nevada
289	Arizona	316	New Hampshire
253	Arkansas	324	New Jersey
276	California	323	New Mexico
266	Colorado	272	New York
305	Connecticut	262	North Carolina
255	Delaware	269	North Dakota
322	Florida	287	Ohio
302	Georgia	270	Oklahoma
306	Hawaiian Islands	267	Oregon
303	Idaho	65-2	Pennsylvania
259	Illinois		Puerto Rico and
284	Indiana		U.S. Virgin Islands
285	Iowa	315	Rhode Island
290	Kansas	273	South Carolina
291	Kentucky	263	South Dakota
256	Louisiana (Revised)	268	Tennessee
292	Maine	252	Texas
	Maryland	277	Utah
	(includes Washington, D.C.)	314	Vermont
274	Massachusetts	293	Virginia
65-3	Michigan	271	Washington
264	Minnesota	275	West Virginia
321	Mississippi	288	Wisconsin
319	Missouri	258	Wyoming
261	Montana		

X3.115-1984 Unformatted 80 Megabyte Trident Pack for Use at 370 tpi and 6000 bpi (General, Physical, and Magnetic Characteristics)

X3.116-1986 Recorded Magnetic Tape Cartridge, 4-Track, Serial 0.250 Inch (6.30 mm) 6400 bpi (252 bpmm), Inverted Modified Frequency Modulation Encoded

X3.117-1984 Printable/Image Areas for Text and Facsimile Communication Equipment

X3.118-1984 Financial Services — Personal Identification Number — PIN Pad

X3.119-1984 Contact Start/Stop Storage Disk, 158361 Flux Transitions per Track, 8.268 Inch (210 mm) Outer Diameter and 3.937 inch (100 mm) Inner Diameter

X3.120-1984 Contact Start/Stop Storage Disk

X3.121-1984 Two-Sided, Unformatted, 8-Inch (200-mm), 48-tpi, Double-Density, Flexible Disk Cartridge for 13 262 ftpr Two-Headed Application

X3.122-1986 Computer Graphics Metafile for the Storage and Transfer of Picture Description Information

X3.124-1985 Graphical Kernel System (GKS) Functional Description

X3.124.1-1985 Graphical Kernel System (GKS) FORTRAN Binding

X3.125-1985 Two-Sided, Double-Density, Unformatted 5.25-inch (130-mm), 48-tpi (1,9-tpmm), Flexible Disk Cartridge for 7958 bpr Use

X3.126-1986 One- or Two-Sided Double-Density Unformatted 5.25-inch (130-mm), 96 Tracks per Inch, Flexible Disk Cartridge

X3.127-1987 Unrecorded Magnetic Tape Cartridge for Information Interchange

X3.128-1986 Contact Start-Stop Storage Disk — 83 000 Flux Transitions per Track, 130-mm (5.118-in) Outer Diameter and 40-mm (1.575-in) Inner Diameter

X3.129-1986 Intelligent Peripheral Interface, Physical Level

X3.130-1986 Intelligent Peripheral Interface, Logical Device Specific Command Sets for Magnetic Disk Drive

X3.131-1986 Small Computer Systems Interface

X3.132-1987 Intelligent Peripheral Interface — Logical Device Generic Command Set for Optical and Magnetic Disks

X3.133-1986 Database Language —NDL

X3.135-1986 Database Language — SQL

X3.136-1986 Serial Recorded Magnetic Tape Cartridge for Information Interchange, Four and Nine Track

X3.139-1987 Fiber Distributed Data Interface (FDDI) Token Ring Media Access Control (MAC)

X3.140-1986 Open Systems Interconnection — Connection Oriented Transport Layer Protocol Specification

X3.141-1987 Data Communication Systems and Services — Measurement Methods for User-Oriented Performance Evaluation

X3.146-1987 Device Level Interface for Streaming Cartridge and Cassette Tape Drives

X3.147-1987 Intelligent Peripheral Interface — Logical Device Generic Command Set for Magnetic Tapes

X3.153-1987 Open Systems Interconnection — Basic Connection Oriented Session Protocol Specification

X11.1-1977 Programming Language MUMPS

IEEE 416-1978 Abbreviated Test Language for All Systems (ATLAS)

IEEE 716-1982 Standard C/ATLAS Language

IEEE 717-1982 Standard C/ATLAS Syntax

IEEE 770X3.97-1983 Programming Language PASCAL

IEEE 771-1980 Guide to the Use of ATLAS

ISO 8211-1986 Specifications for a Data Descriptive File for Information Interchange

MIL-STD-1815A-1983 Reference Manual for the Ada Programming Language

NBS-ICST 1-1986 Fingerprint Identification — Data Format for Information Interchange

X3/TRI-82 Dictionary for Information Processing Systems (Technical Report)

American National Standards for Information Processing

- X3.1-1976** Synchronous Signaling Rates for Data Transmission
X3.2-1970 Print Specifications for Magnetic Ink Character Recognition
X3.4-1986 Coded Character Sets — 7-Bit ASCII
X3.5-1970 Flowchart Symbols and Their Usage
X3.6-1965 Perforated Tape Code
X3.9-1978 Programming Language FORTRAN
X3.11-1969 General Purpose Paper Cards
X3.14-1983 Recorded Magnetic Tape (200 CPI, NRZI)
X3.15-1976 Bit Sequencing of the American National Standard Code for Information Interchange in Serial-by-Bit Data Transmission
X3.16-1976 Character Structure and Character Parity Sense for Serial-by-Bit Data Communication in the American National Standard Code for Information Interchange
X3.17-1981 Character Set for Optical Character Recognition (OCR-A)
X3.18-1974 One-Inch Perforated Paper Tape
X3.19-1974 Eleven-Sixteenths-Inch Perforated Paper Tape
X3.20-1967 Take-Up Reels for One-Inch Perforated Tape
X3.21-1967 Rectangular Holes in Twelve-Row Punched Cards
X3.22-1983 Recorded Magnetic Tape (800 CPI, NRZI)
X3.23-1985 Programming Language COBOL
X3.25-1976 Character Structure and Character Parity Sense for Parallel-by-Bit Data Communication in the American National Standard Code for Information Interchange
X3.26-1980 Hollerith Punched Card Code
X3.27-1978 Magnetic Tape Labels and File Structure
X3.28-1976 Procedures for the Use of the Communication Control Characters of American National Standard Code for Information Interchange in Specified Data Communication Links
X3.29-1971 Specifications for Properties of Unpunched Oiled Paper Perforator Tape
X3.30-1986 Representation for Calendar Date and Ordinal Date
X3.31-1973 Structure for the Identification of the Counties of the United States
X3.32-1973 Graphic Representation of the Control Characters of American National Standard Code for Information Interchange
X3.34-1972 Interchange Rolls of Perforated Tape
X3.37-1980 Programming Language APT
X3.38-1972 Identification of States of the United States (Including the District of Columbia)
X3.39-1986 Recorded Magnetic Tape (1600 CPI, PE)
X3.40-1983 Unrecorded Magnetic Tape (9-Track 800 CPI, NRZI; 1600 CPI, PE; and 6250 CPI, GCR)
X3.41-1974 Code Extension Techniques for Use with the 7-Bit Coded Character Set of American National Standard Code for Information Interchange
X3.42-1975 Representation of Numeric Values in Character Strings
X3.43-1986 Representations of Local Time of Day
X3.44-1974 Determination of the Performance of Data Communication Systems
X3.45-1982 Character Set for Handprinting
X3.46-1974 Unrecorded Magnetic Six-Disk Pack (General, Physical, and Magnetic Characteristics)
X3.47-1977 Structure for the Identification of Named Populated Places and Related Entities of the States of the United States for Information Interchange
X3.48-1986 Magnetic Tape Cassettes (3.81-mm [0.150-Inch] Tape at 32 bps [800 bpi], PE)
X3.49-1975 Character Set for Optical Character Recognition (OCR-B)
X3.50-1986 Representations for U.S. Customary, SI, and Other Units to Be Used in Systems with Limited Character Sets
X3.51-1986 Representations of Universal Time, Local Time Differentials, and United States Time Zone References
X3.52-1976 Unrecorded Single-Disk Cartridge (Front Loading, 2200 BPI) (General, Physical, and Magnetic Requirements)
X3.53-1976 Programming Language PL/I
X3.54-1986 Recorded Magnetic Tape (6250 CPI, Group Coded Recording)
X3.55-1982 Unrecorded Magnetic Tape Cartridge, 0.250 Inch (6.30 mm), 1600 bpi (63 bps), Phase encoded
X3.56-1986 Recorded Magnetic Tape Cartridge, 4 Track, 0.250 Inch (6.30 mm), 1600 bpi (63 bps), Phase Encoded
X3.57-1977 Structure for Formatting Message Headings Using the American National Standard Code for Information Interchange for Data Communication Systems Control
X3.58-1977 Unrecorded Eleven-Disk Pack (General, Physical, and Magnetic Requirements)
X3.59-1981 Magnetic Tape Cassettes, Dual Track Complementary Return-to-Bias (CRB) Four-States Recording on 3.81-mm (0.150-Inch) Tape
X3.60-1978 Programming Language Minimal BASIC
X3.61-1986 Representation of Geographic Point Locations
X3.62-1979 Paper Used in Optical Character Recognition (OCR) Systems
X3.63-1981 Unrecorded Twelve-Disk Pack (100 Megabytes) (General, Physical, and Magnetic Requirements)
X3.64-1979 Additional Controls for Use with American National Standard Code for Information Interchange
X3.66-1979 Advanced Data Communication Control Procedures (ADCCP)
X3.72-1981 Parallel Recorded Magnetic Tape Cartridge, 4 Track, 0.250 Inch (6.30 mm), 1600 bpi (63 bps), Phase Encoded
X3.73-1980 Single-Sided Unformatted Flexible Disk Cartridge (for 6631-BPR Use)
X3.74-1981 Programming Language PL/I, General-Purpose Subset
X3.76-1981 Unformatted Single-Disk Cartridge (Top Loading, 200 tpi 4400 bpi) (General, Physical, and Magnetic Requirements)
X3.77-1980 Representation of Pocket Select Characters
X3.78-1981 Representation of Vertical Carriage Positioning Characters in Information Interchange
X3.79-1981 Determination of Performance of Data Communications Systems That Use Bit-Oriented Communication Procedures
X3.80-1981 Interfaces between Flexible Disk Cartridge Drives and Their Host Controllers
X3.82-1980 One-Sided Single-Density Unformatted 5.25-Inch Flexible Disk Cartridge (for 3979-BPR Use)
X3.83-1980 ANSI Sponsorship Procedures for ISO Registration According to ISO 2375
X3.84-1981 Unformatted Twelve-Disk Pack (200 Megabytes) (General, Physical, and Magnetic Requirements)
X3.85-1981 1/2-Inch Magnetic Tape Interchange Using a Self Loading Cartridge
X3.86-1980 Optical Character Recognition (OCR) Inks
X3.88-1981 Computer Program Abstracts
X3.89-1981 Unrecorded Single-Disk, Double-Density Cartridge (Front Loading, 2200 bpi, 200 tpi) (General, Physical, and Magnetic Requirements)
X3.91M-1987 Storage Module Interfaces
X3.92-1981 Data Encryption Algorithm
X3.93M-1981 OCR Character Positioning
X3.94-1985 Programming Language PANGM
X3.95-1982 Microprocessors — Hexadecimal Input/Output, Using 5-Bit and 7-Bit Teleprinters
X3.96-1983 Continuous Business Forms (Single-Part)
X3.98-1983 Text Information Interchange in Page Image Format (PIF)
X3.99-1983 Print Quality Guideline for Optical Character Recognition (OCR)
X3.100-1983 Interface Between Data Terminal Equipment and Data Circuit-Terminating Equipment for Packet Mode Operation with Packet Switched Data Communications Network
X3.101-1984 Interfaces Between Rigid Disk Drive(s) and Host(s)
X3.102-1983 Data Communication Systems and Services — User-Oriented Performance Parameters
X3.103-1983 Unrecorded Magnetic Tape Minicassette for Information Interchange, Coplanar 3.81 mm (0.150 in)
X3.104-1983 Recorded Magnetic Tape Minicassette for Information Interchange, Coplanar 3.81 mm (0.150 in), Phase Encoded
X3.105-1983 Data Link Encryption
X3.106-1983 Modes of Operation for the Data Encryption Algorithm
X3.110-1983 Videotex/Teletext Presentation Level Protocol Syntax
X3.111-1986 Optical Character Recognition (OCR) Matrix Character Sets for OCR-M
X3.112-1984 14-in (356-mm) Diameter Low-Surface-Friction Magnetic Storage Disk
X3.113-1987 Programming Language FULL BASIC
X3.114-1984 Alphanumeric Machines; Coded Character Sets for Keyboard Arrangements in ANSI X4.23-1982 and X4.22-1983

(Continued on reverse)