NBS PUBLICATIONS



NBSIR 80-2080

NDE Publications: 1978

Leonard Mordfin, editor

Office of Nondestructive Evaluation National Measurement Laboratory National Bureau of Standards U.S. Department of Commerce Washington, DC 20234

December 1979

Issued June 1980



U.S. DEPARTMENT OF COMMERCE

NATIONAL BUREAU OF STANDARDS

QC 100 .U56 80-2080 1980 c, 2

.

NBSIR 80-2080

NDE PUBLICATIONS: 1978

MATIONAL BUREAU OF STANDARDS LIBRARY MAY 1 8 1981 Not ucc - in OC 100 . US no. 80-2020 1980 C. 2

Leonard Mordfin, editor

Office of Nondestructive Evaluation National Measurement Laboratory National Bureau of Standards U.S. Department of Commerce Washington, DC 20234

December 1979

Issued June 1980

U.S. DEPARTMENT OF COMMERCE, Philip M. Klutznick, Secretary

Luther H. Hodges, Jr., Deputy Secretary Jordan J. Baruch, Assistant Secretary for Productivity, Technology, and Innovation

NATIONAL BUREAU OF STANDARDS, Ernest Ambler, Director

Table of Contents

		page
1.	Introduction	
2.	Bibliography and Abstracts	
3.	Subject Index	
4.	How to Obtain Copies	

i



Leonard Mordfin

Office of Nondestructive Evaluation National Measurement Laboratory National Bureau of Standards Washington, DC 20234

1. Introduction

51.

This report is the first annual supplement to NBSIR 78-1557, "NDE Publications: 1972-1977". It presents a bibliography of NBS publications on nondestructive evaluation that appeared in the open literature during calendar year 1978. Also included are citations for several publications that appeared in 1977 or prior years but were not listed in the previous compilation. Almost all of these publications were authored by members of the NBS staff and include papers published in non-NBS media as well as papers and reports from the NBS publications series. A few of the publications cited were written for NBS media by non-NBS authors.

31

These publications address a wide variety of NDE methods, both those that are widely used in industry and some that are relatively new. For completeness, several publications dealing with technologies that directly support NDE, such as pattern recognition and piezoelectricity, have been included.

The format of this report is the same as that used previously, with one major exception; brief, edited abstracts are provided for most of the 1978 citations. The bibliography and the abstracts comprise Section 2 of this report. The first 59 entries in the bibliography are listed in alphabetical order by the surname of the first author. The last thirteen entries, Nos. 60 through 72, were added later and do not follow this sequence.

Section 3 of the report is a subject index for the publications listed. This index is quite comprehensive and, when used together with the abstracts and the alphabetical bibliography, may be expected to enable readers to locate publications of interest without difficulty.

The last section of the report provides some assistance to readers wishing to obtain copies of specific publications listed.

Present plans call for issuance of a 1979 supplement in about a year. To this end, corrections or suggestions for improving the format would be welcomed. Comments should be directed to the Office of Nondestructive Evaluation, National Bureau of Standards, Washington, DC 20234.

2. Bibliography and Abstracts

- Albus, J. S., Hierachical interaction between behavior generation and pattern recognition, <u>Proc. Seventh Annual Automation Imagery</u> <u>Pattern Recognition Symp.</u>, <u>College Park</u>, <u>MD</u>, <u>May 23-24</u>, 1977, <u>pp. 343-383</u> (Electronic Industries Assoc., Washington, DC, 1977).
- Belanger, B. C., The role of NBS in traceability to national standards for advanced measurement systems, <u>Proc. Industry/Joint</u> <u>Services Automatic Test Conf. and Workshop on Advanced Test</u> <u>Technology Management and Support, San Diego, CA, Apr. 3-7, 1978</u>, pp. 295-296 (National Security Industrial Association, Washington, DC, 1978).

NBS's role in traceability to national standards for automated test equipment (ATE) is described. The meaning of traceability vis-a-vis ATE is discussed.

 Bennett, L. H., Page, C. H., Swartzendruber, L. J., Comments on units in magnetism, J. Res. Nat. Bur. Stand. (U.S.), 83, No. 1, 9-12 (Jan.-Feb., 1978).

Suggestions are given on how to express magnetic quantities in SI units.

 Berger, H., Californium-252 as a source for thermal neutron radiography, <u>Proc. Int. Symp. on Californium-252 Utilization</u>, <u>Paris, France, Apr. 26-28, 1976</u>, pp. V-1 to V-14 (E. I. du Pont de Nemours and Co., Aiken, SC, 1978).

Thermal neutron radiography is compared to other methods for nondestructive evaluation; it is shown to offer advantages in many aerospace and nuclear inspection areas. Descriptions and economics of neutron sources including reactors, subcritical assemblies, accelerators and radioactive sources are given. All can be considered for in-plant inspection use; the higher yield sources offer initial economic advantages. Radioactive sources are well suited for field applications.

 Berger, H., Mordfin, L., Calibrations and standards for nondestructive testing, <u>Mater. Eval. 36</u>, No. 11, 36-39 (American Society for Nondestructive Testing, Evanston, IL, Oct., 1978).

Improved nondestructive testing (NDT) standards and calibrations are needed to provide greater reproducibility of NDT measurements and to provide improvements in the quantitative characterization of defects. Different calibration and standards concepts may be required to meet these two needs. This theme is developed and illustrated by radiographic measurements of Trans-Alaska oil pipeline girth welds. 6. Berger, H., Nondestructive testing standards--The role of NBS, Proc. 1978 Annual Meeting American Nuclear Society on Nondestructive Testing in the Nuclear Power Industries, San Diego, CA, June 18-22, 1978, 28, 124-125 (American Nuclear Society, Inc., La Grange Park, IL, 1978).

Reliable, reproducible and meaningful nondestructive inspection has been a goal of the nuclear power industry from the beginning. A new NBS program, Nondestructive Evalution (NDE), is beginning to contribute toward that goal for nuclear power and other qualityconscious industries. A near-term objective of the program is to provide means to improve nondestructive measurement reliability and reproducibility. The long-term objective of the NBS work is to gain a better understanding of the meaning of NDE measurements in terms of material or system performance.

 Birnbaum, G., "New" candidates for ultrasonic NDE standards and calibrations, <u>Proc. ARPA/AFML Review of Progress in Quantitative</u> <u>NDE, Ithaca, NY, June 14-17, 1977</u>, Report AFML-TR-78-55, pp. 289-293 (Air Force Materials Laboratory, Wright-Patterson Air Force Base, OH, May 1978).

The National Bureau of Standards program in acoustic-ultrasonic calibrations and standards, aimed at solving some of the immediate problems, is reviewed. However, many other standards and calibration procedures for ultrasonic NDE have been proposed or are in use.

To provide a fresh look at this area, particularly as it applies to DoD systems, NBS has initiated a program funded by ARPA to assess the status of the field, determine current and future needs, and propose a plan for realizing these needs.

- Blackburn, D. L., Rubin, S., A nondestructive method for the determination of forward-biased safe-operating-area limits for power transitors, <u>Proc. 1977 Power Electronics Specialists Conf.</u>, Palo Alto, CA, June 14-16, 1977, pp. 17-22 (Oct. 1977).
- 9. Blackburn, D. L., Photovoltaic technique for measuring resistivity variations of high resistivity silicon slices, J. Res. Nat. Bur. Stand. (U.S.), 83, No. 3, 265-271 (May-June 1978).

A description of an automated, photovoltaic system for measuring the resistivity variation of high resistivity, large diameter silicon wafers is given. The photovoltaic technique utilizes a scanning light spot to induce a bulk photovoltage and a change in resistance from which is calculated the local variation in resistivity. This nondestructive technique requires no contacts to the useful fabrication area of the wafer. Block, S. (Chairman, ANSI Subcomittee N43-1), American National Standard N43.2; Radiation safety for x-ray diffraction and fluorescence analysis equipment, Nat. Bur. Stand. (U.S.), Handb. 111 Revised, 20 pages (May 1978) SN003-003-01917, \$1.00.

This standard reviews the types of injuries resulting from accidental exposure to ionizing radiation resulting from the operation of x-ray diffraction and fluorescence analysis equipment, establishes equipment design criteria, sets up requirements for approved operating procedures, and recommends the establishment of health surveillance, and personnel monitoring programs.

11. Broadhurst, M. G., Davis, G. T., McKinney, J. E., Collins, R. E., Piezoelectricity and pyroelectricity in polyvinylidene fluoride--A model, J. Appl. Phys. 49, No. 10, 4992-4997 (Oct. 1978).

A description is given of the molecular and morphological structure of polyvinylidene fluoride and a classical model is proposed for calculating the piezoelectric and pyroelectric properties.

 Busching, H. W., Mathey, R. G., Rossiter, W. J., Jr., Cullen, W. C., Effects of moisture in built-up roofing--A state-of-the art literature survey, Nat. Bur. Stand. (U.S.), Tech. Note 965, 78 pages (July 1978) SN003-003-01944-5, \$2.40.

A literature review of the effects of moisture on built-up roofing was made. Nondestructive evaluative methods to locate moisture in roofing systems were summarized and include gravimetric, nuclear, capacitance, infrared imagery, electrical resistance, and microwave methods.

- 13. Caswell, R. S., Neutron measurement intercomparisons, (Proc. Intl. Course at Varenna, Italy, Sept.-Oct. 1974), Paper D-1 in <u>Ionizing</u> <u>Radiation Metrology</u>, pp. 113-132 (Editrice Compositori Bologna, Italy, 1977).
- Christou, A., Semiconductor measurement technology: Automated scanning low-energy electron probe (ASLEEP) for semiconductor wafer diagnostics, Nat. Bur. Stand. (U.S.), Spec. Publ. 400-30, 38 pages (Apr. 1978) SN003-003-01905-4, \$1.50.
- Chwirut, D. J., Boswell, G. D., The evaluation of search units used for ultrasonic reference block calibrations, NBSIR 78-1454, 30 pages (Feb. 1978). Order from NTIS as PB280311, \$4.50.

The effects of using different (nominally identical) quartz search units in the evaluation of ASTM-type standard reference blocks are determined. Various characteristics of the search units are measured and correlated with the amplitude of the ultrasonic response from reference blocks to determine which characteristics must be specified if reproducible results are to be obtained. It is shown by a series of experiments that the exact shape of the distance-amplitude curve in water (axial profile) is a primary characteristic that must be considered. When operational corrections for differences in axial profiles are made, the variability in ultrasonic responses from reference blocks, measured with different search units, is reduced from about 25 percent to 4 percent.

16. Cramp, A. P., Berger, H. W., The development of improved portable x-ray fluorescent lead paint analyzers and lead paint reference standards, Proc. 4th Joint Conf. on Sensing of Environmental Pollutants, New Orleans, LA, Nov. 6-11, 1977, pp. 354-359 (American Chemical Society, Washington, DC, 1978).

Portable x-ray fluorescent lead analyzers offer the most cost effective rapid and adaptable means for the nondestructive detection and measurement of lead paint in housing. This paper discusses the performance and operating characteristics of the lead analyzers developed under HUD contracts and the lead paint reference materials developed by the National Bureau of Standards.

- 17. Cramp, A. P., Berger, H. W., Evaluation of new portable x-ray fluorescent lead analyzers for measuring lead in paint, NBSIR 78-1466, 59 pages (May 1978). Order from NTIS as PB282254, \$5.25.
- 18. Davis, G. T., Broadhurst, M. G., Piezoelectricity and pyroelectricity in polar polymers, <u>Proc. Intl. Symp. on Electrets and Dielectrics</u>, <u>Sao Carlos, Brazil, Sept. 1-6, 1975</u>, pp. 299-319 (Instituto de Fisica e Quimica de Sao Carlos, Universidade de Sao Paulo, 13560 Sao Carlos, SP, Brazil, 1977).
- 19. Davis, G. T., Broadhurst, M. G., Piezoelectricity and pyroelectricity in a polyvinylidenefluoride copolymer, (Proc. Conf. on Electrical Insulation and Dielectric Phenomena, Gaithersburg, MD, Nov. 3-6, 1975), <u>1975 Annual Report</u>, pp. 37-44 (National Academy of Sciences, Washington, DC, 1978).
- 20. Davis, G. T., McKinney, J. E., Broadhurst, M. G., Roth, S. C., Electric-field-induced phase changes in poly(vinylidene fluoride), J. Appl. Phys. 49, No. 10, 4998-5002 (Oct. 1978).
- 21. Dick, C. E., Motz, J. W., New method for the experimental evaluation of x-ray grids, <u>Med. Phys. 5</u>, No. 2, 133-140 (Mar.-Apr. 1978).
- Dick, C. E., Soares, C. G., Motz, J. W., X-ray scatter data for diagnostic radiology, Phys. Med. Biol. 23, No. 6, 1076-1085 (1978).

The ratio of the scattered to the total x-ray fluence (scatter fraction) at the center of the image plane for x-rays transmitted through polystyrene phantoms has been measured.

 Dietz, D. R., Norton, S. J., Linzer, M., Wideband annular array response, (Proc. 1978 Ultrasonics Symp.), <u>IEEE Cat. No. 78CH</u> <u>1344-1 SU</u>, pp. 206-211 (Institute of Electrical and Electronic Engineers, New York, NY, 1978).

Theoretical calculations and experimental measurements of the response of a wideband annular array are presented.

24. Duvall, K. C., Meier, M. M., Wasson, O. A., Huynh, V. D., Neutron flux intercomparison at NBS, <u>J. Res. Nat. Bur. Stand. (U.S.)</u>, 83, No. 6, 555-561 (Nov. - Dec. 1978).

NBS participation in an International Bureau of Weights and Measures sponsored neutron flux intercomparison is described. The efficiencies of two transfer instruments were determined and compared to the quantities determined at other participating standards laboratories.

- 25. Edelman, S., Piezoelectric and pyroelectric polymer sensors, Proc. Conf. on Sensor Technology for Battlefield and Physical Security Applications, Fort Belvoir, VA, July 13-15, 1977, pp. 204-212 (U.S. Army Mobility Equipment Research and Development Command, Fort Belvoir, VA, July 1977).
- 26. Eisenhower, E. H. (Chairman, ANSI Subcommittee N43-3.4), American National Standard N433.1; Safe design and use of self-contained, dry storage gamma irradiators (Category I), Nat. Bur. Stand. (U.S.), Handb. 127, 22 pages (July 1978) SN003-003-01913-5, \$1.10.

This standard applies to self-contained, dry source storage irradiators (Category I) that contain sealed gamma emitting sources for the irradiation of objects or materials. It establishes the criteria to be used in the proper design, fabrication, installation, use, and maintenance of these irradiators which will ensure a high degree of radiation safety at all times.

 Eisenhower, E. H. (Chairman, ANSI Subcommittee N43-3.3), American National Standard N542; Sealed radioactive sources, classification, Nat. Bur. Stand. (U.S.), Handb. 126, 28 pages (July 1978) SN003-003-01903-8, \$1.20.

This standard establishes a system of classification of sealed radioactive sources based on performance specifications related to radiation safety. It provides a manufacturer of sealed sources with a series of tests for evaluating the safety of his product under specified conditions, and also assists a user of such sources to select a type which suits the intended application insofar as maintenance of source integrity is concerned. Ellerbruch, D. A., Belsher, D. R., Electromagnetic technique of measuring coal layer thickness, <u>IEEE Trans. Geosci. Electron. GE-16</u>, No. 2, 126-133 (Apr. 1978).

An FM-CW microwave system was investigated for measuring coal layer thickness. Measurements were made in three different mines. The results indicate that layer thickness can be determined in most cases.

29. Engen, G. G., Advances in microwave measurement science, Proc. IEEE 66, No. 4, 374-384 (Apr. 1978).

With the recent impact of digital technology, a review of the subject of microwave measurements is timely. Following a brief summary of those features which make this a unique science, the current status of the so-called "basic standards" for microwave measurements is noted. This is followed by a review of the use of digital techniques, power equation concepts, connector problems, and related developments. Finally, certain projections for the future are made.

- 30. Evans, J. M., Jr., Keynote address, Proc. Second Conf. Automatic Inspection and Product Control, Chicago, IL, Oct. 19-21, 1976, pp. XIII-XXIII (IIT Research Institute, Chicago, IL, 1976).
- 31. Feldman, A., Measurement of the photoelastic constants of optical materials, <u>Opt. Eng. 17</u>, No. 5, 453-462 (Sept.-Oct. 1978).

The photoelastic constants describe the effect of stress or strain on the refractive indices of material. Interferometric and polarimetric techniques are described for measuring piezo-optic coefficients under static loading conditions. Acousto-optic and Brillouin scattering techniques are described for measuring elasto-optic constants.

32. Fong, J. T., Uncertainties in fatigue life prediction and a rational definition of safety factors, <u>Nuclear Engineering and Design 51</u>, 45-54 (1978).

To cope with uncertainties in mechanical and structural design, engineers exercise their judgement through the use of safety factors based on service experience and laboratory data on relevant design parameters. The relationship between the size of a safety factor and the associated risk and cost-benefit estimates of the engineering function, for a given set of data, is exhibited. A system of ranking the importance of different sources of uncertainties, based on an analysis of service data, is proposed along with an example to "refine" the system using up-to-date laboratory and field measurements. The concept of a rational definition of safety factors as a tool for engineers who design under uncertainty is discussed. 33. Fong, J. T., Editor, <u>Inservice data reporting and analysis for</u> pressure vessels, piping, pumps and valves, PVP-PB-032, ASME Bk. No. H00137, 242 pages (American Society of Mechanical Engineers, New York, NY, 1978).

This volume contains thirteen papers presented at a symposium on technical issues which are faced in connection with the safe operations of pressure vessels, piping, pumps and valves.

34. Grabner, L., Spectroscopic technique for the measurement of residual stress in sintered Al₂O₂, J. Appl. Phys. 49, No. 2, 580-583 (Feb. 1978).

Using the R-line fluorescence of trace Cr^{3+} in sintered alumina as an example, a method of analysis is outlined for determining the residual microstress and macrostress in a polycrystalline aggregate. It uses the shift and broadening, induced by residual stress, of a line due to a transition in an atomic system dissolved in the aggregate.

35. Greenspan, M., Breckenridge, F. R. Tschiegg, C. E., Ultrasonic transducer power output by modulated radiation pressure, <u>J. Acoust.</u> Soc. Am. 63, No. 4, 1031-1038 (Apr. 1978).

We have set up and are using an apparatus for the measurement of total sound power output of a piezoelectric transducer radiating into water. This input is modulated at a low frequency and the output power is intercepted by a target which experiences a force at the modulation frequency. The target is mounted on the armature of an electromagnetic receiver provided with an independent coil through which a current at the modulation frequency is adjusted in amplitude and phase, either manually or automatically by feedback, to arrest the motion of the armature. When the armature is stationary the force depends only on the current, and the apparatus can be calibrated using direct current and dead weights. It is thus absolute.

- 36. Greenspan, M., Breckenridge, F. R., Tschiegg, C. E., Ultrasonic transducer power output by modulated radiation pressure (with details), NBSIR 78-1520, 53 pages (July 1978). Order from NTIS as PB289961, \$5.25.
- 37. Heydemann, P. L. M., The exact fractions interferometer, Proc. 1976 Ultrasonics Symp., Annapolis, MD, Sept. 29-Oct. 1, 1976, pp. 649-652 (Institute of Electrical and Electronics Engineers Group on Sonics and Ultrasonics, New York, NY, 1976).
- 38. Hirshfield, A. T., Hoppes, D. D., Schima, F. J., Germanium detector efficiency calibration with NBS standards, Proc. ERDA X- and Gamma-Ray Symp., Ann Arbor, MI, May 19-21, 1976, pp. 90-93 (Available as ERDA Conf. 760539 from NTIS, 1976).

39. Kirsch, R. A., Algorithms for image analysis of wood pulp fibers, NBSIR 78-1442, 30 pages (Jan. 1978). Order from NTIS as PB278622, \$4.50.

Image analysis technology can be used to measure the visible morphology of pulp fibers. But before such measurements can be accepted, it is necessary to achieve precise definition of the necessary measurements in the form of suitable algorithms that have been experimentally tested on images of actual fiber data. We present such measurement results on both semiautomatically traced fiber and on automatically scanned images. We suggest that the specification of the precise image analysis measurements needed in paper manufacturing can facilitate a technology for process control that will result in savings in paper manufacturing cost and in reduction of energy requirements.

 Koyama, R. Y., Detection of deep levels in high power semiconductor materials and devices, J. Res. Nat. Bur. Stand. (U.S.). 83, No. 3, 273-281 (May-June 1978).

TSM and other deep level measurement techniques are used to detect, characterize, and identify deep level defects which control lifetime and leakage in semiconductor devices. Measurements of the gold acceptor defect density in silicon reveal inhomogeneity in the defect distribution which is directly reflected in the leakage current distribution. This apparatus is a useful extension of routine fabrication-line diagnostic tools.

 Kruger, J., Bertocci, U., Escalante, E., Mullen, J. L., Development of in-situ techniques for the detection and measurement of corrosion of copper concentric neutrals in underground environments, NBSIR 78-1486, 60 pages (June 1978). Order from NTIS as PB283708, \$5.25.

The report describes work to develop in-situ methods for detecting corrosion on buried copper wires. Potential and polarization measurements on buried cables have been performed, and methods for distinguishing the signals of interest from interference due to a.c. applied to the cables, as well as d.c. earth currents, have been developed. Laboratory measurements to test possible corrosion detection techniques have been performed. Analysis of electrochemical noise has been developed and tested, and measurements on some electrochemical systems carried out.

42. Linzer, M., Dietz, D., Parks, S. I., Development of high-sensitivity ultrasonic techniques for in-service inspection of nuclear reactors, NUREG-CR-0460, 34 pages (Oct. 1978). Order from NTIS.

An ultrasensitive ultrasonic system, incorporating real-time signal averaging, pulse compression, dynamic focusing and transducer matching, has been developed. The system was shown to be capable of penetrating highly-attenuating material, such as austenitic steel, and of detecting reflections in the presence of strong background signals due to grain scattering.

9

43. McKinney, J. E. Davis, G. T., Piezo- and pyroelectricity of poly (vinylidene fluoride) from plasma poling, (Proc. 175th Meeting of the American Chemical Society, Anaheim, CA, Mar. 12-17, 1978), Paper in <u>Organic Coatings and Plastics Chemistry 38</u>, 271-277 (American Chemical Society, Washington, DC, 1978).

A plasma poling device is described which allows essentially instantaneous poling of polymeric films at room temperature at very high fields. The piezoelectric coefficients were measured and compared with those estimated from the theory of Mopsik and Broadhurst. The theory gives an accurate representation of the piezoelectric coefficients.

44. Mordfin, L., Ed., NDE publications: 1972-1977, NBSIR 78-1557, 35 pages (Nov. 1978). Order from NTIS as PB289755, \$4.50.

This report is a bibliography of 211 NBS publications on NDE and related technologies for the years 1972 through 1977. A detailed subject index is included, as well as information on how copies of many of the publications may be obtained. A preface by Harold Berger, Chief of the NBS Office of Nondestructive Evaluation, cites several early and significant NBS contributions to NDE, some of them dating back fifty years or more.

45. Motz, J. W., Danos, M., Image information content and patient exposure, Med. Phys. 5, No. 1, 8-22 (Jan.-Feb. 1978).

Presently, patient exposure and x-ray tube kilovoltage are determined by image visibility requirements on x-ray film. With image-processing techniques, image visibility may be manipulated and the exposure may be determined only by the desired information content. This work gives quantitative relationships between image information content and patient exposure. Also, for subject thickness larger than approximately 5 cm, the maximum information content may be obtained at a single kilovoltage and filtration with the simultaneous employment of image-enhancement and antiscatter techniques.

46. Novotny, D. B., Ciarlo, D. R., Semiconductor measurement technology: Automated photomask inspection, Nat. Bur. Stand. (U.S.), Spec. Publ. 400-46, 38 pages (Apr. 1978) SN003-003-01912-7, \$1.50.

Methods suitable for automated photomask inspection for visual defects (spots, pinholes, etc.) or dimensional compliance are analyzed and discussed. The analysis includes examinations of the physical principles and the amount of misalignment that can be tolerated. The methods analyzed for visual defect inspection are the optical-overlay; the dual-beam, flying-spot-scanner; the TV-microscope; and the spatialfiltering methods. For dimensional inspection, an analysis of lineedge location and operating criteria for the microdensitometer are presented. 47. Prince, E., Wlodawer, A., Santoro, A., Flat-cone diffractometer utilizing a linear position-sensitive detector, J. Appl. Cryst. 11 173-178 (1978).

The recent development of linear position-sensitive detectors for neutrons and x-rays leads to the possibility of large improvements in the efficiency of data collection in single-crystal diffractometers. In order to take advantage of the properties of a linear positionsensitive detector it is desirable to use a diffraction geometry which causes the diffracted beams from many different reflecting planes to lie in a common plane. A diffractometer utilizing the flat-cone geometry has been constructed.

 Read, D. T., Ledbetter, H. M., Temperature dependence of the elastic constants of an NbTi/Cu superconducting composite, <u>Composites 9</u>, No. 2, 100-104 (Apr. 1978).

Low-temperature elastic properties are reported for a commercial superconducting composite consisting of niobium-titanium filaments in a copper matrix. Both an ultrasonic pulse-superposition technique and a composite-oscillator technique were used.

49. Reite, M., Zimmerman, J., Magnetic phenomena of the central nervous system, Ann. Rev. Biophys. Bioeng. 7, 167-188 (1978).

Several laboratories have contributed to the present state of knowledge of magnetic phenomena of the central nervous system. A useful feature of magnetic detection is that sources in the brain can be localized more precisely, and more easily, than by surface electric potential measurements.

50. Reneker, D. H., Edelman, S., DeReggi, A. S., Vanderhart, D. L., An ndt method using piezoelectric polymer transducers and computerized vibrational spectroscopy, NDT Intl. 11, No. 1, pp. 15-16 (Feb. 1978).

The normal mode vibrational spectrum of an object contains a wealth of information about the mechanical integrity of the object. The nondestructive evaluation of objects by observation of their vibrational spectra is facilitated by the combination of recently developed low mass, high compliance piezoelectric polymer transducers; a synchronized method for exciting the sample; and a small minicomputer capable of making digital Fourier transforms which convert the complicated, oscillatory, decaying signal from the transducer into the intensities and frequencies of normal modes.

51. Ruff, A. W., Discussion on the Paper, "Ferrographic analysis of wear debris from boundary lubrication experiments with a five ring poly-phenyl ether," ASLE Trans. 18, No. 3, 162 (1975).

52. Ruff, A. W., Quantitative methods in wear debris analysis (Proc. Intl. Conf. on Wear of Materials, St. Louis, MO, Apr. 26-28, 1977), Wear 46, 263-272 (1978).

Wear debris has been recovered from a number of test systems and analyzed using different methods. A magnetic debris recovery method was quantitatively evaluated using actual debris samples and collections of manufactured particulates having known sizes and compositions. Small spheres, some containing nickel, were used to simulate debris. Other particulates in different size ranges were used to investigate size resolution, lubricant dilution techniques, particle overlap difficulties, and the general problem of calibration of debris recovery system. A comparison between chemical analysis and particulate analysis is presented. The application of optical and electron microscope methods and x-ray microanalysis in characterizing the wear particulates was carried out.

 Scott, P. B., Johnson, S. E., Watson, G. W., Berger, H., Neutron radiographs using the ionographic process, <u>J. Appl. Phys. 49</u>, No. 10, 5078-5080 (Oct. 1978).

Thermal neutron radiographs have been made using ionographic techniques. With a fluence of 10^7 neutrons/cm² at the image plane, image resolution of three line pairs per mm was demonstrated. It appears possible to make ionographic neutron radiographs using a transmitted fluence of 10^6 neutrons/cm².

54. Shorten, F. J., Ed., NBS Reactor: Summary of activities July 1976 to June 1977, Nat. Bur. Stand. (U.S.), Tech. Note 969, 188 pages (Apr. 1978) SN003-003-01907-1, \$3.50.

This report summarizes all those programs which depend on the NBS reactor. The programs range from the use of neutron beams to study the structure and dynamics of materials to sample irradiations for neutron radiography and nondestructive evaluations.

- 55. Teague, E. C., Uncertainties in calibrating a stylus type surface texture measuring instrument with an interferometrically measured step, Metrologia 14, 39-44 (1978).
- 56. Tighe, N. J., Wiederhorn, S. M., Fracture of brittle materials at high temperature, Report AFML-TR-78-83, 48 pages (Air Force Materials Laboratory, Wright-Patterson Air Force Base, OH, July 1978).

The brittle nature of ceramic materials requires a design approach based on consideration of crack nucleation and growth. If the initial sizes of pre-existing cracks and their rates of growth are known then the time to reach critical size can be predicted. However, state-ofthe-art NDT equipment does not have the sensitivity to detect the flaws in question, which are generally 100 micrometers or less. An upper limit on tolerable flaw size can be obtained by proof testing, but the validity of this approach needs to be demonstrated.

- 57. Wiederhorn, S. M., Tighe, N. J., Application of proof testing to silicon nitride, Proc. ERDA Workshop on Ceramics for Advanced Heat Engines, Orlando, FL, Jan. 24-26, 1977, pp. 247-258 (Available as ERDA CONF-770110 from NTIS, 1977).
- 58. Yonemura, G. T., Light and vision, Paper in <u>Developments in Lighting-1</u>, J. A. Lynes, Ed., Chapter 2, 25-45 (Applied Science Publishers Ltd., Essex, England, 1978).

Three levels of visual information needs are defined. The criteria for recommending levels of illumination should be 'goodness of seeing' rather than 'just barely able to see'. Blur is introduced as a parameter that has been neglected in task description for lighting. The relative contributions of physiological and psychological variables in visual task performance studies are discussed.

- 59. Zapf, T. L., Harvey, M. E., Larsen, N. T., Stoltenberg, R. E., Ultrasonic calorimeter for beam power measurements from 1 to 15 megahertz, (Proc. 1976 Ultrasonics Symp., Annapolis, MD, Sept. 29-Oct. 1, 1976), <u>IEEE Cat. No. 76CH 1120-5 SU</u>, pp. 573-576 (Institute of Electrical Engineers, New York, NY, 1977).
- Blackburn, D. L., Larrabee, R.D., Automated photovoltaic technique for nondestructively measuring resistivity variations of high resistivity silicon slices, (Proc. Topical Conf. on Characterization Techniques for Semiconductor Materials and Devices, Seattle, WA, May 21-26, 1978), Chapter in <u>Electrochemical Society</u>, P. A. Barnes and G. A. Rozgonyi, Eds., <u>78-3</u>, 168-179 (Electrochemical Society, Princeton, NJ, 1978).

An automated, nondestructive photovoltaic technique for measuring the resistivity variation of high resistivity slices is described.

- 61. Eitzen, D. G., Chwirut, D. J., Improved reliability of ultrasonic measurements: Recent NBS activities (abstract only), <u>Paper Summaries</u>, <u>ASNT National Spring Conf., New Orleans, LA, April 3-6, 1978, p. 62</u> (American Society for Nondestructive Testing, Columbus, OH, 1978).
- 62. Ellerbruch, D. A., Jesch, R. L., Jones, R. N., Bussey, H. E., Boyne, H. S., Electromagnetic scattering properties of soils and snow, <u>Proc. 12th Int. Symp. on Remote Sensing of Environment, Ann Arbor,</u> <u>MI, Apr. 20-26, 1978, II</u>, 957-974 (Environmental Research Institute of Michigan, Ann Arbor, MI, 1978).

The electromagnetic scattering properties of soils and snow are being measured in situ under natural environmental conditions. A physical analysis is done at each test site to determine the physical properties of the sample for correlation with its electromagnetic signature.

- 63. Hsu, N. N., Simmons, J. A., Hardy, S. C., Approach to acoustic emission signal analysis - theory and experiment, <u>Proc. ARPA/AFML</u> <u>Review of Progress in Quantitative NDE, Ithaca, NY, June 14-17, 1977</u>, Report AFML-TR-78-55, 166-169 (Air Force Materials Laboratory, Wright-Patterson Air Force Base, OH, May 1978).
- 64. Hsu, N. N., Sachse, W., Review of ultrasonic techniques for measuring residual stress, <u>Paper Summaries</u>, <u>ASNT National Fall Conf.</u>, <u>Denver</u>, <u>C0</u>, <u>Oct.</u> 2-6, 1978 (American Society for Nondestructive Testing, <u>Columbus</u>, <u>OH</u>, 1978).

Various measurement schemes utilizing surface or bulk elastic waves are described with emphasis on approaches to overcome problems with the field of coverage, transducer coupling effects, texturerelated effects, calibration and resolution. Some analytical work is also described.

65. Hsu, N. N., Hardy, S. C., Experiments in acoustic emission waveform analysis for characterization of AE sources, sensors and structures, Paper in <u>Elastic Waves and Non-Destructive Testing of Materials</u>, <u>AMD 29</u>, Y. H. Pao, Ed., ASME Bk. No. H00112, 85-106 (American Society of Mechanical Engineers, New York, NY, 1978).

We review signal processing techniques used to characterize detected AE signals and then report an experimental system consisting of a large plate, a mechanical step-impulse simulator, and a capacitive transducer. The transfer function of the plate can be computed; it provides a basis for analysis. The transfer function of the transducer is shown to be true displacement measurements. The system is used to explicitly determine unknown sources in terms of forcetime functions through a time-domain deconvolution algorithm. The system also provides means to characterize sensors and structures. Finally, we compare spectral and direct time-domain analyses.

66. Kamper, R. A., Status of RF and microwave calibration services at NBS, NCSL Newsletter 18, No. 3, 40 (Dec. 1978).

This note describes the status of rf microwave calibration services at NBS, and gives a schedule for restoration of some services that had been temporarily closed down.

 Lindstrom, R. M., Harrison, S. H., Harris, J. M., Accurate calibration of gold film standards by neutron activation and gravimetry, <u>J. Appl.</u> Phys. 49, No. 12, 5903-5908 (Dec. 1978).

A set of evaporated gold films on silicon substrates has been prepared for use as standards in the measurement of film thickness by Rutherford backscattering.

- 68. Linzer, M., An ultrasensitive ultrasonic system with applications to nondestructive evaluation and medical diagnosis, <u>Proc. Ultrasonics</u> <u>International 77, Brighton, England, June 28-30, 1977</u>, pp. 28-29 (IPC Science and Technology Press, Guildford, Surrey, England, 1977).
- 69. Miller, E. B., Ultrasonic resolution (letter to the editor), <u>Physics</u> <u>Today 31</u>, No. 6, 48-49 (June 1978).
- 70. Naegele, D., Yoon, D. Y., Broadhurst, M. G., Formation of a new crystal form (α) of poly(vinylidene fluoride) under electric field, Macromolecules ^{ρ}11, No. 6, 1297-1298 (Dec. 1978).
- 71. Sachse, W., Hsu, N. N., Eitzen, D. G., Visualization of transducerproduced sound fields in solids, (Proc. 1978 Ultrasonics Symp.), <u>IEEE Cat. No. 78CH 1344-1 SU</u> (Institute of Electrical and Electronic Engineers, New York, NY, 1978).

Broadband ultrasonic pulses and monochromatic ultrasonic waves are visualized in transparent solids using a photoelastic technique. Application is made to the characterization of the sound field radiated by various transducers operating under various excitation and coupling conditions.

72. Sachse, W., Golan, S., The scattering of elastic pulses and the nondestructive evaluation of materials, Paper in <u>Elastic Waves and</u> <u>Non-Destructive Testing of Materials, AMD 29</u>, Y. H. Pao, Ed., ASME Bk. No. HOO112, 11-31 (American Society of Mechanical Engineers, New York, NY, 1978).

This paper is a review of the results of experiments and their interpretation of the scattering of bulk ultrasonic pulses from various smooth and crack-like obstacles imbedded in an elastic solid. For smooth obstacles, either arrival time or spectral analysis of scattered signals can be used to characterize such obstacles. Crack size can be ascertained from the time delays of various signals scattered by the crack.

3. Subject Index Acoustic emission, 7, 25, 63, 65. Automated inspection, 2, 9, 14, 28, 30, 39, 46, 60. Bibliography, 44. Calibration (also see Transducer calibration), 5, 6, 16, 17, 24, 61, 64, 66, 67. Californium-252, 4. Ceramics, 9, 14, 34, 56, 57. Coal, 28. Composite material, 48. Corrosion detection, 41. Elastic constants, 48. Electrochemical noise, 41. Electron probe, 14. Electronic applications and materials, 8, 9, 14, 40, 46, 60. Energy conservation (see also Nuclear applications), 28, 39, 41, 56, 57. Gamma rays, 26, 27, 38. Gold film, 67. Image analysis, 39. Image processing, 45. In-process inspection, 30, 40. Inservice inspection, 33, 42. Lead in paint, 17, 18. Leak testing, 27. Length measurement, 37. Magnetic measurements, 3, 49. Medical applications, 4, 6, 33, 42, 49, 68, 69. Microwave measurements, 12, 28, 29, 62, 66. Moisture measurement, 12, 62. Neutron activation, 67. detection, 24, 27. diffraction, 47. flux, 13, 24. radiography, 4, 53, 54. sources, 4, 14, 27. Nuclear applications, 4, 6, 33, 42, 68. Optical measurements, 9, 31, 46, 52, 55, 60.

Pattern recognition, 1, 39. Photoelasticity, 31, 71. Photomasks (see Electronic applications). Photovoltaic technique, 9, 60. Piezoelectric polymers, 11, 18-20, 25, 43, 50, 70. Piezospectroscopy, 34. Pipelines, 5. Polyvinylidene fluoride (see Piezoelectric polymers). Pressure vessels, 33. Productivity enhancement (see Automated inspection, In-process inspection). Proof testing, 56, 57. Pumps, 33. Radiation safety, 10, 21, 22, 26, 27, 45. Residual stress (see Stress and strain). Resistance and resistivity measurements, 9, 12, 14, 60. Roofing, 12. Safety (see also Radiation safety), 28, 32. Safety factors, 32. Semiconductors (see Electronic applications). Signal processing, 42, 65, 68. Signature analysis, 25, 62, 63. Snow, 62. Soil, 62. Standards, 2, 5-7, 10, 15, 24, 26, 27, 29, 54, 61, 66, 67. Steel, austenitic, 42, 68. Stress and strain, 25, 31, 34, 64. Superconductors, 48. Surface texture, 55. Thermal measurements, 8, 12, 59. Thickness measurement, 28, 62, 67. Transducer calibration and characterization, 7, 15, 35, 36, 59, 61, 63, 65, 71. Transducers, 15, 23, 25, 35, 36, 50, 63, 65, 68. Transistors (see Electronic applications). Ultrasonic testing, 23, 37, 43, 48, 61, 64, 68. Ultrasonics, 7, 15, 23, 35, 36, 59, 69, 72. Vibration testing, 25, 27, 50. Visual testing, 46, 58. Wear debris analysis, 51, 52. Wood, 39. X-ray detection, 47. diffraction, 10, 47, 70. fluorescence, 10, 16, 17. grids, 21, 22, 45. radiography, 5, 21, 45. scatter, 22, 45. 17

4. How to Obtain Copies

Publications which are available from the Superintendent of Documents, US Government Printing Office, Washington, D.C. 20402 are identified by a Stock Number. Prices quoted are those in effect at the time of the issuance of this document. These prices are for the continental United States, its territories and possessions. In the case of all other countries, add 25% for handling. Prices are subject to change; current prices will be charged as of the date of the order processed. An order blank is provided on page 32 of this report. When ordering include the SD Stock Number for each publication. All orders must contain remittance or your SD account number. Remittances should be made by check or money order payable to the Superintendent of Documents. Do not send postage stamps. Foreign remittances should be made either by international money order or draft on an American bank.

Publications which are available from the National Technical Information Service (NTIS), 5285 Port Royal Road, Springfield, VA 22161, are to be ordered by the "PB," "AD," "COM," or NBS publication number. An order form is provided on page 33 of this report. Contact NTIS for the current prices for hard copy; microfiche is available for \$3.00 per publication.

Papers published in the Journal of Research or in non-NBS media are often available from the author, from the publishers, or from a technical library in your area. Except for NBSIR's, serially numbered NBS publications that are out-of-print may often be consulted in a Regional Depository Library.

Order Bl	ank To Superintendent of Docu- ments, Government Print- ing Office, Washington, D.C. 20402 ,19	роя ине с Е 	inclosed o be maile later	r poca.	
Name Street address City Stote	Zip Code	S R C P	ubscription efund oupon Rel ostage	und	
CATALOG NO. TITY DESIRED	TITLE OF PUBLICATION		PRICE PER COPY	TOTAL S	
FOR ADDITIONAL SPACE ATT	ACH ANOTHER SHEET. TOTAL	AMOUNT ENC	LOSED.	5	

IMPORTANT

GP0 868-156

Please include your ZIP CODE when filling out the mailing label below.

U.S. GOVERNMENT PRINTING OFFICE PUBLIC DOCUMENTS DEPARTMENT WASHINGTON, D.C. 20402 OFFICIAL BUSINESS

POSTAGE AND FEES PAID U.S. GOVERNMENT PRINTING OFFICE 375 SPECIAL FOURTH-CLASS RATE BOOK

Name	 	
Street address	 	
City and State	 ZIP Code	

MAIL ORDER TO:							
National Technical Information Service							
5285 Port Royal Road, Springheld Va. 22151		Date _				-	
		Shin to	· /Entor	if different	from ad	droce at loft)	
*		Ship to	b: (Enter	ir dinerent	trom ad	oress at lent.)	,
	Na	ame					
	Ad	dress					
	Cit	ty, State,	ZIP				
	_						
	т	ELEX 89	-9405				
Attention:	L						
	1						
Send me an application for an NTIS deposit account.	Wherever a for	reign sale	toreign	s NOT spe	ci-	FOR ODC USE	RS ORLY
Purchase order no.	add the follow	ving char	ges to e	ach order.	ODC 1	USER COOE	
Check enclosed for \$	\$2.50	for eac	n aocun h microf	iche	CONT. (LAST	6 CHARACTERS	INLY)
Bill me (not applicable to foreign customers) add 50¢ per title.							
Please allow two weeks for delivery on your order		Magnetic	Tape C	7 track	□ 200 BI	PI PI odd parity	Y
If ordering without a document number, by title only, add	a week.	(tape)	. ape [□ 800 BI	PI even pari	ty
			C] 9 track	800 BPI 6	odd parity only	/
Document Number	Routing Code		Check on	ie	0	Unit	Total
bocament Hamber	(Details	Paper	Micro	Other	tity	Price	Price
	Un Reverse)	Сору	fiche	(specify)			
Titles ordered are from:	Governmer	nt Report	ts Annoi	uncements.			
Weekly Government Abstracts.	or Index.				titles	Enter	
9						Grand	
NTISearch,titles	Unknown	Source.			titles	Grand Total	\$
NTISearch,	Unknown Other:	Source.			titles	Grand Total	2

20

JSCOMM-DC 12323-P73

NBS-114A (REV. 9-78)				
U.S. DEPT. OF COMM.	1. PUBLICATION OR REPORT NO.	2. Gov't. Accession No.	3. Recipient's Ac	cession No.
BIBLIOGRAPHIC DATA SHEET	NBSIR 80-2080			
4. TITLE AND SUBTITLE			5. Publication D.	ate
NDE Publications:	1978			
			6. Performing Or	ganization Code
			a standard and	
7. AUTHOR(S)			8. Performing Or	gan. Report No.
Leonard Mordfin,	editor			
9. PERFORMING ORGANIZATIO	N NAME AND ADDRESS		10. Project/Task,	Work Unit No.
				Alter alter a
NATIONAL BUREAU OF S DEPARTMENT OF COMMI WASHINGTON, DC 20234	STANDARDS ERCE		11. Contract/Gran	it No.
12. SPONSORING ORGANIZATIO	N NAME AND COMPLETE ADDRESS (Stre	et, City, State, ZIP)	13. Type of Report	t & Period Covered
			1978 publ	ications
			14 Spansaring Ar	ency Code
			A Sponsoning Ag	and the second
15. SUPPLEMENTARY NOTES	and the spectrum of the spectr		· · · · · · · · · · · · · · · · · · ·	the second second
Document describes a con	nputer program: SF-185, FIPS Software Summ	nary, is attached.		
16. ABSTRACT (A 200-word or 1	ess factual summary of most significant infe	mmation. If document includ	les a significant bi	bliography or
literature survey, mention it h	ere.)			
This report is	a supplement to NRSIR 78-1	557 "NDE Publica	tions: 197	2_1077 "
It is a bibliography	with selected abstracts.	of 72 National B	ureau of St	andards
(NBS) publications of	n nondestructive evaluatio	n (NDE) and relat	ed technolo	gies,
primarily for the ca	lendar year 1978. A detai	led subject index	is include	d, as well
as information on how	w copies of many of the pu	blications may be	obtained.	
A				
17. KEY WORDS (six to twelve en	atries; alphabetical order; capitalize only th	e first letter of the first key	word unless a prop	er name;
Abstracts; acoustic	emission; bibliography; ed	dy currents; inde	x; National	Bureau of
Standards; nondestrue	ctive evaluation; publicat	ions; radiography	; ultrasonio	CS.
18. AVAILABILITY	A Unlimited	19. SECURIT	Y CLASS	21. NO. OF
		(THIS RE		PRINTED PAGES
For Official Distribution.	Do Not Release to NTIS	UNCLASS	IFIED	
Order From Sup. of Doc., 20402, SD Stock No. SNOO	U.S. Government Printing Office, Washingto 03-003-	n, DC 20. SECURIT	Y CLASS GE)	22. Price
X Order From National Tech	nical Information Service (NTIS), Springfiel	d, UNCLASS	FIED	
VA. 22161		ONCLASS	II ICD	

•

PERIODICALS

JOURNAL OF RESEARCH—The Journal of Research of the National Bureau of Standards reports NBS research and development in those disciplines of the physical and engineering sciences in which the Bureau is active. These include physics, chemistry, engineering, mathematics, and computer sciences. Papers cover a broad range of subjects, with major emphasis on measurement methodology, and the basic technology underlying standardization. Also included from time to time are survey articles on topics closely related to the Bureau's technical and scientific programs. As a special service to subscribers each issue contains complete citations to all recent NBS publications in NBS and non-NBS media. Issued six times a year. Annual subscription: domestic \$17.00; foreign \$21.25. Single copy, \$3.00 domestic; \$3.75 foreign.

Note: The Journal was formerly published in two sections: Section A "Physics and Chemistry" and Section B "Mathematical Sciences."

DIMENSIONS/NBS

This monthly magazine is published to inform scientists, engineers, businessmen, industry, teachers, students, and consumers of the latest advances in science and technology, with primary emphasis on the work at NBS. The magazine highlights and reviews such issues as energy research, fire protection, building technology, metric conversion, pollution abatement, health and safety, and consumer product performance. In addition, it reports the results of Bureau programs in measurement standards and techniques, properties of matter and materials, engineering standards and services, instrumentation, and automatic data processing.

Annual subscription: Domestic, \$11.00; Foreign \$13.75

NONPERIODICALS

Monographs—Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

Handbooks—Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications—Include proceedings of conferences sponsored by NBS, NBS annual reports, and other special publications appropriate to this grouping such as wall charts, pocket cards, and bibliographies.

Applied Mathematics Series—Mathematical tables, manuals, and studies of special interest to physicists, engineers, chemists, biologists, mathematicians, computer programmers, and others engaged in scientific and technical work.

National Standard Reference Data Series—Provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated. Developed under a world-wide program coordinated by NBS. Program under authority of National Standard Data Act (Public Law 90-396). NOTE: At present the principal publication outlet for these data is the Journal of Physical and Chemical Reference Data (JPCRD) published quarterly for NBS by the American Chemical Society (ACS) and the American Institute of Physics (AIP). Subscriptions, reprints, and supplements available from ACS, 1155 Sixteenth St. N.W., Wash., D.C. 20056.

Building Science Series-Disseminates technical information developed at the Bureau on building materials, components, systems, and whole structures. The series presents research results, test methods, and performance criteria related to the structural and environmental functions and the durability and safety characteristics of building elements and systems. Technical Notes-Studies or reports which are complete in themselves but restrictive in their treatment of a subject. Analogous to monographs but not so comprehensive in scope or definitive in treatment of the subject area. Often serve as a vehicle for final reports of work performed at NBS under the sponsorship of other government agencies. Voluntary Product Standards-Developed under procedures published by the Department of Commerce in Part 10, Title 15, of the Code of Federal Regulations. The purpose of the standards is to establish nationally recognized requirements for products, and to provide all concerned interests with a basis for common understanding of the characteristics of the products. NBS administers this program as a supplement to the activities of the private sector standardizing organizations.

Consumer Information Series—Practical information, based on NBS research and experience, covering areas of interest to the consumer. Easily understandable language and illustrations provide useful background knowledge for shopping in today's technological marketplace.

Order above NBS publications from: Superintendent of Documents, Government Printing Office, Washington, D.C. 20402.

Order following NBS publications—NBSIR's and FIPS from the National Technical Information Services, Springfield, Va. 22161.

Federal Information Processing Standards Publications (FIPS PUB)—Publications in this series collectively constitute the Federal Information Processing Standards Register. Register serves as the official source of information in the Federal Government regarding standards issued by NBS pursuant to the Federal Property and Administrative Services Act of 1949 as amended, Public Law 89-306 (79 Stat. 1127), and as implemented by Executive Order 11717 (38 FR 12315, dated May 11, 1973) and Part 6 of Title 15 CFR (Code of Federal Regulations).

NBS Interagency Reports (NBSIR)—A special series of interim or final reports on work performed by NBS for outside sponsors (both government and non-government). In general, initial distribution is handled by the sponsor; public distribution is by the National Technical Information Services (Springfield, Va. 22161) in paper copy or microfiche form.

BIBLIOGRAPHIC SUBSCRIPTION SERVICES

The following current-awareness and literature-survey bibliographies are issued periodically by the Bureau:

Cryogenic Data Center Current Awareness Service. A literature survey issued biweekly. Annual subscription: Domestic, \$25.00; Foreign, \$30.00.

Liquified Natural Gas. A literature survey issued quarterly. Annual subscription: \$20.00. Superconducting Devices and Materials. A literature survey issued quarterly. Annual subscription: \$30.00. Send subscription orders and remittances for the preceding bibliographic services to National Bureau of Standards, Cryogenic Data Center (275.02) Boulder, Colorado 80302.

BS-114A (REV. 9-78)			
U.S. DEPT. OF COMM.	. PUBLICATION OR REPORT NO. 2. Gov	Accession No. 3. Recipient's A	ccession No.
BIBLIOGRAPHIC DATA	NRSTP 80- 2080		
	ND31N 00-2000	5. Publication D	ate
N THE AND SUBTILE			ale
NDE Publications.	1079		
NDE PUDITCACIONS:	1970	6. Performing Or	ganization Code
. AUTHOR(S)		8. Performing Or	gan. Report No.
Leonard Mordfin, ed	litor		
PERFORMING ORGANIZATION	NAME AND ADDRESS	10. Project/Task	/Work Unit No.
	~		
NATIONAL BUREAU OF ST	ANDARDS	11. Contract/Gra	nt No.
WASHINGTON, DC 20234	CE		
2. SPONSORING ORGANIZATION	NAME AND COMPLETE ADDRESS (Street, City, St.	13. Type of Repo	ort & Period Covered
	0 (: .	1978 Pub	lications
		14. Sponsoring A	gency Code
			States and States and States
5. SUPPLEMENTARY NOTES			
(NBS) publications primarily for the well as information	on nondestructive evaluation (I calendar year 1978. A detailed n on how copies of many of the p	NDE) and related tech subject index is inc publications may be ol	nologies, luded, as btained.
 7. KEY WORDS (six to twelve entrasoparated by semicolons) 1.bstracts; acoustic estandards; nondestruc 8. AVAILABILITY 7. For Official Distribution 	<pre>ies; elphabetical order; capitalize only the first lette mission; bibliography; eddy cur tive evaluation; publications; X Unlimited Do Not Release to NTIS</pre>	rents; index; Nationa radiography; ultrason 19. SECURITY CLASS (THIS REPORT)	Per name; 1 Bureau of ics. 21. NO. OF PRINTED PAGE 25
		UNCLASSIFIED 20. SECURITY CLASS	25 22. Price
20402, <u>SD Stock No. SN003</u>	5. Government Frinting Office, Washington, DC 003-	(THIS PAGE)	\$5.00
XX Order From National Techni VA. 22161	cal Information Service (NTIS), Springfield,	UNCLASSIFIED	



