

NIST TIME AND FREQUENCY BULLETIN  
NIST IR 6653-09

No. 609 September 2008

1. GENERAL BACKGROUND INFORMATION.....	2
2. TIME SCALE INFORMATION .....	2
3. PHASE DEVIATIONS FOR WWVB AND LORAN-C .....	4
4. BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS.....	5
5. NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS.....	5
6. BIBLIOGRAPHY .....	5

This bulletin is published monthly. Address correspondence to:

Eyvon M. Petty, Editor  
Time and Frequency Division  
National Institute of Standards and Technology  
325 Broadway  
Boulder, CO 80305-3328  
(303) 497-3295  
Email: [pettye@boulder.nist.gov](mailto:pettye@boulder.nist.gov)



---

U.S. DEPARTMENT OF COMMERCE, CARLOS M. GUTIERREZ, Secretary  
NATIONAL INSTITUTE OF STANDARDS AND TECHNOLOGY, James M. Turner, Deputy Director

## 1. GENERAL BACKGROUND INFORMATION

### ACRONYMS AND ABBREVIATIONS USED IN THIS BULLETIN

ACTS	- Automated Computer Time Service		
BIPM	- Bureau International des Poids et Mesures		
CS	- Cesium Standard		
GPS	- Global Positioning System		
IERS	- International Earth Rotation Service		
LORAN	- Long Range Navigation		
MC	- Master Clock		
MJD	- Modified Julian Date		
NIST	- National Institute of Standards and Technology		
NOAA	- National Oceanic and Atmospheric Administration		
NVLAP	- National Voluntary Laboratory Accreditation Program	ns	- nanosecond
SI	- International System of Units	μs	- microsecond
TA	- Atomic Time	ms	- millisecond
TAI	- International Atomic Time	s	- second
USNO	- United States Naval Observatory	min	- minute
UTC	- Coordinated Universal Time		

## 2. TIME SCALE INFORMATION

The values listed below are based on data from the IERS, the USNO, and NIST. The UTC(USNO,MC) - UTC(NIST) values are averaged measurements from all available common-view GPS satellites (see bibliography on page 5). **UTC - UTC(NIST) data are on page 3.**

0000 HOURS COORDINATED UNIVERSAL TIME			
AUG 2008	MJD	UT1-UTC(NIST) (±5 ms)	UTC(USNO,MC) - UTC(NIST) (±20 ns)
7	54685	-457 ms	5 ns
14	54692	-457 ms	5 ns
21	54699	-460 ms	3 ns
28	54706	-462 ms	-2 ns

The master clock pulses used by the WWV, WWVH, and WWVB time-code transmissions are referenced to the UTC(NIST) time scale. Occasionally, 1 s is added to the UTC time scale. This second is called a leap second. Its purpose is to keep the UTC time scale within ±0.9 s of the UT1 astronomical time scale, which changes slightly due to variations in the Earth's rotation.

**NOTE:** A positive leap second will be added at the end of December 2008.

Positive leap seconds, beginning at 23 h 59 min 60 s UTC and ending at 0 h 0 min 0 s UTC, were inserted in the UTC timescale on 30 June 1972, 1981-1983, 1985, 1992, 1993, 1994, and 1997, and on 31 December 1972-1979, 1987, 1989, 1990, 1995, 1998, and 2005.

The use of leap seconds ensures that UT1 - UTC will always be held within ±0.9 s. The current value of UT1 - UTC is called the DUT1 correction. DUT1 corrections are broadcast by WWV, WWVH, WWVB, and ACTS and are printed below. These corrections may be added to received UTC time signals in order to obtain UT1.

	-0.5 s beginning 0000 UTC 07 August 2008
	-0.4 s beginning 0000 UTC 13 March 2008
DUT1 = UT1 - UTC =	-0.3 s beginning 0000 UTC 29 November 2007
	-0.2 s beginning 0000 UTC 14 June 2007

The difference between UTC(NIST) and UTC has been within  $\pm 100$  ns since July 6, 1994. The table below shows values of UTC - UTC(NIST) as supplied by the BIPM in their Circular T publication for the most recent 310 day period in which data are available. Data are given at 10-day intervals. Five day interval data are available in Circular T.

**0000 Hours Coordinated Universal Time**

<b>DATE</b>	<b>MJD</b>	<b>UTC-UTC(NIST) ns</b>
Jul. 22, 2008	54669	3.5
Jul. 12, 2008	54659	4.1
Jul. 02, 2008	54649	3.9
Jun. 22, 2008	54639	1.1
Jun. 12, 2008	54629	-2.0
Jun. 02, 2008	54619	-4.6
May 23, 2008	54609	-7.8
May 13, 2008	54599	-8.4
May 03, 2008	54589	-10.2
Apr. 23, 2008	54579	-10.1
Apr. 13, 2008	54569	-12.8
Apr. 03, 2008	54559	-12.5
Mar. 24, 2008	54549	-12.6
Mar. 14, 2008	54539	-13.0
Mar. 04, 2008	54529	-9.9
Feb. 23, 2008	54519	-6.7
Feb. 13, 2008	54509	-5.1
Feb. 03, 2008	54499	-3.8
Jan. 24, 2008	54489	-1.2
Jan. 14, 2008	54479	-0.9
Jan. 04, 2008	54469	1.3
Dec. 25, 2007	54459	3.0
Dec. 15, 2007	54449	5.2
Dec. 05, 2007	54439	5.1
Nov. 25, 2007	54429	7.1
Nov. 15, 2007	54419	5.6
Nov. 05, 2007	54409	5.8

### 3. PHASE DEVIATIONS FOR WWVB AND LORAN-C

WWVB - The values shown for WWVB are the time differences between the time markers of the UTC(NIST) time scale and the first positive-going zero voltage crossover measured at the transmitting antenna. The uncertainty of the individual measurements is  $\pm 0.5 \mu\text{s}$ . The values listed are for 1300 UTC.

LORAN-C - The values shown for Loran-C represent the daily accumulated phase shift. The phase shift is measured by comparing the output of a Loran receiver to the UTC(NIST) time scale for a period of 24 h. If data were not recorded on a particular day, the symbol (-) is printed. The stations monitored are Baudette, Minnesota (8970) and Boise City, Oklahoma (9610). The monitoring is done from the NIST laboratories in Boulder, Colorado.

**Note: The values shown for Loran-C are in nanoseconds.**

DATE	MJD	<u>UTC(NIST)-WWVB</u>	<u>UTC(NIST) - LORAN PHASE (ns)</u>	
		(60 kHz)	LORAN-C	LORAN-C
		ANTENNA PHASE	(BAUDETTE)	(BOISE CITY)
		( $\mu\text{s}$ )	(8970)	(9610)
08/01/2008	54679	5.65	+25	+15
08/02/2008	54680	5.65	-15	-18
08/03/2008	54681	5.65	-43	-33
08/04/2008	54682	5.65	-12	+6
08/05/2008	54683	5.65	+88	+6
08/06/2008	54684	5.65	-104	+15
08/07/2008	54685	5.65	+3	-36
08/08/2008	54686	5.65	+30	+65
08/09/2008	54687	5.65	+41	-3
08/10/2008	54688	5.65	+25	+2
08/11/2008	54689	5.65	-10	+17
08/12/2008	54690	5.65	+113	-3
08/13/2008	54691	5.65	+25	+16
08/14/2008	54692	5.65	-67	-10
08/15/2008	54693	5.65	+53	+28
08/16/2008	54694	5.65	-18	-14
08/17/2008	54695	5.65	+21	+26
08/18/2008	54696	5.65	+16	+18
08/19/2008	54697	5.65	+21	+32
08/20/2008	54698	5.65	-103	-33
08/21/2008	54699	5.65	+62	+48
08/22/2008	54700	5.65	-133	-49
08/23/2008	54701	5.65	-76	-9
08/24/2008	54702	5.65	-76	+14
08/25/2008	54703	5.65	-6	-60
08/26/2008	54704	5.65	+12	+31
08/27/2008	54705	5.65	-14	-30
08/28/2008	54706	5.65	+30	+3
08/29/2008	54707	5.65	+13	+13
08/30/2008	54708	5.65	+180	-4
08/31/2008	54709	5.65	-56	-55

#### 4. BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS

OUTAGES OF 5 MINUTES OR MORE						PHASE PERTURBATIONS 2 ms			
Station	Aug 2008	MJD	Began UTC	Ended UTC	Freq.	Aug 2008	MJD	Began UTC	End UTC
WWVB	08-06-08	54684	2304	2312	60 kHz				
WWVB	08-25-08	54703	0946	1001	60 kHz				
WWV									
WWVH	08-21-08	54699	1935	2003	15 MHz				

#### 5. NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS

Primary frequency standards developed and operated by NIST are used to provide accuracy (rate) input to the BIPM. NIST-F1, a cold-atom cesium fountain frequency standard, has served as the U.S. primary time and frequency standard since 1999. The uncertainty of NIST-F1 is currently about 5 parts in  $10^{16}$ .

The AT1 scale is run in real-time by use of data from an ensemble of cesium standards and hydrogen masers. It is a free-running scale whose frequency is maintained as nearly constant as possible by choosing the optimum weight for each clock that contributes to the computation.

UTC(NIST) is generated as an offset from our real-time scale AT1. It is steered in frequency towards UTC by use of data published by the BIPM in its Circular T. Changes in the steering frequency will be made, if necessary, at 0000 UTC on the first day of the month, and occasionally at mid-month. A change in frequency is limited to no more than  $\pm 2$  ns/day. The frequency of UTC(NIST) is kept as stable as possible at other times.

UTC is generated at the BIPM using a post-processed time-scale algorithm and is not available in real-time. The parameters that we use to generate UTC(NIST) in real-time are therefore based on an extrapolation of UTC from the most recent available data.

#### 6. BIBLIOGRAPHY

Allan, D.W.; Hellwig, H.; and Glaze, D.J., "An accuracy algorithm for an atomic time scale," *Metrologia*, Vol.11, No.3, pp.133-138 (1975).

Allan, D.W.; Davis, D.D.; Weiss, M.A.; Clements, A.; Guinot, B.; Granveaud, M.; Dorenwendt, K.; Fischer, B.; Hetzel, P.; Aoki, S.; Fujimoto, M.; Charron, L.; and Ashby, N., "Accuracy of international time and frequency comparisons via global positioning system satellites in common-view," *IEEE Transactions on Instrumentation and Measurement*, Vol. IM-34, pp.118-125 (1985).

Heavner, T.P.; Jefferts, S.R.; Donley, E.A.; Shirley, J.H. and Parker, T.E., "NIST F1; recent improvements and accuracy evaluations," *Metrologia*, Vol. 42, pp. 411-422 (2005).

Jefferts, S.R.; Shirley, J.; Parker, T.E.; Heavner, T.P.; Meekhof, D.M.; Nelson, C., Levi, F.; Costanza, G.; De Marchi, A.; Drullinger, R.; Hollberg, L.; Lee, W.D.; and Walls, F.L., "Accuracy evaluation of NIST-F1," *Metrologia*, Vol. 39, pp. 321-336 (2002).

Lewandowski, W. and Thomas, C.; "GPS Time transfer," *Proceedings of the IEEE*, Vol. 79, pp. 991-1000 (1991).

Parker, T.E.; Jefferts, S.R.; Heavner, T.P.; and Donley, E.A., "Operation of the NIST-F1 caesium fountain primary frequency standard with a maser ensemble, including the impact of frequency transfer noise," *Metrologia*, Vol. 42, pp. 423-430 (2005).

Weiss, M.A.; Allan, D.W.; "An NBS Calibration Procedure for Providing Time and Frequency at a Remote Site by Weighting and Smoothing of GPS Common View Data," *IEEE Transactions on Instrumentation and Measurement*, Vol. IM-36, pp. 572-578 (1987).

Table 7.1 lists parameters that are used to define UTC(NIST) with respect to our real-time scale AT1. To find the value of UTC(NIST) - AT1 at any time T (expressed as a Modified Julian Day, including a fraction if needed), the appropriate equation to use is the one for which the desired T is greater than or equal to the entry in the  $T_0$  column and less than the entry in the last column. The values of  $x_{ls}$ ,  $x$ , and  $y$  for that month are then used in the equation below to find the desired value. The parameters  $x$  and  $y$  represent the offset in time and in frequency, respectively, between UTC(NIST) and AT1; the parameter  $x_{ls}$  is the number of leap seconds applied to both UTC(NIST) and UTC as specified by the IERS. Leap seconds are not applied to AT1.

Table 7.1 UTC(NIST) - AT1 = $x_{ls} + x + y*(T - T_0)$					
Month	$x_{ls}$ (s)	$x$ (ns)	$y$ (ns/d)	$T_0$ (MJD)	Valid until 0000 on: (MJD)
Oct 08	-33	-325894.6	-38.3*	54740	54771
Sep 08	-33	-324745.6	-38.3	54710	54740*
Aug 08	-33	-323558.3	-38.3	54679	54710
Jul 08	-33	-322792.3	-38.3	54659	54679
Jul 08	-33	-322369.9	-38.4	54648	54659†
Jun 08	-33	-321211.9	-38.6	54618	54648
May 08	-33	-320594.3	-38.6	54602	54618
May 08	-33	-320018.3	-38.4	54587	54602†
Apr 08	-33	-319288.7	-38.4	54568	54587
Apr 08	-33	-318867.4	-38.3	54557	54568†
Mar 08	-33	-318178.0	-38.3	54539	54557
Mar 08	-33	-317684.0	-38.0	54526	54539†
Feb 08	-33	-316582.0	-38.0	54497	54526
Jan 08	-33	-315974.0	-38.0	54481	54497
Jan 08	-33	-315405.5	-37.9	54466	54481†
Dec 07	-33	-314230.6	-37.9	54424	54466
Nov 07	-33	-313813.7	-37.9	54435	54424
Nov 07	-33	-313091.7	-38.0	54405	54435†
Oct 07	-33	-312635.7	-38.0	54393	54405
Oct 07	-33	-311911.8	-38.1	54374	54393†
Sep 07	-33	-310768.8	-38.1	54344	54374
Aug 07	-33	-309587.7	-38.1	54313	54344

† Rate change in mid-month  
 †† Rate change one day early  
 \*Provisional value