# Time & Frequency Bulletin No. 377 April 1989 (NISTIR 89-3910-4)

National Institute of Standards & Technology



•

## NIST TIME & FREQUENCY BULLETIN (Supersedes No. 376 March 1989)

. .

NO. 377 APRIL 1989

1.	GENERAL BACKGROUND INFORMATION	•	•	•	•	•	1
2.	TIME SCALE INFORMATION	•	•	•	•	•	1
	International Timing Center comparisons via GPS common-view .	•		•	•		2
3.	UT1 CORRECTIONS AND LEAP SECOND ADJUSTMENTS	•	•	•	•		2
4.	PHASE DEVIATIONS FOR WWVB AND LORAN-C	•		•	•	•	3
5.	GOES TIME CODE INFORMATION	•	•	•	•	•	4
6.	BROADCAST OUTAGES OVER FIVE MINUTES AND WWVB PHASE PERTURBATIONS		•	•	•		4
7.	NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS	•	•	•	•	•	5
8.	SPECIAL ANNOUNCEMENTS					•	7

This bulletin is published monthly. Address correspondence to:

Gwen E. Bennett, Editor Time and Frequency Division National Institute of Standards & Technology 325 Broadway Boulder, CO 80303 (303) 497-3295

NOTE TO SUBSCRIBERS: Please include your address label (or a copy) with any correspondence regarding this bulletin.

## 1. GENERAL BACKGROUND INFORMATION

••••

## ABBREVIATIONS AND ACRONYMS USED IN THIS BULLETIN

APL -	John Hopkins University Applied Physics Laboratory	
BIH -	International Time Bureau, France	
CCIR -	International Radio Consultative Committee	
CRL -	Communications Research Laboratories, Japan	
	Cesium standard	
CSIRO -	Commonwealth Scientific and Industrial Research Organization	n, Australia
GOES -	Geostationary Operational Environmental Satellite	
GPS -	Global Positioning System	
IEN -	National Institute of Electronics, Italy	
INPL -	National Physical Laboratory, Israel	
LORAN -	Long Range Navigation	
MC -	Master Clock	
MJD -	Modified Julian Date	
NIST -	National Institute of Standards & Technology	
	National Physical Laboratory, England	
	National Research Council, Canada	
	National Oceanic and Atmospheric Administration	
	Paris Observatory, France	
	Physical Technical Federal Laboratory, Germany	
	International System of Units	ns - nanosecond
	Space vehicle	us - microsecond
-	Atomic Time	ms - millisecond
	International Atomic Time	s - second
TAO -	Tokyo Astronomical Observatory, Japan	min - minute
	Technical University of Graz, Austria	h - hour
	United States Naval Observatory	d - day
	Coordinated Universal Time	u - uay
	very low frequency	
VSL -	Van Swinden Laboratory, Netherlands	

# 2. TIME SCALE INFORMATION

The values listed below are based on data from the BIH, the USNO, and the NIST. The UTC - UTC(NIST) values are extrapolations since UTC is computed more than two months after the fact. The UTC(USNO,MC) - UTC(NIST) values are averaged measurements from NAVSTAR satellites 3,4,6, and 8 (see references on page 6).

## 0000 HOURS COORDINATED UNIVERSAL TIME

RCH 1989	MJD	UT1 - UTC(NIST) (± 5 ms)	UTC - UTC(NIST) (± 0.2 µs)	UTC(USNO,MC) - UTC(NIST) (± 0.04 µs)
2	47587	-196 ms	-0.2 µs	0.78 µs
9	47594	-208 ms	-0.2 µs	0.73 µs
16	47601	-220 ms	-0.2 µs	0.69 µs
23	47608	-232 ms	-0.3 µs	0.66 µs
30	47615	-242 ms	-0.3 µs	0.64 µs

## INTERNATIONAL TIMING CENTER COMPARISONS VIA GPS COMMON-VIEW

The table below is a weighted average of the indicated GPS satellites used as transfer standards to measure the time difference of Timing Center (i) - UTC(NIST) by the simultaneous common-view approach (see references, page 6). The day-to-dav variations of this technique are a few nanoseconds and the accuracy is about 10 ns. The time of the measurement is interpolated to 0000 UTC for the particular MJD ending in 9. These data are prepared for the BIPM for the computation on TAI and of UTC. All differential delays are 0 unless otherwise noted.

UTC(i) - UTC	C(NIST) (ns)				
UTC(i)	SV NUMBERS	47549	47559	47569	47579
JTC(CRL) - UTC(NIST)	3,6,9, 12	1096*	1037	1017	1007
JTC(CSIRO) - UTC(NIST)	**	19101*	19065	19042	18951
UTC(IEN) - UTC(NIST)	9,11,12	562	598	644	555
JTC(INPL) - UTC(NIST)#	VIA OP	-1033054*	-1049123	-1063599	-1077389
JTC(NPL) - UTC(NIST)	9,11,12	-1133	-788	-597	-493
JTC(NRC) - UTC(NIST)***	3,6,9,11,12,13	13185	13176	13136	13134
TTC(OP) - UTC(NIST)	9,11,12	1532	1508	1475	1429
TTC(PTB) - UTC(NIST)	9,11,12	-4482	-4545	-4632	-4660
TTC(TAO) - UTC(NIST)	3,6,9, 12	2429*	2411	2426	2450
TTC(TUG) - UTC(NIST)	9,11,12	2684	2428	2161	1912
TC(USNO,MC) - UTC(NIST)	3,6,9,11,12,13	824*	763	701	655
TTC(VSL) - UTC(NIST)	9,11,.2	-1301	-1239	-1316	-1352

\* This value has been updated from that printed in last month's Bulletin.

. . .

\*\* UTC(CSIRO) - UTC(NIST) is computed from the average by CRL, TAO, and WWVH.

\*\*\* UTC(NRC) - UTC(NIST) has a differential delay of 41.2 ns; all other comparisons are computed using zero
(0).
# The values for UTC(INPL) - UTC(NIST) were erroneously reported February, 1989. The correct values are

-1001613 ns and -1016971 ns for MJD's 47559 and 47569, respectively.

#### 3. UT1 CORRECTIONS AND LEAP SECOND ADJUSTMENTS

The master clock pulses used by the WWV, WWVH, WWVB, and GOES time code transmissions are referenced to the UTC(NIST) time scale. Occasionally, I second is added to the UTC time scale. This second is called a leap second. Its purpose is to keep the UTC time scale within  $\pm$  0.9 s of the UTI astronomical time scale, which changes slightly due to variations in the rotation of the earth.

Positive leap seconds, beginning at 23 h 59 min 60 s UTC and ending at 0 h 0 min 0 s UTC, were inserted in the UTC timescale on 30 June 1972, 31 December 1972-1979, 30 June 1981-1983, 30 June 1985, and 31 December 1987. When future leap seconds are scheduled, advance notice will be provided in this bulletin.

The use of leap seconds ensures that UT1 - UTC will always be held within  $\pm$  0.9 s. The current value of UT1 - UTC is called the DUT1 correction. DUT1 corrections are broadcast by WWV, WWVH, WWVB, and GOES and are printed below. These corrections may be added to received UTC time signals in order to obtain UT1.

	-	0.0	S	Deginning	0000	UTC	25	August 1988
DUT1 = UT1 - UTC	=	-0.1	s	beginning	0000	UTC	10	November 1988
	=	-0.2	s	beginning	0000	UTC	19	January 1989

# 4. PHASE DEVIATIONS FOR WWVB AND LORAN-C

- WWVB The values shown for WWVB are the time difference between the time markers of the UTC(NIST) time scale and the first positive-going zero voltage crossover measured at the transmitting antenna. The uncertainty of the individual measurements is ± 0.5 µs. The values listed are for 1500 UTC.
- LORAN-C The values shown for Loran-C represent the time difference between the UTC(NIST) time pulses and the 1 Hz output of the Loran-C receiver. The stations monitored are Dana, Indiana (8970 M) and Fallon, Nevada (9940 M). The values shown are four-hour averages taken from 1600 to 2000 UTC daily. If data are lost, the symbol (-) is shown in place of the phase value.

MARCH		UTC(NIST) - WWVB(60 kHz)	UTC(NIST) - RECEIVED PHASE (in us)			
1989	MJD	ANTENNA PHASE (in µs)	LORAN-C (DANA) (100 kHz)	LORAN-C (FALLON) (100 kHz)		
1	4758 <b>6</b>	5.69	5138.42	3950.18		
2	47587	5.70	5138.37	3950.21		
3	47588	5.68	5138.47	3950.14		
4	47589	5.68	5138.27	3949.96		
5	47590	5.67	5138.13	3949.93		
6	47591	5.67	5138.12	3950.03		
7	47592	5.67	5138.39	3950.30		
8	47593	5.67	5138.49	3950.14		
9	47594	5.67	5138.44	3950.09		
10	47595	5.68	5138.43	3950.05		
11	475 <b>96</b>	5.66	5138.50	3949.95		
12	47597	5.65	5138.10	3950.01		
13	47598	5.63	5137.94	3950.22		
14	47599	5.66	5138.08	3950.14		
.5	47600	5.68	5138.11	3950.10		
.6	47601	5.66	5138.08	3950.14		
17	47602	5.67	5138.10	3950.08		
18	47603	5.65	5137.93	3949.90		
19	47604	5.64	5137.86	3949.93		
20	47605	5.62	5138.12	3950.02		
21	47606	5.61	5138.13	3950.06		
22	47607	5.71	5138.21	3950.16		
23	47608	5.76	5138.23	3950.05		
24	47609	5.72	5138.23	3950.11		
25	47610	5.71	5137. <b>99</b>	3949.89		
26	47611	5.69	5137.83	3949.91		
27	47612	5.68	5137.89	3950.06		
28	47613	5.70	5137.72	3950.04		
29	47614		5137.52	3949.74		
30	47615	5.70	5137.70	3949.96		
31	47616	5.71	5137.66	3949.79		
31	-/010	5174				

## 5. GOES TIME CODE INFORMATION

A. TIME CODE PERFORMANCE (1-31 March 1989)

GOES/East: Performance within normal limits during this period.

GOES/West: Performance within normal limits during this period.

- B. SPECIAL REMINDER: Current satellite locations are 65° W. for GOES/East and 135° W. for GOES/West.
- C. GOES STATUS REPORTS

A brief message from NIST giving current GOES time code status information is available from the U.S. Naval Observatory's Automated Data Service computer system in Washington, DC. The message may be accessed 24 hours per day without charge by using a variety of terminals operating at 300, 1200, or 2400 Baud and even parity. Two different sets of telephone access numbers are available: (1) for 300 or 1200 Baud and the Bell 103 standard use (202) 653-1079 (commercial), 653-1079 (FTS), or 294-1079 (Autovon); (2) for 1200 or 2400 Baud with either the CCITT V.22 standard or the Bell standard use (202) 653-1783 (commercial), 653-1783 (FTS), or 294-1783 (Autovon). To receive the GOES status message, use the following procedure:

- 1. Access the USNO computer database by dialing one of the appropriate telephone numbers above;
- 2. In response to the prompt for identification, type your name and the name of your organization, followed by a carriage return;
- 3. Type "@NBSGO" followed by a carriage return to receive the status message at your terminal;
- 4. Disconnect by typing Control-D.

		OUT	PHASE PI	ERTURBAT	TIONS WWV	B 60 kH			
STATION	MARCH 1989	MJD	BEGAN (UTC)	ENDED (UTC)	FREQUENCY	MARCH 1989	MJD	BEGAN (UTC)	ENDED (UTC)
WWVB	NONE					NONE			
WWV	NONE					NONE			
WWVH		47586	0255.30	0301.30	5 MHz	NONE			

#### 6. BROADCAST OUTAGES OVER 5 HIDRUTES AND WAVE PHASE PERTURBATIONS

### 7. NOTES ON NIST TIME SCALES AND PRIMARY STANDARDS

The frequencies of the time scales, TA(NIST) and UTC(NIST), are calibrated with the NIST primary frequency standards. The UTC(NIST) scale is coordinated within a microsecond of the internationally coordinated time scale, UTC, generated at the BIH. It is used to control all of the NIST time and frequency services. The last calibration of the relative frequency offset, y, of UTC(NIST) as generated in Boulder, Colorado, gave:

1)  $y_{\text{HTC}(\text{NIST})}$  (July 1987) -  $y_{\text{NBS-6}}$  (July 1987) = (-0.6 ± 2 (1 sigma)) x 10<sup>-13</sup>

for the date shown. This calibration includes a correction for the systematic offset due to room temperature blackbody radiation, which is approximately (delta  $y_{BB}$ ) = -1.7 x 10<sup>-14</sup>. Using GPS<sup>1</sup>, the frequency of TAI for the dates shown were measured to be:

2)  $y_{TAT}$  (July 1987) -  $y_{NBS-6}$  (July 1987 on geoid) = (+1.7 ± 2 (1 sigma)) x 10<sup>-13</sup>

where account has been taken of the gravitational "red shift."

Starting 1 January 1975, an accuracy algorithm was implemented to bring the second used in the generation of TA(NIST) closer to the NIST "best estimate" of the SI second (see references, p.6). The relative frequency associated with this "best estimate" is denoted  $y_{Cs}(NIST)$ . The last calibration (July 1987) covered the period from October 1986 through July 1987.

```
3) y_{Cs(NIST)} - y_{NBS-6} = (+1.4 \pm 2) \times 10^{-13} (July 1987)
```

and

4)  $y_{TAI} = y_{Cs}(NIST)$  on geoid = (+0.3 ± 0.7) x 10<sup>-13</sup> (July 1987)

This algorithm should provide nearly optimum accuracy and stability for TA(NIST) since it uses all past frequency calibrations with the NIST primary standards. These calibrations are weighted proportionately to the frequency memory of the clock ensemble that generates atomic time. This algorithm, therefore, capitalizes on a weighted combination of all the frequency calibrations with the primary standards in order to gain a "best estimate" of the SI Second while simultaneously obtaining the best uniformity available from the ensemble of working clocks in the atomic time scale system. The relative frequency of TA(NIST) is steered toward  $y_{Cs(NIST)}$ by slight frequency drift corrections of the order of 1 part in  $10^{13}/yr$ .

TA(NIST) and UTC(NIST) are no longer simply related by an equation. TA(NIST) is now computed each month using a Kalman algorithm which minimizes the mean square time dispersion. UTC(NIST) is now independently computed using a different algorithm and is steered in frequency to keep its time within a microsecond of UTC(BIH). Table 7.1 lists monthly values of the time difference between UTC(NIST) and TA(NIST). A linear interpolation between monthly values will typically be within 10 ns of the actual time difference, TA(NIST) - UTC(NIST).

The primary standards of NIST (NBS-4 and NBS-6) are used in either of two modes: as calibrators of frequency to provide a reference for the SI second; or as member clocks of the NIST clock ensemble, to help keep the proper time for TA(NIST) and the coordinated time for UTC(NIST). Operating in the clock mode, NBS-4 and NBS-6 are only used and weighted according to their stability performance. Accuracy enters only when they are used as frequency calibrators, in which case clock operation is necessarily interrupted.

 $<sup>^{1}</sup>$ GPS is the Global Positioning System, a network of navigation satellites.

Table 7.1 is a list of changes in the time scale frequencies of both TA(NIST) and UTC(NIST) as well as a list of the time and frequency differences between TA(NIST) and UTC(NIST) at the dates of leap seconds, and/or frequency or frequency drift changes.

		FI	REQUENCY CHANGE	S		
DATE	(MJD)	TA(NIST)	UTC(NIST)	TA(NIST)	- UTC(NIST)	y[UTC(NIST)] - y[TA(NIST)]
1 Oct 87	47069	0	1.25 ns/d	23.045	102 583 s	-3.47 E-13
1 Nov 87	47100	0	0.50 ns/d	23.045	103 512 s	-3.38 E-13
1 Dec 87	47130	0	0.50 ns/d	23.045	104 367 s	-3.40 E-13
1 Jan 88	47161	0	-1.00 ns/d	24.045	105 306 s	-3.56 E-13
1 Feb 88	47192	0	-1.00 ns/d	24.045	106 272 s	-3.53 E-13
1 Mar 88	47221	0	-1.25 ns/d	24.045	107 1 <b>37 s</b>	-3.58 E-13
1 Apr 88	47252	0	-1.50 ns/d	24.045	108 130 s	-3.85 E-13
1 May 88	47282	0	-1.50 ns/d	24.045	109 170 s	-4.29 E-13
1 Jun 88	47313	0	-1.50 ns/d	24.045	110 358 s	-4.47 E-13
1 Jul 88	47343	0	-1.60 ns/d	24.045	111 52 <b>3 s</b>	-4.64 E-13
1 Aug 88	47374	0	-0.40 ns/d	24.045	112 802 s	-4.89 E-13
1 Sep 88	47405	0	-1.00 ns/d	24.045	114 144 s	-5.15 E-13
1 Oct 88	47435	0	1.00 ns/d	24.045	114 515 s	-5.15 E-13
1 Nov 88	47466	0	1.25 ns/d	24.045	116 854 s	-4.88 E-13
1 Dec 88	47496	0	1.50 ns/d	24.045	118 088 s	-4.69 E-13
l Jan 89	47527	0	1.50 ns/d	24.045	119 325 s	-4.57 <b>E</b> -13
l Feb 89	47558	0	1.00 ns/d	24.045	120 538 s	-4.51 E-13
1 Mar 89	47586	0	-1.25 ns/d		121 622 s	-4.58 E-13

TABLE 7.1

UTC(NIST) is steered in time toward UTC by occasional frequency changes of the order of a few nanoseconds per day; 1 ns/d is approximately 1.16E-14. Otherwise, y[UTC(NIST)] is maintained as stable as possible.

REFERENCES

Allan, David W., et al., "An accuracy algorithm for an atomic time scale," Metrologia, Vol.11, No.3, pp.133-138 (September 1975).

Glaze, D.J., et al., "NBS-4 and NBS-6: The NIST primary frequency standards," Metrologia, Vol.13, pp.17-28 (1977).

Wineland, D.J., et al., "Results on limitations in primary cesium standard operation," IEEE Trans. on Instr. and Meas., Vol.IM-25, No.4, pp.453-458 (December 1976).

Allan, David W. and Weiss, Marc, "Accurate Time and Frequency Transfer During Common View of a GPS Satellite," Proc. 34th Annual Symposium on Frequency Control, p.334 (1980).

Allan, David W. and Barnes, James A., "Optimal Time & Frequency using GPS signals," Proc. 36th Annual Symposium on Frequency Control, p.378 (1982).

#### 8. SPECIAL ANNOUNCEMENTS

#### 43rd Annual Symposium on Frequency Control

The 43rd Annual Symposium on Frequency Control will be held on May 31 - June 2, 1989. The site for this years symposium will be the Marriott Hotel City Center in Denver, Colorado.

The number of summaries submitted to the technical program committee reached an all time high. The quality of these submissions proves to make the 43rd the best symposium ever. Ninety papers will be presented in 21 sessions. Highlights will be a specially organized session on environmental effects and their measurement, a session on surface preparation of quartz, including a tutorial on abrasive processes, and a session on two-way time transfer.

The symposium will begin with a plenary session at which three prestigious awards will be presented. The Cady award is presented annually by the technical program committee to frequency control devices. This year the award recipient will be Dr. D.E. Newell. The Rabi award is presented to recognize outstanding contributions related to fields such as atomic and molecular frequency standards, time transfer, and frequency and time metrology. This year's recipient is Dr. L. Cutler. The third award, sponsored by Sawyer Applied Research Products, is presented in honor of C.B. Sawyer for the most outstanding recent contribution to advancement in the field of quartz crystals and devices. The recipient of the C.B. Sawyer award is selected by an independent committee and will be announced at the symposium.

Special invited presentations will include "Spacecraft Gravitational Wave Experiments" by J.W. Armstrong, JPL; "Shear Mode Grinding" by N.J. Brown and B.A. Fuchs, LLNL; "A High Stability Microwave Oscillator Based on a Sapphire Loaded Superconducting Cavity" by D.G. Blair, A.J. Giles, and S.K. Jones, U. of Western Australia; "Stacked Crystal Filters Implemented with Thin Films" by K.M. Lakin, G.R. Kline, J.T. Martin, and K.T. McCarron, Iowa State U.; and "Low-Cost High-Performance Resonator and Coupled-Resonator Designs: NSPUDT and Other Innovative Structures" by P.V. Wright, RF Monolithics.


The social program will be extra special due to the proximity of the National Institute of Standards and Technology (formerly the National Bureau of Standards). There will be a tour of NIST, including a visit to the nation's time standard, tentatively scheduled for Wednesday evening, May 31. Dinner on Thursday, June 1, will be at a famous Denver attraction The Fort. The Fort is a restaurant specializing in authentic foods of the American West including buffalo, Rocky Mt. oysters and Rocky Mt. trout. This will be an experience to be enjoyed by all.

NBS-1144 (REV. 2-40)		······································	
U.S. DEPT. OF COMM.	1. PUBLICATION OR REPORT NO.	2. Performing Organ. Report No.	3. Publication Date
BIBLIOGRAPHIC DATA	NISTIR 89-3910-4	B89-0064	April . 1989
SHEET (See instructions) 4. TITLE AND SUBTITLE			
Time & Fr	requency Bulletin	-	
		•	
S. AUTHOR(S)			
6. PERFORMING ORGANIZ	ATION (If joint or other than NB)	5. see instructions) 7.	Contract/Grant No.
NATIONAL BUREAU OF			
DEPARTMENT OF COMM WASHINGTON, D.C. 202		8.	Type of Report & Period Covered
9. SPONSORING ORGANIZA	TION NAME AND COMPLETE	ADDRESS (Street, City, State, ZIP)	
10. SUPPLEMENTARY NOT	55		
	5		
•			
		S Software Summary, is attached.	
bibliography or literature		significant information. If documen	Lincigaes a significant
The Time & Pr	anner Bulletin provi	des information on perfe	TRADES OF time
		related information) to	
NIST services.	•, •• •••••••• (••••		
•			
IL. RET WORDS (Six to twelv	ve entries; alphabetical order; co	spitalize only proper names; and se	parate key words by semicolons)
clocks; dissemin	ation; frequency; GPS	; oscillators; time	
13. AVAILABILITY			14. NO. OF
Unlimited			PRINTED PAGES
	tion. Do Not Release to NTIS		8
Order From Superinte		nment Printing Office, Washington,	
20402.			13. Price
Order From National	Technical Information Service (	NTIS), Springfield, VA. 22161	
	•		

.

• .





## AN EQUAL OPPORTUNITY EMPLOYER

rates - Start - Start

U.S. Department of Commerce National Institute of Standards and Technology Time & Frequency Division Boulder, Colorado 80303

OFFICIAL BUSINESS Penalty for Private Use, \$300 FIRST-CLASS MAIL POSTAGE & FEES PAID NIST Permit No. G195

GWEN BENNETT DIVISION 524 - HT II HAR BUREAU OF STADUALD (25 BROADWAY POULDER, CHOOKEL