

# NATIONAL BUREAU OF STANDARDS REPORT

9475

THE SELECTION OF BUILDING SYSTEM BY A DECISION PROCESS  
USING CLIMATOLOGICAL, ENGINEERING AND ECONOMIC DATA

by

William C. Cullen

Materials and Composites Section  
Building Research Division  
Institute for Applied Technology

Office of the Chief of Engineers, U.S. Army  
Directorate of Civil Engineering, U.S. Air Force  
Naval Facilities Engineering Command, U. S. Navy



U.S. DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS

## THE NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards is a principal focal point in the Federal Government for assuring maximum application of the physical and engineering sciences to the advancement of technology in industry and commerce. Its responsibilities include development and maintenance of the national standards of measurement, and the provisions of means for making measurements consistent with those standards; determination of physical constants and properties of materials; development of methods for testing materials, mechanisms, and structures, and making such tests as may be necessary, particularly for government agencies; cooperation in the establishment of standard practices for incorporation in codes and specifications; advisory service to government agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; assistance to industry, business, and consumers in the development and acceptance of commercial standards and simplified trade practice recommendations; administration of programs in cooperation with United States business groups and standards organizations for the development of international standards of practice; and maintenance of a clearinghouse for the collection and dissemination of scientific, technical, and engineering information. The scope of the Bureau's activities is suggested in the following listing of its three Institutes and their organizational units.

**Institute for Basic Standards.** Applied Mathematics. Electricity. Metrology. Mechanics. Heat. Atomic Physics. Physical Chemistry. Laboratory Astrophysics.\* Radiation Physics. Radio Standards Laboratory.\* Radio Standards Physics; Radio Standards Engineering. Office of Standard Reference Data.

**Institute for Materials Research.** Analytical Chemistry. Polymers. Metallurgy. Inorganic Materials. Reactor Radiations. Cryogenics.\* Materials Evaluation Laboratory. Office of Standard Reference Materials.

**Institute for Applied Technology.** Building Research. Information Technology. Performance Test Development. Electronic Instrumentation. Textile and Apparel Technology Center. Technical Analysis. Office of Weights and Measures. Office of Engineering Standards. Office of Invention and Innovation. Office of Technical Resources. Clearinghouse for Federal Scientific and Technical Information.\*\*

---

\*Located at Boulder, Colorado, 80301.

\*\*Located at 5285 Port Royal Road, Springfield, Virginia, 22171.

# NATIONAL BUREAU OF STANDARDS REPORT

## NBS PROJECT

421.04-12-4212447

*March 1967*

## NBS REPORT

9476

### THE SELECTION OF BUILDING SYSTEM BY A DECISION PROCESS USING CLIMATOLOGICAL, ENGINEERING AND ECONOMIC DATA

by

William C. Cullen

Materials and Composites Section  
Building Research Division  
Institute for Applied Technology

Sponsored by

Office of the Chief of Engineers, U.S. Army  
Directorate of Civil Engineering, U.S. Air Force  
Naval Facilities Engineering Command, U. S. Navy

#### IMPORTANT NOTICE

NATIONAL BUREAU OF STANDARDS  
for use within the Government.  
and review. For this reason, the  
whole or in part, is not authorized  
Bureau of Standards, Washington  
the Report has been specifically

Approved for public release by the  
Director of the National Institute of  
Standards and Technology (NIST)  
on October 9, 2015

is accounting documents intended  
subjected to additional evaluation  
listing of this Report, either in  
Office of the Director, National  
by the Government agency for which  
copies for its own use.



U.S. DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS



# THE SELECTION OF BUILDING SYSTEM BY A DECISION PROCESS USING CLIMATOLOGICAL, ENGINEERING AND ECONOMIC DATA

by

William C. Cullen

## I. INTRODUCTION

The selection of a roofing system by a decision maker is often based on either past experience with the performance of a specific roofing system under the service conditions in his area or on the results of simulated service tests conducted in the laboratory. Frequently these sources of information are not available especially in the case of new products or innovations in building systems. The building industry in general and those involved with military construction could profit by having a criterion or criteria to assist in the selection of the more economical building systems which will perform adequately under service requirements.

The object of this report is to propose a simple model to provide a logical and systematic approach to the selection of a building system based on a scientific method.

An attempt has been made to verify the model by deductively processing currently available economic, climatic and engineering information to obtain an indicator which will assist in the selection of one of two asphalt shingle roofing systems. Further an attempt has been made to extrapolate present and past information into the future in order to provide a basis for the selection of a system.

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

...

## 2. ASPHALT ROOFING SYSTEMS

Asphalt roofings account for over 30% of the roof covering materials used in the United States [1]\*. In 1965 the number of shingles produced was sufficient to cover about 4 billion square feet of roof area [2] which alone is adequate testimony of their usefulness as a roof covering. However, they possess, like most building materials, some inherent weaknesses. The most frequent cause of failure of conventional (free-tab) asphalt shingles, which in 1965 amounted to about two-thirds of the total production of asphalt shingles, is damage by wind. To overcome this deficiency various types of wind-resistant shingle is the self-sealing shingle which has been described by Cullen [3]. Suggested criteria for the performance of a wind-resistant shingle was proposed by Cullen [4] and label service is currently being offered for this type of roof covering by Underwriters' Laboratories Inc., based on these criteria [5].

The wind-resistant shingle may be classed as a premium product since the purchaser of these materials must pay a slight additional cost for the additional protection against wind which is afforded. The increased cost is justified in high wind areas where conventional shingles are vulnerable to damage but their use in areas experiencing low wind velocities is sometimes questioned. The question now arises regarding the economic benefit to be gained by the selection of a shingle commensurate with its projected exposure conditions in service.

\*Figures in brackets indicate literature references at the end of this paper.



### 3. PERTINENT PARAMETERS

#### 3.1 Economics

The cost of asphalt shingles including installation, like other building systems, varies to a large degree depending on the type of shingle, the roof area, the method of application, the labor market and the geographical area. Therefore, an accurate assessment of costs is often difficult to make. However, for the purpose of this report and based on information from a number of reliable sources, an approximate installed cost of \$20.00 per square (100 square feet of roof area) has been used for conventional asphalt shingle roofings. A cost differential of one dollar per square has been used for wind-resistant shingles as compared to the use of the conventional type. Assuming the roof area of an average house to be 1500 square feet it follows that the cost to apply a roof with conventional shingles will be about \$300.00. The premium which must be paid for using wind-resistant shingles amounts to an additional penalty of \$15.00 per house.

#### 3.2 Engineering Properties

In a study of the wind resistance of conventional (free-tab) asphalt shingles, Cullen [6] has reported that sustained winds of 30 miles per hour or over are frequently sufficient to lift the unrestrained shingle tabs so that the shingles may become vulnerable to damage by wind gusts of much greater velocity. Therefore, we have used these data to select, for this study only, the criterion of 30 miles per hour wind speed for predicting whether or not conventional asphalt shingles may be vulnerable to damage by wind.



### 3.3 Climatology

We have selected as our criterion the daily fastest observed one-minute wind speed as reported in Local Climatological Data published by ESSA's Weather Bureau. The climatic condition of the Washington, D. C. area for the year 1965 was used as the weather parameter in the model. These data were obtained from Weather Bureau publications [7]. An examination of these data revealed that the daily fastest observed one-minute wind speed exceeded 30 miles per hour on 30 of the 365 days in the Washington, D. C. area or on 8.2% of the total days in 1965.

### 4. THE DECISION PROCESS

Once the decision maker has arrived at the judgement that the new or replacement roof will be asphalt shingles, he has two possible courses of action regarding the selection of the type of shingles in respect to wind resistance. One will be more advantageous under high wind conditions while the other will be the better choice under less severe wind conditions. For example, if potential damaging winds are infrequent to the area in question he can elect to use conventional (free-tab) shingles. On the other hand, the selection of wind-resistant shingles appears to be the logical choice if the building is located in a high wind area. The economics associated with these decisions will depend to a large extent on the actual wind conditions which occur subsequent to the application of the roofing.



This can best be visualized with the aid of the matrix shown in Figure 1.

Wind Conditions	Cost of Roofing	
	Choice $A_1$	Choice $A_2$
$W_1$	$C_{11}$	$C_{21}$
$W_2$	$C_{12}$	$C_{22}$

Figure 1. MODEL FOR DECISION PROCESS

The symbol C in Figure 1 represents the respective cost or loss associated with the decision makers choice in respect to the wind conditions to which the roofing may be subjected.

Let us assume that Choice  $A_1$  is the more economical if wind conditions  $W_1$  are frequently experienced in the Area. On the other hand choice  $A_2$  appears to be the better one where wind conditions  $W_2$  prevail. Costs  $C_{11}$  and  $C_{22}$  would represent the minimum expected costs while  $C_{12}$  and  $C_{21}$  would represent maximum expected costs associated with the decision makers judgement. In the cases where the decision maker correctly matches his choice to the wind conditions of the area, the maximum economic benefit will be attained.

The application of the decision process to the selection of the roofing system can be expressed on a cost-effectiveness basis. Let  $W_1$  represent a wind condition where the daily fastest observed one-minute wind speed is less than 30 miles per hour and let wind condition  $W_2$  represent a daily wind condition



in excess of the 30 mph value. Let Choice  $A_1$  represent the selection of conventional (free-tab) asphalt shingles and Choice  $A_2$  the choice of the wind-resistant variety.

A review of the 1965 local climatological data [7] for the Washington, D.C. area showed that the percentage of days the wind velocity fell below the 30 mph criterion was 91.8% while the value was exceeded on 8.2% of the days. This can be expressed as follows:

$$P(W_1) = .918 \text{ and } P(W_2) = .082$$

The cost associated with the action can be expressed by the regret matrix in Figure 2.

Wind Condition	Action		
	Choice $A_1$ (Free-Tab)	Choice $A_2$ (Wind-Resistant)	
$W_1$ (< 30 mph)	$C_{11}$ (\$0)	$C_{21}$ (\$15)	$P(W_1) = .918$
$W_2$ (> 30 mph)	$C_{12}$ (\$300)	$C_{22}$ (\$15)	$P(W_2) = .082$

Figure 2. REGRET MATRIX

In areas where wind conditions  $W_1$  are prevalent and Choice  $A_1$  is made, the cost,  $C_{11}$ , to the decision maker is zero. Under similar wind conditions and Choice  $A_2$  is decided upon the cost  $C_{21}$  is \$15.00 per house or the additional cost of the wind-resistant roofing over conventional shingles. However, if under wind conditions  $W_2$ , Choice  $A_1$  is made, the potential loss  $C_{12}$  is \$300.00 per house, i.e., if the roof were heavily damaged by strong winds with subsequent damage to the building and its contents. The cost  $C_{22}$  associated with Choice  $A_2$  is \$15.00 per house and subsequent wind conditions do not vary this cost.



If the decision maker ignores or is unaware of local wind conditions in respect to the performance of asphalt roofing shingles, he may elect for various and sundry reasons to make either Choice  $A_1$  all the time or to make Choice  $A_2$  all the time. The expected costs  $\bar{C}_1$  and  $\bar{C}_2$  for always making Choices  $A_1$  and  $A_2$  respectively may be expressed as equations (1) and (2).

$$\bar{C}_1 = P(W_1) C_{11} + P(W_2) C_{12} \quad (1)$$

$$\bar{C}_2 = P(W_1) C_{21} + P(W_2) C_{22} \quad (2) \text{ where:}$$

$P(W_1)$  and  $P(W_2)$  are fractions of the time when wind conditions  $W_1$  ( 30 mph) and  $W_2$  ( 30 mph) prevail in the selected location.

The costs associated with the decision makers choice may be calculated by substituting values given in Figure 2 in equation (1). If he selects conventional (free-tab) shingles all the time (Choice  $A_1$ ) his cost is:

$$\bar{C}_1 = (.918) (0) + (.082) (300) = \$24.00 \text{ per house } (3)$$

On the other hand, if he always chooses to use wind-resistant shingles his expected cost will be from equation (2):

$$\bar{C}_2 = (.918) (15) + (.082) (15) = \$15.00 \text{ per house } (4).$$

Therefore if the assumptions made herein are correct the conclusion may be made that in the absence of an accurate long range forecast of wind conditions the only rational decision for the Washington, D.C. area is to use wind-resistant asphalt shingles all the time and accept the expected cost of \$15.00 per house as opposed to the expected cost of \$24.00 per house if the choice of conventional shingles were made.



If it were possible for the decision maker to obtain perfect wind information for the area in question he would obviously choose conventional shingles when wind conditions  $W_1$  were prevalent and the wind resistant type when wind conditions  $W_2$  prevailed. Under these set of circumstances his cost ( $\bar{C}_p$ ) can be expressed by equation (5).

$$\bar{C}_p = P(W_1) C_{11} + P(W_2) C_{22} \quad (5)$$

By substituting values given in Figure 2 in equation (5) the cost is:

$$\bar{C}_p = (.918) (0) + (.082) (15) = \$1.25 \text{ per house.}$$

The cost of \$1.25 per house based on perfect wind information would be \$13.75 less than his best choice based on wind information obtained from climatology. In actual practice the decision maker will not be able to obtain perfect wind information since this product is not available, therefore he will probably make the more economical choice for his area if he uses the climatological data which is available from the ESSA's Weather Bureau for most localities.

## 5. SUMMARY

Economic, climatic and engineering data can be integrated by means of a decision process so as to serve as a guide in the selection of the more economical roofing system. In this report certain assumptions have been made which will not meet with universal agreement but are, nevertheless, necessary for such an analysis. For example, the 30 miles per hour criterion based on the daily fastest observed one-minute wind speed for conventional asphalt shingles is probably not realistic for all classes of asphalt shingles and, of course, the cost of the applied roof and the price differential between conventional and wind-resistant shingles will vary considerably from area to area.



The utilization of the decision process proposed herein and using values based on the best current information from engineering, economic, and climatological sources has shown that the use of wind-resistant shingles on residential structures in the Washington, D. C. area would effect cost economies. On the other hand the use of similar data available for other areas of the United States may indicate that the conventional shingles are the more economical choice.

The decision process provides a very useful tool to determine cost-benefit ratios based on the climate, price structure including labor and materials, engineering properties and performance characteristics. For example, if the wind resistance of conventional asphalt shingles were improved by manufacturing processes or application procedures by increasing the value of the criterion from the assumed 30 miles per hour daily fastest observed one-minute mile to just 33 miles per hour, a toss of the coin would determine the most economical choice. Further if advances in material and/or labor costs increased the cost differential from \$15.00 to \$25.00 per house between the conventional and wind resistant types of shingles, the choice of either type would be optional on a cost-effectiveness basis.

In comparing cost-usefulness of using wind-resistant shingles in relation to exposure location, the analysis indicated that the wind-resistant shingles offer an economical advantage in those areas where the number of days the 30 miles per hour criterion is exceeded about 4% of the time.



On the other side of the coin the decision process indicated that the conventional shingles appeared to be the more economical choice when:

- a) cost differential of wind-resistant shingles over the conventional type is greater than \$25.00 per house (15 squares) or
- b) criterion for wind damage exceeds the 33 miles per hour fastest observed one-minute wind speed, or
- c) the fastest-observed one-minute wind speed criterion occurs less than 4% of the days of the year.

#### 6. COMPLICATING FACTORS

The decision process used to assist in making a choice to use or not to use the wind-resistant asphalt shingles is much more complex than indicated herein. In actual practice many other factors play roles of varied importance in respect to the wind-resistance of asphalt shingles. For example, a number of the more important factors are:

- a) type, weight and composition of shingle
- b) the exposure, type and slope of roof deck
- c) the number and placement of fasteners used to secure shingles to the deck
- d) the age and temperature of asphalt shingles.



Ideally a probabilistic model should be constructed to take into account all of these factors. However, these factors are either inherently complex or their influence on the performance of a roofing in service is currently unknown. Therefore the development of a model will to include all these factors require a rather large effort both in the laboratory and in the field.

It should be noted that the complicating factors do not necessarily render our simple model useless. On the contrary, it provides the manufacturer, architect, roofing contractor or the home owner with a scientific method to assist him in making a proper and economical choice of a roofing system based on available economic, climatological and engineering information.

#### 7. ACKNOWLEDGMENT

The author acknowledges with thanks the suggestions of J. A. Joseph, Technical Analysis Division NBS during the preparation of this report.



### C. REFERENCES

1. J. L. Strahan. Manufacture, Selection and Application of Asphalt Roofing and Siding Products, Asphalt Roofing Industry Bureau. New York, N.Y., June 1964.
2. Current Industrial Reports - Asphalt and Tar Roofing and Siding Products, Bureau of the Census, U. S. Department of Commerce, Summary for (1965).
3. W. C. Cullen. Sealing Systems for Asphalt Shingles, National Bureau of Standards, Report No. 6442. June 1959.
4. W. C. Cullen, Building Research Institute, National Academy of Science, New Building Research (1960).
5. Requirements for Wind-Resistant Asphalt Shingle Roofing. Underwriters' Laboratories Inc. (1961).
6. W. C. Cullen, Wind Resistance of Free-tab Asphalt Shingles, National Bureau of Standards Report No. 6522. September 1959.
7. Local Climatological Data. Washington, D. C. (1965).





