







•





4 History of Walkway Slip-Resistance Research

at the National Bureau of Standards

National Bureau of Standards Library, E-01 Admin. Bldg.

> MAY 14 1981 190863 QC100 , US7

NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards¹ was established by an act of Congress on March 3, 1901. The Bureau's overall goal is to strengthen and advance the Nation's science and technology and facilitate their effective application for public benefit. To this end, the Bureau conducts research and provides: (1) a basis for the Nation's physical measurement system, (2) scientific and technological services for industry and government, (3) a technical basis for equity in trade, and (4) technical services to promote public safety. The Bureau's technical work is performed by the National Measurement Laboratory, the National Engineering Laboratory, and the Institute for Computer Sciences and Technology.

THE NATIONAL MEASUREMENT LABORATORY provides the national system of physical and chemical and materials measurement; coordinates the system with measurement systems of other nations and furnishes essential services leading to accurate and uniform physical and chemical measurement throughout the Nation's scientific community, industry, and commerce; conducts materials research leading to improved methods of measurement, standards, and data on the properties of materials needed by industry, commerce, educational institutions, and Government; provides advisory and research services to other Government agencies; develops, produces, and distributes Standard Reference Materials; and provides calibration services. The Laboratory consists of the following centers:

Absolute Physical Quantities² — Radiation Research — Thermodynamics and Molecular Science — Analytical Chemistry — Materials Science.

THE NATIONAL ENGINEERING LABORATORY provides technology and technical services to the public and private sectors to address national needs and to solve national problems; conducts research in engineering and applied science in support of these efforts; builds and maintains competence in the necessary disciplines required to carry out this research and technical service; develops engineering data and measurement capabilities; provides engineering measurement traceability services; develops test methods and proposes engineering standards and code changes; develops and proposes new engineering practices; and develops and improves mechanisms to transfer results of its research to the ultimate user. The Laboratory consists of the following centers:

Applied Mathematics — Electronics and Electrical Engineering² — Mechanical Engineering and Process Technology² — Building Technology — Fire Research — Consumer Product Technology — Field Methods.

THE INSTITUTE FOR COMPUTER SCIENCES AND TECHNOLOGY conducts research and provides scientific and technical services to aid Federal agencies in the selection, acquisition, application, and use of computer technology to improve effectiveness and economy in Government operations in accordance with Public Law 89-306 (40 U.S.C. 759), relevant Executive Orders, and other directives; carries out this mission by managing the Federal Information Processing Standards Program, developing Federal ADP standards guidelines, and managing Federal participation in ADP voluntary standardization activities; provides scientific and technological advisory services and assistance to Federal agencies; and provides the technical foundation for computer-related policies of the Federal Government. The Institute consists of the following centers:

Programming Science and Technology -- Computer Systems Engineering.

¹Headquarters and Laboratories at Gaithersburg, MD, unless otherwise noted; mailing address Washington, DC 20234. ²Some divisions within the center are located at Boulder, CO 80303.

A History of Walkway Slip-Resistance Research at the National Bureau of Standards

Sanford C. Adler and Brian C. Pierman

Center for Building Technology National Engineering Laboratory National Bureau of Standards Washington, D.C. 20234



U.S. DEPARTMENT OF COMMERCE Luther H. Hodges, Jr., Under Secretary Jordan J. Baruch, Assistant Secretary for Science and Technology

NATIONAL BUREAU OF STANDARDS, Ernest Ambler, Director

Issued December 1979

Library of Congress Catalog Card Number: 79-600179

National Bureau of Standards Special Publication 565 Nat. Bur. Stand. (U.S.), Spec. Publ. 565, 36 pages (Dec. 1979) CODEN: XNBSAV

> U.S. GOVERNMENT PRINTING OFFICE WASHINGTON: 1979

For sale by the Superintendent of Documents, U.S. Government Printing Office Washington, D.C. 20402 - Price

Stock No. 003-003-

TABLE OF CONTENTS

Page

.

ABST	TRACT	1
1.	INTRODUCTION	2
2.	HISTORICAL PERSPECTIVE	2
	 2.1 R. B. Hunter 2.2 P. A. Sigler 2.3 Federal Construction Council 2.4 T. H. Boone 2.5 The Man in the Shoe 	3 6 10 13 15
3.	RECENT NBS ACTIVITY	16 16 17
	3.4 Problem-Oriented Research	21
4.	NOW AND THE FUTURE	22
	 4.1 Data Base Development	23 23 24
5.	SUMMARY	24
APPE RESI	ENDIX - BASIC CONCEPTS RELATING TO FRICTION AND SLIP- ISTANCE MEASUREMENT	26
REFE	CRENCES	30

LIST OF TABLES

Table 1	Sigler's Ch Values for	naracterization c Floor and Deck S	of Antislip Surfaces	8	;
Table 2	Comparison from Three	of Slip-Resistan Test Methods	nce Readings	1	.8

LIST OF FIGURES

Page

Page

Figure 1.	The Hunter Machine	4
Figure 2.	The Original Model of Sigler's Pendulum Tester	7
Figure 3.	The NBS Electro-Mechanical Force Plate (1951)	11
Figure 4.	The British Portable "Skid-Resistance" Tester	14
Figure 5.	NBS-Brungraber Portable Slip-Resistance Tester	20

A History of Walkway Slip-Resistance Research at the

National Bureau of Standards

Sanford C. Adler and Brian C. Pierman

ABSTRACT

This report summarizes NBS research in the area of walkway and shoe slip-resistance measurement since 1924 and outlines current activities that will provide a technical basis for slip-resistance measurement. The work of Sigler, Hunter, Boone and Brungraber represents the historic perspective. Current activities in data base development and identification of standard reference surfaces contribute to a rational basis for quantitative slip-resistance criteria for building codes and standards. Proposed future research thrusts include personal factors such as human biokinetic and perceptual variables, as well as environmental factors such as lighting in the built environment. This research will contribute to the development of new intervention strategies to reduce deaths and injuries due to slips and falls.

Key Words: Friction; measurement; reference standards; safety research; walkway slip-resistance.

1. INTRODUCTION

The National Safety Council reports that slips and falls are the major building-related cause of accidental death and injury [1].¹ In 1976, over 8 million falls resulted in 1.6 million disabling injuries and 14,896 deaths. The victims are primarily the young and the old, with more serious consequences for the elderly. Children under 15 (approximately 30% of the U.S. population) suffered nearly half of the disabling injuries. Adults over 65 (approximately 10% of the U.S. population) experienced 20% of the fatalities. In more than half of the falls, slippery surfaces were identified as a major contributing factor.

Existing standards and codes for walkway surfaces are generally vague and difficult to enforce since they lack quantitative definition of acceptable levels of slip-resistance.

The Center for Building Technology is advancing research to permit the inclusion of quantitative criteria for slip-resistance now missing from voluntary standards and mandatory regulations.

2. HISTORICAL PERSPECTIVE

The earliest work at the National Bureau of Standards (NBS) related to slips and falls focused exclusively on the measurement of coefficient of friction. Later work demonstrated a recognition of the complex array of factors which affect the risk of a slip or fall on a walkway surface.

¹ Numbers in brackets refer to References.

2.1 R. B. Hunter

NBS has been involved in slip-resistance research for over 50 years. As early as the 1920's there was a recognized need for a quantitative safety code for walkway surfaces.

A committee of the American Standards Association¹ examined the problem and found that available data were inadequate. A new manufacturers' subcommittee was formed within the American Standards Association and arrangements were made to sponsor a research fellowship at NBS to investigate the frictional resistance of walkway surface materials.

The investigations carried out from 1924 to 1926 by R. B. Hunter included the development of a process for preparing (abrading to simulate wear) the specimens and a test device and procedure for measuring the coefficient of friction. Additional investigations were carried out by Hunter at NBS during 1928 to 1929. The results of all of the studies have been reported by Hunter [2].

Hunter established the following test conditions:

- The walkway materials tested were abraded sufficiently to be representative of worn surfaces.
- The contact area between the surfaces was comparable to the contact area between an average shoe sole and a walkway.
- 3. The load applied to the test sole was approximately the same as the average load to the shoe sole in walking.

Founded in 1918. Changed name in 1966 to the United States Standards Institute, and again in 1969 to the American National Standards Institute (ANSI).



rigure i The Hunter Machine 4. The test apparatus gave repeatable results on the same surfaces.

Hunter described his test apparatus, illustrated in Figure 1 as

follows:

"It operates on an oblique thrust principle corresponding to the thrust on the shoe in walking and consists of a right-angled frame carrying a slotted 75-pound weight between two vertical bars of the frame which serves as guides to the weight. A 10-inch thrust arm is pivoted at one end near the center of gravity of the weight and at the other end through the center of an area of a 3 by 3 inch The weight may be raised by means of the windlass, and is shoe. supported in the raised position by the friction of the shoe on the surface under test. By means of a screw and lug the shoe may be drawn forward by small increments, increasing the horizontal component of the force until the shoe slips on the surface, letting the weight drop. The lug is left in the position at which the slip occurred. The lug carries an index which shows (on a scale graduated in inches) the horizontal distance of the shoe from its position when the thrust arm is vertical."

The Hunter Machine measured dynamic rather than static friction, since the shoe was dragged across the walkway specimen until slip occurred. Hunter used rubber and leather shoe sole materials to evaluate a number of walkway surfaces, including natural and artificial stone, vitrified tile, wood, metal and various manufactured products.

Hunter found that there was no direct relationship between the coefficients of friction on clean, dry surfaces and on the same materials under various actual service conditions. For example, he found that the coefficient of friction for leather appeared to increase on wet and/or oily surfaces. For most materials, the coefficient of friction depended upon the smoothness, cleaness, and moisture content of the two surfaces. Adaptations of his test device have been incorporated into currently used test devices such as the James Machine [3], and the newly developed NBS-Brungraber Portable Tester [4].

2.2 P. A. Sigler

During the 1940's and the early 1950's, an extensive program of slip-resistance research was carried out under the direction of Percy A. Sigler. The work included analysis of slow-motion photography of people walking, a study of wear patterns of shoe heels, development of a new pendulum-type tester, and electromechanical determination of the forces exerted by the foot on a walkway surface.

Sigler reviewed the previous investigations of the slip-resistance of floors and noted that measurements made of the coefficient of static friction between floor surfaces and leather soles yielded the counterintuitive result that some smooth-faced materials had a higher coefficient of friction when wet than when dry. Sigler attributed this result to the comparatively large area of contact between the leather sole and the floor surface; a condition representative of a person standing rather than walking. In retrospect, it now seems more likely that the improved slip-resistance of wet surfaces arises from the adhesion that can be developed by a thin layer of liquid between the surfaces. The relatively long delay time between the application of the normal force and the application of the lateral force that is inherent in most slip-resistance testers can encourage the development of this adhesion.



Figure 2 The Original Model of Sigler's Pendulum Tester

Sigler approached the problem by developing a pendulum-type laboratory machine which estimated dynamic friction by indicating the energy loss of a mechanical heel sliding over a walkway surface. The Sigler laboratory machine is illustrated in Figure 2. Sigler reported "antislip coefficients" for samples of over 100 materials which he categorized as poor, fair and good [5]. In general, he found almost all flooring surfaces were "good" under dry conditions, and many rated "poor" under wet conditions. Table 1 describes the range of "antislip" values Sigler considered as "poor, fair and good."

Table 1. Siglers' Characterization of Antislip Values for Floor and Deck Surfaces.

Classification	Leather Heel as Sensor	Rubber Heel as Sensor
Poor	Less than 0.15	Less than 0.25
Fair	0.15 to 0.30	0.25 to 0.40
Good	More than 0.30	More than 0.40

Taken from Sigler, Percy A., <u>Relative Slipperiness of Floor and Deck</u> Surfaces, BMS Report 100, NBS, July 1, 1943.

Sigler recognized that the <u>difference</u> in slip-resistance of the same material wet and dry may represent a hazard [5]. For example, the difference in slip-resistance of wet and dry rubber heels is greater than the difference in slip-resistance of wet and dry leather heels. Hence, wet rubber heels offer more of a "surprise" to the user than wet leather heels, even though rubber heels are generally more slipresistant. Current NBS research, which considers factors like "surprise" is discussed in Section 4.3 of this report.

As a further fundamental study of the reasons for slips and falls, and to aid in the design of slip-resistance testers, an analysis was made of human locomotion [6]. Slow motion pictures of people walking were taken with concealed cameras in a natural setting. The films showed that when the leading foot is first placed upon the walkway, the rear foot remains in contact with the walkway, bearing part of the vertical load until the leading heel rocks forward and the foot is fully planted. A survey was also made of worn heels to determine the probable angles at which heels of shoes make initial contact with walkway surfaces. Information gained from the human locomotion studies was utilized in the design of a portable model of the pendulum tester. The portable model of the tester was used by Sigler, Geib, and Boone to test a number of floors in actual service. A careful series of tests showed the device to give repeatable results. However, adjustment of the machine settings, such as level and spring tension could appreciably change the antislip values obtained. For this reason, Sigler indicated that the antislip coefficients obtained should be considered as relative, rather than absolute values, and if incorporated into a specifcation or code should be based on a definite method of testing.

In a related study under Sigler's direction, an electro-mechanical force plate developed by W. E. Williams was used to give a quantitative determination of the vertical and horizontal components of the force exerted by the leg on a walkway surface during locomotion [7]. The

published data seemed to indicate that a coefficient of friction greater than 0.2 is required to prevent slippage in the forward direction and a coefficient of friction greater than 0.4 is required to prevent slippage in a backward direction. The device is illustrated in Figure 3.

2.3 Federal Construction Council

In 1961, NBS contributed substantially to a definitive study which established a rational framework for the development of quantitative slip-resistance standards [8]. The Federal Construction Councils' Operating Committee appointed a task group of qualified technical personnel for six Federal agencies to examine the causes and measurement of walking slipperiness.

Thomas H. Boone was the NBS participant in this group which sought to recommend performance tests to be used as a basis for establishing slip-resistant characteristics of various surfaces, with a primary focus on interior surfaces subject to pedestrian traffic.

The Task Group reviewed the literature of the field, observed demonstrations of various testing machines, and contacted flooring product manufacturers, insurance companies, trade associations, research laboratories, and others to assess the state-of-the-art of slip-resistance measurement. The Task Group reported the following conclusions and recommendations in 1961:

Task Group Conclusions

Present Status of Knowledge and Practice Considerable research has been done.



The NBS Electro-mechanical Force Plate (1951). Used to study forces exerted by the leg on a walkway surface.

- b. Existing machines and methods are useful tools for measuring the relative slip-resistance of various materials under controlled, laboratory conditions.
- c. Available data on friction are too closely associated with the type of apparatus used and the operator's techniques to be given broad significance.
- d. A designer who has determined the slip-resistance requirements he desires in a structure has no means of translating his requirements into a meaningful specification except by selecting products which provided satisfactory performance in past experience. Similarly, maintenance personnel have no exact method of checking to ensure that the slip-resistant properties of a flooring material are preserved.
- e. Given the current state-of-the-art, it would be impracticable to attempt to establish a specific standard to ensure safety from slips.
- f. In the absence of a universally accepted criterion and method of measurement, slip-resistance claims for a particular product or material are of questionable validity.
- 2. Future Needs
 - a. To develop a set of standard reference surfaces for use by designers and manufacturers and to serve as constants for calibrating and comparing all types of friction measuring equipment.
 - b. To develop or select a simple, portable, economical piece of equipment which could be readily used by maintenance personnel to establish a comparative relationship between surfaces in service and a standard surface.

Task Group Recommendations

- 1. At the present time (1961). Initiate research and development program to:
 - a. Develop a set of standard reference surfaces which are economically reproduced; usable under field or laboratory conditions, and have long-term stability/durability or are expendable.
 - b. Select or develop a simple portable device for field use in measuring slip-resistance.
 - c. Conduct a comprehensive series of tests on in-service floor surfaces thought to be hazardous and correlate the results with the standard surfaces.
 - d. Develop slip-resistance standards which consider locations and conditions of use.
- 2. In the Interim
 - a. Before installing any material which claims slip-resistant characteristics, it should be tested under conditions which simulate actual usage conditions.

- b. No single criterion should be established for all pedestrian surfaces.
- 3. In the Future

The Task Group should be reconvened after the recommended research and development is completed, with the following objectives:

- a. To classify materials intended for pedestrian traffic with respect to slip-resistance and appropriate use.
- b. To recommend the most suitable type of "antislip" materials for each type of walkway surface.
- c. To recommend maintenance procedures.

The Task Group also suggested that the recommended activities might appropriately be done by NBS.

2.4 T. H. Boone.

At the time the Federal Construction Council's report was published, work was in process at NBS on the slip-resistance of walkway and roadway surfaces [9].

Thomas H. Boone, the NBS representative in the FCC study group, directed research at NBS in cooperation with the Bureau of Public Roads and ASTM Committee E-17 on Skid-resistance.

The test measurements were made with the British Portable Skid-Resistance Tester (Figure 4) developed by the Road Research Laboratory of England. This tester is identical in principle with the NBS tester developed by Sigler in 1943. The research included an evaluation of a synthetic rubber developed as a material for vehicle tires, and tests to determine the effect of 4 years of pedestrian use on samples of asphalt tile, vinyl asbestos tile, cork, lineoleum and vinyl.

An attempt was also made to identify materials that could be used as standard reference surfaces. However the difficulties encountered



in controlling the instrument's variables precluded an exacting study. Further research on slip-resistance was not carried out at NBS until the early 1970's.

2.5 The Man in the Shoe

In January 1973, the Social and Engineering Sciences Group of the Technical Analysis Division of NBS produced an internal memorandum entitled "The Man in the Shoe" which outlined a research program on human walking. The goal of the proposed research was to develop requirements for shoe construction and materials which would reduce the risk of slips and falls. In addition to proposing extensive research programs on the human engineering aspects of walking, the memorandum reviewed the concept of "equivalent adherence."

A major cause of slips and falls may be an <u>unexpected</u>, i.e., sudden change in the adherence characteristics of the surface being walked upon. If the factor of unexpectedness could be avoided or controlled, the majority of slips and falls might be avoided. Hence, the development of a sole and heel material and tread design which offers the same slip-resistance, or "equivalent adherence" to most surfaces under most conditions could significantly reduce accidental slips and falls. While it was reported that the French have successfully developed such material for footwear used in the marine industry [10] the concept has not been extended for footwear in general. The concept of "equivalent adherence" implied that an optimum level of slip-resistance must strike a balance between slipperiness and excessive gripping.

However, a major impediment to carrying out the recommended research program was the lack of a portable, easy to use, reliable tester and a set of standard reference surfaces for calibration of test results.

3. RECENT NBS ACTIVITY

Recent NBS research on slip-resistance was initiated in 1974 by the Building Safety Section (BSS) of the Center for Building Technology (CBT). The mission of the Building Safety Section was to reduce building-related accidental deaths and injuries by conducting research to support the development of safety criteria, test methods and standards.

An initial analysis of accident statistics developed by the National Safety Council and the Consumer Product Safety Commission clearly identified slips and falls as the major cause of building-related accident death and injury. Hence, one of the first projects undertaken by the Building Safety Section was a preliminary study of the slipperiness of flooring.

3.1 Preliminary Study of Floor Slip-Resistance

A preliminary study by Cramp and Masters involved three test methods, three flooring materials and two sensor materials under dry and wet conditions [11]. The three test methods included the James Static Friction Tester [3], the British Portable Skid Tester [12], and the Horizontal Pull Slipmeter [13], a device designed to measure static or dynamic friction. Samples of vinyl asbestos tile, vinyl tile and lineoleum were selected as representative of the three most commonly

used types of resilient flooring. The sensor materials were cowhide and styrene butadiene rubber. Table 2 is a summary of the test results.

A brief examination of the test results indicates that (a) absolute friction values are a function of the test device as well as the materials being tested, and (b) different testers are inconsistent with respect to relative ranking of materials. For example, the British Portable Tester ranked dry leather as more slip-resistant than wet leather on all three surfaces, while the Horizontal Pull Slipmeter ranked wet leather as more slip-resistant than dry leather on two surfaces and found no difference on the third surface.

3.2 Literature Review

From June 1974 to November 1976, Dr. Robert Brungraber of Bucknell University joined the NBS staff as a visiting scholar under the terms of the Intergovernmental Personnel Act. During this period he made significant contributions to the slip-resistance research program at NBS. One of his first tasks was to conduct an extensive review of the literature on slip-resistance and related fields [14]. The resulting document, NBS Tech Note 895, contains an annotated bibliography of over 120 relevant publications. However, Dr. Brungraber's most important contribution to this field was the development of a reliable, easily calibrated, portable slip-resistant tester.

3.3 NBS-Brungraber Portable Slip-Resistance Tester

Most published research on slip-resistance assumes that slipresistance is related to coefficient of friction in a fundamental way.

Table 2. Comparison of Slip-Resistance Readings From Three Test Methods (Data from Table 17 of NBSIR 74-613, Preliminary Study of the Slipperiness of Flooring by A. Phillip Cramp and Larry W. Masters)

TEST METHOD				
Test	James Static ¹	British Portable ²	Horizontal Pull ³	
Condition	Friction Tester	Skid Tester	Slipmeter	
VINYL ASBESTOS	FILE			
LEATHER/DRY	• 42	36.9	•44	
LEATHER/WET	• 41	10.2	•66	
RUBBER/DRY		101.4	•82	
RUBBER/WET		24.3	•81	
VINYL TILE				
LEATHER/DRY	•60	19.4	•60	
LEATHER/WET	•35	10.4	•60	
RUBBER/DRY		91.1	•94	
RUBBER/WET		14.2	•96	
LINEOLEUM				
LEATHER/DRY	• 57	57.8	•64	
LEATHER/WET	• 45	26.3	•88	
RUBBER/DRY		117.2	• 80	
RUBBER/WET	-	41.3	• 87	

¹ Tables values for the James Static Friction tester are static coefficient of friction.

- ² Table values for the British Portable Skid Tester are expressed in "British Portable Skid Tester Numbers," which cannot be readily converted into coefficients of friction. The values can be used to compare testers as to "relative ranking" of materials.
- ³ Table values for the Horizontal Pull Slip Meter are coefficient of friction values derived from the "slip index" measured by the tester.

More specifically, there are considerable research data which indicate that static coefficient of friction (rather than dynamic) is the relevant variable when considering normal walking [15, 16, 17]. Owing to the serious limitations found in existing devices, Dr. Brungraber developed at NBS a new portable tester for measuring the static coefficient of walkway surfaces. The new NBS-Brungraber Tester (Figure 5) has the following characteristics:

- It is based on the same principle of operation as the James Machine, a recognized ASTM Standard.
- It is completely portable, and can be used under wet or dry, laboratory or field conditions.
- 3. It provides highly repeatable and accurate results.
- 4. It can be easily and reliably calibrated.
- It accepts a wide variety of sensor materials which may be representative of bare or shod feet.
- 6. It is self-starting and produces a measurement immediately after being placed on a walkway surface, thereby reducing the problem of time-dependent adhesion.

7. It can be used on stairs, and on ramps inclined up to 4°. Details of the tester development and operation are contained in NBS Tech Note 953 [4]. In 1977, R. Braun and R. Brungraber carried out an reported [18] an extensive evaluation of the theoretical basis for and empirical operation of the NBS-Brungraber tester.



3.4 Problem-Oriented Research

A number of recent, narrow-in-scope research activities have been carried out for other agencies, using the NBS-Brungraber Tester and other test machines.

The Building Safety Section measured and compared the slipresistance of five deck paints to the slip-resistance of bare concrete. A leather sensor mounted on a standard James Machine [3] was used to measure the slip-resistance of the five paints applied to both smooth and rough finished concrete under dry and wet/icy conditions. Under all test conditions, bare concrete was more slip-resistant than any of the painted specimens.

The Architectural Research Section of the Center for Building Technology, NBS, directed an extensive field study to identify characteristics of existing stairways which increase the likelihood of an accidental slip or fall. As a part of this study, the NBS-Brungraber Tester was used to collect over 3,000 measurements on 112 stairways. A comparison of the slip-resistance of stairways in general to the slip-resistance of stairways where accidents were known to have occurred led to the conclusion that slip-resistance is not a significant factor in stairway accidents [19]. This important finding may have a significant impact on stairway accident research.

In response to a petition from the National Swimming Pool Institute and the Aquaslide 'N' Dive Corp., the Consumer Product Safety Commission (CPSC) requested and subsequently funded a study by the Building Safety Section of the slip-resistance of swimming pool deck surfaces.

The objective of the study was to develop a test procedure for reference in a national safety standard for slippery surfaces around in-ground swimming pools. Preliminary results of the study indicated that the slip-resistance of pool deck surfaces could be adequately evaluated with the NBS-Brungraber Tester.

In the spring of 1975, ASTM Subcommittee F15.03.1 (Specifications and Test Methods for Slip-Resistance of Bathing Facilities) requested technical assistance from the Building Safety Section in developing a performance test for quantitatively establishing an acceptable level of slip-resistance for bathtub and shower bases. Close cooperation between the subcommittee members and the Building Safety Section staff resulted in the development of a reliable performance test which approximates the conditions that are likely to occur on a bathtub or shower surface, and adequately discriminates between currently available tub and shower materials. The test procedure uses an NBS-Brungraber Tester equipped with a silicone rubber sensor immersed in a soap solution. The work was funded by the CPSC and the proposed test procedure is currently under ASTM review [20, 21].

4. NOW AND THE FUTURE

The slip-resistance work is now being conducted in the newly created Building Safety and Security Group, of the Environmental Design Research Division at the National Bureau of Standards. This group and the Construction Safety Group have assumed the tasks previously performed by the Building Safety Section.

4.1 Data Base Development

An extensive series of tests of commonly encountered walking surfaces has been conducted at selected locations including Bucknell University, Lewisburg, Pennsylvania, and Gallaudet College and the National Gallery of Art, in Washington, D.C. Many of the surfaces have had long service histories with a variety of maintenance regimes. The goal of this work is to provide an understanding of the range of existing walkway conditions typically encountered in public places. Data for common floor materials including polished and worn wood, terrazo, marble, concrete and vinyl-asbestos tile will be provided. Both wet and dry measurements have been completed and a report will be published in 1979.

4.2 Standard Reference Surfaces

The Building Safety and Security Group is investigating the feasibility of utilizing standardized reference surfaces as a universal calibration system for slip-resistance testers. The objective is to develop a set of reference surfaces which are:

- 1. Easy to duplicate.
- 2. Durable (or inexpensive enough to be expendable).
- 3. Stable over the duration of recommended use.
- Suitable for laboratory and field use, i.e. usable in a wet or contaminated environment.
- 5. Uniform and sufficiently close in coefficient of friction values to permit assessment of a tester's ability to discriminate between similar but not identical materials.

 Sufficient in number to cover a wide range of slip-resistance values.

A universal calibration system will give researchers in different laboratories, utilizing different test devices, a meaningful way to compare interlaboratory results. Similarly, codes and standards requirements for slip-resistance could be expressed in terms of standard reference surfaces.

4.3 A More General Investigation of Slips and Falls

Even for relatively slippery surfaces, slips and falls are rare events. Current NBS projects are expanding research on falls to include other variables such as related environmental factors (lighting, appearance), biomechanical considerations (gait, human structural deviations), and human perception and behavior ("surprise" concept).

Examination of these additional factors and their interactions will lead to a fuller understanding of slips and falls and identification of appropriate intervention strategies.

5. SUMMARY

The National Bureau of Standards has a long history of research in the measurement of walking surface friction and the causes of slips and falls on walkway surfaces. Current activities are concerned with further quantification of coefficient of friction measurements of walkway surfaces, as well as the development of a broader perspective on the nature, causes, and prevention of slips and falls. Proposed future research thrusts are related to the evaluation of personal as well as environmental factors that contribute to falls, including biomechanical,

perceptual and behavioral considerations of users and lighting and differential conditions of the environmental.

APPENDIX

Basic Concepts Relating to Friction and Slip-Resistance Measurement

Friction - The force which resists the relative movement of two surfaces in contact with each other.

Static Friction - The resisting force at the instant relative motion begins.

<u>Dynamic Friction</u> - The resisting force when movement is occurring without interruption. For most materials, dynamic friction is less than static friction.

<u>Coefficient of Friction</u> - Defined as the ratio of the force required to move one surface over another to the total force pressing the two surfaces together.,

$\mu = \frac{\text{HORIZONTAL FORCE}}{\text{VERTICAL FORCE}}$

<u>Measurement of Friction</u> - There are two approaches to measuring friction. In the direct approach, the test device measures or indicates the horizontal and vertical forces. This includes drag-type meters and articulated strut devices. The indirect approach calculates the frictional force by observing an energy loss in the test device. The most common example of the indirect approach is a pendulum-type device. These devices are illustrated in Fig. A-1.

Drag-Type Meters - A weight of known value, faced with a shoe sole or heel material is pulled across a floor surface. The force required to



Figure Al

Typical Friction Measurement Devices

start motion (static friction) or maintain motion (dynamic friction) is recorded. (Figure Al-a)

<u>Articulated Strut Devices</u> - A known vertical force is applied to a shoe faced with shoe sole or heel material. An increasing lateral force is then applied until slip occurs. The ratio of lateral force at slip to the known vertical force is the coefficient of friction.

Note in Figure Al-b, there are three ways of going from the initial position to the position at the instant of slip.

- The shoe can be pushed/pulled to the left until slip occurs (dynamic friction, Hunter Machine).
- The floor surface can be moved to the left until the shoe slips (static friction, James Machine).
- The weight can move to the right until the shoe slips (static friction, NBS-Brungraber Tester).

<u>Pendulum-type Tester</u> - In a pendulum-type tester, a pendulum, faced with a shoe sole or heel material sweeps a path across a flooring surface. The potential energy of the pendulum at the beginning of a swing and its residual energy at the end of a swing can be determined from the known weight and position of the center of gravity of the pendulum. The difference, or loss in energy, is equal to the work done in sliding the contact material over the walkway surface, which is the average contact friction force times the distance of contact. By definition, the average frictional force is equal to the coefficient of friction times the average force normal to the plane of contact. From these relationships

an equation can be established for the coefficient of friction in which all factors except the scale reading at the end of the swing are known constants of the instrument. (Fig. Al-c)

References

- U.S. Nat. Safety Council, <u>Accident Facts</u>: 1977 Edition, Chicago, Ill.
- Hunter, R. B., "A Method of Measuring Frictional Coefficients of Walkway Materials," <u>National Bureau of Standards Journal of Research</u>, RP 204, Vol. 5, p. 329 (August 1930).
- 3. ASTM, "Standard Method of Test for Static Coefficient of Friction of Polish Coated Floor Surfaces as Measured by the James Machine," ASTM D2047, American Society for Testing and Materials, Philadelphia, Pa.
- Brungraber, R. J., <u>A New Portable Tester for the Evaluation of the Slip-Resistance of Walkway Surfaces</u>, National Bureau of Standards Tech. Note 953, Aug. 1977.
- 5. Sigler, P. A., "Relative Slipperiness of Floor and Deck Surfaces," <u>Building Materials and Structures Report</u>, BMS 100, National Bureau of Standards (July 1, 1943).
- 6. Sigler, P. A., Geib, M. N., Boone, T. H., "Measurement of the Slipperiness of Walkway Surfaces," <u>National Bureau of Standards</u> Journal of Research, RP 1879, Vol. 40, p. 339 (May 1948).
- 7. "Electronic Stepmeter Revels Mechanics of Walking," <u>National Bureau</u> of Standards Technical News Bulletin, Vol. 35, No. 4, April 1951.
- <u>Causes and Measurement of Walking Slipperiness</u>, Federal Construction Council Technical Report #43, National Academy of Sciences, National Research Council Publication 899, Washington, D.C., 1961.
- Boone, T. H. and Auld, C. W., <u>Standard Measurements of Slipperiness</u> on Walkway and Roadway Surfaces, Progress Report 1, National Bureau of Standards Report 7510, May 1962.
- "How an Antislip Sole was Born," <u>National Safety News</u>, Nov. 1966, pp. 38-39.
- 11. Cramp, A. P. and Masters, L. W. <u>Preliminary Study of the Slipperi-</u> ness of Flooring, National Bureau of Standards Report, NBSIR 74-613 (July 1974).
- 12. ASTM, "Standard Method of Test for Measuring Surface Frictional Properties Using the British Portable Tester," ASTM E303-69, American Society for Testing and Materials, Philadelphia, Pa.
- 13. Irvine, C. H., "A New Slipmeter for Evaluating Walkway Slipperiness," <u>Materials Research and Standards</u>, Vol. 7, No. 12, Dec. 1967, pp. 535-541, American Society for Testing and Materials, Philadelphia, Pa.

- 14. Brungraber, R. J., <u>An Overview of Floor Slip-Resistance With Anno-tated Bibliography</u>, National Bureau of Standards Tech Note 895 (Jan. 1976).
- 15. Carlsoo, Sven, <u>How Man Moves: Kinesiological Methods and Studies</u>, Heinemann: London, 1972.
- 16. Ekkebus, C. F. and Kelly, W., "Measurement of Safe Walkway Surfaces," Soap/Cosmetics/Chemical Specialities, Feb. 1973.
- Schuster, K., "Slip-An Investigation of Practical Accident Prevention," <u>Die Berufagenossenschaft/Betriebssicherheit</u>, Sept. 1966.
- 18. R. Braun and R. J. Brungraber, "A Comparison of Two Slip-Resistance Testers", in <u>Walkway Surfaces: Measurement of Slip Resistance</u>, Proceedings of the ASTM Symposium in Denver, Colo., 30 June 1977, American Society for Testing and Materials, Philadelphia, Pa.
- 19. Carson, D. H., Archea, J., Margulis, S. T., and Carson, F. C., <u>Safety on Stairs</u>, National Bureau of Standards Building Science Series (No. 108, Dec 78).
- 20. Final Report of ASTM Task Group F15.03 on Safety Standards for Bathtub and Shower Structures, Aug. 31, 1976, contains a detailed description of the proposed test method. Available from American Society for Testing and Materials, Philadelphia, Pa.
- 21. R. J. Braungraber and S. C. Adler, "Technical Support for a Slip-Resistance Standard," in <u>Walkway Surfaces: Measurement of Slip-Resistance</u>, proceedings of the ASTM Symposium in Denver, Colo.; 30 June 1977, American Society for Testing and Materials, Philadelphia, Pa.

NBS-114A (REV. 9-78)				1	
U.S. DEPT. OF COMM. BIBLIOGRAPHIC DATA SHEFT	PUBLICATION OR REPORT NO.	2.Gov't. Accession No.	3. Recipient's Ac	cession No.	
4. TITLE AND SUBTITLE	ND0 51 303	1	5. Publication Da	ate	
A History & He	llesse Olim Desigteres	Pagaamah	Decembe	er 1979	
A History of Walkway Slip-Resistance Research at the National Bureau of Standards			6. Performing Organization Code		
7. AUTHOR(S)			8. Performing Org	gan. Report No.	
Sanford C. Adle	er and Brian C. Pierma	in			
9. PERFORMING ORGANIZATION	NAME AND ADDRESS		10. Project/Task/ 743320	Work Unit No. 05	
NATIONAL BUREAU OF STANDARDS DEPARTMENT OF COMMERCE WASHINGTON, DC 20234			11. Contract/Grant No.		
12. SPONSORING ORGANIZATION	NAME AND COMPLETE ADDRESS (Street	City, State, Z1P)	13. Type of Report & Period Covered		
			Final		
Same as ab	ove		14. Sponsoring Agency Code		
				· · · · · ·	
 15. SUPPLEMENTARY NOTES Library of Congress Catalog Card Number: 79-600179 Document describes a computer program; SF-185, FIPS Software Summary, is attached. 16. ABSTRACT (A 200-word or less factual summary of most significant information. If document includes a significant bibliography or literature survey, mention it here.) This report summarizes NBS research in the area of walkway and shoe slip-resistance measurement since 1924 and outlines current activities that will provide a technical basis for slip-resistance measurement. The work of Sigler, Hunter, Boone and Brungraber represents the historic perspective. Current activities in data base development and identification of standard reference surfaces contribute to a rational basis for quantitative slip-resistance criteria for building codes and standards. Proposed future research thrusts include personal factors such as human biokinetic and perceptual variables, as well as environmental factors such as lighting in the built environment. This research will contribute to the development of new intervention strategies to reduce deaths and injuries due to slips and falls.					
seperated by semicolons) Friction; measurement; reference standards; safety research; walkway slip-resistance.					
18. AVAILABILITY	I Unlimited	19. SECURIT (THIS RE	Y CLASS PORT)	21. NO. OF PRINTED PAGES	
For Official Distribution. D	o Not Release to NTIS	UNCLASS	IFIED	36	
X Order From Sup. of Doc., U. 20402, SD Stock No. SN003-	S. Government Printing Office, Washington	, DC 20. SECURIT (THIS PA	Y CLASS GE)	22. Price \$1.75	
Order From National Technic VA. 22161	cal Information Service (NTIS), Springfield,	UNCLASS	IFIED		

USCOMM-DC

NBS TECHNICAL PUBLICATIONS

PERIODICALS

JOURNAL OF RESEARCH—The Journal of Research of the National Bureau of Standards reports NBS research and development in those disciplines of the physical and engineering sciences in which the Bureau is active. These include physics, chemistry, engineering, mathematics, and computer sciences. Papers cover a broad range of subjects, with major emphasis on measurement methodology and the basic technology underlying standardization. Also included from time to time are survey 'articles on topics closely related to the Bureau's technical and scientific programs. As a special service to subscribers each issue contains complete citations to all recent Bureau publications in both NBS and non-NBS media. Issued six times a year. Annual subscription: domestic \$17; foreign \$21.25. Single copy, \$3 domestic; \$3.75 foreign.

NOTE: The Journal was formerly published in two sections: Section A "Physics and Chemistry" and Section B "Mathematical Sciences."

DIMENSIONS/NBS—This monthly magazine is published to inform scientists, engineers, business and industry leaders, teachers, students, and consumers of the latest advances in science and technology, with primary emphasis on work at NBS. The magazine highlights and reviews such issues as energy research, fire protection, building technology, metric conversion, pollution abatement, health and safety, and consumer product performance. In addition, it reports the results of Bureau programs in measurement standards and techniques, properties of matter and materials, engineering standards and services, instrumentation, and automatic data processing. Annual subscription: domestic \$11; foreign \$13.75.

NONPERIODICALS

Monographs—Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

Handbooks—Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications—Include proceedings of conferences sponsored by NBS, NBS annual reports, and other special publications appropriate to this grouping such as wall charts, pocket cards, and bibliographies.

Applied Mathematics Series—Mathematical tables, manuals, and studies of special interest to physicists, engineers, chemists, biologists, mathematicians, computer programmers, and others engaged in scientific and technical work.

National Standard Reference Data Series—Provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated. Developed under a worldwide program coordinated by NBS under the authority of the National Standard Data Act (Public Law 90-396). NOTE: The principal publication outlet for the foregoing data is the Journal of Physical and Chemical Reference Data (JPCRD) published quarterly for NBS by the American Chemical Society (ACS) and the American Institute of Physics (AIP). Subscriptions, reprints, and supplements available from ACS, 1155 Sixteenth St., NW, Washington, DC 20056.

Building Science Series—Disseminates technical information developed at the Bureau on building materials, components, systems, and whole structures. The series presents research results, test methods, and performance criteria related to the structural and environmental functions and the durability and safety characteristics of building elements and systems.

Technical Notes—Studies or reports which are complete in themselves but restrictive in their treatment of a subject. Analogous to monographs but not so comprehensive in scope or definitive in treatment of the subject area. Often serve as a vehicle for final reports of work performed at NBS under the sponsorship of other government agencies.

Voluntary Product Standards—Developed under procedures published by the Department of Commerce in Part 10, Title 15, of the Code of Federal Regulations. The standards establish nationally recognized requirements for products, and provide all concerned interests with a basis for common understanding of the characteristics of the products. NBS administers this program as a supplement to the activities of the private sector standardizing organizations.

Consumer Information Series—Practical information, based on NBS research and experience, covering areas of interest to the consumer. Easily understandable language and illustrations provide useful background knowledge for shopping in today's technological marketplace.

Order the above NBS publications from: Superintendent of Documents, Government Printing Office, Washington, DC 20402.

Order the following NBS publications—FIPS and NBSIR's—from the National Technical Information Services, Springfield, VA 22161.

Federal Information Processing Standards Publications (FIPS PUB)—Publications in this series collectively constitute the Federal Information Processing Standards Register. The Register serves as the official source of information in the Federal Government regarding standards issued by NBS pursuant to the Federal Property and Administrative Services Act of 1949 as amended, Public Law 89-306 (79 Stat. 1127), and as implemented by Executive Order 11717 (38 FR 12315, dated May 11, 1973) and Part 6 of Title 15 CFR (Code of Federal Regulations).

NBS Interagency Reports (NBSIR)—A special series of interim or final reports on work performed by NBS for outside sponsors (both government and non-government). In general, initial distribution is handled by the sponsor; public distribution is by the National Technical Information Services, Springfield, VA 22161, in paper copy or microfiche form.

BIBLIOGRAPHIC SUBSCRIPTION SERVICES

The following current-awareness and literature-survey bibliographies are issued periodically by the Bureau:

Cryogenic Data Center Current Awareness Service. A literature survey issued biweekly. Annual subscription: domestic \$25; foreign \$30.

Liquefied Natural Gas. A literature survey issued quarterly. Annual subscription: \$20.

Superconducting Devices and Materials. A literature survey issued quarterly. Annual subscription: \$30. Please send subscription orders and remittances for the preceding bibliographic services to the National Bureau of Standards, Cryogenic Data Center (736) Boulder, CO 80303.

U.S. DEPARTMENT OF COMMERCE National Bureau of Standards Washington, D.C. 20234

OFFICIAL BUSINESS

Penalty for Private Use, \$300

POSTAGE AND FEES PAID U.S. DEPARTMENT DF COMMERCE COM-215



SPECIAL FOURTH-CLASS RATE BOOK