



A11107 259757

NBS

PUBLICATIONS

National Bureau of Standards
Library


JUL 31 1985

NBS SPECIAL PUBLICATION

693

U.S. DEPARTMENT OF COMMERCE /National Bureau of Standards

A Workshop on STEEL RESEARCH NEEDS FOR BUILDINGS

QC
100
.U57
693
1985
C. 2



The National Bureau of Standards¹ was established by an act of Congress on March 3, 1901. The Bureau's overall goal is to strengthen and advance the nation's science and technology and facilitate their effective application for public benefit. To this end, the Bureau conducts research and provides: (1) a basis for the nation's physical measurement system, (2) scientific and technological services for industry and government, (3) a technical basis for equity in trade, and (4) technical services to promote public safety. The Bureau's technical work is performed by the National Measurement Laboratory, the National Engineering Laboratory, the Institute for Computer Sciences and Technology, and the Center for Materials Science.

The National Measurement Laboratory

Provides the national system of physical and chemical measurement; coordinates the system with measurement systems of other nations and furnishes essential services leading to accurate and uniform physical and chemical measurement throughout the Nation's scientific community, industry, and commerce; provides advisory and research services to other Government agencies; conducts physical and chemical research; develops, produces, and distributes Standard Reference Materials; and provides calibration services. The Laboratory consists of the following centers:

- Basic Standards²
- Radiation Research
- Chemical Physics
- Analytical Chemistry

The National Engineering Laboratory

Provides technology and technical services to the public and private sectors to address national needs and to solve national problems; conducts research in engineering and applied science in support of these efforts; builds and maintains competence in the necessary disciplines required to carry out this research and technical service; develops engineering data and measurement capabilities; provides engineering measurement traceability services; develops test methods and proposes engineering standards and code changes; develops and proposes new engineering practices; and develops and improves mechanisms to transfer results of its research to the ultimate user. The Laboratory consists of the following centers:

- Applied Mathematics
- Electronics and Electrical Engineering²
- Manufacturing Engineering
- Building Technology
- Fire Research
- Chemical Engineering²

The Institute for Computer Sciences and Technology

Conducts research and provides scientific and technical services to aid Federal agencies in the selection, acquisition, application, and use of computer technology to improve effectiveness and economy in Government operations in accordance with Public Law 89-306 (40 U.S.C. 759), relevant Executive Orders, and other directives; carries out this mission by managing the Federal Information Processing Standards Program, developing Federal ADP standards guidelines, and managing Federal participation in ADP voluntary standardization activities; provides scientific and technological advisory services and assistance to Federal agencies; and provides the technical foundation for computer-related policies of the Federal Government. The Institute consists of the following centers:

- Programming Science and Technology
- Computer Systems Engineering

The Center for Materials Science

Conducts research and provides measurements, data, standards, reference materials, quantitative understanding and other technical information fundamental to the processing, structure, properties and performance of materials; addresses the scientific basis for new advanced materials technologies; plans research around cross-country scientific themes such as nondestructive evaluation and phase diagram development; oversees Bureau-wide technical programs in nuclear reactor radiation research and nondestructive evaluation; and broadly disseminates generic technical information resulting from its programs. The Center consists of the following Divisions:

- Inorganic Materials
- Fracture and Deformation³
- Polymers
- Metallurgy
- Reactor Radiation

¹Headquarters and Laboratories at Gaithersburg, MD, unless otherwise noted; mailing address Gaithersburg, MD 20899.

²Some divisions within the center are located at Boulder, CO 80303.

³Located at Boulder, CO, with some elements at Gaithersburg, MD.

Steel Research Needs for Buildings

Proceedings of a Workshop Sponsored By:

National Bureau of Standards
National Science Foundation
American Institute of Steel Construction
American Iron and Steel Institute
Metal Building Manufacturers Association

Held at the National Bureau of Standards
Gaithersburg, Maryland
March 5-6, 1985

Edited by:

Charles Culver
National Bureau of Standards

Nestor Iwankiw
American Institute of Steel Construction

Albert Kuentz
American Iron and Steel Institute



U.S. DEPARTMENT OF COMMERCE, Malcolm Baldrige, Secretary

NATIONAL BUREAU OF STANDARDS, Ernest Ambler, Director

Issued May 1985

Library of Congress Catalog Card Number: 85-600546

National Bureau of Standards Special Publication 693
Natl. Bur. Stand. (U.S.), Spec. Publ. 693, 89 pages (May 1985)
CODEN: XNBSAV

ABSTRACT

This report identifies experimental and analytical research needed to advance the state-of-the-art and improve safety and economy in the design, fabrication and construction of steel buildings. A five year plan for a coordinated research program is included. Recommendations for research projects dealing with the following topics are presented: total building systems, connections and members, frames, seismic design, load and resistance factor design, fire protection, and design loads. The recommendations were developed at a workshop involving participation by steel industry representatives, design professionals, Federal agency representatives and university researchers.

Keywords: buildings, design, fire protection, loads, research, steel, structural engineering.

CONTENTS

ABSTRACT	iii
INTRODUCTION	1
Background	1
Steel Industry Building Research	4
Research Needs Workshop	8
Coordinated Research Program	9
RESEARCH OPPORTUNITIES	11
A. Total Building System	11
A1: On-Site Fabrication	11
A2: Erection Procedures	12
A3: Innovative Systems	12
A4: Large-Scale Testing	13
B. Connections and Members	13
B1: Steel Structures Exposed to Severe Environments	13
B2: Performance of Connections in Weathering Steel Structures	14
B3: Web Stiffeners	14
B4: Seated Beam Connections	15
B5: Semi-Rigid Connections	16
B6: Beam-to-Column Connections	16
B7: Load Deformation Behavior of Welds	17
B8: Moment Connections to Column Webs	18
B9: Lateral and Local Instability of Beams	18
B10: Strength of Webs and Plates Under Fillet Weld Groups	19
B11: Composite Columns	19
B12: Composite Floor Systems	20
B13: Bar Joist Systems	20
B14: New Structural Members	21
C. Frames	21
C1: Three Dimensional Behavior	21
C2: Influence of Connections	22
C3: Cladding and Infilling	22
C4: Lateral Deflection	23

C5:	Field Measurements	24
C6:	Composite Construction	24
C7:	Cold-Formed Construction	25
C8:	Non-Compact Sections	25
D.	Seismic Design	26
D1:	Behavior of Semi-Rigid Connections	26
D2:	Drift Control Criteria	27
D3:	Seismic Performance	28
D4:	Steel Stud Walls	28
D5:	Beam-Column Joints	29
D6:	Beam-Columns	30
D7:	Tubular Members	31
D8:	End-Plate Beam-to-Column Connections	32
D9:	Bolted Web Moment Connections	33
D10:	Bracing Connections	34
D11:	Viscoelastic Damping	35
D12:	Ductility Demand	36
D13:	Braced Frame Stability	36
D14:	Lateral Bracing	37
D15:	Overall System Response	38
D16:	Evaluation of Existing Buildings	39
E.	Load and Resistance Factor Design	40
E1:	Connections With Oversize Holes	40
E2:	Web Crippling	40
E3:	Technology Transfer	41
E4:	Resistance Factors	41
E5:	Serviceability Criteria	42
E6:	Lateral Motion Criteria	43
E7:	Vibration Control for Light Floor Systems	43
E8:	Plastic Design	44
E9:	System Reliability	44
E10:	Wind and Seismic Effects	45
E11:	Existing Buildings	46
F.	Fire Protection	47
F1:	Fire Resistant Design	47
F2:	Design Aids	47
F3:	Shop Applied Fire Protection	48
F4:	Large Area/Large Volume Structures	49
F5:	Fire Research Review	49
G.	Design Loads	49
G1:	Crane Loads	50
G2:	Drifted Snow	50
G3:	Cladding Behavior	50

G4: Wind Loads on Low Rise Buildings	51
G5: Internal Pressure Loading	51
G6: Building Response to Winds	52
G7: Large Area Roofs	52
ACKNOWLEDGMENTS	54
APPENDICES	55
Appendix A - Workshop Keynote Session	55
Appendix B - Workshop Program	67
Appendix C - Workshop Participants	71

INTRODUCTION

BACKGROUND

Steel construction is an important segment of the U.S. economy. Approximately 94 percent of the output of the fabricated structural metal industry is consumed by construction markets. Industrial and commercial building construction account for about two-thirds of this output. Over the past decade the fabricated structural steel market has varied from 3.5 million tons per year to almost 6 million tons per year.

Since its formation more than 60 years ago, the American Institute of Steel Construction, Inc. (AISC) has been the U.S. trade association for the structural steel fabrication industry. The Institute has provided information for structural steel engineering and construction such as the much referenced design specification, standard shape properties and design aids, which are published in the AISC Manual, and has provided services in the form of technical seminars and conferences, marketing and research. The latter activity, sponsored at leading universities and laboratories, has contributed the substance that makes the AISC Specification a world-class design standard. The steel industry has continued to provide funds for research programs even throughout the recent recession. The commitment of AISC and its membership to future research is strong. This research will help advance the state-of-the-art of steel design towards a new generation of AISC Specifications, starting with the Load and Resistance Factor Design (LRFD) Specification and, improved design procedures.

Eight editions of the AISC Manual and Specification provide clear historical evidence of the technical work that has been done and the progress achieved. Plastic design, composite construction, and now LRFD are some of the significant advances. Beginning in 1964, AISC began publishing the quarterly ENGINEERING JOURNAL, which contains articles of current interest to practicing designers. This publication provides a convenient outlet for distribution of new design criteria based on recently completed research and it describes in greater detail the developments in steel design practice.

In addition to its Manual and ENGINEERING JOURNAL, AISC also periodically publishes special texts on particular topics. During the past 2 years, two books have been prepared: Detailing for Steel Construction and Engineering for Steel Construction which contain updated steel design and detailing practice. Ongoing AISC research has provided important input to these books.

The American Iron and Steel Institute (AISI), incorporated in 1908, is a non-profit association of the iron and steel industry. Its purposes are 1) to collect statistics and other

information about the industry; 2) to engage in investigations and research; 3) to provide a forum for the exchange of information and discussion of problems relating to the industry; and 4) to promote the use of iron and steel. Institute activities embrace research and technology, engineering, collection and dissemination of statistics, public distribution of information about the industry and its products, public affairs, and discussion of industrial relations including health safety, and hygiene. The Institute has members in the United States, Canada and Latin America.

Promotional activities of the Institute include applied research, product publicity, booklets, trade show participation, motion pictures, seminars, and educational programs. Many of these activities are carried out in cooperation with important customer associations such as the American Institute of Steel Construction (AISC).

AISI staff engineers work with public agencies and private organizations to promote maximum use of steel mill products in construction. They are responsible for industry activities related to construction codes and regulatory standards, and for research and studies on fire protection of steel in buildings and seismic-resistant design. These activities benefit architects, design engineers, and the public, and have helped introduce new standards for steel construction and the revision of many obsolete code requirements. These changes have broadened the use of conventional steel construction, stimulated the development of new types of cold-formed steel floor, roof, and wall construction, and reduced building and highway costs. In order to carry out this code-related responsibility more effectively, the Institute maintains field offices in cities throughout the United States.

Thirteen Product Promotion Committees within AISI carry on selected research and promotion programs of specific interest to their members who produce a particular product. Committee members include producers of specialty steels such as stainless steel and tool steel, and producers specifically interested in such mill products as hot rolled and cold finished bars, sheet and strip, large diameter line pipe, steel plate, and structural steel.

The Metal Building Manufacturers Association, Inc. (MBMA), organized in 1956 with 13 companies, grew to 35 member firms in 1980. As the industry matured, the number of Association members decreased to 27 in 1985, principally due to mergers consummated between member companies. Association members presently maintain 71 manufacturing plants in 25 states, plus additional facilities in Canada, Europe, Australia, South America and the Middle East. Pre-engineered metal building systems are sold through a network of over 8,800 building contractors.

At present, MBMA manufacturers account for well over 50% of the total market for low-rise, non-residential construction.

Achieving a high in 1983 of 55.1%, pre-engineered metal buildings must now be regarded as the "conventional" way to build 1 and 2 story commercial, community, and industrial buildings. Sales of metal building systems by MBMA members, who presently represent approximately 90% of the pre-engineered market, have topped the billion-dollar mark in five of the past six years. Since a metal building system only accounts for approximately 20% of the total cost of a building project, the 1984 industry sales high of \$1.33 billion represents about \$6.7 billion of in-place construction. Steel tonnage rose 33% in 1984 to a record high of 1.14 million tons.

In close cooperation with AISC and AISI, MBMA attacks a broad range of problems facing the steel industry. Through various standing committees, MBMA marshalls its forces through research and other activities to develop and support new design standards, improve the provisions of model building codes, develop new construction practices and safety regulations as they apply to the metal building industry, and generally advance the state-of-the-art in the design and construction of steel buildings. The MBMA Committees include the Technical, Construction, Mill Relations, Marketing Communications, Fire Protection and Related Insurance Matters, Public Relations, and Post-Disaster Committees, to name just a few. Although the Technical Committee is charged with the primary responsibility for developing and monitoring the research effort, appropriate interaction between all committees is maintained to ensure that the industry produces a high quality, reliable building while, at the same time, adequate attention is given to the need to safeguard economy.

Recently, MBMA joined with AISI to explore ways to obtain greater acceptance of metal building systems by industrial park developers and the financial community. MBMA is also working to assist the Metal Building Dealers Association (MBDA) and its members in reaching these and other important interests.

One of the primary objectives of the Metal Building Manufacturers Association, Inc., is to collect, analyze, and disseminate information. These data are then offered to member companies, customers, architects, engineers, and students at engineering schools across the country in the most comprehensive manner possible. By sharing and publishing the results of research, MBMA seeks to generally improve the understanding and acceptance of metal building systems. The data collected through research are published in various documents. The METAL BUILDING SYSTEMS MANUAL, which was updated for the third time in 1981 by the Technical Committee, incorporated the codified standards on wind load criteria from the Western Ontario wind tunnel research project. The Technical Committee also published a structural design text book entitled, The Design of Single Story Rigid Frames, a Crane Manual for Metal Building Systems, and cooperated with MBDA in the publication of the book entitled, Metal Building Systems. This year will mark the completion of an entirely new publication, Low Rise Building Systems Manual, which is a primer

on design and construction practices for low-rise, non-residential construction and reflects the end result of three decades of research by the industry. Many of the provisions contained in the Design Practices section of the Manual are generally applicable to all types of low-rise construction.

STEEL INDUSTRY BUILDING RESEARCH

There is a continuing need for steel research related to building construction. The steel industry, through the American Institute of Steel Construction (AISC), the American Iron and Steel Institute (AISI), the Metal Building Manufacturers Association (MBMA) and individual companies, has sponsored research on steel building construction for over 70 years. Currently, the industry is pursuing an aggressive program of collaborative research and development with a variety of organizations.

The AISC research activities have always been well defined and regularly monitored by its Committee on Steel Structures Research and the engineering staff. Smaller project task groups composed of industry personnel and outside experts also helped to guide research progress. In most cases, university graduate student teams performed the work under the leadership of an experienced faculty investigator. Results of the research are not only documented in a detailed final report, but are also disseminated in useable form to the structural engineering profession through AISC seminars, publications, and Specification revisions.

The main thrust of steel research in the 1950's was plastic design. Annual funding in the \$100,000 to \$200,000 range was committed by AISC to research in those years, which culminated with the introduction of the AISC Specification Part 2 on plastic design, and with several beneficial changes in allowable stress design due to a recognition of steel's ductility.

From the mid-60's to the 70's, the AISC total research funding declined to about \$60,000 - \$70,000 per year. In the 1980's, during a very competitive construction market environment, greater resources were again devoted to steel research on the order of \$150,000 - \$200,000 per year.

Typically, a single AISC research contractor receives \$20,000 to \$50,000 annually, thereby permitting AISC to support 5 to 10 different projects.

Since the heyday of plastic design studies, the last 20 years of AISC research has been primarily focused on connections - their reliability and economy. The members of AISC, including steel fabricators and professional members, recognize that the integrity of steel structures depends, to a large extent, on the performance of connections. High strength bolts, weldments, composite beams, end plate and shear plate connections have been

included in the AISC research program during recent years.

Considering the number, complexity, and potential scope of the various technical questions posed by engineers, architects, and fabricators, the AISC research budget by itself does not permit much broadly based basic research in structural steel. Most AISC studies are short range and aimed at developing answers to immediate design problems. Interspersed with this necessary reactive work are some developmental projects aimed at innovative concepts or procedures that will improve the design of steel structures. This AISC effort is extended by cooperative sponsorship of larger scale projects with organizations such as the National Science Foundation (NSF), the National Bureau of Standards (NBS) and the Metal Buildings Manufacturers Association (MBMA). Special attention is given to the coordination of AISC research with that of the American Iron and Steel Institute (AISI). The latter organization is making significant contributions towards longer range building research. To maintain technical liaison with related research councils, AISC also supports the work of the Research Council on Structural Connections, the Structural Stability Research Council, the Welding Research Council, and the Steel Structures Painting Council.

The AISI structural steel research program is monitored by the Committee of Steel Plate Producers and the Committee of Structural Steel Producers. The program has been in operation since 1963. The research covers markets which utilize structural steel and steel plate, with special emphasis on heavy construction. To serve the needs of the majority of users, concentration has been on buildings and bridges.

A prime objective of this research in steel utilization is the creation of new or improved design procedures for structural steel and plate. These procedures frequently form the basis of industry specifications and government codes. A secondary objective is the development of data to mitigate unnecessarily stringent provisions in various design specifications.

The program began with a budget of \$250,000 per year and climbed to \$600,000 by 1970. Then in the 70's the research funding gradually declined back to the \$250,000 figure. The 1980's have seen an increase to \$350,000 to meet new challenges in the building construction market. The program consists of an ongoing series of projects - typically 12 are underway at any time - encompassing analytical studies, physical testing and preparation of design manuals. Some are started and finished the same year. More complicated studies can encompass a four- to six-year period. The program recently marked an important milestone with completion of over 100 individual projects since its inception.

The selection of research projects begins with a recommendation from an Engineering Subcommittee consisting of engineers from AISI member steel companies. The final approval

is made by consensus of the Committees of Structural Steel and Steel Plate Producers.

Once a project is approved, a member of the Engineering Subcommittee is appointed project supervisor, overseeing a task force that will plan and direct the project from commencement to completion to ensure that its objectives are met. Task force members can include consultants, educators, engineers, scientists government and code officials, and steel industry personnel.

The research is performed primarily by universities, with some done by private research and consulting organizations, and some by steel company research laboratories. Over 20 universities have taken part in the program.

When a project has been completed, the results are widely disseminated. One technique is to hold seminars in key cities to discuss the project findings. Frequently, the full project report is printed in an AISI "Steel Research for Construction" bulletin - 27 have been printed to date - with copies made available in response to requests.

AISI's research over the years on beam, column and frame behavior has resulted in significant improvements to the provisions of various design specifications - increasing both the economy and safety of steel construction. Significant research accomplishments include:

Load and Resistance Factor Design

Studies begun in 1970 resulted in new limit state criteria containing provisions for loads and load-combinations and rules for the proportioning of structural members and connections. Work continues to improve the reliability of the design format.

Type 2 Construction with Wind Moment Connections

The investigation begun in 1977 demonstrated the viability of the design procedure and led to a better understanding of the effect of connection flexibility on frame stability.

Connections

Studies on single plate framing connections resulted in publication of guidelines for the design of these economical connections and provided a clear understanding of their ductility and moment rotation capacity.

In addition, the Institute's studies of fire hazards and fire protection have contributed to new regulatory concepts relative to the use of non-combustibles, matching protection requirements to the severity of hazards, and avoidance of imbalance in fire risks. The result is greater fire safety, often at lower building costs.

The MBMA research activity has culminated in new and improved design specifications introduced from time to time into the AISC and AISI Specifications and the MBMA Design Practices Manual. The current provisions contained in these documents relative to end-plate connection design, web crippling, the design of tapered members, stability and strength of cold-formed purlins and girts, are but a few of the more notable examples. The recent trend in research activity by MBMA is to focus on building "system" behavior as compared to that of individual components. Thus, new specification provisions are presently being prepared with regard to the required strength, stiffness, and bracing requirements for complete roof systems.

In 1976, MBMA assumed a leadership role in developing new wind load criteria for the design of low-rise buildings. During the ensuing period, extensive research has been conducted in the Boundary Layer Wind Tunnel Laboratory at the University of Western Ontario under the joint sponsorship of MBMA, AISI and the CSICC. This research has culminated in new wind load provisions which have been accepted in the United States and Canada by a number of the appropriate code bodies. Research on wind effects is continuing at the present time.

MBMA research activities are originated and closely monitored by various small task groups or subcommittees composed of industry personnel, outside experts, representatives from AISC and AISI, and staff personnel. In spite of recent dips in the economy, MBMA's basic commitment to research has been steadfastly maintained through the years and the present level of activity is in the \$100,000 - \$150,000 per year range. The number of individual projects vary from year to year. During the current year, for example, six separate projects are underway. Additionally, MBMA awards two fellowships annually to engineering students pursuing a course of study related to steel buildings. The fellowship objective is to encourage creative design investigation of specialized areas relative to fabricated metal building systems.

The MBMA research effort is extended by cooperative efforts with organizations such as AISC, AISI, and hopefully, in the immediate future, NSF. MBMA also supports the research activities of, and maintains technical liaison with, the Wind Engineering Research Council, the Structural Stability Research Council, the Welding Research Council, the Research Council on Structural Connections and the Building Seismic Safety Council.

Although the steel industry is now experiencing difficult economic conditions, its commitment to continued and expanded steel research is evident. With the cooperation and assistance of government and the engineering community, the industry is confident that this effort will lead to new technological advances that will enhance the state-of-the-art of steel design and construction.

RESEARCH NEEDS WORKSHOP

Recognizing the importance of steel research and the need for a coordinated, well-planned program, AISC, AISI, MBMA and the National Bureau of Standards (NBS) decided in 1984 to organize a workshop for the purpose of identifying needed research. The AISC Research Committee, the AISI Building Task Force and the NBS Center for Building Technology developed the initial plan for the workshop. Subsequently, a steering committee consisting of design professionals, industry representatives, government representatives and university researchers was established to plan the technical details.

This report constitutes the proceedings of the workshop on Steel Research Needs for Buildings. The workshop objective was to develop recommendations for experimental and analytical research needed to advance the state-of-the-art and improve safety and economy in the design, fabrication and construction of steel buildings. The recommendations are intended for use by government, industry, and the research community in establishing a cooperative program. Research in the following areas is considered:

Total Building System

Connections and Members

Frames

Seismic Design

Load and Resistance Factor Design

Fire Protection

Design Loads

Workshop participants included representatives from the steel industry, design professionals, Federal agency representatives and university researchers.

The opening session of the workshop included presentations by representatives from the Office of Science and Technology Policy, the National Bureau of Standards and the steel industry. These presentations are included in Appendix A. They provide a perspective on structural steel usage in buildings, consider cooperative research efforts involving industry and government, and provide background material for the workshop recommendations.

The recommendations were developed in two days of intensive subcommittee meetings and plenary sessions. Draft recommendations developed by the participants prior to the workshop served as a starting point for the subcommittee discussion. Each subcommittee focused on one of the seven research areas covered by the workshop. A plenary session

following the subcommittee meetings provided all participants with the opportunity to comment on recommendations developed by each subcommittee. This procedure was repeated to achieve consensus among the participants on the final recommendations.

COORDINATED RESEARCH PROGRAM

The workshop recommendations provide the basis for a comprehensive program to improve safety and economy in the design, fabrication and construction of steel buildings. Activities in this direction are underway. AISC is planning a special educators session on May 21, 1985 in Chicago prior to its International Engineering Symposium on Structural Steel with the theme, "Opportunities for Structural Steel Research". Industry and government speakers will outline the major problem areas. Approximately 100 faculty from across the country are expected to attend.

The level of effort required for each workshop recommendation is indicated in terms of man years. A precise estimate of the funds required cannot be determined without detailed planning for each project. Costs for test specimens, computer time, laboratory personnel, etc., need to be established. The total program represents a substantial effort. A well planned multi-year effort using results obtained in each phase to plan subsequent work is clearly more cost effective than simultaneous initiation of work on each recommendation. Recognizing this, the workshop Steering Committee developed the five-year plan given in Table 1. Recommended funding requirements were established on the basis of the immediacy of the need for the information by the design profession, the ability to achieve synergism between research projects and the opportunity to obtain results as rapidly as possible. It is anticipated that funding would be provided by the private sector and government organizations.

An effective research program requires a coordinated effort. Industry representatives, government representatives, design professionals and researchers should be involved. This can best be achieved by establishing a steering group to provide guidance in establishing required funding levels for the various activities. The goal of the group would be to provide a vehicle for implementing the research results to achieve rapid improvement in the design and construction of steel buildings. This group would meet on a regular basis, monitor progress of the research and update the research needs. Establishing this steering group should be given priority consideration.

TABLE 1

FIVE YEAR PLAN

Structural Steel Research for Buildings

Program Area	FUNDS (in thousands of dollars)				
	Year 1	Year 2	Year 3	Year 4	Year 5
Total Building System	300	300	200	200	200
Connections and Members	800	1000	1000	600	600
Frames	700	800	1000	900	500
Seismic Design	700	1000	1000	600	300
Load and Resistance Factor Design	600	800	800	1000	1000
Fire Protection	300	400	300	200	100
Design Loads	600	700	700	500	300
TOTAL	4000	5000	5000	4000	3000

RESEARCH OPPORTUNITIES

The workshop recommendations provide opportunities for constructing safer and more economical steel buildings. They represent a comprehensive program with emphasis on:

- o characterizing the behavior of individual structural components
- o establishing the performance of total building systems
- o developing improved design procedures and design criteria

They cover the important areas of building design. Synthesis of existing information, experimental work and analytical studies are included.

The individual recommendations should not be considered in isolation. Although they are grouped according to the research areas dealt with at the workshop, other groupings are possible. In addition, many of the recommendations are interrelated. For example, the research on frames and total building systems should draw upon the work on connections and individual members. Similarly, work on load and resistance factor design encompasses both structural elements and systems.

Each recommendation deals with an important problem area. It is assumed they will all be included in a coordinated research program and therefore they are not listed in priority order. The level of effort for each recommendation represents an estimate of the professional manpower required. Detailed research plans for each project are required to establish specific funding requirements.

A. TOTAL BUILDING SYSTEM

Much of the research in the past has concentrated on the behavior of individual components and subassemblages of portions of building systems. Consideration should be given to the total building system and various aspects of the building process, including fabrication and erection, to achieve economy for steel buildings.

RECOMMENDATION A1: ON-SITE FABRICATION

**STUDIES SHOULD BE CONDUCTED TO EXPLORE THE
FEASIBILITY OF ON-SITE FABRICATION OF
STRUCTURAL STEEL COMPONENTS.**

The construction industry has made considerable progress in

developing improved techniques for the fabrication and erection of concrete buildings. Similar innovative erection practices should be developed for steel buildings. One possibility includes utilizing mobile fabrication plants set up at the building site to manufacture large units that could not ordinarily be transported.

Needed research includes identification of fabrication activities more economically carried out on-site rather than in a fabrication shop. Possibilities include fabrication of steel plate shear walls and large tilt-up frame assemblies. Constraints imposed by weather conditions, on-site space limitations, etc., should be considered. Costs associated with each possible on-site activity should be established and compared with current fabrication and transportation costs.

A two man-year level of effort is required.

RECOMMENDATION A2: ERECTION PROCEDURES

IMPROVED COST EFFECTIVE TECHNIQUES SHOULD BE DEVELOPED FOR ERECTING STEEL BUILDINGS.

A research program should be undertaken to develop a coordinated approach to the fabrication and erection of steel buildings. The program should involve a multidisciplinary group composed of designers, detailers, fabricators, and mill and erection engineers. Techniques used on a recently completed 72-story building in Toronto, Canada such as the use of oversized elevators and the panelizations of the steel and granite skin can provide background data. Opportunities to minimize field welding and simplify connection details and development of new framing design concepts should be studied.

A two man-year level of effort is required.

RECOMMENDATION A3: INNOVATIVE SYSTEMS

INNOVATIVE STRUCTURAL FRAMING SYSTEMS SHOULD BE DEVELOPED FOR STEEL BUILDINGS.

Development of the tube concept as a more efficient mechanism than traditional moment resistant or braced frames for resisting lateral loads resulted in more economical high rise structures. New structural systems employing innovative concepts that take advantage of the unique attributes of steel elements should be developed.

A task force composed of architects and structural engineers should be established to identify innovative structural framing concepts. Analytical studies of these concepts should be carried

out and cost comparisons made with traditional framing systems.

A two man-year level of effort is required.

RECOMMENDATION A4: LARGE-SCALE TESTING

LARGE-SCALE TESTS SHOULD BE CONDUCTED TO ESTABLISH THE PERFORMANCE OF INNOVATIVE STRUCTURAL COMPONENTS AND SYSTEMS.

Innovative systems may employ concepts not amenable to traditional structural analysis. In these cases, experiments are required to evaluate the performance of such systems, identify the limit states and establish adequate levels of safety. Large-scale tests will be required to minimize scale effects inherent in testing small-scale laboratory specimens or to determine how the scale effects can be taken into account.

A mechanism should be established for conducting these experiments utilizing existing large-scale structural research facilities throughout the United States.

A multi man-year level of effort is required.

B. CONNECTIONS AND MEMBERS

From the fabricators' point of view, except for the cost of material, freight, shop drawings, and cutting members to length, all other costs are associated with providing connections. From the erectors' point of view on a high rise building, about 30 to 40 percent of the erectors' cost is in making the connections. Connection design is important in achieving safe structures. Continued research is needed for improved understanding of connection behavior to achieve more economical and safe structures.

RECOMMENDATION B1: STEEL STRUCTURES EXPOSED TO SEVERE ENVIRONMENTS

RESEARCH IS NEEDED TO DETERMINE THE EFFECTS OF SEVERE ENVIRONMENTS (COLD AND MOISTURE) ON COMMONLY-USED FABRICATION PROCEDURES.

Commonly used fabrication procedures and steel materials have resulted in several failures in steel structures exposed to low temperatures. These are design, fabrication and construction related issues.

Commonly used cutting techniques often result in plate edge conditions that are not suitable for low temperature service.

Welded details can result in crack-like conditions with backing bars, runoff tabs or flame cut preparations and transitions. High deposition submerged arc weldments can result in low fracture resistance.

Experimental and analytical studies are needed to evaluate the suitability of using current fabrication procedures for exposed building structures with commonly used steel materials (i.e., A36, A572, A588).

A two man-year level of effort is required.

RECOMMENDATION B2: PERFORMANCE OF CONNECTIONS IN WEATHERING STEEL STRUCTURES

DESIGN RECOMMENDATIONS NEED TO BE DEVELOPED FOR BOLTED CONNECTIONS IN BARE WEATHERING STEEL STRUCTURES, SUCH AS BUILDINGS OR TOWERS, TO INSURE THAT THE INTEGRITY OF THE CONNECTIONS IS NOT DEGRADED WITH CONTINUED EXPOSURE TO WEATHERING.

Guidelines have been developed for bolt spacing and edge distance limitations that appear to be required to prevent severe bowing caused by corrosion between faying surfaces of lapped connection elements. This condition arises because the corrosion resistance of weathering steel within such lapped areas is no better than that of carbon steel.

Tests of connections that have been exposed for significant time periods should be conducted to determine how such weathering has affected strength and ductility. Important variables would include bolt spacing and edge distance, bolt type and installation method, time and conditions of the exposure, type of loading (tension, compression, shear-static or cyclic), etc. Possible repair methods for such joints should also be investigated. Evaluations of improved methods for making such details (washers for self-draining features; coatings or sheets of adhesives or mastics for the lapped areas) should be made.

A two man-year level of effort is required.

RECOMMENDATION B3: WEB STIFFENERS

PROCEDURES NEED TO BE DEVELOPED FOR BOTH DESIGN AND DETAILING OF BEARING AND TRANSVERSE WEB STIFFENERS.

Significant research has been completed on the strength of webs subjected to concentrated loads or shear. The design rules in the AISC specification give, with reasonable reliability, the

strength of unstiffened webs. When stiffeners are required to support the loads or shear, the current methods for detailing stiffeners are difficult to document because little research is available. For example, bearing stiffeners are commonly fitted between the flanges at great expense, but no data are available to support this practice. The bearing stiffeners are sometimes designed to carry all the load in spite of the ability of the web itself to carry a significant portion of the load. The design of the bearing stiffener-web combination as a column is based on rules of thumb for K factors and the portion of the web acting with the stiffener. When stiffeners are required to improve the shear buckling capacity of a web, they must have enough moment of inertia to prevent the web from buckling at the stiffener location. Rules of thumb or approximate energy solutions are used to develop design rules. No experimental evidence is available to verify the recommendations.

An analytical and experimental program is needed to study the problem of bearing stiffener and transverse stiffener behavior and design for static loading. Different web depth-thickness ratios should be considered to cover the range of rolled beams and practical plate girders. Specific attention should be given to the effect of the detail at the far end of the stiffener on the stiffener behavior. A few full size specimens should be tested to verify the analytical studies.

A two to three man-year level of effort is required.

RECOMMENDATION B4: SEATED BEAM CONNECTIONS

TABULATED ULTIMATE STRENGTH DESIGN VALUES ARE NEEDED FOR BOLTED AND WELDED SEATED BEAM CONNECTIONS.

Seated connections are often used in steel construction as an erection necessity. Although allowable stress values have been tabulated in the AISC manual for many years, there are few recorded tests. The tabulated values are based on a hypothetical static model. Both welded and bolted seated connections are involved. It is thought that the present load tables may be excessively conservative.

Experimental and analytical studies are required to develop an ultimate strength design basis for seated connections. Both welded and bolted connections should be considered and the studies should include both stiffened and unstiffened seats.

A one man-year level of effort is required.

RECOMMENDATION B5: SEMI-RIGID CONNECTIONS

MOMENT-ROTATION AND DUCTILITY CHARACTERISTICS FOR VARIOUS TYPES OF CONNECTIONS ARE NEEDED TO FACILITATE TYPE 3 CONSTRUCTION.

Analytical techniques are now in existence and are being refined via the computer to analyze and design steel frames with flexible connections. However, a major shortcoming that has prevented regular design office use of Type 3 semi-rigid construction has been lack of reliable data on the structural characteristics of flexible connections, namely their moment-rotation curves. Detailed published information on the nonlinear moment-rotation performance of the connection is limited and not readily available to the practicing engineer. Thus, only idealized Type 1 (rigid) and Type 2 (simple) framing have been employed in buildings. More use could be made of simple low cost semi-rigid connections, with full recognition of their stiffness, strength and ductility, if more complete information was available on their moment-rotation characteristics.

Additional tests are needed to determine typical moment-rotation curves for a given type of connection and their sensitivity to the major design variables. This work, if supplemented by extensive computer analyses should provide a solid basis for generalized methods to approximate moment-rotation properties for any connection. Flexible flange plate and cap and seat angle connections have been studied to some extent. Continuation of this work is desirable to establish a valid and complete moment-rotation data base for future design application. It is expected that such research would provide the necessary impetus for more efficient and economical steel design by demonstrating a good alternative to the often restrictive and expensive fully rigid frame.

A three man-year level of effort is required.

RECOMMENDATION B6: BEAM-TO-COLUMN CONNECTIONS

A COMPREHENSIVE RESEARCH PROGRAM SHOULD BE UNDERTAKEN TO DEVELOP PROBABILITY-BASED DESIGN CRITERIA FOR BEAM-TO-COLUMN CONNECTIONS.

Continued research on connections has led to the development of design procedures for designing frames with partially restrained connections. Parallel to this analytical advancement, a coordinated effort is necessary to collect reliable moment-rotation data, and to produce optimal data for the development of probability-based design criteria.

An experimental and analytical research program including the following work should be undertaken:

- o Collection of moment-rotation data for connections and evaluation and development of analytical models (see RECOMMENDATION B5).
- o Systematic categorization of all connection types and the classification of all relevant limit states.
- o Development of a computerized data bank on all available experimental and analytical research results relating to connections.
- o Identification of the gaps in the available data. Modern tests on many types of connections, performed on the basis of statistical methods, are not available (e.g., column bases, anchorages).
- o Development and implementation of a plan to obtain the needed data.
- o Development of a logical design method for proportioning the beams, connections and the columns.
- o Verification test of a full-scale flexibly-joined frame.
- o Systems reliability analysis of all connection types to determine the reliability against the limit states.
- o Development of design criteria which result in optimal reliability and economy.

A multi year level of effort is required.

RECOMMENDATION B7: LOAD DEFORMATION BEHAVIOR OF WELDS

ACCURATE DETERMINATION OF THE LOAD-DEFORMATION BEHAVIOR FOR ALL WELDING PROCESSES, WELD STRENGTHS, AND LOAD CONDITIONS IS NEEDED.

Analytical work has been published which substantiates experimental results indicating that transversely loaded fillet welds are stronger than longitudinally loaded welds. In addition, stress concentrations are known to affect weld strength. Current information is based on tests under near optimum conditions using E60 electrodes.

Research should be undertaken to investigate the range of variables which affect weld strength. In particular, strength and ductility should be investigated considering load orientation with respect to weld axis, weld wire strengths, and welding processes. In addition, single-pass versus multipass welds should be studied to determine the effect of the root pass and mixing of base metal with weld metal. Finally, the effects of

stress concentrations with regard to load orientation should be investigated.

A one to two man-year level of effort is required.

RECOMMENDATION B8: MOMENT CONNECTIONS TO COLUMN WEBS

DESIGN CRITERIA AND DETAILING PROCEDURES ARE NEEDED FOR MOMENT PRODUCING CONNECTIONS MADE DIRECTLY TO THE COLUMN WEB.

In cases where end plate connections or other moment producing connections (such as single plate framing connections) are framed into a column web, little is known regarding the effect on the web.

Research should be initiated to determine allowable beam moments for various web and end plate configurations. Determination should also be made as the most economical fabrication method to be used to strengthen the column web if required. The project would require both physical testing and analytical work.

A two man-year level of effort is required.

RECOMMENDATION B9: LATERAL AND LOCAL INSTABILITY OF BEAMS

THE EFFECT OF SIMULTANEOUS LATERAL AND LOCAL INSTABILITY ON STRENGTH AND DEFORMATION CAPACITY OF BEAMS SHOULD BE STUDIED FOR LRFD.

The lateral and local instability provisions for beams in the proposed LRFD specification are similar to those in the current allowable stress design (ASD) for compact beams, not those required for beams in plastic design (PD). Which set of provisions to adopt depends on the inelastic deformation capacity to be achieved or required in design.

Research is needed to examine the inelastic behavior of beams with width-to-thickness ratios of flange and web and lateral bracing spacings at the limits specified in ASD and PD. Special factors to consider include:

- o High strength steel beams, repeated and reversed loading, etc.
- o The range of parameters to be studied include: $b_f/2t_f$, d/t_w and l_b and the values should range between those specified in ASD and PD.

An experimental program of research should include full-scale testing of continuous beams and single-story frames. The analytical research should include nonlinear, inelastic frame analysis to determine required deformation capacity.

A two to three man-year level of effort is required.

**RECOMMENDATION B10: STRENGTH OF WEBS AND PLATES
UNDER FILLET WELD GROUPS**

**DESIGN AND DETAILING PROCEDURES ARE NEEDED FOR
DETERMINING WEB OR PLATE THICKNESS REQUIRED TO
MATCH FILLET WELD STRENGTH.**

Current practice uses a method which equates fillet throat allowable stress to web or plate allowable shear stress in order to determine the web or plate thickness required to match the fillet weld strength. For shear alone, this method is correct for a directly welded web connection, but is excessively conservative for a connection using web framing angles. However, when connections are subjected to axial as well as transverse loads, the method referred to above is excessively conservative for both types of connections.

Research is needed to determine accurate procedures and criteria for determining the web or plate thickness required to match fillet weld strength. The parameters to be studied include loads ranging from pure shear to pure axial, coped and uncoped beams, length of connections ranging from 5 1/2 in. to 29 1/2 in. and various clip and angle leg sizes. Testing of full size components is required. An analytical counterpart may also be desirable.

A two man-year level of effort is required.

RECOMMENDATION B11: COMPOSITE COLUMNS

**ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD
BE CONDUCTED TO DEVELOP IMPROVED DESIGN
PROVISIONS FOR COMPOSITE COLUMNS.**

There is a lack of up-to-date information on the strength of composite columns. Existing test data were obtained from laboratory specimens. Design rules included in the LRFD specification are an extension of the Structural Stability Research Council studies concerned with allowable stress design. These formulas may be unnecessarily conservative especially for eccentrically loaded columns.

Experimental studies should be conducted on full-scale composite columns. The tests should include the following range

of parameters: eccentricity ratio - 0 to 2; slenderness ratio - 30 to 90; steel area - 5 to 20 percent. Analytical models should be developed for predicting the ultimate strength behavior.

A three man-year level of effort is required.

RECOMMENDATION B12: COMPOSITE FLOOR SYSTEMS

A COMPREHENSIVE RESEARCH PROGRAM SHOULD BE UNDERTAKEN TO ESTABLISH STRENGTH CRITERIA FOR COMPOSITE BEAMS AND FLOOR SYSTEMS AND THE DEVELOPMENT OF INNOVATIVE SYSTEMS USING SUCH CONSTRUCTION.

Past research has provided the supporting data for the current design provisions of the proposed LRFD Specification. These provisions govern the design of beam sections subjected to positive or negative bending. Work is needed to establish the strength of continuous composite beam and floor systems including the effect of connections with partial rigidity and strength. Preliminary work is underway to investigate the moment-rotation behavior and low-cost composite beam-column connections that rely on the floor reinforcing steel to resist the tension force created by the moment.

The research program on composite construction should consider the following: The effects of construction loads and service loads on permanent deflections; models for predicting the deflection behavior of partially composite systems; the behavior of low cost beam-column connections for composite members; the use of post-tensioned concrete slabs and/or steel beams. Applications to braced frames with composite floors and structures with prefabricated composite units should be studied.

A multi year level of effort is required.

RECOMMENDATION B13: BAR JOIST SYSTEMS

EXPERIMENTS SHOULD BE CONDUCTED TO ESTABLISH SHEAR CAPACITY AND MINIMUM SIDE COVER IN COMPOSITE BAR JOIST SYSTEMS.

Economies can be obtained in bar joist construction if the floor slab can be made to act compositely with the girder supporting the bar joists by using shear studs on the girder flange. Information is not available on the performance of shear studs in this condition with bar joists supported on the girder flange in the vicinity of the studs.

Pushout tests on stud assemblies and several full-scale girder tests should be conducted to establish stud capacities and

side cover requirements for the studs.

A one-half man-year level of effort is required.

RECOMMENDATION B14: NEW STRUCTURAL MEMBERS

NEW STRUCTURAL SHAPES SHOULD BE DEVELOPED FOR IMPROVING THE ECONOMY OF STEEL FRAME BUILDINGS.

The use of large built-up structural members for framing systems is increasing. Economies could be achieved if larger rolled sections with higher moments of inertia were available.

Studies should be conducted to determine the feasibility of producing larger rolled structural shapes, identify the potential market for these shapes and evaluate the savings in fabrication costs.

A one-man year level of effort is required.

C. FRAMES

Considerable research has been carried out on the behavior of individual structural elements and on plane frames of small to moderate size. There is also a large body of information available on the behavior of connections, floor systems, partitions, and cladding - elements that affect the loading on frames and their resistance. As indicated by recommendations in other sections of this report, much additional research is needed on all of these elements. But there is a primary need for research directed towards correlating and integrating these influences. Improved understanding of the three dimensional behavior of total building systems involving more realistic assessment of strength, stability, and stiffness is required to reduce costs of steel buildings. The recommendations of this section are intended in various ways to support the attainment of this basic objective.

RECOMMENDATION C1: THREE DIMENSIONAL BEHAVIOR

ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD BE CONDUCTED ON THE THREE DIMENSIONAL BEHAVIOR OF STEEL FRAMES.

The response of bare steel frames to given loads has been, and will probably remain, the basis for the development of design equations. This response - the stiffness and strength of the bare frame - is affected by a number of things: imperfections, residual stresses, material nonlinearities, loading history, large deflections, post-buckling strength, and connection

behavior.

Analytical and experimental studies are needed to improve the presently inadequate level of understanding of bare frame behavior. Realistic analytical modeling of three dimensional frames that includes these effects is needed. Parallel laboratory testing of three dimensional subassemblages and small buildings should be conducted to provide information needed to calibrate or to confirm these models. The physical research should be on multistory frames - of the order of three to eight stories - and should include both service load and ultimate load behavior.

A multi man-year level of effort is required.

RECOMMENDATION C2: INFLUENCE OF CONNECTIONS

ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD BE CONDUCTED TO EVALUATE THE INFLUENCE OF SEMI-RIGID CONNECTIONS ON THE BEHAVIOR OF STEEL FRAMES.

Connection behavior, the most important factor influencing bare frame behavior, requires special attention. It is the subject of several other recommendations in this report, e.g., B5, B6, and D1. A separate topic should be the influence of connections on frame behavior - as distinct from studies of the characteristics of connections as individual elements. Of particular concern is the influence of partially rigid connections. This research should include an evaluation of the available analytical models and experimental data on the moment rotation characteristics of semi-rigid connections. Existing computer programs for including connection flexibility should be studied, evaluated, and extended. Further research should be conducted on the influence of connection rigidity on column stability. A major effort should be made to extend this research into the determination of the influence of connection rigidity on overall, three dimensional frame behavior. This should be related to the analytical and experimental research called for in RECOMMENDATION C1.

A multi man-year effort is required.

RECOMMENDATION C3: CLADDING AND INFILLING

ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD BE CONDUCTED ON THE INFLUENCE OF FLOORS, PARTITIONS, AND CLADDING ON STIFFNESS AND STRENGTH.

It is well known that the various types of infilling control the ways in which loads are transmitted to the steel frame and that they often interact structurally with the frame in resisting

these loads. Infilling can offer major - even dominant - resistance to displacement at service loads and it can also contribute significantly to the ultimate resistance of the total building system. At present this influence is either ignored, accounted for by judgment, or calculated in some ad-hoc approximate way. Many studies have been made on the stiffness and strength of different types of floors, partitions, and exterior cladding in direct tension and compression, flexure, and shear (racking and diaphragm action). Relatively little quantitative research has been done on infilling-frame interaction however.

There is a need to extend analytical models of the type called for in RECOMMENDATION C1 to include the effect of infilling. Associated with this is the need to collect and correlate available quantitative information on the structural characteristics of major types of infilling. Laboratory testing of three dimensional steel frames containing representative infill elements should be conducted for the purpose of calibrating or confirming analyses.

A multi man-year level of effort is required.

RECOMMENDATION C4: LATERAL DEFLECTION

ANALYTICAL METHODS SHOULD BE DEVELOPED FOR CALCULATING LATERAL DEFLECTIONS OF BUILDINGS.

Related to the previous three recommendations but having a different major thrust is the need to develop improved analytical methods for the calculations of lateral deflection under both static (or quasi-static) and dynamic (wind and earthquake) loads. Experience has shown that the lateral deflection of low to medium rise steel buildings subjected to wind loading is often far less than predicted by conventional analytical methods. Recent studies suggest that the discrepancies between observed and calculated drift are not due to the methods of assessing wind loading but must be accounted for by structural actions. Conversely, some tall buildings have experienced undesirable, uncalculated lateral motion effects. Analytical methods that include the features described in RECOMMENDATION C1 to C3 (three dimensional behavior and the influence of connections and infilling) and realistic first and second order elastic static and dynamic response characteristics are needed. These methods should be used in studies directed toward the establishment of realistic drift criteria or guidelines for wind loading and moderate earthquake loading.

A multi man-year level of effort is required.

RECOMMENDATION C5: FIELD MEASUREMENTS

FIELD MEASUREMENTS OF THE RESPONSE OF ACTUAL BUILDINGS SHOULD BE MADE.

Most research is effectively conducted under the controlled conditions obtainable either in the laboratory or in analysis of systems of specified geometry, element properties, and support conditions, under prescribed loading. Nevertheless, studies of analytical or physical models can never fully duplicate the behavior of actual buildings. Although field measurements of building response cannot be the primary basis for research, they are essential for the purpose of calibrating, correcting, or exposing the imperfections of laboratory and analytical research.

Buildings in earthquake and hurricane regions have been instrumented, but additional efforts of this type are needed. They should be long range studies and they should be correlated with controlled environment (laboratory or analytical) research. The phenomena studied should include relative resistance of frame and infilling, frequencies, drift, twist, acceleration and other factors that influence the serviceability or strength of the total system.

A multi man-year level of effort is required.

RECOMMENDATION C6: COMPOSITE CONSTRUCTION

ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD BE CONDUCTED TO ESTABLISH THE BEHAVIOR OF COMPOSITE STEEL-CONCRETE FRAMING SYSTEMS AND ELEMENTS.

One of the most pronounced recent trends in tall building construction has been in the direction of using structural steel and reinforced concrete in combination as primary structural elements. The composite tubular system has become increasingly popular in the construction of tall buildings over the past few years. In this system the framed tube, consisting of closely spaced reinforced concrete exterior columns and deep spandrel beams made of reinforced concrete or structural steel, resists lateral loads produced by wind and/or earthquake. Structural steel framing supports the gravity loads. The steel floor members are connected to small steel columns which are embedded in the reinforced concrete exterior columns. The efficiency of this system is attributed to the advantageous use of the best characteristics of both steel and concrete. The steel floor framing is light and, as a result, smaller interior steel columns are needed. In addition, the light framing provides flexibility for space planning, particularly in the core. Above all, the steel frame can be erected rapidly. The economy of the tube system with steel spandrels has been proven, and a few buildings

in Dallas and Houston, Texas have already been constructed with this combination. In about 90 percent of the tube designs to date, reinforced concrete spandrels have been used mainly because of the uncertainties associated with the connection between a steel beam and a concrete column.

Research is needed on the overall performance of composite framing systems in addition to work on individual composite elements such as beams and columns. The three-dimensional performance of these systems, time-dependent changes in stiffness, damping characteristics, and stiffness changes under dynamic loads require study. An experimental and analytical parametric study is also needed to determine efficient means of developing the moment capacity of the steel spandrel beams at the steel beam-concrete column joint and to determine the rigidity of the joint itself.

A multi man-year effort is required.

RECOMMENDATION C7: COLD-FORMED CONSTRUCTION

EXPERIMENTAL STUDIES SHOULD BE CONDUCTED TO ESTABLISH THE BEHAVIOR OF MULTI-STORY FRAMING SYSTEMS USING COLD-FORMED STEEL MEMBERS.

Cold-formed members are starting to be used for multi-story buildings up to five stories. Such construction offers opportunities for innovative design concepts including "monocoque" construction, improvements in incorporating architectural and mechanical elements with the structural system, and more effective use of material and improved structural efficiency resulting from the ability to control the shapes of members.

Analytical and experimental research is needed to address aspects of the following problems unique to cold-formed members in building frames: local and overall stability of members, connections including adhesive bonding, diaphragm action, composite construction using mixed materials (wood-metal, fiber reinforced materials - metal, etc.) and prefabricated assemblies.

A multi man-year effort is required.

RECOMMENDATION C8: NON-COMPACT SECTIONS

RESEARCH SHOULD BE CONDUCTED TO DETERMINE IF MOMENT REDISTRIBUTION CAN BE UTILIZED TO ADVANTAGE IN FRAMES COMPOSED OF NON-COMPACT SECTIONS.

A large percentage of low-rise steel construction utilizes

non-compact members in the framing systems. Significant cost-savings could be achieved if the principles of moment redistribution commonly used in plastic design could be applied to such structures.

The following research is needed:

- o Study of analysis methods to determine failure mechanisms in typical low-rise frames composed of non-compact sections.
- o Comparison of frames designed using moment redistribution with frames using elastic analysis.
- o Full-scale tests of frames designed using moment redistribution to confirm procedures.

A two man-year level of effort is required.

D. SEISMIC DESIGN

Approximately three-fourths of the annual construction investment in the United States is in some 40 states that have experienced moderate or major earthquakes in the past. Seismic design is obviously an important consideration for steel buildings. Earthquake related research has been conducted on steel structures. Additional work is needed to establish the behavior of connections and individual members and the performance of structural systems subject to large inelastic cyclic deformations of the type produced by earthquake loading.

RECOMMENDATION D1: BEHAVIOR OF SEMI-RIGID CONNECTIONS

AN EXPERIMENTAL AND ANALYTICAL RESEARCH PROGRAM SHOULD BE UNDERTAKEN TO EVALUATE THE INELASTIC CYCLIC PERFORMANCE OF SEMI-RIGID BUILDING CONNECTIONS.

Studies are needed to quantify the cyclic hysteretic behavior of semi-rigid beam-to-column connections in building structures designed for conditions of low to moderate earthquake loadings. Specific topics of needed research include:

- o Cyclic tests of various types of semi-rigid connections (end plates, cap and seat angles) to determine their mode(s) of distress (local instability, fatigue), and to quantify their moment-rotation response and hysteretic energy absorption capability under repeated displacement excursions.
- o Develop analytical models to predict the non-linear response of connections of varying stiffness, and generate computer programs to assess the inelastic cyclic response, including resistance to incremental collapse, of a complete building system.
- o Determine efficacy of available low cycle fatigue relationships and cumulative damage models to predict the cumulative effect of seismically induced inelastic displacement excursions on the connections.

A multi man-year effort is required.

RECOMMENDATION D2: DRIFT CONTROL CRITERIA

STUDIES SHOULD BE UNDERTAKEN TO CORRELATE SERVICE LOAD WIND DRIFT CONTROL CRITERIA WITH LATERAL DISPLACEMENT PERFORMANCE UNDER EARTHQUAKE LOAD HISTORIES FOR FLEXIBLY-CONNECTED BUILDING FRAMES DESIGNED IN REGIONS OF LOW TO MODERATE SEISMICITY.

Flexibly-connected (AISC Type 2) frames are common in low rise building structures designed primarily for drift control from wind at service loads. Research is needed to evaluate their inelastic lateral displacement behavior under seismically induced ground motions. Studies are required in the following areas:

- o Develop a rational method for calculating lateral displacements (wind drift) at service loads in Type 2 building structures, including the contribution of cladding and other non-structural elements to overall frame behavior (see RECOMMENDATION C2 and C4).
- o Develop analytical models to assess the inelastic cyclic lateral displacement performance (including consideration of frame instability and incremental collapse) of flexibly-connected frames under earthquake load histories.
- o Formulate design guidelines for flexibly-connected building frames (including connection strength and ductility requirements, panel zone shear deformation limits, bracing requirements, etc.) to ensure adequate drift control at service loads, and to satisfy

ductility, strength, and stability demands for extreme loads during a seismic event.

A multi man-year level of effort is required.

RECOMMENDATION D3: SEISMIC PERFORMANCE

A RESEARCH PROJECT SHOULD BE UNDERTAKEN TO SUMMARIZE EXISTING PERFORMANCE DATA FOR STEEL BUILDINGS SUBJECTED TO SIGNIFICANT EARTHQUAKES.

Steel buildings which were not designed in accordance with today's seismic design criteria have survived significant earthquakes sustaining little or minor damage. Examples of earthquakes where steel buildings survived and data are available include San Francisco, Caracas, Mexico City, Managua, Guatamala and several Japanese cities. The design profession and code writers do not have the resources to evaluate past performance because documentation is scattered. The work should include:

- o Review reconnaissance reports and identify types of steel building construction and relative damage.
- o Compare types of construction with current seismic design procedures and determine if the structures were in general conformance with code philosophy. If not, identify reasons for lack of expected damage.
- o Identify information that can be readily used for code development and design.
- o Analyze past performance of various construction systems and review the need for fully ductile systems.

A one man-year level of effort is required.

RECOMMENDATION D4: STEEL STUD WALLS

A COMPREHENSIVE RESEARCH PROGRAM SHOULD BE UNDERTAKEN TO DETERMINE THE ALLOWABLE SHEAR RESISTANCE OF WALL SHEETING MATERIALS COMMONLY USED WITH COLD FORMED STEEL STUD WALLS.

Load-bearing steel stud wall systems are commonly designed for lateral force resistance using flat strap acting as in-plane bracing. Limited work has been done to determine the allowable shear force resistance provided by sheeting material such as wallboard, lath and plaster and plywood.

Past research has provided limited data for use with lath and plaster, plywood and wallboard shear walls. No work has been done to evaluate the effectiveness of the bracing systems used in conjunction with these common sheeting materials. An advantage of steel studs in building construction is their non-combustible classification. However, only plaster or wallboard materials are currently used in these non-combustible classifications since plywood is combustible. Unfortunately, plaster and wallboard have relatively low shear resistance. Other options need to be investigated. The following work is needed:

- o Develop a wide range of shear values for common sheeting materials by studying the effects of varying attachment spacing, steel stud base metal gage and various anchorage details.
- o Develop a methodology for calculating the allowable shear value for untested materials.
- o Study the effects of combining the braced frame and wall sheeting materials.
- o Investigate anchorage details and their impact on allowable loads.
- o Develop new non-combustible shear resisting systems such as steel sheet shear walls using tension field action.

A multi man-year effort is required.

RECOMMENDATION D5: BEAM-COLUMN JOINTS

AN INTEGRATED EXPERIMENTAL AND ANALYTICAL RESEARCH PROGRAM SHOULD BE UNDERTAKEN TO CLARIFY CYCLIC BEHAVIOR AND RELIABILITY OF BEAM-COLUMN JOINTS HAVING BEAM-TO-COLUMN FLANGE CONNECTIONS AS WELL AS THOSE ATTACHED TO A WEAK COLUMN AXIS.

Moment-Resistant Frames are predominant in seismic design of steel frames. In addition to their conventional use, they are also employed in the perimeter framing of tall buildings. The critical element in such framing is the joint, i.e., the entire assemblage at the intersection of members. The connection consisting of those elements that connect the member to the joint, which may be affected by the behavior of the entire joint, is usually the most critical element of the assemblage. In spite of the wide use of such joints, the seismic design criteria are poorly defined, and there is a considerable degree of uncertainty regarding their capacity. Very limited research information is available on the cyclic behavior of joints of realistic size. Due to competitive pressures, inadequate designs are sometimes

accepted even for new frames. There is no real consensus, and it is essential to clarify for the designers the proper bounds.

The following research is needed:

- o Carry out analytical studies for the design of experiments to simulate the relevant size range of beam-column connections. This study should be supplemented with inelastic dynamic frame analyses to determine the bounds on joint loadings.
- o Design and carry out two-dimensional experiments on joints of realistic sizes (approximately half-size and larger) for connections of two types:
 - a. Beam-to-column flange connections
 - b. Beam-to-column web connections

For either type, the all-welded as well as connections with bolted web and welded flanges should be studied. The possibility of reinforcing bolted webs with welding to inhibit bolt slip should be explored.

- o Extend the the two-dimensional studies to three dimensions.
- o Formulate practical rules for sizing panel zones, stiffeners (continuity plates), as well as flange and web connections.

A multi man-year effort is required.

RECOMMENDATION D6: BEAM-COLUMNS

A COMPREHENSIVE RESEARCH PROGRAM INVOLVING EXPERIMENTAL AND THEORETICAL STUDIES SHOULD BE UNDERTAKEN IN ORDER TO GAIN REALISTIC KNOWLEDGE OF THE CYCLIC INELASTIC BEHAVIOR OF BEAM-COLUMNS.

Although it would not be desirable to design beam-columns for inelastic cyclic buckling, analytical tools are needed to represent their behavior when studying inelastic dynamic response of structures subjected to severe earthquake motions. In braced frames with relatively heavy bracing members the columns may be subjected to large cyclic axial forces and moments which may lead to overall structural instability. The research work to date on beam-column behavior has been almost exclusively devoted to unidirectional loading. In the absence of data on the cyclic behavior of beam-columns, a few attempts have been made to formulate simple models derived from the knowledge of behavior of beams and bracing members.

The research should involve the following:

- o Effect of end conditions.
- o Effect of strength and stiffness of columns in comparison to that of beams.
- o Loading history to include ratio of end moments as well as their magnitudes relative to axial force.
- o Effect of geometrical properties.
- o Experimental work should include small scale and full scale members, as well as subassemblages and prototypes.
- o Analytical work should be aimed at development of realistic and practical hysteresis models for analysis purposes, as well as development of design criteria to alleviate structural instability.

A three to five man-year level of effort is required.

RECOMMENDATION D7: TUBULAR MEMBERS

A COMPREHENSIVE RESEARCH PROGRAM INVOLVING EXPERIMENTAL AND THEORETICAL STUDIES SHOULD BE UNDERTAKEN IN ORDER TO EVALUATE THE DUCTILITY AND ENERGY DISSIPATION CAPACITY OF STEEL TUBULAR MEMBERS SUBJECTED TO LARGE CYCLIC DEFORMATIONS.

Cold formed rectangular steel tubes have gained popularity in recent years especially as bracing members in multistory frames. Lighter structures utilize these shapes for columns and beams as well. In a few past studies it has become quite clear that under cyclic loading severe cross section deformation in regions of plastic hinges leads to local buckling and premature failures. Concrete filling is one way to delay this mode of failure. The concrete inside the tubes prevents severe local buckling of steel tubes while the tube itself gives excellent confinement to concrete. Some preliminary work has produced very promising results. Research is needed to study the hysteresis behavior and modes of failure under different cyclic load conditions. Theoretical procedures should be developed to synthesize the hysteresis models and establish design criteria for such composite members.

The research should involve the following:

- o Effect of confinement via relationship between the area or volume of steel and concrete.

- o Effect of bond between steel tube and concrete.
 - o Effect of relative strength of steel and concrete. Normal strength, high strength and light weight concrete should be included.
 - o Effect of width-thickness ratio of tube walls.
 - o Effect of different loading histories.
 - o Experimental work should involve:
 - a. Reduced scale as well as full scale specimens
 - b. Beams, columns, and bracing members
 - c. Connections
 - d. Subassemblages and prototypes
 - o Development of analysis techniques and design criteria.
- A multi man-year effort is required.

RECOMMENDATION D8: END-PLATE BEAM-TO-COLUMN CONNECTIONS

DESIGN CRITERIA AND PROCEDURES SHOULD BE DEVELOPED FOR END-PLATE MOMENT CONNECTIONS SUBJECTED TO EARTHQUAKE MOTIONS.

In recent years, considerable experimental and analytical research has been conducted on the behavior of end-plate moment connections under static loading. Some limited work has been done in Italy and New Zealand on the behavior of moment end-plate connections under cyclic loading; however, design rules have not been formulated. Still these connections are being used in buildings located in moderate to severe earthquake areas. Thus, there is need for a comprehensive study of the cyclic behavior of end-plate connections for safety reasons.

Research is needed on the cyclic behavior of moderate to large capacity, 4- and 8-bolt, extended configurations as used in multi-story frames. End-plate thicknesses for these connections are typically between 3/4 in. and 2 in. and corresponding bolt diameters are between 3/4 in. and 1-1/2 in. The experimental work should consist of subjecting full-scale, end-plate connected beam and column assemblies to severe cyclic loading. The loading must simulate the effects of strong earthquakes. Major parameters of the study should be end-plate geometry, grade of steel, bolt diameter and bolt type, and the random nature of earthquake cyclic effects. Analytical studies should include the development of a finite element model and associated coding to predict the connection behavior. The finite element model must account for the effects of nonlinear material properties and possible plate separations at the end-plate/column flange interface. Portions of both the beam and column must be modeled.

A two to three man-year level of effort is required.

RECOMMENDATION D9: BOLTED WEB MOMENT CONNECTIONS

LOW CYCLE FATIGUE LIFE OF BEAM-TO-COLUMN MOMENT CONNECTIONS MUST BE INVESTIGATED TO PROVIDE A RELIABLE BASIS FOR SEISMIC DESIGN.

In seismic design of ductile moment resisting frames, beam-to-column moment connections must be capable of developing the full plastic capacity of the beam section unless it can be shown that adequate ductility is provided by a lesser connection. For reasons of economy, it is common practice to use full-penetration flange welds and friction-type bolted web connections. Due to slippage of the bolted web connections under a combination of high moment and shear, the beam flanges must develop the plastic moment capacity of the section at the beam-to-column connection. While welded-flange, bolted-web connections have been found to exhibit considerable ductility, their low-cycle fatigue life under large inelastic deformations is not as good as that found for fully welded connections. In a strong motion earthquake, even a symmetrical structural system is likely to behave unsymmetrically. In reality, then, the welded-flange connections will be subjected to out-of-plane bending and torsion. The low-cycle fatigue life of the beam-to-column connections will be influenced by the additional stresses. For a reliable prediction of the three-dimensional behavior of real buildings, the hysteretic behavior of moment connections under three-dimensional deformations must be known. Since such predictions must be carried out by computer, a reliable analytical model of connection behavior is necessary.

The proposed study would have a comprehensive experimental program and an analytical counterpart. The experimental work would require testing of a variety of connection configurations, under several three-dimensional load histories. The configurations should represent a range of member sizes and the loads should simulate the inelastic three-dimensional response of a real building under a strong motion earthquake. The development of an analytical model for the representation of connection behavior should be carried out in conjunction with the experimental program. The analytical model should capture the dominant behavior of this type of connection under extreme cyclic deformations. When implemented in a computer program, the model should permit a reliable assessment of the behavior of a complex structure including its resistance to incremental collapse.

A three to four man-year level of effort is required.

RECOMMENDATION D10: BRACING CONNECTIONS

ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD BE UNDERTAKEN TO ESTABLISH THE PERFORMANCE OF GUSSETED BRACING CONNECTIONS.

Diagonal bracing provides an efficient means of resisting lateral loads both in tension and compression. The ability of these members to yield and buckle in a controlled manner provides substantial increased energy absorption to the structural system. Much work is needed to understand the fundamental behavior and modes of failure of gusseted bracing connections and their influence on the response of the bracing and total structural system.

The research should include:

- o Single diagonal and X-braced diagonal configurations with various structural shapes, such as single angles, double angles, channel sections, rectangular tubes, circular tubes (pipes), and wide flange sections.
- o In-plane and out-of-plane buckling behavior should be studied to determine the connection detail differences and bracing behavioral differences for these systems.
- o Both concentric and eccentric brace connection details should be included in this program.
- o Gusset plate connections should include the appropriate attachments to the associated beams and columns as well as to the braces. Welded and bolted connection details are needed.
- o Experimental studies at full and reduced scales should be conducted to establish reliable data for the development of design recommendations.
- o Theoretical and analytical studies to explore the dominant behavioral characteristics of gusset plate connected bracing members should be conducted in concert with the experimental studies.
- o Design procedures, recommendations, and specifications should be developed to ensure satisfactory performance of the connections under severe earthquake ground motions.

A four man-year level of effort is required.

RECOMMENDATION D11: VISCOELASTIC DAMPING

A RESEARCH PROGRAM IS NEEDED WHICH (1) WILL DESCRIBE AND DOCUMENT THE RELATIONSHIPS BETWEEN VISCOELASTIC MATERIAL PROPERTIES AND DAMPING PROVIDED BY MECHANICAL SYSTEMS, (2) WILL PERFORM EXPERIMENTAL STUDIES TO ESTABLISH AND VERIFY APPROPRIATE ANALYTICAL ALGORITHMS FOR STRUCTURAL DESIGN AND ANALYSIS, AND (3) WILL DEMONSTRATE THROUGH TYPICAL STRUCTURAL CASE STUDIES THE EFFECTIVENESS OF MECHANICAL VISCOELASTIC DAMPING SYSTEMS FOR EARTHQUAKE RESISTANT DESIGN.

Mechanical damping systems can dissipate significant amounts of energy during vibratory motions. It is well known that structures subjected to severe earthquake ground motions must dissipate some of the input earthquake energy through nonlinear material damping. By adding mechanical viscoelastic damping it is possible to reduce the structural vibrations caused by earthquakes and the amount of structural and nonstructural damage.

The following research is needed:

- o Develop mechanical damping systems which utilize viscoelastic materials for energy absorption. These can be of the direct shear type, rotary shear type, or other.
- o Experimentally determine the characteristics of full size mechanical viscoelastic damping systems.
- o Establish appropriate analytical algorithms for these damping systems. The analytical algorithms would be used for design purposes and analytical verifications of the dynamic response characteristics of complete building systems.
- o Conduct a parameter study to determine the optimum amount of mechanical damping to be added to various structural systems in order to minimize economically the earthquake hazard for these systems.
- o Develop recommended procedures for the design of mechanical damping systems considering ease of application by the design profession.
- o Extend the results to retrofit of existing buildings and design for strong winds.

A multi man-year effort is required.

RECOMMENDATION D12: DUCTILITY DEMAND

RESEARCH SHOULD BE CONDUCTED TO QUANTIFY DUCTILITY DEMANDS AND CAPACITIES FOR STRUCTURAL SYSTEMS, ELEMENTS AND CONNECTIONS AND DEVELOP CRITERIA FOR PERFORMANCE ASSESSMENT.

Deterioration in strength of elements of steel structures is often a consequence of localized failures, such as crack propagation and fracture at connections, or localized instabilities (local and lateral torsional buckling) within members. The deterioration caused by these localized failures is a function of the number and magnitudes of inelastic excursions. The profession and code writing bodies need information that permits a quantitative assessment of seismic performance in order to develop acceptable detailing criteria. Consideration must be given to the randomness of seismic input and the cumulative effects of inelastic excursions on structural damage. Cumulative damage models, of the type used extensively in mechanical engineering, can provide much of the needed information.

The following research is needed:

- o Evaluation of the number and magnitudes of inelastic excursions a structure or structural element is expected to experience in an earthquake.
- o Development of cumulative damage models for structural elements based on low-cycle fatigue concepts.
- o Conduct laboratory tests to validate damage models.
- o Development of representative cyclic loading histories for testing, so that test results can be generalized to damage prediction under random loading histories.

A three man-year level of effort is required.

RECOMMENDATION D13: BRACED FRAME STABILITY

ANALYTICAL AND EXPERIMENTAL STUDIES SHOULD BE CONDUCTED TO DETERMINE THE STABILITY OF BUILDING SYSTEMS WITH THE LATERAL FORCE RESISTANCE PROVIDED BY K OR CHEVRON BRACING.

One of the basic concepts of seismic design is that if the building system is designed to respond in an inelastic manner to ground shaking having an intensity much larger than the yield level of the structures, the structure should yield without undergoing collapse. Building systems using K or Chevron bracing

for lateral resistance of seismic forces and movements frequently have been used in areas of high probability of strong seismic shaking. In the K braced system, the column to which the apex of the brace is connected continuously supports vertical dead and live loads. If the compression segment of the brace were to buckle, the column would have additional forces induced by the remaining brace segment which are not usually accounted for in design. Similarly, the Chevron brace would induce forces into the horizontal flexural member which are not usually considered in design.

Analytical and experimental work should determine the inelastic behavior of these bracing systems and appropriate design criteria should be established to provide adequate stability during large intensity earthquakes.

A two man-year level of effort is required.

RECOMMENDATION D14: LATERAL BRACING

AN EXPERIMENTAL STUDY SHOULD BE CONDUCTED TO DETERMINE LATERAL SUPPORT REQUIREMENTS FOR MEMBERS SUBJECT TO SIGNIFICANT INELASTIC RESPONSE DURING EARTHQUAKES.

There have been numerous tests of subassemblages composed of steel beams and columns. In almost all cases the lateral supports of the members tested were not under study. Thus the lateral supports provided were essentially rigid and closer together than needed. Over the years there have been many studies to determine the spacing of lateral support members. These tests, however, do not provide the information needed to evaluate the requirements for lateral bracing properly for members undergoing the potentially large inelastic deformations required for members in areas of high seismicity.

New experimental research should be conducted to determine the design requirements for members of seismic frames having reversing, high moment gradients and non-linear response characteristics. The tests should also consider the lateral support offered by a composite floor slab. A variety of bracing configurations should be studied.

A multi man-year effort is required.

RECOMMENDATION D15: OVERALL SYSTEM RESPONSE

AN INTEGRATED ANALYTICAL RESEARCH PROGRAM SHOULD BE UNDERTAKEN TO DETERMINE THE THREE-DIMENSIONAL EFFECTS IN THE NONLINEAR RANGE OF ARCHITECTURAL AND STRUCTURAL CHARACTERISTICS OF IRREGULAR BUILDINGS IN ORDER TO DETERMINE THEIR CAPACITY TO RESIST EARTHQUAKES OF VARYING LEVELS OF SEVERITY.

Architects are becoming conscious of the importance of including earthquake resistance considerations in their conceptual designs. Architectural concepts take advantage of the versatility of steel framed structures, and the use of configurations involving setbacks, asymmetry, and combinations of shear walls and moment frames is quite common. There is very limited quantified information on strength and drift for various types of building concepts. Architects as well as engineers need data on bounds for irregularity, interaction of structural and non-structural elements, and effects of mixed structural systems. Torsion, relative importance of shear walls and frames in the nonlinear range, and interaction of the structural frame with non-structural elements, such as curtain walls, are effects that are best investigated through three-dimensional models. Analyses that utilize computer software for three-dimensional nonlinear analyses can be very helpful in determining drift and strength characteristics of structures that cannot be reliably modeled in two dimensions. An additional benefit of three-dimensional analyses is to establish limits on setbacks, asymmetry, etc., within which two-dimensional modeling gives acceptable results.

The following research is needed:

- o Documentation of architectural systems for low-rise buildings that incorporate features which require three-dimensional evaluation.
- o Classification of structural systems into groups that are susceptible to analysis with existing software.
- o Evaluation of structural systems for which new software or modified software needs development.
- o Analysis of typical structures from each classification to determine their response characteristics into the nonlinear range.
- o Engineering investigations, utilizing the results of analysis, to establish bounds on drift and strength requirements for categories of building concepts.
- o Guideline documents that architects and engineers can use for design.

A five man-year level of effort is required.

RECOMMENDATION D16: EVALUATION OF EXISTING BUILDINGS

AN EXPERIMENTAL AND ANALYTICAL STUDY SHOULD BE CONDUCTED TO ESTABLISH LEVELS OF SEISMIC RESISTANCE OF LOW-RISE STEEL FRAME BUILDINGS, AND PROCEDURES SHOULD BE DEVELOPED TO STRENGTHEN THEM WHERE NECESSARY TO ACCEPTABLE LEVELS.

Initial emphasis on retrofit and strengthening of existing buildings has been on unreinforced masonry buildings. Whereas it was originally felt that such buildings had to be demolished, recent experimental and analytical work showed that it was possible to strengthen them and make them earthquake resistant. The economics of strengthening such buildings was a major consideration in this evaluation. Although low-rise structural steel buildings are less susceptible to damage, their level of earthquake resistance has not as yet been demonstrated through experiments and analysis. Dynamic analyses of buildings to calculate their response to earthquake excitations is now a routine procedure, but the emphasis has been on the analysis of structures that are being designed for new construction. It is necessary to investigate existing structures to find their earthquake resistance capacity and to develop methods of retrofit to bring their resistance up to acceptable levels.

An extensive analytical and experimental program should be carried out to identify the seismic resistance capacity of existing steel structures of various typical configurations that have not been designed to present seismic codes. The experimental work should consist of testing existing buildings and laboratory experiments of framing that corresponds to the structural systems of typical classes of existing buildings. Since existing buildings cannot be tested to destruction, information obtained from such tests must be supplemented by laboratory tests to determine the capacity of major elements of the structures. Subsequently, concepts should be developed for strengthening buildings found susceptible to damage at practical seismic excitation levels. Criteria should then be developed for economic methods of strengthening and procedures should be recommended for analysis and design to meet these criteria.

A six man-year level of effort is required.

E. LOAD AND RESISTANCE FACTOR DESIGN

The proposed AISC Load and Resistance Factor Design (LRFD) specification for structural steel buildings was released for review and trial use in 1983. The LRFD specification is the prototype for a new generation of structural design codes. Research opportunities exist for facilitating and expediting implementation of the LRFD specification. They range from assembly of existing data to laboratory testing to resolve specific questions on topics where the new specification may be overly conservative.

RECOMMENDATION E1: CONNECTIONS WITH OVERSIZE HOLES

AN ANALYTICAL STUDY SHOULD BE CONDUCTED TO DETERMINE THE INFLUENCE OF SLIP IN BOLTED CONNECTIONS ON FRAME GEOMETRY AND FRAME STABILITY.

The slip critical high-strength bolted joints are designed in LRFD at service loads and the nominal specified shear strength is the same as the allowable shear for such bolts in ASD. Thus, slip may occur at overloads. Is slip at overloads a strength/safety problem in such joints when built with oversized holes? The question arises in bracing connections in high rise buildings. It has been suggested that slip at overloads could distort the frame to such a degree that instability may occur.

Research along two lines of attack is needed: First, considering the random alignment of holes, how much slip will realistically occur in a multifastener joint? A reexamination of the existing test data is needed to assure that this problem is handled adequately in the specifications. Second, an analytical study is needed on the influence of slip in bolted connections with oversize holes on frame geometry to determine whether frame instability problems could result. The type and size of buildings for which higher bolt design values can be used in slip-critical connections should be determined.

A one-half man-year level of effort is required.

RECOMMENDATION E2: WEB CRIPPLING

EXPERIMENTAL STUDIES SHOULD BE CONDUCTED TO EVALUATE WEB CRIPPLING BEHAVIOR OF LIGHT BEAM SECTIONS WITH SEATED CONNECTIONS.

The proposed LRFD formula for web crippling at bearing ends of beams (i.e., seated connections or wall bearing beams) may seriously affect the use of seated connections. The web

crippling capacity of some of the lighter sections (W14x22, W12x14, W10x12) will be reduced well below the equivalent ASD capacity.

The LRFD specification requires that lateral support be provided at bearing ends. The present AISC manual infers that side clips or top clips must be used with seated connections. For the lighter sections, a typical side clip will not only provide the required lateral support but also will provide significant vertical load reaction capacity.

Tests should be conducted for the lighter beam sections to evaluate the contribution of the side and or top clip to web stability (see also RECOMMENDATIONS B3 and B4).

A one-half man-year level of effort is required.

RECOMMENDATION E3: TECHNOLOGY TRANSFER

TEACHING MATERIALS AND DESIGN AIDS SHOULD BE PREPARED TO ACQUAINT BUILDING OFFICIALS WITH THE USE OF LRFD.

Rapid acceptance and use of LRFD is contingent upon building officials having a thorough understanding of the principles and details of this new design procedure.

Educational material should be prepared to teach the use of LRFD to building officials. It should include any special information or design aids needed by building departments to review and check LRFD designs. Video cassette type lectures and the establishment of a point of contact to respond to questions on details of the specification should be considered. Material should be prepared for administrative level officials and plan examiners.

A one-fourth man-year level of effort is required.

RECOMMENDATION E4: RESISTANCE FACTORS

A SYSTEMATIC STUDY SHOULD BE UNDERTAKEN TO COLLECT INFORMATION ON ACTUAL PRODUCTS AND STRUCTURES FOR USE IN COMPUTING RESISTANCE FACTORS FOR STRUCTURAL MEMBERS.

Data have been collected on the variation of geometrical and mechanical properties of steel members. A systematic assembly of these data for the broad range of steel products and fabricated structural elements has not been reported. Higher ϕ factors could be used for those cases where higher mean values or smaller coefficients of variation than presently used are obtained.

The following research is needed:

- o Systematic collection of data on the variations in the geometric properties of the major rolled shapes, tubes, fabricated sections, bolts and welds.
- o Systematic collection of data on the variations in the mechanical properties of rolled shapes, plates, cold-formed and hot-rolled tubes, bolts, welding electrodes, and welds.
- o Systematic collection of data on as-built imperfections, such as out-of-plumb, sweep, camber, etc., as a function of quality control.
- o The calculation of ϕ based on the above data base for the various products and class of members and/or structures.

A three man-year level of effort is required.

RECOMMENDATION E5: SERVICEABILITY CRITERIA

RESEARCH SHOULD BE UNDERTAKEN TO DEVELOP THE DATA BASE AND ANALYSIS PROCEDURES NEEDED TO PREPARE RATIONAL AND PRACTICAL SERVICEABILITY CHECKING PROCEDURES FOR LRFD.

The use of the computer as a design tool and modern architectural requirements have led to building systems that are flexible and lightly damped. Since structural stiffness has remained the same or declined as strength has increased, modern buildings and building systems are increasingly susceptible to objectionable static or dynamic structural movement. Present codes and standards offer little guidance on these problems. Serviceability is more an economic than safety issue, and serviceability requirements are negotiable between engineer, architect and building owner. Serviceability criteria need to be flexible and adaptable to different building use requirements. However, the present lack of any meaningful criteria may be interpreted by some to mean that serviceability is not important, which raises questions of professional responsibility. With the move to limit states design, serviceability will become an increasingly important and delicate regulatory and design problem.

The following research should be conducted:

- o Serviceability limit states should be identified through surveys of building owners and occupants, and correlated with measurements of structural loading and response. Serviceability limits should be related to occupancy.

- o Dynamic properties of structural systems must be identified through a program to measure in situ static and dynamic structural response.
- o Load combinations should be developed for checking deflections under static loads against tolerable limits.
- o Simple serviceability checks must be developed to control objectionable structural motions, taking into account the load levels, the dynamic characteristics of the load, and the structural response.

A multi man-year effort is required.

RECOMMENDATION E6: LATERAL MOTION CRITERIA

LIMIT STATE CRITERIA SHOULD BE DEFINED FOR THE LATERAL MOTION OF BUILDINGS AND PERFORMANCE CRITERIA DEFINED.

Drift or lateral motion of buildings is an important design consideration. These criteria become a controlling factor for buildings greater than two to three stories. In the absence of wind tunnel tests, arbitrary limits are imposed for this drift in design. There is no information available to substantiate these limits. In many cases, these limits result in an economic disadvantage for steel structures.

Research should be conducted to define drift values associated with the following limit states: internal partition failure, elevator tolerances, human comfort and building crane operation.

A two man-year effort for three years is required.

RECOMMENDATION E7: VIBRATION CONTROL FOR LIGHT FLOOR SYSTEMS

TECHNIQUES ARE NEEDED TO INCREASE THE DAMPING IN FLOOR SYSTEMS WHICH WILL ALLOW REDUCTION IN WEIGHT WITHOUT ADVERSELY AFFECTING THE ACCEPTABILITY OF THE FLOOR WITH REGARD TO ANNOYING, OCCUPANT-INDUCED FLOOR VIBRATIONS.

If the weight of steel beam- or steel joist-concrete slab floor systems is reduced, the savings in building costs can be significant due to the pyramiding effects of beam, column, and footing sizes. The obvious maximum effects on weight reduction are to decrease the concrete slab thickness, reduce the unit

weight of the concrete or substitute a lighter material. The resulting reduction in mass will, however, have an adverse effect on the vibration characteristics of the floor system. Since damping is the most important vibration parameter for floor systems excited by normal office or residential human occupancy, the acceptability of an ultra-light floor system can be improved by increasing the system damping.

Research is needed on methods and/or materials that can be used to increase the damping in floor systems. The problem is difficult because of the extremely small amplitudes (0.030 to 0.050 in.) that are perceived by humans to be annoying. Full-scale floor systems would have to be used in the research and particular attention paid to the economics of the damping materials selected, as well as the cost of the installation technique. Pilot applications in existing buildings will also be needed.

A two to three man-year level of effort is required.

RECOMMENDATION E8: PLASTIC DESIGN

STUDIES SHOULD BE UNDERTAKEN TO DETERMINE IF THE LRFD SPECIFICATION CONTAINS ADEQUATE PROVISION FOR THE USE OF PLASTIC DESIGN.

The LRFD Specification rules for plastic design have been incorporated as an integral part of the overall design provisions rather than presented in a section of their own. As a result, plastic design using LRFD is not as readily apparent as with the 1978 and earlier AISC Specifications.

A study is needed to develop guidance for plastic design using LRFD. The results should be presented in a series of papers illustrating the use of plastic design concepts with the LRFD provisions.

A one-quarter man-year level of effort is required.

RECOMMENDATION E9: SYSTEM RELIABILITY

RESEARCH SHOULD BE UNDERTAKEN TO DEVELOP THE ANALYSIS PROCEDURES AND DATA NEEDED TO TAKE ADVANTAGE OF SYSTEM BEHAVIOR IN LRFD.

Development of LRFD and supporting reliability analyses have focused on behavioral models and statistics for individual members. While these behavior models are believed to be realistic for describing response of individual members under design loads, they ignore the fact that such members are integral to a system, the behavior of which under extreme loads is

complex. In certain highly redundant structures the system reliability is considerably higher than that of any individual member; in other systems, the system reliability may be less. Since one of the ultimate goals of LRFD is more uniform reliability for all structures, it is plain that systems effects should be considered in some way.

The following research is needed:

- o Establish realistic limit states for systems in terms of the member limit states which are known.
- o Develop and validate procedures for computing system reliability.
- o Develop criteria to take systems effects into account in design through the use of partial factors or other simple devices to reflect the mode and consequence of system failure.

A multi man-year effort is required.

RECOMMENDATION E10: WIND AND SEISMIC EFFECTS

RESEARCH SHOULD BE CONDUCTED TO ESTABLISH A RATIONAL AND CONSISTENT BASIS FOR WIND AND SEISMIC EFFECTS IN LRFD.

The application of LRFD to buildings subjected to wind and seismic effects has not been thoroughly considered. In considering wind effects, wind directionality and structural enveloping have been taken into account only in an approximate fashion. The seismic analyses consider the ability of the structural system to dissipate energy through inelastic cyclic deformation in a rudimentary way. Moreover, unlike the limit states for gravity loads, the limit state for seismic effects consists of some poorly defined deformation limit. The present static-for-dynamic reliability analyses indicate lower reliabilities for wind and seismic effects than for other loads. Research data presently are insufficient to determine whether these discrepancies are real or only apparent, and they could not be resolved in developing the current LRFD specification.

The following research is needed:

- o Identify appropriate limit states for earthquakes.
- o Develop reliability analyses that take into account time-dependent nonlinear behavior explicitly.

- o Examine wind-directionality effects on the reliability of wind-sensitive structures.
- o Develop equivalent lateral force requirements and performance requirements.
- o Coordinate LRFD with wind and earthquake engineering communities.

A multi man-year effort is required.

RECOMMENDATION E11: EXISTING BUILDINGS

RESEARCH SHOULD BE CONDUCTED TO EXTEND LRFD TO INCLUDE STRENGTHENING AND REHABILITATION OF EXISTING STRUCTURES.

The proposed LRFD Specification was developed essentially for the design of new buildings. For example, the material characteristics used in the development of LRFD were derived from tests of current and recently replaced materials. However, everyday design practice requires the application of specification provisions to older structures for repairs, renovation etc. Research specifically directed to this problem will extend the applicability of LRFD to this area of design.

The following work is needed:

- o Development of a systematic method for evaluation of material properties of existing structures. Note that these properties are likely to be very different from present day materials, and a statistically based sampling procedure may be desirable.
- o Development of methods of evaluating resistance factors and reliability indices for structural components that were built by very different construction methods as well as factors for different classes of connections.
- o Possible consideration of reduced life expectancy for existing structures and evaluation of such implications on load factors and reliability. Consideration of the value of past performance of the building on the LRFD evaluation.
- o Formal application of the method to existing structures through development of an applications manual or example calculations.

A multi man-year effort is required.

F. FIRE PROTECTION

Research opportunities exist for reducing the costs of providing fire protection for steel structures while maintaining current levels of safety. The work would also provide a more rational basis for fire protective design. It includes the development of analytical design procedures, design aids, new fire protective materials and fire models for special structures.

RECOMMENDATION F1: FIRE RESISTANT DESIGN

A COMPREHENSIVE ENGINEERING DESIGN PROCEDURE SHOULD BE DEVELOPED FOR EVALUATING THE PERFORMANCE OF STEEL FRAME BUILDINGS UNDER FIRE EXPOSURE CONDITIONS.

In many cases current design criteria based on arbitrary limits such as the imposition of limits on steel temperature are overly conservative. During the past two decades, our understanding of fire phenomena and their impact on buildings has increased dramatically to the point where it is now possible to design specific buildings for anticipated fire conditions in a manner analogous to current structural design. Unfortunately, the procedures and techniques for accomplishing an integrated fire resistant design are not readily available to the design community. Performance criteria such as deflection limits and required strength conditions have not been developed. Current fire resistance requirements also do not take into account the probabilistic nature of fire occurrence in a manner comparable to other extreme loads such as earthquakes and extreme winds.

A design procedure should be developed using a load and resistance factor format. This will involve an analytical study modeling structural response taking into account stability problems, large deflection theory, occupancy and fire loading, influence of other fire protection features, and compartment geometry and ventilation. Design limit states and load combinations will need to be defined. The Fire Analysis of Steel Building Systems (FASBUS II) computer program should be used as a basis for this work.

A five man-year level of effort is required.

RECOMMENDATION F2: DESIGN AIDS

DESIGN AIDS SHOULD BE DEVELOPED FOR CALCULATING FIRE PROTECTION MATERIAL THICKNESSES FOR STEEL BUILDING ELEMENTS.

Hundreds of ASTM E119 fire tests for establishing fire resistance ratings for steel columns, beams, floors, roofs and

walls have been conducted. Such tests are expensive and time consuming, and each test has a limited application by virtue of the construction details of that particular tested construction. Test data are available which can provide a basis for developing analytical methods to predict fire resistance ratings for these building elements. This will provide an economical method for determining fire resistance ratings for untested steel constructions which differ in construction details from those tested. In addition, the ASTM E119 test of floors and roofs identifies two fire resistance ratings - restrained and unrestrained. In order to prove that most steel floor designs in a building are restrained, AISI developed the FASBUS II computer program. Many code authorities require an analysis of the floor system using FASBUS II to prove the floor system is restrained. Design aids can reduce the need for an analysis of every floor construction.

Analyses should be conducted to determine the structural response of typical steel floor systems under fire exposure conditions. FASBUS II can be used for this. Full-scale fire tests may be required to provide additional data or verification of equations for an engineering guide. This information should be used to develop a simple guide for the structural engineer and building official to agree on the use of restrained test results to establish fire protection material thicknesses on steel floors and steel framing.

A two man-year level of effort is required.

RECOMMENDATION F3: SHOP APPLIED FIRE PROTECTION

NEW FIRE PROTECTION MATERIALS SUITABLE FOR SHOP APPLICATION TO STEEL MEMBERS SHOULD BE DEVELOPED.

Field application of fire protective coatings for steel structures is costly. Material and application cost can amount to as much as 15 % of the cost of the steel frame. Existing materials cannot withstand the rigors of transportation and erection and are not suitable for shop application. Ablative coatings which could be applied in the shop are prohibitively expensive.

Background information should be collected to stimulate materials manufacturers to develop new coatings. This information would include a definition of the size of the potential market for such materials and the characteristics required to insure adequate performance during shop application, transportation, erection and subsequent fire conditions.

A two man-year level of effort is required.

RECOMMENDATION F4: LARGE AREA/LARGE VOLUME STRUCTURES

MATHEMATICAL MODELS SHOULD BE DEVELOPED FOR MODELING FIRE GROWTH IN LARGE AREA OR LARGE VOLUME STRUCTURES.

During the past two decades, a considerable amount of research has been done on the modeling of fully developed compartment fires. Much of this work is empirical and is based on experiments involving relatively small compartments. There are many large area/large volume structures which are commercially important to the steel industry. Examples include atriums, covered shopping malls, transportation terminals, covered stadiums and sports complex's and industrial plants. It is questionable whether currently available models are applicable to such structures.

Fire models should be developed for large area/large volume structures taking into account the following factors: ventilation, plume theory, relatively low fire loading, heat dissipation, and the probability of occurrence of fully developed fire conditions (flash over).

A three man-year level of effort is required.

RECOMMENDATION F5: FIRE RESEARCH REVIEW

A COMPILATION AND ASSESSMENT OF FIRE RESEARCH AROUND THE WORLD SHOULD BE PREPARED ON A PERIODIC BASIS.

There is a great deal of fire research being conducted throughout the world. It is important that this work be summarized to minimize duplication of effort and enhance the opportunity for synergism. The summary should deal with all aspects of fire research of importance to building design. It should be updated on a periodic basis, perhaps every 3-5 years.

A one man-year level of effort is required.

G. DESIGN LOADS

Loading characteristics such as load magnitude, duration and probability of occurrence are important elements of design criteria for producing safe, economic structures. Research is needed to characterize snow loads, wind loads and crane loads. Information is also needed on the response of structures and structural elements to these loads.

RECOMMENDATION G1: CRANE LOADS

DESIGN LOADS SHOULD BE DETERMINED FOR OVERHEAD AND UNDERHUNG CRANE SYSTEMS.

There is a lack of information available on the lateral forces developed by crane systems in industrial buildings.

Research involving field investigations should be conducted to determine the magnitude of these loads. Information should be obtained on the probability of occurrence of various load combinations. Using this information, analytical and experimental studies should be carried out to establish fatigue requirements, serviceability and strength design criteria. Design requirements should also be established.

A three man-year level of effort is required.

RECOMMENDATION G2: DRIFTED SNOW

DESIGN LOAD DATA SHOULD BE DEVELOPED FOR DRIFTED SNOW ON MULTI-LEVEL ROOFS.

Drift snow loads account for about 75 percent of snow related roof collapses. The problem is particularly important for low rise steel buildings with a change in roof elevation such as industrial or manufacturing buildings with attached offices, school buildings, etc.

Needed research includes snow load measurements from full-scale structures and statistical analysis of drift snow load case histories to determine the effects of geometrical and environmental parameters and establish annual probabilities of exceedance.

A one man-year level of effort is required for a two to three year period.

RECOMMENDATION G3: CLADDING BEHAVIOR

RATIONAL DESIGN PROCEDURES FOR CLADDING SHOULD BE DEVELOPED TAKING INTO ACCOUNT THE CHARACTERISTICS OF FLUCTUATING WIND PRESSURES, CLADDING MATERIALS AND CONSTRUCTION PRACTICES.

Pressure coefficients contained in current loading standards and building codes reflect improvements in wind tunnel modeling of buildings. The techniques and instrumentation used to measure surface pressures on wind tunnel models have not been

standardized. However, data obtained in full-scale and model scale tests suggest that peak pressure coefficients based on localized fluctuations may be underestimated in the wind tunnel by 15 to 25 percent. Certain phenomena associated with flow separation are not observed on wind tunnel pressure models because of instrumentation limitations.

Research should be conducted to validate wind tunnel modeling techniques (including the associated instrumentation) through carefully conducted measurement programs in both model and full-scale. The behavior of cladding elements subjected to fluctuating loads needs to be investigated systematically. Special laboratory equipment capable of duplicating actual load time histories obtained from field measurements will be needed. This information should be synthesized and rational design procedures should be developed that account for fluctuating pressures, cladding geometry and type of material, and fastener details.

A three man-year level of effort is required for the full-scale measurements and a five man-year level of effort for the behavior of cladding materials and development of design procedures.

RECOMMENDATION G4: WIND LOADS ON LOW RISE BUILDINGS

THE VARIABILITY OF WIND LOADING ON LOW RISE BUILDINGS SHOULD BE BETTER DEFINED.

Additional information is needed on the effects of geometric and environmental factors on the variability of wind loads for low rise buildings.

The required research includes a synthesis of information available in the literature and wind tunnel studies.

A two to three man-year level of effort is required.

RECOMMENDATION G5: INTERNAL PRESSURE LOADING

MODELS FOR MEAN AND PEAK INTERNAL PRESSURES ASSOCIATED WITH WIND LOADS ON BUILDINGS SHOULD BE VERIFIED.

Internal pressures affect the design of cladding on low rise buildings and curtain wall systems in high rise buildings. Current analytical models for the mean and peak internal pressures are based on assumptions of the leakage distribution of the building envelope, the presence of large openings in the exterior, the distribution of interior leakage paths (doors, walls, etc.) and the building flexibility.

Experiments at both model scale and full-scale should be conducted to evaluate these models and develop improved design criteria.

A three man-year level of effort is required.

RECOMMENDATION G6: BUILDING RESPONSE TO WINDS

MEASUREMENTS SHOULD BE MADE OF THE RESPONSE OF FULL-SCALE STRUCTURES SUBJECTED TO WIND LOADS.

Serviceability requirements and building performance as perceived by the occupants for high rise buildings subject to wind loads are important design considerations. Additional information on the dynamic performance of full-scale structures is needed to develop improved design criteria.

Research should be conducted on full-scale high rise structures subjected to wind loads to obtain information on the following: effective structural damping (nominal values available to the designer give concrete buildings an advantage), evaluation of building periods and comparison with calculated values, building drift and rotation, and building accelerations. The work should be carried out in hurricane prone areas where there is a high probability of experiencing strong winds.

A three man-year level of effort is required.

RECOMMENDATION G7: LARGE AREA ROOFS

MEASUREMENTS SHOULD BE MADE ON THE DISTRIBUTION OF SNOW IN THE PRESENCE OF STRONG WINDS ON ROOFS OF LARGE AREA.

Snow loads for roofs of low rise industrial, commercial or public buildings where the roof system represents a major portion of the construction cost are an important design consideration. Current research in the United States and Canada includes full-scale monitoring programs, probabilistic modeling of the formation and statistical variability of snow loads and physical model studies. The presence of strong winds, however, can cause significant non-uniform deposition and drifting.

Snow load monitoring programs should be conducted on full-scale structures, with emphasis on roofs of large area or unusual shape, to obtain information on the joint occurrence of extreme snow and wind loads, snow load distributions, and the duration of design snow loads. The program should include re-examination of existing data to develop correlations with climatic information, development of improved physical modeling techniques for wind tunnels and/or water flumes, and evaluation of existing

mathematical models.

A three man-year level of effort is required.

ACKNOWLEDGMENTS

The success of the workshop was due to the enthusiastic participation of all the attendees.

The workshop Steering Committee played a key role in defining the research areas for the individual working groups and selecting the participants. The workshop was sponsored and jointly funded by the American Institute of Steel Construction, the American Iron and Steel Institute, the Metal Building Manufacturers Association, the National Science Foundation and the National Bureau of Standards. Funding for participation of the university researchers was provided by the National Science Foundation through the efforts of Dr. John Scalzi.

Several participants, who were unable to attend the workshop, contributed problem statements for the working groups to consider. We appreciate the contributions received from Theodore Galambos, Hal Iyengar, Arthur Arndt, and Harry Weese.

John Gross assisted in preparing the report and Bruce Ellingwood reviewed the final draft.

Mrs. Wanda Eader from the National Bureau of Standards provided administrative support in planning and conducting the workshop and typing the proceedings.

APPENDIX A
WORKSHOP KEYNOTE SESSION

Remarks

by

Dr. Ernest Ambler
Director, National Bureau of Standards

I appreciate the opportunity to appear before you today to welcome you to the National Bureau of Standards. NBS is pleased to sponsor this workshop along with the National Science Foundation, the American Institute of Steel Construction, the American Iron and Steel Institute, and the Metal Building Manufacturers Association.

This workshop has been convened to develop consensus recommendations for steel building research, and to establish priorities for consideration by industry and government. In these two days you will begin to establish the basis for a collaborative relationship among federal agencies, university researchers, design professionals, and the U.S. steel industry.

Here at the National Bureau of Standards we are very proud of our participation in many strong and productive cooperative research efforts with industry, universities, and other federal agencies. We are all working together to assure the continued growth and strengthening of our economy, especially through the application of science and technology to our industries. Our research programs at NBS are enriched by the type of cooperation and collaboration in which you are expressing an interest by your presence here today.

I would like to give you some background on the rather long history of cooperation between NBS and the steel industry. For more than 80 years, NBS has been working with the steel industry to improve the durability and performance of metals and alloys. Starting in 1903, NBS began work to determine the melting points of pure metals as part of our mission to perform basic measurements. In 1912, because of an alarming number of railroad accidents, Congress appropriated special funds for NBS to conduct materials investigations on railroad iron and steel. By 1913, our Metallurgy Division had been formed. In 1919, NBS provided the first explanation of the phenomenon of age hardening of metals. By 1930, through improved technology, better steels were being used for rails and cars and the railroad accident rate fell by 2/3, from a high of 36,000 accidents in 1920.

World War II brought national concern for conservation of strategic raw materials such as chromium, tungsten, and

molybdenum used in steel manufacturing. NBS investigated "lean alloy" steels and developed new coatings and processes to help meet these concerns.

Since the post-war years, NBS has been actively pursuing our present mission. We provide industry, government agencies, and scientific organizations with data, measurement methods, standard reference materials, concepts, and information on the fundamental aspects of processing, structure, physical properties, and performance of metals and alloys.

Currently there are quite a few NBS programs supportive of the U.S. steel industry. For example: Steel producers use our Standard Reference Materials (SRM's) to provide quality assurance for their materials. These samples have specific chemical or physical properties certified by the Bureau. They are used in calibrating instruments, checking chemical composition, and controlling production of various steels. Today, approximately 30 percent of the 40,000 SRM's sold annually are to producers and users of steel and metal alloys.

NBS is working with the American Iron and Steel Institute (AISI) to develop process control sensors for rapid measurement of temperature distributions and automatic detection of porosity during manufacture. Also with AISI we are working to develop diagrams that will help designers select A36 structural steel products for load-bearing capacity and other performance characteristics related to fire safety.

The American Society for Metals (ASM) has raised \$4 million to cover its participation in a collaborative effort in which NBS is providing technical guidance on alloy phase diagrams. In 1982 the National Association of Corrosion Engineers (NACE) and NBS established a cooperative corrosion data program to help reduce corrosion damage to the nation's infrastructure -- its bridges, buildings, industrial plants, vehicles, and utilities.

In our welding research program, NBS scientists are working side-by-side with researchers sponsored by the Welding Research Council (WRC) and the American Welding Institute (AWI), formerly known as the American Welding Technology Application Center (AWTAC). NBS welding research is developing the scientific basis to control the formation of flaws during welding, to nondestructively inspect welds to measure flaw size, and to develop models to predict the effect of weld flaws on structural integrity. Most of those examples are collaborations involving the NBS Center for Materials Research.

In the Center for Building Technology (CBT) our research has supported the development by the American Institute of Steel Construction (AISC) of load and resistance factor design for steel structures. CBT is currently working with AISC on a project to determine the performance of connections in steel braced frames. We have good reason to be proud of our support for the steel industry. We are delighted now to have the

opportunity to focus more attention on structural engineering. We are particularly excited about this new focus because of the current interest in testing large scale structural components and systems.

This afternoon you are scheduled to visit our 12-million pound capacity Large Scale Structural Research Facility and the 3-Dimensional Structural Testing Facility. The Large Scale Structural Research Facility will be used later this year to test the performance of full-scale bridge and building components subjected to earthquake loads. NBS research facilities are available for cooperative work with industry and, under certain conditions, facilities are even available for proprietary research.

In closing, I would like to state that we look forward to continued cooperation with the steel industry. I trust you will have a productive workshop and that you will enjoy your meeting here at NBS.

Remarks

by

Dr. John McTague
Deputy Director, Office of Science and
Technology Policy

Thank you for the opportunity to get outside the Beltway for a brief period. It's nice to see real scientists and engineers again. Even the air is different--there's no odor of fire and brimstone coming from our neighbors in the Executive Office Building!

This workshop involving industry, government, and university participants to discuss research needs for steel buildings comes at a highly symbolic time. Just over a month ago, the President's Commission on Industrial Competitiveness reported to the President on ways to improve the U.S. position in an increasingly international and increasingly competitive world market. These eminent individuals--corporate CEO's, bankers, labor leaders, lawyers, and government officials--deliberated for some eighteen months. They identified eight major factors which affect this, or any other, Nation's ability to compete.

They were items such as the cost of labor, the cost of capital, exchange rates, trade policies, etc. They then rated these as advantageous, neutral, or disadvantageous for the U.S. competitive position. The cost of labor is obviously disadvantageous for the U.S. competitive position, and we wouldn't have it any other way--we want American workers to be the most prosperous in the world. None of the others I enumerated possess potential advantage for us, either. The only advantages we have lie in technology and talent. To quote from the report:

"....America owes much of its standard of living to U.S. preeminence in technology. In order to make technology a continuing competitive advantage for the United States, we need to do three basic things: (1) create a solid foundation of science and technology that is relevant to commercial uses; (2) apply advances in knowledge to commercial products and processes; and (3) protect intellectual property..."

So here you are today, one step ahead of the President's Commission. You are already using the combined strengths of the three sectors to cooperate to the advantage of all. If you are successful in handling cooperative government-industry-university research to advance the art in your field, and if your efforts are repeated in other fields, we as a Nation can be confident of success in this global competition.

It is also particularly fitting that you should convene at the National Bureau of Standards, which has such a long and successful track record in cooperative ventures to strengthen our technology base. As the slogan of a former employer of mine goes, this is "Where Science Gets Down to Business."

Best wishes for a stimulating and successful workshop.

Remarks

by

John H. Busch
Chairman
American Institute of Steel Construction

Thank you for inviting me to be with you today. It is my pleasure to welcome you on behalf of a very important segment of the steel construction industry, the American Institute of Steel Construction. Most of you are familiar with AISC, what it does, and where it has been. This morning I would like to use my time to tell you about some of the things AISC is doing, where we could be headed, and offer a few challenges.

First, a little background information. AISC is the trade group that represents the fabricated structural steel industry with over 430 active member firms in the United States. AISC member firms are involved in the fabrication of diverse structures for a wide range of building and non-building construction applications. The most prominent of these are custom designed steel framed buildings and steel bridges. Throughout its 63 year history, AISC has been highly engineering oriented with a strong emphasis on steel research and steel design techniques. It has published many technical publications including the "bible" of the industry - the AISC Manual of Steel Construction - which contains the well known AISC Code of Standard Practice and the AISC Specifications for the Design, Fabrication and Erection of Structural Steel for Buildings. These documents are the basis for most steel building contracts and designs in this country as well as other parts of the world.

Currently the fabricated structural steel industry is shipping over 4.5 million tons annually worth over 5 billion dollars. This is down from nearly 7.0 million tons and 8 billion dollars four years ago. This industry has been in a free fall and the slide has not ended for many. Building steel represents approximately 65% of the total tonnage shipped for our standard industrial classification No. 3441.

AISC operates on a budget of nearly \$4.0 million annually with a staff of over 55 people including its highly prized 20 regional engineers located in key cities throughout the United States. In a word, AISC is a "technical" organization.

A few years ago, AISC Headquarters were moved from New York to Chicago. A change, and as part of that change, AISC decided to market its technical expertise. That marketing effort, based on statistical data and backed by hard core engineering and research studies, is gradually reaping benefits. This, despite the overall decline in the capital sector of the economy and its negative impact on the fabricated structural steel industry. Our objective is to gain a bigger share of a shrinking pie for the

fabricated structural steel industry.

To organize for this goal a long range strategic planning task group was formed over a year ago. Detailed studies are being developed, and the current schedule calls for this strategic plan to be presented to the industry by December of this year. The plan will incorporate five key objectives:

- Market Share Penetration
- Technology
- Membership Enlargement and Involvement
- Government Relations
- Public Image

As you may note, technology is a vital factor in this planning.

The American Association of Engineering Societies in a recent paper points out that the United States is faltering in the area of research and development and concludes that the activities which move new technology from research to defined commercial potential are inadequate. This group goes on to report the strong correlation between research and improved productivity in manufacturing. Economist Edward F. Denison rates the various contributions to productivity as follows:

Technology.....	38%
Capital.....	26%
Quality of Labor.....	14%
Economies of Scale.....	12%
Resource Allocation.....	10%

Again, technology is the largest single factor to secure strength for our industry in the market place through productivity improvements. Some of the technological areas that have been identified for progress include:

- Computer - Aided Engineering
- Flexible Manufacturing Systems
- Office Operations
- Advanced Manufacturing Methods
- Advanced Software Systems

- Computers
- Materials Technology
- Energy

The American Association of Engineering Societies asks the key question: Who is going to do these studies? They point out that these long term programs require patience, organized and steady administration along with continuous funding. They further suggest that new imaginative cooperative arrangements deriving support from many sources, deserve urgent consideration. In Japan and Germany, institutes from many industries not only work closely with the academic experts but have substantial government support as well. We need to look closer at these possibilities in the United States.

As a mature industry, we cannot compete dollar for dollar with the high growth sectors of the economy in our research efforts. But we can compete with them conceptually in our research direction. Let's look at a leading technical company for comparative purposes. United Technologies is a 16 billion dollar company with an after tax return on equity of over 16 percent. Its growth rate for the past five years averages about 8 percent per year (despite a major downturn in 1982). United Technologies employs over 200,000 people and includes the following companies in its conglomerate portfolio:

Carrier Air Conditioning

Otis Elevator

Essex

Building Systems Company

Pratt & Whitney

Elliott

Sikorsky

Norden, Inmont

Mostek and others

In their 1984 annual report, United Technologies states,

"High technology is the common denominator of all we do. Through the successful management of technology we are able to grow and to contribute to the world economy. Few corporations spend as much as we do on research and development. Our long standing policy is to invest wisely substantial amounts of company funds in

advanced technology to yield superior products at the lowest possible cost."

Conceptually, despite the flair for high technology, their goals of superior products at the lowest possible cost should not be that much different from ours. This appears to match my earlier remarks about having an improved position in the market through innovative technology.

So, as you meet here today and tomorrow, the challenge is not only to involve your detailed and specific thoughts, but also to encourage creative new thinking. Traditionally, the research done in our industry has been more market reactive than that of anticipating the markets needs. AISC needs to provide you with more help in this area so that our research dollars can be spent in the direction that meets the needs of the market to secure the best results. I encourage you to consider these facts during your deliberations. From a fabricator's viewpoint, there are many factors that affect cost, but five major variables need to be collectively optimized to find the lowest cost. They are:

Engineering Labor

Drafting Labor

Shop Labor

Erection Labor

Raw Material Cost

Many steel designers correlate total cost savings with the reduced weight of the structure as it relates to raw material cost only and totally neglect the other variables. How many researchers are guilty of the same process? In other words, we need to be practical and consider all the factors that will affect our products and services in the reality of the market place. I feel confident that this workshop can be an important step in that direction. Thank you.

Remarks

by

Robert B. Peabody
President, American Iron and Steel Institute

On behalf of the American Iron and Steel Institute, I want to extend to all of you a warm welcome to this workshop on Steel Research Needs for Buildings. We at AISI are genuinely pleased to be one of the sponsors and to join with the American Institute of Steel Construction, the Metal Building Manufacturers Association, the National Science Foundation, and the National Bureau of Standards in an effort to identify realistic programs that will advance the state-of-the-art and improve safety and economy in building design, fabrication and construction.

Building construction is a large market for steel. We estimate some 4 million tons of steel are consumed each year in buildings of all types. You can understand, then, the importance we place on this workshop.

This morning I would like to spend a few minutes to tell you something about AISI - who we are, what we do. Then I would like to comment on AISI structural research over the years and the impact of this research on building construction. Finally, I hope to leave you with some thoughts that you may wish to consider during your deliberations over the next two days.

Who are we? AISI is an association of steel producing companies. It is truly "American" in that its membership includes companies from North, Central and South America who account for 90% of the raw steel production in the Western Hemisphere.

Our activities embrace research and technology to improve the steel manufacturing process, the collection and dissemination of statistics, public affairs, international trade and industrial relations including health, safety and hygiene. In addition, the Institute maintains field offices in cities throughout the United States, staffed by engineers who are responsible for industry activities related to building codes and regulatory standards that effect the use of steel mill products in construction.

A key part of our code work has been the Institute's continuing studies of fire hazards and fire protection. The object here is greater fire safety at lower building costs. In fact, I see that one of your workshop sessions is dedicated to the subject of needed fire research for buildings. We consider this to be an area where real economies can be effected.

The Institute also engages in promotional activities of general interest to the steel industry. These include publicity,

booklets, trade show participation, motion pictures, seminars and educational programs. In addition, special promotion programs are carried out by individual product promotion committees whose company members produce a particular steel mill product - hot rolled and cold finished bars, sheet and strip, large diameter line pipe, steel plate, structural steel and wire rope, to name a few.

With this brief description, you can see that AISI is a multifaceted organization engaged in all aspects that effect the steel industry.

This, then, briefly, is who we are.

Now let's be specific and turn our attention to AISI's structural research. This, after all, is why we are here. AISI's research in the structural area began in earnest about 20 years ago and it has embraced a number of topics included in this workshop - connections and members, frames, seismic design, and load and resistance factor design. Throughout this period, the main objective has been to increase the economy and safety of steel construction by (1) developing new structural concepts, (2) improving and updating the provisions of various design specifications and (3) preparing design guidelines and recommendations for use by the engineer.

The eccentrically braced frame is an example of a new structural concept developed through AISI research. The load and resistance factor design specification, another AISI project, will give engineers a rational guide for building design.

I should note here our cooperative research programs with government agencies, notably the Federal Highway Administration and the National Science Foundation. We have a joint program now underway with the Federal Highway Administration to test a one-half scale model of a prototype bridge designed using innovative structural concepts. The model is to be tested sometime this year at the FHWA Turner-Fairbank Research Center, McLean, Virginia. Also, over the years, we have collaborated in projects of the National Science Foundation relating to the design of earthquake-resistant structures.

These joint efforts with the government have been an important part of our research program.

In closing, I would like to leave you with a few thoughts. In the past, the steel producing and fabricating industries have been a major source of funding for structural related research. At one time these industries were able to freely support most proposals that were submitted for consideration by various research agencies. But, as you know, recent severe economic pressures have eroded the funds that were once available. Obviously, we must now evaluate and prioritize projects on a more precise basis. Economy and safety now become essential factors when considering a research topic for funding. In fact, the

words "economy" and "safety" are used in the stated objective of this workshop. I would urge you to keep these words in mind during your discussions within each working session. Please remember that the research priorities you set during the next two days will become important guidelines upon which the steel industry will base its future building research program.

The industry sincerely thanks you for the valuable time you are spending in its behalf and wishes you success in the arduous task to which you have committed yourself. I know the results of your work will provide benefits for all. Thank you.

APPENDIX B

STEEL RESEARCH NEEDS FOR BUILDINGS

Program

TUESDAY, MARCH 5, 1985

- 9:00- Opening Remarks
 9:45
- Ernest Ambler
 Director, National Bureau of Standards
 - John McTague
 Deputy Director, Office of Science and
 Technology Policy
 - John Busch
 Chairman, American Institute of Steel
 Construction
 - Robert Peabody
 President, American Iron and Steel Institute
- 9:45 - Workshop Introduction
 10:00
- Geerhard Haaiker
 American Institute of Steel Construction
- Charles Culver
 National Bureau of Standards
- 10:00 - Coffee Break
 10:30

10:30 - 1:00	Working Group Sessions
	Group 1 - Total Building Systems Chairman, Joseph Colaco
	Group 2 - Connections and Members Chairman, Robert Disque
	Group 3 - Frames Chairman, William McGuire
	Group 4 - Seismic Design Chairman, Mike Agbabian
	Group 5 - Load and Resistance Factor Design Chairman, Ivan Viest
	Group 6 - Fire Protection Chairman, Richard Gewain
	Group 7 - Loads Chairman, Dale Perry
1:00 - 1:45	Lunch
1:45 - 4:00	Working Group Sessions (continued)
4:00 - 5:00	Plenary Session Lecture Room A
5:00 - 5:30	Structures Laboratory Tour
6:30 -	Social Hour and Dinner

Speaker

Dr. Nam Suh
Assistant Director of Engineering
National Science Foundation
**"Cooperative Government/Industry/
University Research"**

WEDNESDAY, MARCH 6

9:00 -	Working Group Sessions
1:00	(continued)
1:00 -	Lunch
1:45	
1:45 -	Plenary Session
4:00	Lecture Room A
	Develop final recommendations
4:00 -	Closing Remarks
4:15 -	Adjourn

LOCATION:

National Bureau of Standards
Gaithersburg, Maryland

SPONSORED BY:

National Bureau of Standards
National Science Foundation
American Institute of Steel Construction
American Iron and Steel Institute
Metal Building Manufacturers Association

OBJECTIVE:

To develop consensus recommendations for steel building research and establish priorities for industry and government consideration.

PARTICIPANTS:

Invited representatives from the steel industry, design professionals, Federal agency representatives and university researchers.

STEERING COMMITTEE:

Charles G. Culver, NBS (Chairman)
Joseph P. Colaco, CBM Engineers
Robert O. Disque, AISC
Richard Gewain, AISI
Geerhard Haaijer, AISC
Nestor R. Iwankiw, AISC
Albert C. Kuentz, AISI
William McGuire, Cornell University
Dale C. Perry, MBMA
Werner H. Quasebarth, Atlas Machine and Iron Works
Ivan M. Viest, Consulting Engineer

APPENDIX C
WORKSHOP PARTICIPANTS

DESIGN PROFESSIONALS

Mr. Horatio Allison
President
Allison, McCormac & Nickolaus, P.A.
11810 Parklawn Drive
Rockville, Maryland 20852

Mr. Irwin G. Cantor
Office of Irwin G. Cantor
919 Third Avenue
New York, New York 10022

Dr. Joseph P. Colaco
President
CBM Engineers, Inc.
1700 West Loop South - Suite 830
Houston, Texas 77027-3092

Mr. Henry J. Degenkolb
H. J. Degenkolb Associates, Engineers
350 Sansome Street, Room 500
San Francisco, California 94104

Dr. James M. Fisher
Vice President
Computerized Structural Design, Inc.
5678 W. Brown Deer Road
Milwaukee, Wisconsin 53223

Mr. Jerome S.B. Iffland
President, Iffland Kavanagh Waterbury
1501 Broadway
New York, New York 10036

Mr. Socrates Ioannides
Senior Engineer
Stanley D. Lindsey & Associates, Ltd.
1906 West End Avenue
Nashville, Tennessee 37203-2371

Dr. Stanley D. Lindsey
President
Stanley D. Lindsey & Associates, Ltd.
1906 West End Avenue
Nashville, Tennessee 37203-2371

Dr. Walter P. Moore, Jr.
Chairman & President
Walter P. Moore & Associates, Inc.
2905 Sackett Street
Houston, Texas 77098

Mr. Clarkson W. Pinkham
President
S.B. Barnes & Associates
2236 Beverly Blvd.
Los Angeles, California 90057

Mr. Dell Shields
Vice President
Herrick Corporation
P.O. Box 3007
Hayward, California 94540

Mr. Leslie V. Shute
Vice President
Turner Construction Company
633 3rd Avenue
New York, New York 10017

Dr. John D. Stevenson
President, Stevenson & Associates
9217 Midwest Avenue
Cleveland, Ohio 44125

Mr. Edward J. Teal
Seismic Engineering Associates, Ltd.
1300 4th Street
Santa Monica, California 90401

Mr. Raymond H.R. Tide
Wiss, Janney, Elstner, Associates, Inc.
330 Pfingsten Road
Northbrook, Illinois 60062

Dr. Ivan M. Viest
Consulting Engineer
P.O. Box 1428
Bethlehem, Pennsylvania 18016

Mr. Kenneth B. Wiesner, P.E.
LeMessurier Associates/SCI
1033 Massachusetts Avenue
Cambridge, Massachusetts 02238

INDUSTRY REPRESENTATIVES

Mr. Edward P. Becker, P.E.
Chief Engineer
Lehigh Structural Steel Company
Box 626
One Allen Street
Allentown, Pennsylvania 18015

Mr. Delbert F. Boring
Regional Director, Construction
Codes & Standards
American Iron and Steel Institute
4937 West Broad Street
Columbus, Ohio 43228

Mr. Roger L. Brockenbrough
Research Consultant
Heavy Products Division
U.S. Steel Corporation
Technical Center
One Tech Center Drive
Monroeville, Pennsylvania 15146

Mr. John H. Busch
President, Haven-Busch Company
3443 Chicago Drive, S.W.
Grandville, Michigan 49418

Mr. Andrew K. Courtney
Chief Engineer
Owen Steel Company, Inc.
801 Blossom Street
P.O. Box 1698
Columbia, South Carolina 29202

Mr. Robert O. Disque
Assistant Director of Engineering
American Institute of Steel Construction, Inc.
The Wrigley Bldg.
400 North Michigan Avenue
Chicago, Illinois 60611-4185

Mr. William Y. Epling
Director of Government Affairs
American Institute of Steel Construction, Inc.
Suite 400
1629 K Street, NW
Washington, DC 20006

Mr. Walter H. Fleischer
Senior Structural Consultant
Bethlehem Steel Corporation
255 SGO
Bethlehem, Pennsylvania 18016

Mr. Richard Gewain
Chief, Fire Protection Engineer
American Iron & Steel Institute
1000 16th Street, NW
Washington, DC 20036

Mr. Michael Gilmor
Manager of Engineering
Canadian Institute of Steel Construction
201 Consumers Road
Suite 300
Willowdale, Ontario, M2J 4G8
Canada

Mr. John D. Griffiths
Vice President - Engineering
Paxton & Vierling Steel Co.
P.O. Box 1085
Omaha, Nebraska 68101

Mr. Joshua Gurman
American Iron and Steel Institute
1000 16th Street, NW
Washington, DC 20036

Dr. Geerhard Haaijer
Vice President
American Institute of Steel Construction
The Wrigley Bldg.
400 North Michigan Avenue
Chicago, Illinois 60611-4185

Mr. J. W. Hotchkies
Manager, Market Development Engineering
The Algoma Steel Corporation, Ltd.
Mississauga Executive Center, Suite 900
Four Robert Speck Parkway
Mississauga, Ontario
Canada L4Z 1S1

Mr. Nestor Iwankiw
Assistant Director of Engineering
American Institute of Steel Construction
The Wrigley Bldg.
400 North Michigan Avenue
Chicago, Illinois 60611-4185

Mr. Juris Jauntirans
3210 Watlong Street
Inland Steel Company
East Chicago, Indiana 46312

Mr. David C. Jeanes
American Iron and Steel Institute
1000 16th Street, NW
Washington, DC 20036

Mr. Donald L. Johnson
Senior Research Engineer
Butler Manufacturing Company
Research Center
135th Street and Botts Road
Grandview, Missouri 64030

Mr. Larry Kloiber
Vice President
L. L. LeJeune Company
118 West 60th Street
Minneapolis, Minnesota 55419

Mr. Henry V. Kominek
Regional Director
Construction Codes & Standards
American Iron & Steel Institute
1150 Wilmette Avenue
Wilmette, Illinois 60091

Mr. Albert C. Kuentz
Staff Representative
American Iron & Steel Institute
1000 16th Street, NW
Washington, DC 20036

Mr. Hank Martin
Regional Director, Codes &
Standards
American Iron & Steel Institute
671 Newcastle Road, Suite 1
Newcastle, California 95658-9702

Mr. Daniel M. McGee, P.E.
Regional Director, Construction Codes
& Standards
American Iron & Steel Institute
P.O. Box 311
Matawan, New Jersey 07747

Mr. William E. Moore
Vice President - Engineering
Taurrier Street and Bredford
P.O. Box 753
Ferro Products Company
Charleston, West Virginia 25323

Mr. Heinz Pak
Engineering Consultant
United States Steel Corporation
600 Grant Street
Pittsburgh, Pennsylvania 15230

Mr. Robert B. Peabody
President, American Iron &
Steel Institute
1000 16th Street, NW
Washington, DC 20036

Dr. Dale C. Perry
Metal Building Manufacturers Association
Director of Engineering and Research
1230 Keith Building
Cleveland, Ohio 44115

Mr. Werner H. Quasebarth
President
Atlas Machine & Iron Works, Inc.
7308 Wellington Road
Gainesville, Virginia 20065

Mr. Bill Richey
Vice President Engineering
Havens Steel Company
7219 East 17th Street
Kansas City, Missouri 64126-2890

Mr. Robert E. Roll
Manager of Structural Shapes & Piling Marketing
Bethlehem Steel Corporation
Bethlehem, Pennsylvania 18016

Mr. Dell Shields
Vice President
Herrick Corporation
P.O. Box 3007
Hayward, California 94540

Mr. Gary F. Tilson
Regional Director, Codes & Standards
American Iron & Steel Institute
798 Rays Road, Suite 105A
Stone Mountain, Georgia 30083

Dr. William Thornton
Chief Engineer
Cives Steel Company
411 Rouse Lane
P.O. Box 768180
Atlanta, Georgia 30338

Ms. Lisa Vornholt
Regional Director
American Iron and Steel Institute
13500 Midway Road, Suite 111
Dallas, Texas 75234

Mr. Walter G. Wells
American Iron and Steel Institute
1000 16th Street, NW
Washington, DC 20036

Mr. R. T. Willson
American Iron and Steel Institute
1000 16th Street, NW
Washington, DC 20036

Mr. James Wooten
Chief, Structural Design Engineer
AFCO Steel
P.O. Box 231
1423 East Sixth Street
Little Rock, Arkansas 72201

UNIVERSITY RESEARCHERS

Dr. Joel I. Abrams
Chairman, Department of Civil Engineering
University of Pittsburgh
949 Benedum Hall
Pittsburgh, Pennsylvania 15261

Professor Mihran S. Agbabian
Chairman, Department of Civil Engineering
University of Southern California
Los Angeles, California 90089

Dr. Wai Fah Chen
Professor & Head, Structural Engineering
School of Civil Engineering
Civil Engineering Building
Purdue University
West Lafayette, Indiana 47907

Professor John W. Fisher
Fritz Engineering Laboratory
Building 13
Lehigh University
Bethlehem, Pennsylvania 18015

Professor Kurt H. Gerstle
Department of Civil Environmental and
Architectural Engineering
University of Colorado
Campus Box 428
Boulder, Colorado 80309

Dr. Robert D. Hanson
Professor of Civil Engineering
University of Michigan
Department of Civil Engineering
304 West Engineering Bldg.
Ann Arbor, Michigan 48109-1092

Professor Helmut Krawinkler
Department of Civil Engineering
Stanford University
Stanford, California 94305

Professor Le-Wu Lu
Civil Engineering Department
Fritz Engineering Laboratory
Lehigh University
Bethlehem, Pennsylvania 18015

Professor William McGuire
Cornell University
School of Civil and Environmental Engineering
Hollister Hall
Ithaca, New York 14853

Professor Thomas M. Murray
University of Oklahoma
School of Civil Engineering
202 W. Boyd Street, Room 334
Norman, Oklahoma 73019

Dr. Michael J. O'Rourke
Associate Professor, Civil Engineering
Rensselaer Polytechnic Institute
Troy, New York 12181

Professor Egor Popov
Professor Emeritus of Civil Engineering
University of California, Berkeley
College of Engineering
Berkeley, California 94720

Dr. James B. Radzimirski
University of South Carolina
Department of Civil Engineering
College of Engineering
Columbia, South Carolina 29208

Dr. Charles W. Roeder
Department of Civil Engineering
University of Washington
233 More Hall, FX-10
Seattle, Washington 98195

Dr. D. Surry
Boundary Layer Wind Tunnel Laboratory
Faculty of Engineering Science
London, Ontario
Canada N6A 5B9

Professor Joseph A. Yura
Warren Bellows Professor of Civil Engineering
University of Texas at Austin
Department of Civil Engineering
10100 Burnet Road
Austin, Texas 78758-4497

GOVERNMENT REPRESENTATIVES

Mr. Gifford Albright
National Science Foundation
1800 G Street, NW
Washington, DC 20550

Dr. Hans Ashar
Research Manager
U.S. Nuclear Regulatory Commission
(NL 5650)
Washington, DC 20555

Dr. Charles G. Culver
Chief, Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Dr. Robert M. Dinnat
Associate Technical Director
Construction Engineering Research Laboratory
U.S. Army Corps of Engineers
Box 4005
Champaign, Illinois 61820

Dr. Bruce R. Ellingwood
Leader, Structural Engineering
Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Mr. Michael Gaus
National Science Foundation
1800 G Street, NW
Washington, DC 20550

Dr. John L. Gross
Research Engineer
Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Dr. H. S. Lew
Leader, Construction Safety
Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Dr. Edgar V. Leyendecker
Leader, Earthquake Hazards Reduction
Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Dr. Richard D. Marshall
Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Dr. John McTague
Deputy Director
Office of Science & Technology Policy
Executive Office of the President
Room 5005
New Executive Office Building
Washington, DC 20506

Mr. Irving E. Minkin, P.E.
Deputy Commissioner
NYC Department of Buildings
120 Wall Street
New York, New York 10005

Dr. Jack Scalzi
National Science Foundation
1800 G Street, NW
Washington, DC 20550

Dr. Emil Simiu
Structural Research Engineer
Structures Division
National Bureau of Standards
Gaithersburg, Maryland 20899

Dr. Nam Suh
Assistant Director of Engineering
National Science Foundation
1800 G Street, NW
Washington, DC 20005

Mr. Michael Yachnis
Chief Engineer
Naval Facilities Engineering Command
(04B)
Department of the Navy
200 Stovall Street
Alexandria, Virginia 22332-2300

U.S. DEPT. OF COMM. BIBLIOGRAPHIC DATA SHEET (See Instructions)	1. PUBLICATION OR REPORT NO. NBS/SP-693	2. Performing Organ. Report No.	3. Publication Date May 1985
4. TITLE AND SUBTITLE A Workshop on Steel Research Needs for Buildings			
5. AUTHOR(S) Culver, C.G., Iwankiw, N., and Kuentz, A.			
6. PERFORMING ORGANIZATION (If joint or other than NBS, see instructions) National Bureau of Standards U.S. Department of Commerce Gaithersburg, MD 20899			7. Contract/Grant No. 8. Type of Report & Period Covered Final
9. SPONSORING ORGANIZATION NAME AND COMPLETE ADDRESS (Street, City, State, ZIP) See title page			
10. SUPPLEMENTARY NOTES Library of Congress Catalog Card Number:85-600546 <input type="checkbox"/> Document describes a computer program; SF-185, FIPS Software Summary, is attached.			
11. ABSTRACT (A 200-word or less factual summary of most significant information. If document includes a significant bibliography or literature survey, mention it here) This report identifies needed experimental and analytical research to advance the state-of-the-art and improve safety and economy in the design, fabrication and construction of steel buildings. A five year plan for a coordinated research program is included. Recommendations for research projects dealing with the following topics are presented: Total building systems, connections and members, frames, seismic design, load and resistance factor design, fire protection, and design loads. The recommendations were developed at a workshop involving participation by steel industry representatives, design professionals, Federal agency representatives and university researchers.			
12. KEY WORDS (Six to twelve entries; alphabetical order; capitalize only proper names; and separate key words by semicolons) Buildings; design; fire protection; loads; research; steel; structural engineering.			
13. AVAILABILITY <input checked="" type="checkbox"/> Unlimited <input type="checkbox"/> For Official Distribution. Do Not Release to NTIS <input type="checkbox"/> Order From Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. <input checked="" type="checkbox"/> Order From National Technical Information Service (NTIS), Springfield, VA. 22161			14. NO. OF PRINTED PAGES 89 15. Price

NBS *Technical Publications*

Periodical

Journal of Research—The Journal of Research of the National Bureau of Standards reports NBS research and development in those disciplines of the physical and engineering sciences in which the Bureau is active. These include physics, chemistry, engineering, mathematics, and computer sciences. Papers cover a broad range of subjects, with major emphasis on measurement methodology and the basic technology underlying standardization. Also included from time to time are survey articles on topics closely related to the Bureau's technical and scientific programs. Issued six times a year.

Nonperiodicals

Monographs—Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

Handbooks—Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications—Include proceedings of conferences sponsored by NBS, NBS annual reports, and other special publications appropriate to this grouping such as wall charts, pocket cards, and bibliographies.

Applied Mathematics Series—Mathematical tables, manuals, and studies of special interest to physicists, engineers, chemists, biologists, mathematicians, computer programmers, and others engaged in scientific and technical work.

National Standard Reference Data Series—Provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated. Developed under a worldwide program coordinated by NBS under the authority of the National Standard Data Act (Public Law 90-396).

NOTE: The Journal of Physical and Chemical Reference Data (JPCRD) is published quarterly for NBS by the American Chemical Society (ACS) and the American Institute of Physics (AIP). Subscriptions, reprints, and supplements are available from ACS, 1155 Sixteenth St., NW, Washington, DC 20056.

Building Science Series—Disseminates technical information developed at the Bureau on building materials, components, systems, and whole structures. The series presents research results, test methods, and performance criteria related to the structural and environmental functions and the durability and safety characteristics of building elements and systems.

Technical Notes—Studies or reports which are complete in themselves but restrictive in their treatment of a subject. Analogous to monographs but not so comprehensive in scope or definitive in treatment of the subject area. Often serve as a vehicle for final reports of work performed at NBS under the sponsorship of other government agencies.

Voluntary Product Standards—Developed under procedures published by the Department of Commerce in Part 10, Title 15, of the Code of Federal Regulations. The standards establish nationally recognized requirements for products, and provide all concerned interests with a basis for common understanding of the characteristics of the products. NBS administers this program as a supplement to the activities of the private sector standardizing organizations.

Consumer Information Series—Practical information, based on NBS research and experience, covering areas of interest to the consumer. Easily understandable language and illustrations provide useful background knowledge for shopping in today's technological marketplace.

Order the above NBS publications from: Superintendent of Documents, Government Printing Office, Washington, DC 20402.

Order the following NBS publications—FIPS and NBSIR's—from the National Technical Information Service, Springfield, VA 22161.

Federal Information Processing Standards Publications (FIPS PUB)—Publications in this series collectively constitute the Federal Information Processing Standards Register. The Register serves as the official source of information in the Federal Government regarding standards issued by NBS pursuant to the Federal Property and Administrative Services Act of 1949 as amended, Public Law 89-306 (79 Stat. 1127), and as implemented by Executive Order 11717 (38 FR 12315, dated May 11, 1973) and Part 6 of Title 15 CFR (Code of Federal Regulations).

NBS Interagency Reports (NBSIR)—A special series of interim or final reports on work performed by NBS for outside sponsors (both government and non-government). In general, initial distribution is handled by the sponsor; public distribution is by the National Technical Information Service, Springfield, VA 22161, in paper copy or microfiche form.

U.S. Department of Commerce
National Bureau of Standards
Gaithersburg, MD 20899

Official Business
Penalty for Private Use \$300