



A11106 082775

UNITS FOR MAGNETIC PROPERTIES

NIST PUBLICATIONS

Quantity	Symbol	Gaussian & cgs emu ^a	Conversion factor, C ^b	SI & rationalized mks ^c
Magnetic flux density, magnetic induction	<i>B</i>	gauss (G) ^d	10 ⁻⁴	tesla (T), Wb/m ²
Magnetic flux	Φ	maxwell (Mx), G·cm ²	10 ⁻⁸	weber (Wb), volt second (V·s)
Magnetic potential difference, magnetomotive force	<i>U, F</i>	gilbert (Gb)	10/4 π	ampere (A)
Magnetic field strength, magnetizing force	<i>H</i>	oersted (Oe), ^e Gb/cm	10 ³ /4 π	A/m ^f
(Volume) magnetization ^g	<i>M</i>	emu/cm ^{3h}	10 ³	A/m
(Volume) magnetization	4 πM	G	10 ³ /4 π	A/m
Magnetic polarization, intensity of magnetization	<i>J, I</i>	emu/cm ³	4 π × 10 ⁻⁴	T, Wb/m ²ⁱ
(Mass) magnetization	σ, M	emu/g	1 4 π × 10 ⁻⁷	A·m ² /kg Wb·m/kg
Magnetic moment	<i>m</i>	emu, erg/G	10 ⁻³	A·m ² , joule per tesla (J/T)
Magnetic dipole moment	<i>j</i>	emu, erg/G	4 π × 10 ⁻¹⁰	Wb·m ⁱ
(Volume) susceptibility	χ, κ	dimensionless, emu/cm ³	4 π (4 π) ² × 10 ⁻⁷	dimensionless henry per meter (H/m), Wb/(A·m)
(Mass) susceptibility	χ_p, κ_p	cm ³ /g, emu/g	4 π × 10 ⁻³ (4 π) ² × 10 ⁻¹⁰	m ³ /kg H·m ² /kg
(Molar) susceptibility	χ_{mol}, κ_{mol}	cm ³ /mol, emu/mol	4 π × 10 ⁻⁶ (4 π) ² × 10 ⁻¹³	m ³ /mol H·m ² /mol
Permeability	μ	dimensionless	4 π × 10 ⁻⁷	H/m, Wb/(A·m)
Relative permeability ^j	μ_r	not defined		dimensionless
(Volume) energy density, energy product ^k	<i>W</i>	erg/cm ³	10 ⁻¹	J/m ³
Demagnetization factor	<i>D, N</i>	dimensionless	1/4 π	dimensionless

- a. Gaussian units and cgs emu are the same for magnetic properties. The defining relation is $B = H + 4\pi M$.
- b. Multiply a number in Gaussian units by C to convert it to SI (e.g., 1 G × 10⁻⁴ T/G = 10⁻⁴ T).
- c. SI (*Système International d'Unités*) has been adopted by the National Bureau of Standards. Where two conversion factors are given, the upper one is recognized under, or consistent with, SI and is based on the definition $B = \mu_0(H + M)$, where $\mu_0 = 4\pi \times 10^{-7}$ H/m. The lower one is not recognized under SI and is based on the definition $B = \mu_0 H + J$, where the symbol *I* is often used in place of *J*.
- d. 1 gauss = 10⁵ gamma (γ).
- e. Both oersted and gauss are expressed as cm^{-1/2}·g^{1/2}·s⁻¹ in terms of base units.
- f. A/m was often expressed as "ampere-turn per meter" when used for magnetic field strength.
- g. Magnetic moment per unit volume.
- h. The designation "emu" is not a unit.
- i. Recognized under SI, even though based on the definition $B = \mu_0 H + J$. See footnote c.
- j. $\mu_r = \mu/\mu_0 = 1 + \chi$, all in SI. μ_r is equal to Gaussian μ .
- k. $B \cdot H$ and $\mu_0 M \cdot H$ have SI units J/m³; $M \cdot H$ and $B \cdot H/4\pi$ have Gaussian units erg/cm³.

QC
100
.U57
#696
1985
2

