National Bureau of Standards Library, E-01 Admin. Bldg.

DEC 3 0 1970

ED STATES MENT OF MERCE CATION

NBS TECHNICAL NOTE 538

. .

Automated Fingerprint Identification

U.S. ARTMENT OF MMERCE National Bureau of tandards

NBS TECHNICAL PUBLICATIONS

PERIODICALS

JOURNAL OF RESEARCH reports National Bureau of Standards research and development in physics, mathematics, chemistry, and engineering. Comprehensive scientific papers give complete details of the work, including laboratory data, experimental procedures, and theoretical and mathematical analyses. Illustrated with photographs, drawings, and charts.

Published in three sections, available separately:

• Physics and Chemistry

Papers of interest primarily to scientists working in these fields. This section covers a broad range of physical and chemical research, with major emphasis on standards of physical measurement, fundamental constants, and properties of matter. Issued six times a year. Annual subscription: Domestic, \$9.50; foreign, \$11.75*.

• Mathematical Sciences

Studies and compilations designed mainly for the mathematician and theoretical physicist. Topics in mathematical statistics, theory of experiment design, numerical analysis, theoretical physics and chemistry, logical design and programming of computers and computer systems. Short numerical tables. Issued quarterly. Annual subscription: Domestic, \$5.00; foreign, \$6.25*.

• Engineering and Instrumentation

Reporting results of interest chiefly to the engineer and the applied scientist. This section includes many of the new developments in instrumentation resulting from the Bureau's work in physical measurement, data processing, and development of test methods. It will also cover some of the work in acoustics, applied mechanics, building research, and cryogenic engineering. Issued quarterly. Annual subscription: Domestic, \$5.00; foreign, \$6.25*.

TECHNICAL NEWS BULLETIN

The best single source of information concerning the Bureau's research, developmental, cooperative and publication activities, this monthly publication is designed for the industry-oriented individual whose daily work involves intimate contact with science and technology—for engineers, chemists, physicists, research managers, product-development managers, and company executives. Annual subscription: Domestic, \$3.00; foreign, \$4.00*.

* Difference in price is due to extra cost of foreign mailing.

Order NBS publications from:

NONPERIODICALS

Applied Mathematics Series. Mathematical tables, manuals, and studies.

Building Science Series. Research results, test methods, and performance criteria of building materials, components, systems, and structures.

Handbooks. Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications. Proceedings of NBS conferences, bibliographies, annual reports, wall charts, pamphlets, etc.

Monographs. Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

National Standard Reference Data Series. NSRDS provides quantitive data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated.

Product Standards. Provide requirements for sizes, types, quality and methods for testing various industrial products. These standards are developed cooperatively with interested Government and industry groups and provide the basis for common understanding of product characteristics for both buyers and sellers. Their use is voluntary.

Technical Notes. This series consists of communications and reports (covering both other agency and NBS-sponsored work) of limited or transitory interest.

Federal Information Processing Standards Publications. This series is the official publication within the Federal Government for information on standards adopted and promulgated under the Public Law 89–306, and Bureau of the Budget Circular A–86 entitled, Standardization of Data Elements and Codes in Data Systems.

CLEARINGHOUSE

The Clearinghouse for Federal Scientific and Technical Information, operated by NBS, supplies unclassified information related to Government-generated science and technology in defense, space, atomic energy, and other national programs. For further information on Clearinghouse services, write:

> Clearinghouse U.S. Department of Commerce Springfield, Virginia 22151

Superintendent of Documents Government Printing Office Washington, D.C. 20402 UNITED STATES DEPARTMENT OF COMMERCE Maurice H. Stans, Secretary



Nat. Bur. Stand. (U.S.), Tech. Note 538, 33 pages (Aug. 1970) CODEN: NBTNA

Automated Fingerprint Identification

J. H. Wegstein

Center for Computer Sciences and Technology National Bureau of Standards Washington, D.C. 20234



NBS Technical Notes are designed to supplement the Bureau's regular publications program. They provide a means for making available scientific data that are of transient or limited interest. Technical Notes may be listed or referred to in the open literature.

For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402 (Order by SD Catalog No. C13.46:538). Price 40 cents



Contents

	•	Page
1.	Introduction	1
2.	Tools for Performance Analysis	2
3.	Experimental Results with Constellation Matcher	4
4.	A Statistical Matching Procedure	5
5.	Experimental Results with Statistical Matchers	8
6.	Discussion of Results	10
7.	References	12



Automated Fingerprint Identification

by J.H. Wegstein

A procedure is described for determining whether two fingerprint impressions were made by the same finger. The procedure uses the x and y coordinates and the individual directions of the minutiae (ridge endings and bifurcations). The identity of two impressions is established by computing the density of clusters of points in $\Delta x - \Delta y$ space where Δx and Δy are the differences in coordinates that are found in going from one of the fingerprint impression to the other. Experimental results using machine-read minutiae data are given along with results from a previously reported procedure that utilized constellations of minutiae in its matching process.

Key words: Computerized-fingerprint-identification, fingerprint, pattern recognition.

1. Introduction

This paper follows a previous paper ¹ that describes a procedure for matching fingerprint impressions by computer using two types of minutiae: ridge endings and bifurcations. With a fingerprint impression in the first quadrant, data is obtained by reading the X coordinate, Y coordinate, and the angle θ which the minutia direction makes with the X axis for each minutia in the print. When the data is taken manually, θ is measured in degrees and X and Y are measured in <u>units</u> of one tenth millimeter on an actual fingerprint or a millimeter on a ten-fold enlargement of the print. There are about 80 minutiae in an average rolled fingerprint.

To test the performance of a matching procedure, the minutiae data for a set of fingerprints is entered into a computer file. Next, working with minutiae data for a second set of prints (the search prints), the computer compares each of the search prints with each of the prints in the file. Thus, if there are N prints in the file and n search prints, the computer will make n x N comparisons in a given matching run. Each comparison yields a score and the higher the score the more likely it is that both of the prints being compared came from the same finger. In the course of adjusting parameters and improving matching procedures many thousands of pairs of prints have been compared. These experiments have used data that was read manually at the National Bureau of Standards as well as data that was read by machine at the Autonetics Division of North American Rockwell Corporation and Cornell Aeronautical Laboratory, Inc.

2. Tools for Performance Analysis

In the development of pattern recognition techniques it is essential to have ways of measuring performance. New results, after a change in the recognition technique, must be compared with previous results and ultimately it should be possible to compare the achievements of one research effort with the achievements of others in the same field of endeavor.

One tool for displaying the results of fingerprint recognition as well as voice signature recognition is a <u>score matrix</u>. For example if a set of five fingerprints identified as XIII-I, XIII-2,---, XIII-5 is compared with a file of twenty prints identified as XIV-1, XIV-2,---, XIV-20, the results can be displayed as shown in Figure 1. Each of the 100 pairs of prints are compared and the resulting score is entered in the matrix. In Figure 1 prints XIII-n and XIV-n came from the same finger where n=1, 2,----5. Therefore the leftmost diagonal should contain the highest scores in the matrix.

In voiceprint file searches, Tosi² has defined a <u>closed task</u> as a file search in which the search print is known to be in the file. The searcher must simply find the best match. Analogously, if print XIII-2 is known to be in the file, then one need only look for the highest score, 80, in the XIII-2 row. Tosi has defined an <u>open task</u> as a file search in which the searcher does not know if the print being sought is in the file. This is a difficult task because the searcher must judge if the degree of match exceeds some <u>threshold value</u>. By analogy, if a score of 70 is set as a threshold for a match in this fingerprint file search, then XIII-1, XIII-2, and XIII-3 would be correctly identified. However, the search would conclude that XIII-4 and XIII-5 were not in the file. The discrimination matrix can be reduced to a <u>binary matrix</u> by recording only scores that exceed the threshold as X and leaving all other spaces blank.

If a computer is comparing an unknown print with prints in a file as a <u>closed task</u>, the computer will always indicate that some print from the file has the highest matching score and a fingerprint expert must compare the unknown print with the file print to determine if they are from the same finger. In a practical system where some of the unknown prints are not in the file, the expert must still look at some file print for each of the unknown prints. On the other hand, if the computer is operating in the <u>open task</u> mode, it will indicate only those prints from the file that exceed some matching score threshold. The obvious objective in the design of a matching procedure is to achieve such a level of discrimination that only those pairs of prints that came from the same finger will exceed the matching score threshold and require verification by the fingerprint expert.

In order to compare the performance of one matching run with another, one might reduce the data in a discrimination matrix to two numbers: M the percentage of misses, and F the percentage of false

matches. Let

t

TM = total number of matches that should have occurred

TF = total number of failures to match that should have occurred

MS = number of misses

FM = number of false matches

hen
$$M = \frac{100 \text{ MS}}{\text{TM}}$$

F $= \frac{100 \text{ FM}}{\text{TF}}$

In Figure 1, TM = 5, TF = 95 and if a threshold score has been set at 50, MS = 1 and FM = 3. Therefore F = 3.2% and M = 20%.

The values of F and M can be plotted against their corresponding threshold scores as shown in Figure 2. As the threshold value decreases, the percentage of misses decreases as is shown by the solid line. Unfortunately, this is accompanied by an increase in the number of false matches. When a large number of prints are compared, the curves appear to be exponential curves as shown in Figure 3. The point P where the curves cross is of considerable interest in perfecting a matching procedure. P should be as low as possible when a very large number of fingerprints are compared.

The F and M scores are actually impractical for tuning and improving matcher performance with the available general purpose computer because more than 26 pairs of prints in a given matching run exceeds the storage capacity of the high speed memory. When a promising level of performance is achieved, there will be a significant portion of the curves where F and M are zero as seen in Figure 4. Accordingly, three other scores are used: OS, CS, and AA. <u>OS</u> is used to measure performance as an <u>open</u> task and is the highest score for a pair of prints that should not match divided by the lowest score for a pair of prints that should match multiplied by 100 (rounded to the nearest integer). Using the data from Figure 1,

$$0S = \frac{55}{37} \times 100 = 149.$$

<u>CS</u> is used to measure performance as a <u>closed</u> task. In Figure 1, the highest off-diagonal score in each row is divided by the diagonal score for that row (where there should be a match) and this is multiplied by 100. Thus, there is a score for each row. The highest (or worst) of these is taken as the score CS. In Figure 1, CS = 124, corresponding to the highest row score, occurring in row 5, where

$$\frac{46}{37} \times 100 = 124.$$

A print is correctly identified if CS < 100, and the objective in this developmental work is to obtain as low a value as possible for CS and OS. One bad print in the set can cause CS and OS to be very high, but the matcher may be doing a relatively good job with the rest of the prints. Accordingly, still another score, AA, is defined as the mean off-diagonal score divided by the mean diagonal score times 100. In Figure 1,

$$AA = \frac{19.95}{76.6} \times 100 = 26$$

It is desirable to have as low a value as possible for AA.

3. Experimental Results with Constellation Matcher

The fingerprint matcher reported in NBS Technical Note 466 1. as well as several subsequent variations of this matcher compared two fingerprint impressions by finding several minutiae (a constellation) in one print that approximately coincide with a similar constellation from another print. Relative positions of the minutiae as well as direction angles of the minutiae were utilized in computing whether or not there was a coincidence. To minimize the amount of computer time and data storage required, only a portion of the available minutiae from a fingerprint was used. Only those minutiae in a circle of 6mm radius centered at the core of the print were used, and there was an average of about 24 minutiae in the circle on the prints used. Using minutiae that were carefully read manually, matching twenty pairs of average fingerprint impressions after extensive parameter tuning and matcher modifications led to the results shown in Figure 4. Here, the number of minutiae in the constellation being matched is used as the score and hence as the discrimination factor. The point P has been lowered to zero, but the range in the number of minutiae in the matching constellations is discouraging. The maximum number of nine matching minutiae found here fall short of the 12 or more predicted by Caudra ^{3.} as necessary to get adequate odds in favor of recognizing two prints from the same finger when working with a large file. If other parameters in the matcher are "loosened up" such as increasing the allowable difference in position of matching minutiae, then the number of false matches invariably rises.

The reason for a false match can be seen by referring to Figure 5. Minutiae tracings from fingerprint impression XIII-11 (enlarged 10 times) are superimposed on tracings from impression XIV-2 which came from a different finger. Minutiae XIII-11-48 is positioned to coincide with minutia XIV-2-13. If the maximum allowed difference in coordinate values for the other minutiae are:

> $\Delta X = 6$ units $\triangle Y = 6$ units $\triangle \theta$ =15 degrees. 4

then the two constellations of seven minutiae produce a false match. If parameter ΔX or ΔY is reduced to 5 units then this false match is eliminated.

On the other hand, these same parameters may fail to produce matches of two impressions from the same finger because of ever-present distortions. All rolled fingerprint impressions tend to be stretched or twisted in varying amounts. To illustrate a worse-than usual case, minutiae from impression IIP2 are superimposed on minutiae from impression IIP8 in Figure 6. Both impressions are from the same finger and minutia 79 is positioned to coincide with minutia 79'. While minutiae 79, 33, and others to the left tend to coincide, minutiae to the right move further and further apart. Furthermore, distortions may be strangely localized. In Figure 7 two different impression IIP5 and IIP6 from the same finger are superimposed with minutiae 28 and 28' coinciding. While the degree of coincidence is good in the upper left, lower left, and lower right, there is X-distortion in the upper right portion of the print.

The method of matching pre-defined portions of fingerprints by starting with some minutia as a nucleus and developing a constellation of coinciding minutiae has been unsatisfactory. The main reason for this is that only five minutiae were tried as the nucleus for a constellation. This number was limited to five in order to hold down the amount of computing time needed on a general purpose computer to make extensive matching tests. It may be that trying more minutiae as a nucleus would result in satisfactory matching. To adequately test this method of matching prints, it will either be necessary to use more generalpurpose computer time or use a special-purpose device designed for minutiae matching such as that described by Thiebault ⁴ which can utilize parallel operations for very fast matching.

4. A Statistical Matching Procedure

In spite of the distortion shown in Figure 7, it is desirable to take advantage of those pairs of minutiae such as 28, 27, 34, 35, 52, 53, 70, 74, and 75 and others not shown that do coincide. To illustrate how this can be done, some minutiae data from four prints will be used. In Figure 8, the print A and B data are from two different prints made by the same finger and the print C and D data are from prints from two different fingers. Minutiae i in print A is the same as minutiae j in print B if i = j. Minutia 6 (labeled B6 in Figure 9) is not found in print A. The minutiae of both prints are plotted in Figure 9. This is typical of the appearance of superimposed minutiae from two prints that have been read by machine. One print is rotated about six degrees and is shifted about 35 units in the x direction with respect to the other print, but, of course, this information is unknown to the computer when it attempts to match these prints. Figure 10 shows the superimposed minutiae from prints C and D. The simplest version of the statistical matcher, known as M19, begins by computing

$$\Delta x = x_{i} - x_{j}$$
$$\Delta y = y_{i} - y_{j}$$
$$\Delta \theta = \theta_{i} - \theta_{j}$$

for all possible combinations of pairs of minutiae. Only those pairs of minutiae that satisfy the following conditions simultaneously are retained.

Δx	\leq LS
∆y	\leq LS
∆0	$< \Gamma \theta$

If the matcher parameters have the values

$$LS = 60$$

 $L\theta = 25$

then the resulting difference table for prints A and B is shown in Figure 11 and the difference table for prints C and D is shown in Figure 12. These points can be plotted in a Δx , Δy coordinate system as shown in Figure 13 for prints A and B and in Figure 14 for prints C and D. If the prints are from the same finger, then many points will tend to be in a cluster as seen in Figure 13. If the prints are from different fingers, then the points tend to be randomly located over the entire area. It will be noted that there is no pronounced clustering in Figure 14.

The task of the matcher is to compute a matching score that increases as the density of the cluster increases. The M19 matcher accomplishes this by starting from each point in the graph and counting the number of steps in the Δx and Δy directions to each of the other points. If this number of steps, TR, is less than a matcher parameter KR, then the quantity KR-TR is added to an accumulating sum R. To see how this works, let KR = 10 and refer to Figure 15 which is an enlargement of the area around the cluster in Figure 13. Point 1,1 in Figure 15 indicates the distance from minutia B1 to A1 in Figure 9. The number of steps from point 1,1 in Figure 15 to any other point exceeds 10 so that nothing is added to R. However, the number of steps from 2,2 to 4,4 is TR=8. Therefore, the score R is increased by KR-TR=10-8=2. Similarly, there are 8 steps between points 2,2 and 5,5 and this increases the value of R to 4. The contributions from all points are shown in

Figure 16 giving a total R=24. The score actually used is RS=R/S where S is the total number of points found in Figure 13. Therefore in this example S=7 and comparing print A with print B yields a score

$$RS = \frac{24}{7} = 3.42$$

The comparison of print C with print D yields a score

RS = $\frac{14}{7}$ = 2.00

In actual practice, prints that match tend to produce very dense clusters of points in their difference graphs with correspondingly high RS scores. The complete details for the M19 matcher are shown in Flow Chart 1.

The M27 Matcher

The M27 matcher is an expansion of the M19 matcher. It can handle data from prints that are not as accurately positioned in the reader as prints whose data is used by the M19 matcher. As in M19, M27 computes different tables for Δx , Δy , and $\Delta \theta$ where

> $|\triangle x| \le LS1$ $|\triangle y| \le LS1$ $|\triangle \theta| \le L\theta1$

The distribution of the values of Δx is then determined among eleven equal intervals between -LS1 and +LS1. A similar computation is performed for Δy and $\Delta \theta$ except with $\Delta \theta$ the range is from -L θ 1 to L θ 1. The parameter values

LS1 = 60 $L\theta1 = 25$

used in matching print A with print B produce the same difference table shown in Figure 11. The distributions of these values of Δx and Δy are shown in Figure 17. Prints from the same finger produce peaks in the distribution table, but prints from different fingers produce random distributions. The M27 matcher computes the matching score as did M19 except that it uses only those points in an area 2 x LS2 by 2 x LS2 centered at the peak of the Δx distribution, -36, and the peak of the Δy distribution, 12. These points must simultaneously satisfy the condition that $\Delta \theta$ lies within the range of \pm L θ 2 from the peak of the $\Delta \theta$ distribution which is 0 in this example.

The parameters

LS2 = 10 $L\theta2 = 20$ KR = 10

cause M27 to compute a matching score using only the points found in the area enclosed by the broken line in Figure 15. As before, R = 24 but there are only S = 5 points to consider. Therefore, in comparing print A with print B, the M27 matcher produces a score

$$RS = \frac{R}{S} = \frac{24}{5} = 4.80$$

The comparison of print C with print D yields a score of RS = 0. Here there are two peaks in the Δx distribution and in choosing the first or leftmost, the matcher locates the reduced scoring area in a place where no points are close enough together to score. The complete procedure for the M27 matcher is given in Flow Chart 2.

The M32 Matcher

When a fingerprint impression is placed in a reader, whatever may be defined as the center of the print may be displaced from the center of the reader window. The M27 matcher can cope with this situation. However, the direction line of the finger may also be rotated with respect to the y-axis of the reader, and the M27 matcher may then fail to make a correct match. The M32 matcher is designed to overcome this difficulty. It begins by performing the same comparison procedure as the M27 matcher. The computer then re-computes the data for one of the prints being compared to represent the rotation of this print through V degrees from its original position, and another M27 comparison is made. Altogether, the M32 matcher compares the pair of prints seven times with one print being set at each of the following angles with respect to its original position.

$$V = -15^{\circ}, -10^{\circ}, -5^{\circ}, 0^{\circ}, 5^{\circ}, 10^{\circ}, 15^{\circ}$$

When prints from the same finger are compared, there is always a sharp peak in the graph of RS vs V and the highest of the seven RS scores is taken as the M32 matching score. A typical graph is shown in Figure 18.

5. Experimental Results with Statistical Matchers

Numerous matching runs have been made with these statistical matchers using the NBS UNIVAC 1108 computer. Each run is identified by number and the RS scores from each run are entered in a score matrix as described earlier. Each fingerprint is identified by an Arabic number. The set of search prints is identified by a Roman number and the set of file prints is identified by the next larger Roman number. Each pair of sets is identified by a capital letter.

The score matrix resulting from computer run number 280 is shown in Figure 19. Set XXVI consisting of 14 search prints was compared with set XXVII consisting of 14 file prints. The prints are always ordered such that the scores for prints that should match occur on the diagonal. For example, print 272 and print 1122 are two different impressions from the same finger but print 272 and print 1132 are from different fingers. For this particular run, the minutiae data was read by machine from standard fingerprint cards. The prints were selected as "good looking" rolled prints. Each print was manually positioned in the reader so that the estimated center of the inked impression was at the center of the reader window and the estimated direction of the finger was parallel to the yaxis of the reader. The open task score OS = 60 is found by dividing the highest off-diagonal score, 45 (times 100), by the lowest diagonal score, 75. The closed task score CS = 51 is caused by the second row where 40 is divided by 78. Since both OS and CS are less than 100, the search was a success either as an open or closed search. The score AA = 15 is found by dividing the mean off-diagonal score by the mean diagonal score. It may be feasible to use the score AA from matching runs on small samples of fingerprints to predict the performance in searching large files.

The results of all of the computer runs that have been made using the statistical matchers are summarized in Figure 20. The previous example may be found by referring to computer run number 280 in Figure 20 Part 2. The 28 prints used in this and 7 other runs are identified as Pair F. The smallest number of minutiae read from any of the prints in set XXVI was 81 and the largest number of minutiae was 238. Since the average number of minutiae on a rolled print is about 80, the reader obviously produced many false minutiae, but these false minutiae did not prevent successful identifications in all of the tests with this pair of sets of data.

The same 28 prints were also read by a different reader and the data is identified as pair E consisting of sets XXX and XXXI. See Figure 20 Part 1. Here the prints were not positioned in the reader but instead, the finger-boxes on the fingerprint card were positioned manually in the reader. In some cases the fingerprint was at an angle with the y-axis of the finger-box or the print was not centered in the box. The OS and CS scores in runs 282 and 283 are accordingly high.

Runs 286, 287, 289, 290, and 291 were made to determine the best possible scores attainable with this data. To do this, the minutiae of all 28 prints were plotted using the machine-read data. The plots for each pair of prints from sets XXX and XXXI that should match were manually superimposed and positioned by eye to give the best looking match. The amounts by which each print from set XXX needed to be shifted in the x and y directions and also rotated were measured. These data xx, yy, and v were supplied to the computer and at match time it computed new data representing the corrected position for each print from set XXX prior to computing the match score. The resulting scores show a considerable improvement. The AA scores for runs 289-291 may identify

the lower limit for what can be achieved in practical matching runs. All other matching runs that were made with this type of pre-positioning are identified by the words "See text" in the Notes Column of Figure 20.

6. Discussion of Results

The amount of time required for the computer to compare a pair of prints varys considerably depending on the parameters used and the number of minutiae in each print. Run 282 using the M27 matcher took an average time of 0.1667 seconds to compare a pair of prints. Run 286 using the M19 matcher on the same data took an average time of 0.0845 seconds to compare a pair of prints. This is obviously too slow for the practical search of a large file but it is hoped that these matching techniques can be utilized in a specially built device that can compare a pair of prints in a few microseconds.

Aside from the problems with the matcher itself, the sources of difficulty with minutiae matching can be broken into the following categories, and a discussion of each one follows.

- 1. Poor quality prints.
- 2. Only a partial print available.
- 3. A stretched or twisted print.
- 4. Print displaced in reader in x and y directions.
- 5. Print rotated in reader.
- 6. Reader falsely reports minutiae.
- 7. Reader misses minutiae.

1. Prints accepted for classification in the Henry system need to be only clear enough so that a fingerprint expert can identify the pattern type and count the ridges between core and delta. Light inking, heavy inking, smudges, and missing portions of the print can often be tolerated in the Henry system. The pairs of prints sets A, B, C, and D were randomly selected from such system files. Set pair C was further limited to those prints where the reader produced more than 50 minutiae per print. The matching runs made with set pairs C and D, using machineread minutiae from these prints, gave unsatisfactory scores. The runs 199, 218, and 306 with set pairs A and B where the minutiae data was read manually gave better results. Runs 236 and 237 were made on the same minutiae data that produced the results with the constellation matcher reported in Figure 4. Future improvements in minutiae readers may produce some improvement in matching scores. However, it will probably be more effective to change the rules and require higher quality prints for an automated identification system than are required for the Henry system.

The determination of the quality of fingerprints is a very subjective procedure. In the future it may be feasible for the minutiae reader itself to determine the acceptability of fingerprints based on the character and number of minutiae read. The prints for set pairs E, F, and H were selected prior to machine reading on the basis that they looked as though they would read well. The resulting matching scores are very encouraging and produce an optimistic outlook for automating fingerprint identification.

2. Minutiae data from partial prints and particularly latent fingerprints have not been tested with the statistical matchers. However, the outlook is optimistic. The advantage of manually read minutiae data as indicated by the low AA scores with set-pairs A and B may also apply to latent prints where the minutiae data must also be read manually.

3. The low scores with set-pairs E and F suggest that the problem due to flexing and twisting in rolled prints has been solved. Since plain prints tend to be devoid of the flexing and twisting that plagues rolled prints, the nearly equivalent scores with set-pairs F (rolled) and set-pairs H (plain) supports this suggestion.

4. The problem that results from x-y displacement of the print in the reader can be handled by the matchers with suitable parameter adjustments. In particular, the parameter LS in M19 and LS1 in M27 must be set large enough to accomodate any displacement that can occur. Unfortunately, increases in these parameters are accompanied by increase in both computer time and memory capacity requirements.

5. As was seen in Figure 18, the RS scores are very sensitive to the angular orientation of the print in the reader. The print must be oriented within plus or minus 5 degrees for best results. Further experiments should demonstrate that the M32 matcher can handle this problem if the print is not carefully positioned in the reader. However, this too requires additional computer time and would require many more circuit elements in some future specially-built device. Accordingly, it may be more economical to handle both the x-y positioning and angular orientation problem at the reader. The low scores with set-pairs E, F, and H indicate that manual positioning is satisfactory and it may be feasible for this to be accomplished automatically by the reader.

6,7. The number of minutiae missed as well as the number of false minutiae reported by an automatic reader tend to increase as the quality of prints goes down. Accordingly, the remarks under 1 above also apply here. The degree to which these phenomena degrade matcher performance is under study and future improvements in minutiae readers are expected to decrease the number of missed and falsely read minutiae.

The computer programs used in this work were written and managed by J.F. Rafferty and D. Zimmerman of the National Bureau of Standards and W.J. Pencak, a Guest Worker at NBS from the Federal Bureau of Investigation. The author is also indebted for advice and assistance to R.T. Moore of NBS, and Agents C.S. Voelker and R. Payne of the FBI. The work was financially supported by the FBI.

7. References

- Wegstein, J.H. and Rafferty, J.F., <u>Matching Fingerprints</u> by Computer, National Bureau of Standards Technical Note 466, U.S. Government Printing Office, Washington, D.C., 1968.
- Tosi, O. and Nash, E., "Operational/Technical Analysis of Voiceprint Technology", <u>Proceedings of the Third National</u> <u>Symposium on Law Enforcement and Technology, 1970</u>, (in publication).
- Caudra, C.A., <u>A Feasibility Study for Automated Fingerprint</u> <u>Identification</u>, System Development Corporation, Santa Monica, California, 1966, p. 60.
- Thiebault, R., "Automatic Process for the Identification of Fingerprints," <u>Proceedings</u>, <u>International Symposium</u> <u>on Automation of Population Register Systems</u>, Vol. 1, Jerusalem, Israel, 1967, 207-226.

											X	EV									
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	1	<u>128</u>	46	8	11	23	8	32	30	13	18	22	42	22	6	53	54	22	19	32	12
	2	55	80	8	12	11	12	28	29	6	12	17	25	18	27	40	34	10	8	8	10
XIII	3	9	11	75	35	16	20	19	9	19	30	23	9	14	13	16	18	36	25	14	17
	4	6	1	19	<u>63</u>	14	16	2	4	11	21	22	23	15	13	17	7	22	18	9	26
	5	11	13	13	27	<u>37</u>	28	14	22	20	40	25	13	16	14	24	20	46	36	29	22

Figure 1. Score Matrix



Corresponding to Figure 1.







Idealized Discrimination Graph



(Discrimination Factor)

Figure 4. Discrimination Graph Showing Experimental Results with Constellation Matching. Set XIII vs Set XIV Using Minutiae from 6 mm Radius Circle at Center of Print.

Scale 1 40 22 10 20 Units 0 30 29 7 4 1/28 45 30 44 XII-1 XIV-2-Minutiae from Print XIII 11 2 / Minutiae from Print XIV

Figure 5. Superimposed Minutiae Tracings from Prints of Different Fingers



Figure 6. Superimposed Minutiae Tracings from Prints of the Same Finger

28 28'



8

* 8'

34: 34





Minutiae from Print IIP 5

Figure 7.

Superimposed Minutiae Tracings from Prints of the Same Finger

	Pr	int /	f		Pr	int H	3
i.	x	у	θ	 j	x	У	θ
1 2 3 4 5	48 27 68 136 142	252 190 174 233 181	67 226 205 111 327	1 2 3 4 5 6	75 62 109 174 182 157	241 181 161 229 175 226	65 225 222 128 346 111
	Pri	int (2		Pr	int I)
i	x	у	θ	j	х	У	θ
1 2 3 4 5 6	38 27 89 143 117 153	217 154 244 210 175 128	56 223 15 115 300 334	1 2 3 4 5 6 7	55 41 120 173 77 65 172	227 164 226 180 132 121	54 227 305 276 320 325 285

Figure 8. Minutiae Data







Figure 10. Superimposed Machine Read Minutiae from Prints of Different Fingers.

i	j	∆x	∆у	Δθ
1	1	-27	11	2
2	2	-35	9	1
3	2	6	- 7	-20
3	3	-41	13	-17
4	4	-38	4	-17
4	6	-21	• 7	0
5	5	-40	6	-19



i	j	∆x	∆у	$\Delta \theta$
1	1	- 17	- 10	2
2	2	-14	- 10	-4
5	3	- 3	-51	- 5
5	4	- 56	- 5	24
5	5	40	43	-20
5	6	52	54	-25
5	7	- 55	33	15









Figure 14. Difference Graph for Prints C and D of Different Fingers





1	From	Steps	to Score
point	to point	TR	KR-TR
1,1		>10	0
2,2	4,4	8	2
2,2	5,5	8	2
3,3	5,5	8	2
4,4	2,2	8	2
4,4	5,5	4	6
5,5	2,2	8	2
5,5	3,3	8	2
5,5	4,4	4	6
			R = 24
Figure	16. Comput	ation of Score f	or Figure 15.

In	terv	al	Distr ∆x	ibution ∆y	Center of Interval	
-60	to	-55	0	0	-60	
- 54	to	-43	0	0	-48	
-42	to	-31	4	0	- 36	Peak ∆x
-30	to	-19	2	0	-24	
-18	to	- 7	0	1	- 12	
- 6	to	5	0	1	0	
6	to	17	1	5	12	Peak ∆y
18	to	29	0	0	24	, i i i i i i i i i i i i i i i i i i i
30	to	41	0	0	36	
42	to	53	0	0	48	
54	to	60	0	0	60	

Figure 17. Distribution of $\triangle x$ and $\triangle y$ for Print A vs Print B





Results from M32 Comparison of Prints XVII 71 and XVIII 921 from the Same Finger

						2	set XX	VII .			(Comp	puter	Kun 1	F 280))
	Print	1122	1132	1157	1167	1182	1187	1188	1212	1217	1242	1257	1332	1337	1492
	272	<u>119</u>	30	13	24	20	28	31	14	15	20	23	8	22	20
	282	34	78	12	21	19	7	12	10	15	40	18	14	10	12
	307	10	12	<u>104</u>	20	26	31	30	16	20	9	22	15	16	19
Set	317	29	20	21	75	36	17	34	16	18	32	31	32	21	25
XXVI	332	13	19	30	15	266	10	24	30	16	6	8	13	17	23
	337	12	29	39	8	31	86	22	15	11	17	28	15	20	30
	338	24	26	15	22	24	25	<u>105</u>	6	16	27	39	17	42	17
	362	20	19	25	15	22	5	14	<u>158</u>	5	12	3	8	22	15
	367	14	17	24	24	10	26	21	13	115	13	32	1	16	18
	392	28	32	10	19	19	11	10	19	6	109	18	20	7	20
	407	40	23	14	34	30	17	45	28	22	22	132	9	15	28
	482	7	10	3	10	18	14	19	12	11	10	8	<u>145</u>	19	15
	487	27	8	15	29	17	10	31	0	21	19	19	16	143	19
	642	20	18	10	28	30	29	19	21	15	22	22	14	27	<u>116</u>

Figure 19

Score Matrix for M27 Matching of Good-Quality Machine-Read Prints OS = 60 CS = 51 AA = 15

	0		4	AA	18	77	Ĩ					18			28		26		31			33	31	36	36	31		<u>1</u> 2	19			ω	<u>~</u>	t
	core		20	ß	124	1 2 Q	1			76		76			750		190		121		65	126	155	135	200	153		80	102	53	20	40	с С Г	2
	Š		r c	3	149	153				141		145			1175		288		415		108	250	206	249	317	206		149	153	96	88	94	1100	++++
			С, Г	Ę	10	O L) 1			10		10			10	1	10		10		10	8	0	10	10	IO		10	10	10	TO	IO	10	2
	S S	1	SM	P	18	18) 			10		18			18		18		18		20	15	10	Ч	Ч	10		15	18	20	ìn	5		2
府	letei		T C D	ZOLL	12	л Г	Ĥ					12			13		5		13			10	10	10	10	10		10	15			10	10	2 F
TCHI	aran		ΤGT	TPT	52	32	2			18		22			25		30		52		18	15	5	12	51	TO		15	25	15	12	15	Ч, с И с	2
MA			LS	a	100	00 L)) 			15	,	09			100		120		100		51	35	5	22	30	50		60	60	18	54	22	20	22
	her			1																1											-			1
	Matc		6TM	17M	M2	7CM				MI9		M27			M27		M27		M32	1	ML9	M27	M27	M27	M27	M27		M27	M27	MI 9	MI9	M27	7.CM	דיוב ו
	ter		<u>د</u>	I								~							~															
	ndwo	un	umbe	-	199	218		-		236		237			201		224		285		177	254	252	256	257	258		282	283	286	287	289	290	C7+
-	C	Ř	N	+		-	-	0			_	دىـ			-	<u>с</u>	X					-	~			bg	_	-	_	DX.	>	<	~	-
	tes				with	CC.	Llel	ease	cex.t	ciae	6mm	e a	τo ζ	t n	ne	witl	er-bo	urd	ered	sadel	cex.t	ne	wi th	ally	ered	ente	S	ne	wi tł	er-bo	urd	red	ext	
ADER	.oN				Manua	X-ax	para	to ci	See 1	Minu	from	circ.	Core	print	Machi	read	finge	on ca	cente	TUL	See 1	Machi	read	manua	cente	k ori	print	Machi	read	finge	on ca	cente	See 1	
E RE	iae	ad	>		Ę	Τ	50	_		-	39	-	74			17	T	24				-	20	Ī.	0				24	Ť	98	-		-
UTTA	inut	t Re	2	TIT	L Z	_	H V				0			_			+							-	2		_		1 2	-		_		-
MIM	of M	Prin	eade	0 7 0	75		69.				24.(0	22			80.6		82.							150.(80.		74.			
	No.	Per	By R	11711	42		36				13	-	Τđ			57		23				1	5		39				39		40			
0	. of	ints	Set		0		0				0		-																-+		-+			
NOIS	No	Ч Д	Tn	4	Ň		м М		_		~ ~		Ň			2	-	5					~		~				H -					
PRES	of	File	Set				ΛTΧ) \ \ \ \ \					TTTVX							XXIV						XXXI			
TIV TIV	ame	rch		1	III						с н					H	T		-					T					X	T				
PRIN	Z	Sea	Set	-	×						XTT					AX	1			_			XX		_	_			XX	1	-			
NGER	s of	د			rage	Litv	Led	nts			Ф. Ф.	nts	A			rage	Lity	Led	nts				Ð	nts	5				scte	800	cing	led	lts	
E	Pair	Prin	Sets		Ave:	Qua	Rol.	Pri			Sam	LLLL	с N N			Ave	Qua	Rol	Pri				Sam	Pri	as				Sel	an S'S	Lool	Rol.	ILLI	
L			-		A					PA					C							A						되						

Summarized Results Using Statistical Matcher Figure 20 Part 1

	10			AA		15	19	19	17	77	123		27	1			20	510	100	19	20	19	20	17	19	210		À.
	ore			CS	10	66,	67	69	146	95	хч		200)) 	58		66		,99	81	ъ 20 20	71	78	26	69	200	2 2 2	5
	SC			OS.	74	69	86	80	5	6 20	277		1001)	111		100	101	- 22	80	20	71	16	94.	69	65	10	2
		E	푀	KR	80	8	10	10	10	10	100		0) 	10		 დ (CL	8	10	10	ω	10	10		2
		1.1.1	MD	102 I	15	10	5	Ъ	10	10	504		18) 	10		17	с и Н г	ע ר ל ר		11	10	10	10	Ч О			
1	ters		1	525	10	10	10	10	10	10	10		ىر ب	ì			10				P, P	10	10	10	10	10	01	2
CHE	ame		Ð		12	12	5	12	10	10	101		06	2	18		17	1 r				10,1	5	Ъ	01	ц.	L L	
MAT	Par	*	2	N N	5	۲ س	20	30	35	30	520		000	2	15		35.	L L L L L L L L L L L L L) <u>1</u> (200	30	20	30	25	52	50	N V V
	er	╶╠														_												-
	Match		MLLY	M27	M27	M27	M27	M27	M27	M27	M27 M27		7 CW	1 71.1	ML 9		M27	M27	L CM	LCM L	M27	M27	M27	M27	M27	M27	M27) 7M
	uter		er		6	0	_		3		60		C	5	Ч		1		2 6	- a) O	, 0		2	<i>с</i>	-T.		0
	Comp	TINU	GUINN		у С	26	26	26	26	27	23		00) <u></u>	718		26	50			202	27	27.	27	27	27	27	17
	es				e	ith	Γv	ed "	nted			0	ith		ed.	der			٥	, + + (TV T	ed	nted					
ADER	Not				Machin	read w	manual	center	& orie	prints		Machin	read W	en li Turd	center	in rea			ทำปายพ	M Peou	manual	center	& orie	prints				
AE RE	utige	บอลน		max.		238		175				ĩ	24	78	2			17	946) 								
I L UN IW	of Min Duint	ייין ייי	eader	ave		134.7		128.9					۲ ۰ ۵۲	27.0				58.8	68 3									
	No.	191	ਮਿੰਸ	min		81		80					53	00	 J J			36	ប	+								
SNC	No. of Doints	SULL SULL	TU Set			14		14				t t).T	21				0	C F	2								
TRESSI(of Trilo		Det					IIVXX						X X	4				VYTY									
RINT IN	Name	TID.TPAC	Dac			KXVI							XTX					IIIAXX										
FINGERF	Pairs of Duint	011T.11	Dets		ĿЧ	Same	Prints	as E				5	Average	Plain	Prints		Η	Selected	as "good"	Plain	Prints							

Figure 20 Part 2







Flow Chart 2 Part 2 M27 Matcher Cont.





· •

U.S. DEPARTMENT OF COMMERCE WASHINGTON, D.C. 20230

OFFICIAL BUSINESS



POSTAGE AND FEES PAID U.S. DEPARTMENT OF COMMERCE